django-elasticsearch-dsl-drf Documentation

Release 0.20.4

Artur Barseghyan <artur.barseghyan@gmail.com>

Dec 25, 2019

Contents

1 Documentation **3**

2 Prerequisites **5**

3 Main features and highlights **7**

4 Demo **9**

5 Installation **11**

6 Quick start **13**

7 Testing **15**

8 Writing documentation **17**

9 License **19**

10 Support **21**

11 Author **23**

12 Project documentation **25**

12.1 Dependencies . . . 25
12.2 Installing Elasticsearch . . . 26
12.2.1 Docker . . . 27
12.2.1.1 6.x . . . 27
12.2.1.2 7.x . . . 27
12.3 Quick start . . . 27
12.3.1 Installation . . . 29
12.3.2 Example app . . . 29
12.3.2.1 Sample models . . . 30
12.3.2.1.1 Required imports . . . 30
12.3.2.1.2 Book statuses . . . 30
12.3.2.1.3 Publisher model . . . 31
12.3.2.1.4 Author model . . . 31
12.3.2.1.5 Tag model . . . 32
12.3.2.1.6 Book model . . . 32

12.3.2.2 Admin classes . . . 33
12.3.2.3 Create database tables . . . 34
12.3.2.4 Fill in some data . . . 34
12.3.2.5 Sample document . . . 34
12.3.2.5.1 Required imports . . . 35
12.3.2.5.2 Index definition . . . 35
12.3.2.5.2.1 Settings . . . 35
12.3.2.5.2.2 Document index . . . 36
12.3.2.5.3 Custom analyzers . . . 36
12.3.2.5.4 Document definition . . . 36
12.3.2.6 Syncing Django's database with Elasticsearch indexes . . . 38
12.3.2.6.1 Full database sync . . . 38
12.3.2.6.2 Sample partial sync (using custom signals) . . . 38
12.3.2.6.2.1 Required imports . . . 38
12.3.2.6.2.2 Update book index on related model change . . . 38
12.3.2.6.2.3 Update book index on related model removal . . . 39
12.3.2.7 Sample serializer . . . 40
12.3.2.7.1 Required imports . . . 40
12.3.2.7.2 Serializer definition . . . 40
12.3.2.8 ViewSet definition . . . 42
12.3.2.8.1 Required imports . . . 42
12.3.2.8.2 ViewSet definition . . . 42
12.3.2.9 URLs . . . 44
12.3.2.9.1 Required imports . . . 44
12.3.2.9.2 Router definition . . . 45
12.3.2.9.3 URL patterns . . . 45
12.3.2.10 Check what you've done so far . . . 45
12.3.2.10.1 URLs . . . 45
12.3.2.10.2 Test in browser . . . 45
12.3.3 Development and debugging . . . 46
12.3.3.1 Profiling tools . . . 46
12.3.3.1.1 Installation . . . 46
12.3.3.1.2 Configuration . . . 46
12.3.3.2 Debugging . . . 47
12.4 Filter usage examples . . . 47
12.4.1 Search . . . 48
12.4.1.1 Search in all fields . . . 48
12.4.1.2 Search a single term on specific field . . . 48
12.4.1.3 Search for multiple terms . . . 48
12.4.1.4 Search for multiple terms in specific fields . . . 48
12.4.2 Filtering . . . 49
12.4.2.1 Supported lookups . . . 49
12.4.2.1.1 Native . . . 49
12.4.2.1.1.1 term . . . 49
12.4.2.1.1.2 terms . . . 49
12.4.2.1.1.3 range . . . 49
12.4.2.1.1.4 exists . . . 50
12.4.2.1.1.5 prefix . . . 50
12.4.2.1.1.6 wildcard . . . 50
12.4.2.1.1.7 ids . . . 50
12.4.2.1.2 Functional . . . 50
12.4.2.1.2.1 contains . . . 51
12.4.2.1.2.2 in . . . 51
12.4.2.1.2.3 gt . . . 51

12.4.2.1.2.4 gte . . . 51
12.4.2.1.2.5 lt . . . 51
12.4.2.1.2.6 lte . . . 51
12.4.2.1.2.7 startswith . . . 51
12.4.2.1.2.8 endswith . . . 52
12.4.2.1.2.9 isnull . . . 52
12.4.2.1.2.10 exclude . . . 52
12.4.3 Usage examples . . . 52
12.5 Search backends . . . 52
12.5.1 Compound search filter backend . . . 52
12.5.1.1 Sample view . . . 53
12.5.1.2 Sample request . . . 53
12.5.1.3 Generated query . . . 53
12.5.2 Multi match search filter backend . . . 54
12.5.2.1 Sample view . . . 54
12.5.2.2 Sample request . . . 55
12.5.2.3 Generated query . . . 55
12.5.2.4 Options . . . 55
12.5.2.4.1 Type options . . . 56
12.5.2.4.2 Operator options . . . 56
12.5.3 Simple query string filter backend . . . 56
12.5.3.1 Sample view . . . 56
12.5.3.2 Sample request 1 . . . 57
12.5.3.3 Generated query 1 . . . 57
12.5.3.4 Sample request 2 . . . 57
12.5.3.5 Generated query 2 . . . 58
12.5.3.6 Sample request 3 . . . 58
12.5.3.7 Generated query 3 . . . 58
12.5.3.8 Options . . . 59
12.5.3.8.1 Default Operator options . . . 59
12.6 Basic usage examples . . . 59
12.6.1 Example app . . . 60
12.6.1.1 Sample models . . . 60
12.6.1.2 Sample document . . . 61
12.6.1.3 Sample serializer . . . 62
12.6.1.4 Sample view . . . 63
12.6.1.5 Usage example . . . 64
12.6.1.5.1 Sample queries . . . 64
12.6.1.5.1.1 Search . . . 64
12.6.1.5.1.2 Filtering . . . 65
12.6.1.5.1.3 Ordering . . . 65
12.7 Advanced usage examples . . . 66
12.7.1 Example app . . . 68
12.7.1.1 Sample models . . . 68
12.7.1.2 Sample document . . . 70
12.7.1.2.1 Index definition . . . 70
12.7.1.2.1.1 Settings . . . 70
12.7.1.2.1.2 Document index . . . 71
12.7.1.3 Sample serializer . . . 73
12.7.1.4 Sample view . . . 74
12.7.1.5 Usage example . . . 75
12.7.1.5.1 Search . . . 75
12.7.1.5.2 Filtering . . . 76
12.7.1.5.3 Ordering . . . 77

12.7.1.6 Ids filter . . . 78
12.7.1.7 Faceted search . . . 78
12.7.1.8 Post-filter . . . 79
12.7.1.8.1 Sample view . . . 79
12.7.1.8.2 Sample queries . . . 81
12.7.1.9 Geo-spatial features . . . 81
12.7.1.9.1 Filtering . . . 81
12.7.1.9.2 Ordering . . . 82
12.7.1.10 Suggestions . . . 82
12.7.1.10.1 Completion suggesters . . . 82
12.7.1.10.1.1 Document definition . . . 82
12.7.1.10.1.2 Serializer definition . . . 84
12.7.1.10.1.3 ViewSet definition . . . 84
12.7.1.10.1.4 Sample requests/responses . . . 85
12.7.1.10.1.5 Suggestions on Array/List field . . . 87
12.7.1.10.1.6 Sample requests/responses . . . 87
12.7.1.10.1.7 Context suggesters . . . 88
12.7.1.10.1.8 *category* context . . . 88
12.7.1.10.1.9 *geo* context . . . 90
12.7.1.10.2 Term and Phrase suggestions . . . 91
12.7.1.10.2.1 Document definition . . . 91
12.7.1.10.2.2 ViewSet definition . . . 93
12.7.1.10.2.3 Sample requests/responses . . . 96
12.7.1.10.2.4 Completion . . . 97
12.7.1.10.2.5 Term . . . 98
12.7.1.10.2.6 Phrase . . . 99
12.7.1.11 Functional suggestions . . . 100
12.7.1.11.1 Document definition . . . 100
12.7.1.11.2 ViewSet definition . . . 101
12.7.1.12 Highlighting . . . 103
12.7.1.13 Pagination . . . 105
12.7.1.13.1 Page number pagination . . . 105
12.7.1.13.2 Limit/offset pagination . . . 105
12.7.1.13.3 Customisations . . . 105
12.8 Nested fields usage examples . . . 106
12.8.1 Example app . . . 107
12.8.1.1 Sample models . . . 107
12.8.1.2 Sample document . . . 111
12.8.1.2.1 Index definition . . . 111
12.8.1.2.1.1 Settings . . . 111
12.8.1.2.1.2 Document index . . . 112
12.8.1.3 Sample serializer . . . 115
12.8.1.4 Sample view . . . 115
12.8.1.5 Usage example . . . 117
12.8.1.5.1 Sample queries . . . 118
12.8.1.5.1.1 Search . . . 118
12.8.1.5.1.2 Nested filtering . . . 118
12.8.1.5.1.3 Nested search . . . 118
12.8.1.5.1.4 Sample models . . . 118
12.8.1.5.1.5 Sample document . . . 119
12.8.1.5.1.6 Sample view . . . 121
12.8.1.5.1.7 Sample request . . . 123
12.8.1.5.1.8 Filtering . . . 123
12.8.1.5.1.9 Ordering . . . 123

12.8.1.6 Suggestions . . . 123
12.8.1.7 Nested aggregations/facets . . . 124
12.9 More like this . . . 127
12.9.1 Usage example . . . 127
12.9.1.1 Sample document . . . 127
12.9.1.2 Sample view . . . 128
12.9.1.3 Sample request . . . 129
12.9.1.4 Generated query . . . 129
12.9.1.5 Options . . . 130
12.10 Global aggregations . . . 130
12.10.1 Sample view . . . 130
12.10.2 Sample request . . . 131
12.10.3 Generated query . . . 131
12.10.4 Sample response . . . 132
12.11 Configuration tweaks . . . 133
12.11.1 Ignore certain Elasticsearch exceptions . . . 133
12.12 Source filtering backend . . . 133
12.13 Indexing troubleshooting . . . 134
12.13.1 Timeout . . . 134
12.13.2 Chunk size . . . 135
12.13.3 Use parallel indexing . . . 135
12.13.4 Limit the number of items indexed at once . . . 136
12.14 FAQ . . . 137
12.14.1 Questions and answers . . . 137
12.15 Demo . . . 138
12.15.1 Run demo locally . . . 138
12.15.2 Prerequisites . . . 138
12.16 frontend demo for django-elasticsearch-dsl-drf . . . 138
12.16.1 Quick start . . . 138
12.16.1.1 Install the django requirements . . . 139
12.16.1.2 Install Elasticsearch requirements . . . 139
12.16.1.3 Run Elasticsearch . . . 139
12.16.1.4 Build Elasticsearch index . . . 139
12.16.1.5 Install React requirements . . . 139
12.16.1.6 Run Django . . . 140
12.16.1.7 Run React demo app . . . 140
12.17 Release history and notes . . . 140
12.17.1 0.20.4 . . . 140
12.17.2 0.20.3 . . . 140
12.17.3 0.20.2 . . . 140
12.17.4 0.20.1 . . . 141
12.17.5 0.20 . . . 141
12.17.6 0.19 . . . 141
12.17.7 0.18 . . . 141
12.17.8 0.17.7 . . . 141
12.17.9 0.17.6 . . . 142
12.17.100.17.5 . . . 142
12.17.110.17.4 . . . 142
12.17.120.17.3 . . . 142
12.17.130.17.2 . . . 142
12.17.140.17.1 . . . 142
12.17.150.17 . . . 142
12.17.160.16.3 . . . 143
12.17.170.16.2 . . . 143

12.17.180.16.1 . . . 143
12.17.190.16 . . . 143
12.17.200.15.1 . . . 144
12.17.210.15 . . . 144
12.17.220.14 . . . 144
12.17.230.13.2 . . . 144
12.17.240.13.1 . . . 144
12.17.250.13 . . . 145
12.17.260.12 . . . 145
12.17.270.11 . . . 145
12.17.280.10 . . . 146
12.17.290.9 . . . 146
12.17.300.8.4 . . . 147
12.17.310.8.3 . . . 147
12.17.320.8.2 . . . 147
12.17.330.8.1 . . . 147
12.17.340.8 . . . 147
12.17.350.7.2 . . . 148
12.17.360.7.1 . . . 148
12.17.370.7 . . . 148
12.17.380.6.4 . . . 148
12.17.390.6.3 . . . 148
12.17.400.6.2 . . . 149
12.17.410.6.1 . . . 149
12.17.420.6 . . . 149
12.17.430.5.1 . . . 149
12.17.440.5 . . . 149
12.17.450.4.4 . . . 149
12.17.460.4.3 . . . 150
12.17.470.4.2 . . . 150
12.17.480.4.1 . . . 150
12.17.490.4 . . . 150
12.17.500.3.12 . . . 150
12.17.510.3.11 . . . 151
12.17.520.3.10 . . . 151
12.17.530.3.9 . . . 151
12.17.540.3.8 . . . 151
12.17.550.3.7 . . . 151
12.17.560.3.6 . . . 151
12.17.570.3.5 . . . 151
12.17.580.3.4 . . . 151
12.17.590.3.3 . . . 152
12.17.600.3.2 . . . 152
12.17.610.3.1 . . . 152
12.17.620.3 . . . 152
12.17.630.2.6 . . . 152
12.17.640.2.5 . . . 152
12.17.650.2.4 . . . 152
12.17.660.2.3 . . . 152
12.17.670.2.2 . . . 153
12.17.680.2.1 . . . 153
12.17.690.2 . . . 153
12.17.700.1.8 . . . 153
12.17.710.1.7 . . . 153

12.17.720.1.6 . . . 153
12.17.730.1.5 . . . 153
12.17.740.1.4 . . . 154
12.17.750.1.3 . . . 154
12.17.760.1.2 . . . 154
12.17.770.1.1 . . . 154
12.17.780.1 . . . 154
12.18 django_elasticsearch_dsl_drf package . . . 154
12.18.1 Subpackages . . . 154
12.18.1.1 django_elasticsearch_dsl_drf.fields package . . . 154
12.18.1.1.1 Submodules . . . 154
12.18.1.1.2 django_elasticsearch_dsl_drf.fields.common module . . . 154
12.18.1.1.3 django_elasticsearch_dsl_drf.fields.helpers module . . . 156
12.18.1.1.4 django_elasticsearch_dsl_drf.fields.nested_fields module . . . 156
12.18.1.1.5 Module contents . . . 159
12.18.1.2 django_elasticsearch_dsl_drf.filter_backends package . . . 162
12.18.1.2.1 Subpackages . . . 162
12.18.1.2.1.1 django_elasticsearch_dsl_drf.filter_backends.aggregations package 162
12.18.1.2.1.2 Submodules . . . 162
12.18.1.2.1.3 django_elasticsearch_dsl_drf.filter_backends.aggregations.bucket_aggregations module . . . 162
12.18.1.2.1.4 django_elasticsearch_dsl_drf.filter_backends.aggregations.metrics_aggregations module . . . 162
12.18.1.2.1.5 django_elasticsearch_dsl_drf.filter_backends.aggregations.pipeline_aggregations module . . . 162
12.18.1.2.1.6 Module contents . . . 162
12.18.1.2.1.7 django_elasticsearch_dsl_drf.filter_backends.filtering package . . . 162
12.18.1.2.1.8 Submodules . . . 162
12.18.1.2.1.9 django_elasticsearch_dsl_drf.filter_backends.filtering.common module . . . 162
12.18.1.2.1.10 django_elasticsearch_dsl_drf.filter_backends.filtering.geo_spatial module . . . 170
12.18.1.2.1.11 django_elasticsearch_dsl_drf.filter_backends.filtering.ids module . 174
12.18.1.2.1.12 django_elasticsearch_dsl_drf.filter_backends.filtering.nested module . . . 176
12.18.1.2.1.13 django_elasticsearch_dsl_drf.filter_backends.filtering.post_filter module . . . 177
12.18.1.2.1.14 Module contents . . . 179
12.18.1.2.1.15 django_elasticsearch_dsl_drf.filter_backends.ordering package . . . 193
12.18.1.2.1.16 Submodules . . . 193
12.18.1.2.1.17 django_elasticsearch_dsl_drf.filter_backends.ordering.common module . . . 193
12.18.1.2.1.18 django_elasticsearch_dsl_drf.filter_backends.ordering.geo_spatial module . . . 196
12.18.1.2.1.19 Module contents . . . 198
12.18.1.2.1.20 django_elasticsearch_dsl_drf.filter_backends.search package . . . 203
12.18.1.2.1.21 Subpackages . . . 203
12.18.1.2.1.22 django_elasticsearch_dsl_drf.filter_backends.search.query_backends package . . . 203
12.18.1.2.1.23 Submodules . . . 203
12.18.1.2.1.24 django_elasticsearch_dsl_drf.filter_backends.search.query_backends.base module . . . 203
12.18.1.2.1.25 django_elasticsearch_dsl_drf.filter_backends.search.query_backends.match module . . . 203

12.18.1.2.1.26 django_elasticsearch_dsl_drf.filter_backends.search.query_backends.match_phrase module . . . 203
12.18.1.2.1.27 django_elasticsearch_dsl_drf.filter_backends.search.query_backends.match_phrase_prefix module . . . 204
12.18.1.2.1.28 django_elasticsearch_dsl_drf.filter_backends.search.query_backends.multi_match module . . . 204
12.18.1.2.1.29 django_elasticsearch_dsl_drf.filter_backends.search.query_backends.nested module . . . 205
12.18.1.2.1.30 django_elasticsearch_dsl_drf.filter_backends.search.query_backends.simple_query_string module . . . 206
12.18.1.2.1.31 Module contents . . . 207
12.18.1.2.1.32 Submodules . . . 211
12.18.1.2.1.33 django_elasticsearch_dsl_drf.filter_backends.search.base module . 211
12.18.1.2.1.34 django_elasticsearch_dsl_drf.filter_backends.search.compound module . . . 212
12.18.1.2.1.35 django_elasticsearch_dsl_drf.filter_backends.search.historical module . . . 212
12.18.1.2.1.36 django_elasticsearch_dsl_drf.filter_backends.search.multi_match module . . . 214
12.18.1.2.1.37 django_elasticsearch_dsl_drf.filter_backends.search.query_string module . . . 214
12.18.1.2.1.38 django_elasticsearch_dsl_drf.filter_backends.search.simple_query_string module . . . 214
12.18.1.2.1.39 Module contents . . . 215
12.18.1.2.1.40 django_elasticsearch_dsl_drf.filter_backends.suggester package . 218
12.18.1.2.1.41 Submodules . . . 218
12.18.1.2.1.42 django_elasticsearch_dsl_drf.filter_backends.suggester.functional module . . . 218
12.18.1.2.1.43 django_elasticsearch_dsl_drf.filter_backends.suggester.native module . . . 223
12.18.1.2.1.44 Module contents . . . 227
12.18.1.2.2 Submodules . . . 234
12.18.1.2.3 django_elasticsearch_dsl_drf.filter_backends.faceted_search module . . . 234
12.18.1.2.4 django_elasticsearch_dsl_drf.filter_backends.highlight module . . . 237
12.18.1.2.5 django_elasticsearch_dsl_drf.filter_backends.mixins module . . . 238
12.18.1.2.6 Module contents . . . 239
12.18.1.3 django_elasticsearch_dsl_drf.tests package . . . 240
12.18.1.3.1 Submodules . . . 240
12.18.1.3.2 django_elasticsearch_dsl_drf.tests.base module . . . 240
12.18.1.3.3 django_elasticsearch_dsl_drf.tests.data_mixins module . . . 240
12.18.1.3.4 django_elasticsearch_dsl_drf.tests.test_faceted_search module . . . 240
12.18.1.3.5 django_elasticsearch_dsl_drf.tests.test_filtering_common module . . . 241
12.18.1.3.6 django_elasticsearch_dsl_drf.tests.test_filtering_geo_spatial module . . . 244
12.18.1.3.7 django_elasticsearch_dsl_drf.tests.test_filtering_global_aggregations module . . . 245
12.18.1.3.8 django_elasticsearch_dsl_drf.tests.test_filtering_nested module . . . 245
12.18.1.3.9 django_elasticsearch_dsl_drf.tests.test_filtering_post_filter module . . . 247
12.18.1.3.10 django_elasticsearch_dsl_drf.tests.test_functional_suggesters module . . 249
12.18.1.3.11 django_elasticsearch_dsl_drf.tests.test_helpers module . . . 250
12.18.1.3.12 django_elasticsearch_dsl_drf.tests.test_highlight module . . . 250
12.18.1.3.13 django_elasticsearch_dsl_drf.tests.test_more_like_this module . . . 250
12.18.1.3.14 django_elasticsearch_dsl_drf.tests.test_ordering_common module . . . 250
12.18.1.3.15 django_elasticsearch_dsl_drf.tests.test_ordering_geo_spatial module . . . 252
12.18.1.3.16 django_elasticsearch_dsl_drf.tests.test_pagination module . . . 252

12.18.1.3.17 django_elasticsearch_dsl_drf.tests.test_pip_helpers module 252
12.18.1.3.18 django_elasticsearch_dsl_drf.tests.test_search module 253
12.18.1.3.19 django_elasticsearch_dsl_drf.tests.test_search_multi_match module . . . 254
12.18.1.3.20 django_elasticsearch_dsl_drf.tests.test_search_simple_query_string module 254
12.18.1.3.21 django_elasticsearch_dsl_drf.tests.test_serializers module 255
12.18.1.3.22 django_elasticsearch_dsl_drf.tests.test_suggesters module 256
12.18.1.3.23 django_elasticsearch_dsl_drf.tests.test_views module 256
12.18.1.3.24 django_elasticsearch_dsl_drf.tests.test_wrappers module 257
12.18.1.3.25 Module contents 257
12.18.2 Submodules 271
12.18.3 django_elasticsearch_dsl_drf.analyzers module 271
12.18.4 django_elasticsearch_dsl_drf.apps module 271
12.18.5 django_elasticsearch_dsl_drf.compat module 272
12.18.6 django_elasticsearch_dsl_drf.constants module 272
12.18.7 django_elasticsearch_dsl_drf.helpers module 272
12.18.8 django_elasticsearch_dsl_drf.pagination module 273
12.18.9 django_elasticsearch_dsl_drf.pip_helpers module 275
12.18.10 django_elasticsearch_dsl_drf.serializers module 275
12.18.11 django_elasticsearch_dsl_drf.utils module 276
12.18.12 django_elasticsearch_dsl_drf.versions module 276
12.18.13 django_elasticsearch_dsl_drf.viewsets module 277
12.18.14 django_elasticsearch_dsl_drf.wrappers module 278
12.18.15 Module contents 278

13 Indices and tables **279**

Python Module Index **281**

Index **283**

Integrate Elasticsearch DSL with Django REST framework in the shortest way possible, with least efforts possible.

Package provides views, serializers, filter backends, pagination and other handy add-ons.

You are expected to use django-elasticsearch-dsl for defining your Elasticsearch documents.

CHAPTER 1

Documentation

Documentation is available on Read the Docs.

Make sure to read FAQ.

CHAPTER 2

Prerequisites

- Django 1.11, 2.0, 2.1, 2.2 and 3.0.
- Python 2.7, 3.5, 3.6, 3.7, 3.8.
- Elasticsearch 6.x, 7.x. For older versions use `django-elasticsearch-dsl-drf` version 0.18.

CHAPTER 3

Main features and highlights

- *Dynamic serializer for Documents*.
- *Search filter backend*.
- *Ordering filter backend*.
- *Filtering filter backend* (big variety of native- and functional- query lookups, such as `gt`, `gte`, `lt`, `lte`, `endswith`, `contains`, `wildcard`, `exists`, `exclude`, `isnull`, `range`, `in`, `prefix` (same as `startswith`), `term` and `terms` is implemented.
- *Geo-spatial filtering filter backend* (the following filters implemented: `geo_distance`, `geo_polygon` and `geo_bounding_box`).
- *Geo-spatial ordering filter backend* (the following filters implemented: `geo_distance`).
- *Faceted search filter backend*.
- *Post-filter filter backend*.
- *Nested filtering filter backend*.
- *Highlight backend*.
- *Suggester filter backend*.
- *Functional suggester filter backend*.
- *Pagination (Page number and limit/offset pagination)*.
- *Ids filter backend*.
- *Multi match search filter backend*.
- *Simple search query search filter backend*.
- *More-like-this support (detail action)*.
- *Global aggregations support*.
- *Source filter backend*.

Do you need a similar tool for GraphQL? Check graphene-elastic.

CHAPTER 4

Demo

A frontend demo (React based) is available. See the dedicated docs for more information.

To bootstrap evaluation, clone the repository locally and run *docker-compose*.

```
docker-compose up
```

It will set up:

- Elasticsearch on http://localhost:9200
- Django REST framework on http://localhost:8000
- React on http://localhost:3000

CHAPTER 5

Installation

(1) Install latest stable version from PyPI:

```
pip install django-elasticsearch-dsl-drf
```

or latest stable version from GitHub:

```
pip install https://github.com/barseghyanartur/django-elasticsearch-dsl-drf/
↪archive/stable.tar.gz
```

or latest stable version from BitBucket:

```
pip install https://bitbucket.org/barseghyanartur/django-elasticsearch-dsl-drf/
↪get/stable.tar.gz
```

(2) Add `rest_framework`, `django_elasticsearch_dsl` and `django_elasticsearch_dsl_drf` to `INSTALLED_APPS`:

```
INSTALLED_APPS = (
    # ...
    # REST framework
    'rest_framework',

    # Django Elasticsearch integration
    'django_elasticsearch_dsl',

    # Django REST framework Elasticsearch integration (this package)
    'django_elasticsearch_dsl_drf',
    # ...
)
```

CHAPTER 6

Quick start

Perhaps the easiest way to get acquainted with `django-elasticsearch-dsl-drf` is to read the *quick start tutorial*.

See it as a guide of diving into integration of Elasticsearch with Django with very low knowledge entry level.

CHAPTER 7

Testing

Project is covered with tests.

To test with all supported Python/Django versions type:

```
tox
```

To test against specific environment, type:

```
tox -e py38-django30
```

To test just your working environment type:

```
./runtests.py
```

To run a single test in your working environment type:

```
./runtests.py src/django_elasticsearch_dsl_drf/tests/test_filtering.py
```

Or:

```
./manage.py test django_elasticsearch_dsl_drf.tests.test_ordering
```

To run a single test class in a given test module in your working environment type:

```
./runtests.py src/django_elasticsearch_dsl_drf/tests/test_suggesters.
↪py::TestSuggesters
```

It's assumed that you have all the requirements installed. If not, first install the test requirements:

```
pip install -r examples/requirements/test.txt
```

CHAPTER 8

Writing documentation

Keep the following hierarchy.

```
=====
title
=====

header
======

sub-header
----------

sub-sub-header
~~~~~~~~~~~~~~

sub-sub-sub-header
^^^^^^^^^^^^^^^^^^

sub-sub-sub-sub-header
++++++++++++++++++++++

sub-sub-sub-sub-sub-header
**************************
```

CHAPTER 9

License

GPL-2.0-only OR LGPL-2.1-or-later

CHAPTER 10

Support

For any issues contact me at the e-mail given in the *Author* section.

CHAPTER 11

Author

Artur Barseghyan <artur.barseghyan@gmail.com>

CHAPTER 12

Project documentation

Contents:

Table of Contents

- *django-elasticsearch-dsl-drf*
  - *Documentation*
  - *Prerequisites*
  - *Main features and highlights*
  - *Demo*
  - *Installation*
  - *Quick start*
  - *Testing*
  - *Writing documentation*
  - *License*
  - *Support*
  - *Author*
  - *Project documentation*
  - *Indices and tables*

12.1 Dependencies

elasticsearch and elasticsearch-dsl

Depending on your `Elasticsearch` version (either 2.x, 5.x, 6.x or 7.x) you should use 2.x, 5.x, 6.x or 7.x versions of the `elasticsearch` and `elasticsearch-dsl` packages accordingly.

Current compatibility matrix is:

This package	Elasticsearch
0.20.x	6.x, 7.x
0.19.x	6.x
0.18.x	2.x, 5.x, 6.x

django-elasticsearch-dsl

You are advised to use the latest version of django-elasticsearch-dsl.

The following versions have been tested and work well together:

elasticsearch	elasticsearch-dsl	django-elasticsearch-dsl
2.4.1	2.2.0	0.5.1
5.4.0	5.3.0	0.5.1

5.4.0 | 5.3.0 | 0.5.1 |

As of `django-elasticsearch-dsl-drf` 0.19, support for Elasticsearch versions prior 6.x has been dropped.

Django/ Django REST Framework

Initial version of this package was written for djangorestframework 3.6.2.

Starting from `django-elasticsearch-dsl-drf` version 0.18, support for `Django` versions prior 1.11 and `Django REST Framework` versions prior 3.9 has been dropped.

Current compatibility matrix is:

The version 0.17.7 has been tested with the following versions of Django and Django REST Framework:

Django	Django REST Framework
1.8	3.6.2
1.9	3.6.2
1.10	3.6.2
1.11	3.7.7
2.0	3.7.7
2.1	3.8.2
2.2	3.9.2

12.2 Installing Elasticsearch

For development and testing purposes, it's often handy to be able to quickly switch between different Elasticsearch versions. Since this packages supports 2.x, 5.x and 6.x branches, you could make use of the following boxes/containers for development and testing.

Note: As of `django-elasticsearch-dsl-drf` 0.19, support for Elasticsearch versions prior 6.x has been dropped.

For all containers/boxes mentioned below, no authentication is required (for Elasticsearch).

12.2.1 Docker

Using `docker-compose` (persistent):

```
docker-compose up elasticsearch
```

12.2.1.1 6.x

6.3.2

```
docker pull docker.elastic.co/elasticsearch/elasticsearch:6.3.2
docker run -p 9200:9200 -e "discovery.type=single-node" -e "xpack.security.
↪enabled=false" docker.elastic.co/elasticsearch/elasticsearch:6.3.2
```

6.4.0

```
docker pull docker.elastic.co/elasticsearch/elasticsearch:6.4.0
docker run -p 9200:9200 -e "discovery.type=single-node" -e "xpack.security.
↪enabled=false" docker.elastic.co/elasticsearch/elasticsearch:6.4.0
```

12.2.1.2 7.x

7.3.0

```
docker pull docker.elastic.co/elasticsearch/elasticsearch:7.3.0
docker run -p 9200:9200 -e "discovery.type=single-node" -e "xpack.security.
↪enabled=false" docker.elastic.co/elasticsearch/elasticsearch:7.3.0
```

12.3 Quick start

The best way to get acquainted with `django-elasticsearch-dsl-drf`.

See it as a guide of diving into integration of Elasticsearch with Django with very low knowledge entry level.

Contents:

Table of Contents

- *Quick start*
  - *Installation*
  - *Example app*
    - *Sample models*

- *Required imports*
- *Book statuses*
- *Publisher model*
- *Author model*
- *Tag model*
- *Book model*

* *Admin classes*
* *Create database tables*
* *Fill in some data*
* *Sample document*
  - *Required imports*
  - *Index definition*
  - *Settings*
  - *Document index*
  - *Custom analyzers*
  - *Document definition*
* *Syncing Django's database with Elasticsearch indexes*
  - *Full database sync*
  - *Sample partial sync (using custom signals)*
  - *Required imports*
  - *Update book index on related model change*
  - *Update book index on related model removal*
* *Sample serializer*
  - *Required imports*
  - *Serializer definition*
* *ViewSet definition*
  - *Required imports*
  - *ViewSet definition*
* *URLs*
  - *Required imports*
  - *Router definition*
  - *URL patterns*
* *Check what you've done so far*
  - *URLs*
  - *Test in browser*

- *Development and debugging*
  - *Profiling tools*
    - *Installation*
    - *Configuration*
  - *Debugging*

12.3.1 Installation

(1) Install latest stable version from PyPI:

```
pip install django-elasticsearch-dsl-drf
```

(2) Add `rest_framework`, `django_elasticsearch_dsl` and `django_elasticsearch_dsl_drf` to `INSTALLED_APPS`:

```
INSTALLED_APPS = (
    # ...
    # REST framework
    'rest_framework',

    # Django Elasticsearch integration
    'django_elasticsearch_dsl',

    # Django REST framework Elasticsearch integration (this package)
    'django_elasticsearch_dsl_drf',
    # ...
)
```

(3) Basic Django REST framework and `django-elasticsearch-dsl` configuration:

```
REST_FRAMEWORK = {
    'DEFAULT_AUTHENTICATION_CLASSES': (
        'rest_framework.authentication.BasicAuthentication',
        'rest_framework.authentication.SessionAuthentication',
    ),
    'DEFAULT_PAGINATION_CLASS':
        'rest_framework.pagination.PageNumberPagination',
    'PAGE_SIZE': 100,
    'ORDERING_PARAM': 'ordering',
}

# Elasticsearch configuration
ELASTICSEARCH_DSL = {
    'default': {
        'hosts': 'localhost:9200'
    },
}
```

12.3.2 Example app

To get started, let's imagine we have a simple book register with a couple of models.

- *Publisher model*: The book publisher model. Each book might have only one publisher (`ForeignKey` relation).
- *Author model*: The book author model. Each book might have unlimited number of authors (`ManyToMany` relation).
- *Tag model*: The tag model. Each book might have unlimited number of tags (`ManyToMany` relation).
- *Book model*: The book model.

To keep things separate, our Django models will reside in the `books` app. Elasticsearch documents and Django REST framework views will be defined in a `search_indexes` app. Both of the apps should be added to the `INSTALLED_APPS`.

```
INSTALLED_APPS = (
    # ...
    'books',  # Books application
    'search_indexes',  # Elasticsearch integration with the Django
                       # REST framework
    # ...
)
```

12.3.2.1 Sample models

Content of the `books/models.py` file. Additionally, see the code comments.

12.3.2.1.1 Required imports

Imports required for model definition.

books/models/book.py

```
import json

from django.conf import settings
from django.db import models
from django.utils.translation import ugettext, ugettext_lazy as _

from six import python_2_unicode_compatible
```

12.3.2.1.2 Book statuses

books/models/book.py

```
# States indicate the publishing status of the book. Publishing might
# be in-progress, not yet published, published, rejected, etc.
BOOK_PUBLISHING_STATUS_PUBLISHED = 'published'
BOOK_PUBLISHING_STATUS_NOT_PUBLISHED = 'not_published'
BOOK_PUBLISHING_STATUS_IN_PROGRESS = 'in_progress'
BOOK_PUBLISHING_STATUS_CANCELLED = 'cancelled'
BOOK_PUBLISHING_STATUS_REJECTED = 'rejected'
BOOK_PUBLISHING_STATUS_CHOICES = (
    (BOOK_PUBLISHING_STATUS_PUBLISHED, "Published"),
    (BOOK_PUBLISHING_STATUS_NOT_PUBLISHED, "Not published"),
    (BOOK_PUBLISHING_STATUS_IN_PROGRESS, "In progress"),
```

(continues on next page)

(continued from previous page)

```
    (BOOK_PUBLISHING_STATUS_CANCELLED, "Cancelled"),
    (BOOK_PUBLISHING_STATUS_REJECTED, "Rejected"),
)
BOOK_PUBLISHING_STATUS_DEFAULT = BOOK_PUBLISHING_STATUS_PUBLISHED
```

12.3.2.1.3 Publisher model

books/models/book.py

```
@python_2_unicode_compatible
class Publisher(models.Model):
    """Publisher."""

    name = models.CharField(max_length=30)
    address = models.CharField(max_length=50)
    city = models.CharField(max_length=60)
    state_province = models.CharField(max_length=30)
    country = models.CharField(max_length=50)
    website = models.URLField()
    latitude = models.DecimalField(null=True,
                                   blank=True,
                                   decimal_places=15,
                                   max_digits=19,
                                   default=0)
    longitude = models.DecimalField(null=True,
                                    blank=True,
                                    decimal_places=15,
                                    max_digits=19,
                                    default=0)

    class Meta(object):
        """Meta options."""

        ordering = ["id"]

    def __str__(self):
        return self.name

    @property
    def location_field_indexing(self):
        """Location for indexing.

        Used in Elasticsearch indexing/tests of `geo_distance` native filter.
        """
        return {
            'lat': self.latitude,
            'lon': self.longitude,
        }
```

12.3.2.1.4 Author model

books/models/author.py

```
@python_2_unicode_compatible
class Author(models.Model):
    """Author."""

    salutation = models.CharField(max_length=10)
    name = models.CharField(max_length=200)
    email = models.EmailField()
    headshot = models.ImageField(upload_to='authors', null=True, blank=True)

    class Meta(object):
        """Meta options."""

        ordering = ["id"]

    def __str__(self):
        return self.name
```

12.3.2.1.5 Tag model

books/models/tag.py

```
class Tag(models.Model):
    """Simple tag model."""

    title = models.CharField(max_length=255, unique=True)

    class Meta(object):
        """Meta options."""

        verbose_name = _("Tag")
        verbose_name_plural = _("Tags")

    def __str__(self):
        return self.title
```

12.3.2.1.6 Book model

books/models/book.py

```
@python_2_unicode_compatible
class Book(models.Model):
    """Book."""

    title = models.CharField(max_length=100)
    description = models.TextField(null=True, blank=True)
    summary = models.TextField(null=True, blank=True)
    authors = models.ManyToManyField('books.Author', related_name='books')
    publisher = models.ForeignKey(Publisher, related_name='books')
    publication_date = models.DateField()
    state = models.CharField(max_length=100,
                             choices=BOOK_PUBLISHING_STATUS_CHOICES,
                             default=BOOK_PUBLISHING_STATUS_DEFAULT)
    isbn = models.CharField(max_length=100, unique=True)
    price = models.DecimalField(max_digits=10, decimal_places=2)
```

(continues on next page)

(continued from previous page)

```
    pages = models.PositiveIntegerField(default=200)
    stock_count = models.PositiveIntegerField(default=30)
    tags = models.ManyToManyField('books.Tag',
                                  related_name='books',
                                  blank=True)

    class Meta(object):
        """Meta options."""

        ordering = ["isbn"]

    def __str__(self):
        return self.title

    # The only publisher information we're going to need in our document
    # is the publisher name. Since publisher isn't a required field,
    # we define a properly on a model level to avoid indexing errors on
    # non-existing relation.
    @property
    def publisher_indexing(self):
        """Publisher for indexing.

        Used in Elasticsearch indexing.
        """
        if self.publisher is not None:
            return self.publisher.name

    # As of tags, again, we only need a flat list of tag names, on which
    # we can filter. Therefore, we define a properly on a model level,
    # which will return a JSON dumped list of tags relevant to the
    # current book model object.
    @property
    def tags_indexing(self):
        """Tags for indexing.

        Used in Elasticsearch indexing.
        """
        return [tag.title for tag in self.tags.all()]
```

12.3.2.2 Admin classes

This is just trivial. A couple of correspondent admin classes in order to ba able to fill some data.

books/admin.py

```
from django.contrib import admin

from .models import *


@admin.register(Book)
class BookAdmin(admin.ModelAdmin):
    """Book admin."""

    list_display = ('title', 'isbn', 'price', 'publication_date')
```

(continues on next page)

(continued from previous page)

```
    search_fields = ('title',)
    filter_horizontal = ('authors', 'tags',)


@admin.register(Author)
class AuthorAdmin(admin.ModelAdmin):
    """Author admin."""

    list_display = ('name', 'email',)
    search_fields = ('name',)


@admin.register(Publisher)
class PublisherAdmin(admin.ModelAdmin):
    """Publisher admin."""

    list_display = ('name',)
    search_fields = ('name',)


@admin.register(Tag)
class TagAdmin(admin.ModelAdmin):
    """Tag admin."""

    list_display = ('title',)
    search_fields = ('title',)
```

12.3.2.3 Create database tables

For now, just run the migrations to create the database tables.

```
./manage.py makemigrations books
./manage.py migrate books
```

12.3.2.4 Fill in some data

If you have followed the instructions, you should now be able to log into the Django admin and create a dozen of Book/Author/Publisher/Tag records in admin.

```
http://localhost:8000/admin/books/publisher/
http://localhost:8000/admin/books/author/
http://localhost:8000/admin/books/tag/
http://localhost:8000/admin/books/book/
```

Once you've done that, proceed to the next step.

12.3.2.5 Sample document

In Elasticsearch, a document is a basic unit of information that can be indexed. For example, you can have a document for a single customer, another document for a single product, and yet another for a single order. This document is expressed in JSON (JavaScript Object Notation) which is an ubiquitous internet data interchange format.

Within an index/type, you can store as many documents as you want. Note that although a document physically resides in an index, a document actually must be indexed/assigned to a type inside an index.

Simply said, you could see an Elasticsearch index as a database and a document as a database table (which makes a Document definition in Elasticsearch DSL similar to a Django Model definition).

Often, complex SQL model structures are flatterned in Elasticsearch indexes/documents. Nested relations are denormalized.

In our example, all 4 models (`Author`, `Publisher`, `Tag`, `Book`) would be flatterned into a single `BookDocument`, which would hold all the required information.

Content of the `search_indexes/documents/book.py` file. Additionally, see the code comments.

12.3.2.5.1 Required imports

search_indexes/documents/book.py

```
from django.conf import settings
from django_elasticsearch_dsl import Document, Index, fields
from elasticsearch_dsl import analyzer

from books.models import Book
```

12.3.2.5.2 Index definition

To separate dev/test/staging/production indexes, the following approach is recommended.

12.3.2.5.2.1 Settings

Note: In the examples below the `search_indexes.documents.book` and `search_indexes.documents.publisher` are the pythonic file paths to modules where documents are defined.

settings/base.py

Note: In this example, `book` and `publisher` are Elasticsearch index names.

```
# Name of the Elasticsearch index
ELASTICSEARCH_INDEX_NAMES = {
    'search_indexes.documents.book': 'book',
    'search_indexes.documents.publisher': 'publisher',
}
```

settings/testing.py

Note: In this example, `test_book` and `test_publisher` are Elasticsearch index names.

```
# Name of the Elasticsearch index
ELASTICSEARCH_INDEX_NAMES = {
    'search_indexes.documents.book': 'test_book',
    'search_indexes.documents.publisher': 'test_publisher',
}
```

settings/production.py

```
# Name of the Elasticsearch index
ELASTICSEARCH_INDEX_NAMES = {
    'search_indexes.documents.book': 'prod_book',
    'search_indexes.documents.publisher': 'prod_publisher',
}
```

12.3.2.5.2.2 Document index

search_indexes/documents/book.py

```
# Name of the Elasticsearch index
INDEX = Index(settings.ELASTICSEARCH_INDEX_NAMES[__name__])

# See Elasticsearch Indices API reference for available settings
INDEX.settings(
    number_of_shards=1,
    number_of_replicas=1
)
```

12.3.2.5.3 Custom analyzers

```
html_strip = analyzer(
    'html_strip',
    tokenizer="standard",
    filter=["standard", "lowercase", "stop", "snowball"],
    char_filter=["html_strip"]
)
```

12.3.2.5.4 Document definition

search_indexes/documents/book.py

```
@INDEX.doc_type
class BookDocument(Document):
    """Book Elasticsearch document."""

    id = fields.IntegerField(attr='id')

    title = fields.StringField(
        analyzer=html_strip,
        fields={
            'raw': fields.StringField(analyzer='keyword'),
        }
```

(continues on next page)

(continued from previous page)

```
    )

    description = fields.StringField(
        analyzer=html_strip,
        fields={
            'raw': fields.StringField(analyzer='keyword'),
        }
    )

    summary = fields.StringField(
        analyzer=html_strip,
        fields={
            'raw': fields.StringField(analyzer='keyword'),
        }
    )

    publisher = fields.StringField(
        attr='publisher_indexing',
        analyzer=html_strip,
        fields={
            'raw': fields.StringField(analyzer='keyword'),
        }
    )

    publication_date = fields.DateField()

    state = fields.StringField(
        analyzer=html_strip,
        fields={
            'raw': fields.StringField(analyzer='keyword'),
        }
    )

    isbn = fields.StringField(
        analyzer=html_strip,
        fields={
            'raw': fields.StringField(analyzer='keyword'),
        }
    )

    price = fields.FloatField()

    pages = fields.IntegerField()

    stock_count = fields.IntegerField()

    tags = fields.StringField(
        attr='tags_indexing',
        analyzer=html_strip,
        fields={
            'raw': fields.StringField(analyzer='keyword', multi=True),
            'suggest': fields.CompletionField(multi=True),
        },
        multi=True
    )

    class Django(object):
```

(continues on next page)

(continued from previous page)

```
        """Inner nested class Django."""

        model = Book  # The model associate with this Document
```

12.3.2.6 Syncing Django's database with Elasticsearch indexes

So far, we have a couple of Django models and a single (decentralized) Elasticsearch index/document (Book).

12.3.2.6.1 Full database sync

The excellent `django-elasticsearch-dsl` library makes a good job of keeping the Book index fresh. It makes use of signals, so whenever the Book model is changed, the correspondent BookDocument indexes would be updated.

To simply run the full sync between Django's database and Elasticsearch, do as follows:

(1) Create Elasticsearch indexes:

```
./manage.py search_index --create -f
```

(2) Sync the data:

```
./manage.py search_index --populate -f
```

However, in case if a Tag, Publisher or Author models change, the Book index would not be automatically updated.

12.3.2.6.2 Sample partial sync (using custom signals)

In order to keep indexes fresh, you will have to write a couple of simple lines of code (using Django's signals). Whenever a change is made to any of the Tag, Publisher or Author models, we're going to update the correspondent BookDocument index.

12.3.2.6.2.1 Required imports

search_indexes/signals.py

```
from django.db.models.signals import post_save, post_delete
from django.dispatch import receiver

from django_elasticsearch_dsl.registries import registry
```

12.3.2.6.2.2 Update book index on related model change

search_indexes/signals.py

```
@receiver(post_save)
def update_document(sender, **kwargs):
    """Update document on added/changed records.

    Update Book document index if related `books.Publisher` (`publisher`),
```

(continues on next page)

(continued from previous page)

```
    `books.Author` (`authors`), `books.Tag` (`tags`) fields have been updated
    in the database.
    """
    app_label = sender._meta.app_label
    model_name = sender._meta.model_name
    instance = kwargs['instance']

    if app_label == 'book':
        # If it is `books.Publisher` that is being updated.
        if model_name == 'publisher':
            instances = instance.books.all()
            for _instance in instances:
                registry.update(_instance)

        # If it is `books.Author` that is being updated.
        if model_name == 'author':
            instances = instance.books.all()
            for _instance in instances:
                registry.update(_instance)

        # If it is `books.Tag` that is being updated.
        if model_name == 'tag':
            instances = instance.books.all()
            for _instance in instances:
                registry.update(_instance)
```

12.3.2.6.2.3 Update book index on related model removal

search_indexes/signals.py

```
@receiver(post_delete)
def delete_document(sender, **kwargs):
    """Update document on deleted records.

    Updates Book document from index if related `books.Publisher`
    (`publisher`), `books.Author` (`authors`), `books.Tag` (`tags`) fields
    have been removed from database.
    """
    app_label = sender._meta.app_label
    model_name = sender._meta.model_name
    instance = kwargs['instance']

    if app_label == 'books':
        # If it is `books.Publisher` that is being updated.
        if model_name == 'publisher':
            instances = instance.books.all()
            for _instance in instances:
                registry.update(_instance)
                # registry.delete(_instance, raise_on_error=False)

        # If it is `books.Author` that is being updated.
        if model_name == 'author':
            instances = instance.books.all()
            for _instance in instances:
                registry.update(_instance)
```

(continues on next page)

(continued from previous page)

```
                # registry.delete(_instance, raise_on_error=False)

        # If it is `books.Tag` that is being updated.
        if model_name == 'tag':
            instances = instance.books.all()
            for _instance in instances:
                registry.update(_instance)
                # registry.delete(_instance, raise_on_error=False)
```

12.3.2.7 Sample serializer

At this step we're going to define a serializer to be used in the Django REST framework ViewSet.

Content of the `search_indexes/serializers.py` file. Additionally, see the code comments.

12.3.2.7.1 Required imports

search_indexes/serializers/book.py

```
import json

from rest_framework import serializers
from django_elasticsearch_dsl_drf.serializers import DocumentSerializer

from .documents import BookDocument
```

12.3.2.7.2 Serializer definition

Simplest way to create a serializer, is to just specify which fields are needed to be serialized and leave it further to the dynamic serializer.

search_indexes/serializers/book.py

```
class BookDocumentSerializer(DocumentSerializer):
    """Serializer for the Book document."""

    class Meta(object):
        """Meta options."""

        # Specify the correspondent document class
        document = BookDocument

        # List the serializer fields. Note, that the order of the fields
        # is preserved in the ViewSet.
        fields = (
            'id',
            'title',
            'description',
            'summary',
            'publisher',
            'publication_date',
            'state',
```

(continues on next page)

(continued from previous page)

```
            'isbn',
            'price',
            'pages',
            'stock_count',
            'tags',
        )
```

However, if dynamic serializer doesn't work for your or you want to customize too many things, you are free to use standard `Serializer` class of the Django REST framework.

search_indexes/serializers/book.py

```
class BookDocumentSerializer(serializers.Serializer):
    """Serializer for the Book document."""

    id = serializers.IntegerField(read_only=True)

    title = serializers.CharField(read_only=True)
    description = serializers.CharField(read_only=True)
    summary = serializers.CharField(read_only=True)

    publisher = serializers.CharField(read_only=True)
    publication_date = serializers.DateField(read_only=True)
    state = serializers.CharField(read_only=True)
    isbn = serializers.CharField(read_only=True)
    price = serializers.FloatField(read_only=True)
    pages = serializers.IntegerField(read_only=True)
    stock_count = serializers.IntegerField(read_only=True)
    tags = serializers.SerializerMethodField()

    class Meta(object):
        """Meta options."""

        # List the serializer fields. Note, that the order of the fields
        # is preserved in the ViewSet.
        fields = (
            'id',
            'title',
            'description',
            'summary',
            'publisher',
            'publication_date',
            'state',
            'isbn',
            'price',
            'pages',
            'stock_count',
            'tags',
        )

    def get_tags(self, obj):
        """Get tags."""
        if obj.tags:
            return list(obj.tags)
        else:
            return []
```

12.3.2.8 ViewSet definition

At this step, we're going to define Django REST framework ViewSets.

Content of the `search_indexes/viewsets.py` file. Additionally, see the code comments.

12.3.2.8.1 Required imports

search_indexes/viewsets/book.py

```
from django_elasticsearch_dsl_drf.constants import (
    LOOKUP_FILTER_TERMS,
    LOOKUP_FILTER_RANGE,
    LOOKUP_FILTER_PREFIX,
    LOOKUP_FILTER_WILDCARD,
    LOOKUP_QUERY_IN,
    LOOKUP_QUERY_GT,
    LOOKUP_QUERY_GTE,
    LOOKUP_QUERY_LT,
    LOOKUP_QUERY_LTE,
    LOOKUP_QUERY_EXCLUDE,
)
from django_elasticsearch_dsl_drf.filter_backends import (
    FilteringFilterBackend,
    IdsFilterBackend,
    OrderingFilterBackend,
    DefaultOrderingFilterBackend,
    SearchFilterBackend,
)
from django_elasticsearch_dsl_drf.viewsets import BaseDocumentViewSet
from django_elasticsearch_dsl_drf.pagination import PageNumberPagination

from .documents import BookDocument, PublisherDocument
from .serializers import BookDocumentSerializer
```

12.3.2.8.2 ViewSet definition

search_indexes/viewsets/book.py

```
class BookDocumentView(BaseDocumentViewSet):
    """The BookDocument view."""

    document = BookDocument
    serializer_class = BookDocumentSerializer
    pagination_class = PageNumberPagination
    lookup_field = 'id'
    filter_backends = [
        FilteringFilterBackend,
        IdsFilterBackend,
        OrderingFilterBackend,
        DefaultOrderingFilterBackend,
        SearchFilterBackend,
    ]
    # Define search fields
    search_fields = (
```

(continues on next page)

(continued from previous page)

```
        'title',
        'description',
        'summary',
    )
    # Define filter fields
    filter_fields = {
        'id': {
            'field': 'id',
            # Note, that we limit the lookups of id field in this example,
            # to `range`, `in`, `gt`, `gte`, `lt` and `lte` filters.
            'lookups': [
                LOOKUP_FILTER_RANGE,
                LOOKUP_QUERY_IN,
                LOOKUP_QUERY_GT,
                LOOKUP_QUERY_GTE,
                LOOKUP_QUERY_LT,
                LOOKUP_QUERY_LTE,
            ],
        },
        'title': 'title.raw',
        'publisher': 'publisher.raw',
        'publication_date': 'publication_date',
        'state': 'state.raw',
        'isbn': 'isbn.raw',
        'price': {
            'field': 'price.raw',
            # Note, that we limit the lookups of `price` field in this
            # example, to `range`, `gt`, `gte`, `lt` and `lte` filters.
            'lookups': [
                LOOKUP_FILTER_RANGE,
                LOOKUP_QUERY_GT,
                LOOKUP_QUERY_GTE,
                LOOKUP_QUERY_LT,
                LOOKUP_QUERY_LTE,
            ],
        },
        'pages': {
            'field': 'pages',
            # Note, that we limit the lookups of `pages` field in this
            # example, to `range`, `gt`, `gte`, `lt` and `lte` filters.
            'lookups': [
                LOOKUP_FILTER_RANGE,
                LOOKUP_QUERY_GT,
                LOOKUP_QUERY_GTE,
                LOOKUP_QUERY_LT,
                LOOKUP_QUERY_LTE,
            ],
        },
        'stock_count': {
            'field': 'stock_count',
            # Note, that we limit the lookups of `stock_count` field in
            # this example, to `range`, `gt`, `gte`, `lt` and `lte`
            # filters.
            'lookups': [
                LOOKUP_FILTER_RANGE,
                LOOKUP_QUERY_GT,
                LOOKUP_QUERY_GTE,
```

(continues on next page)

(continued from previous page)

```
                LOOKUP_QUERY_LT,
                LOOKUP_QUERY_LTE,
            ],
        },
        'tags': {
            'field': 'tags',
            # Note, that we limit the lookups of `tags` field in
            # this example, to `terms, `prefix`, `wildcard`, `in` and
            # `exclude` filters.
            'lookups': [
                LOOKUP_FILTER_TERMS,
                LOOKUP_FILTER_PREFIX,
                LOOKUP_FILTER_WILDCARD,
                LOOKUP_QUERY_IN,
                LOOKUP_QUERY_EXCLUDE,
            ],
        },
        'tags.raw': {
            'field': 'tags.raw',
            # Note, that we limit the lookups of `tags.raw` field in
            # this example, to `terms, `prefix`, `wildcard`, `in` and
            # `exclude` filters.
            'lookups': [
                LOOKUP_FILTER_TERMS,
                LOOKUP_FILTER_PREFIX,
                LOOKUP_FILTER_WILDCARD,
                LOOKUP_QUERY_IN,
                LOOKUP_QUERY_EXCLUDE,
            ],
        },
    }
    # Define ordering fields
    ordering_fields = {
        'id': 'id',
        'title': 'title.raw',
        'price': 'price.raw',
        'state': 'state.raw',
        'publication_date': 'publication_date',
    }
    # Specify default ordering
    ordering = ('id', 'title', 'price',)
```

12.3.2.9 URLs

At this step, we're going to define url patterns.

Content of the `search_indexes/urls.py` file. Additionally, see the code comments.

12.3.2.9.1 Required imports

search_indexes/urls.py

```
from django.conf.urls import url, include
from rest_framework.routers import DefaultRouter
```

(continues on next page)

(continued from previous page)

```
from .views import BookDocumentView
```

12.3.2.9.2 Router definition

search_indexes/urls.py

```
router = DefaultRouter()
books = router.register(r'books',
                        BookDocumentView,
                        basename='bookdocument')
```

12.3.2.9.3 URL patterns

search_indexes/urls.py

```
urlpatterns = [
    url(r'^', include(router.urls)),
]
```

12.3.2.10 Check what you've done so far

At this point, you are one step away from a working example of integrating Elasticsearch DSL with Django.

12.3.2.10.1 URLs

If you didn't add the urls of the `search_indexes` example application to your project's global url patterns, make sure to do it now.

```
from django.conf.urls import include, url
from search_indexes import urls as search_index_urls

urlpatterns = [
    # ...
    # Search URLs
    url(r'^search/', include(search_index_urls)),
    # ...
]
```

12.3.2.10.2 Test in browser

Open the following URL in your browser.

```
http://localhost:8000/search/books/
```

Perform a number of lookups:

```
http://localhost:8001/search/books/?ids=54|55|56
http://localhost:8001/search/books/?summary__contains=photography
http://localhost:8001/search/books/?tags__contains=ython
http://localhost:8001/search/books/?state=published
http://localhost:8001/search/books/?pages__gt=10&pages__lt=30
```

12.3.3 Development and debugging

12.3.3.1 Profiling tools

Looking for profiling tools for Elasticsearch?

Try django-elasticsearch-debug-toolbar package. It's implemented as a panel for the well known Django Debug Toolbar and gives you full insights on what's happening on the side of Elasticsearch.

12.3.3.1.1 Installation

```
pip install django-debug-toolbar
pip install django-elasticsearch-debug-toolbar
```

12.3.3.1.2 Configuration

Change your development settings in the following way:

settings/dev.py

```
MIDDLEWARE += (
    'debug_toolbar.middleware.DebugToolbarMiddleware',
    'debug_toolbar_force.middleware.ForceDebugToolbarMiddleware',
)

INSTALLED_APPS += (
    'debug_toolbar',
    'elastic_panel',
)

DEBUG_TOOLBAR_CONFIG = {
    'INTERCEPT_REDIRECTS': False,
}

DEBUG_TOOLBAR_PANELS = (
    # Defaults
    'debug_toolbar.panels.versions.VersionsPanel',
    'debug_toolbar.panels.timer.TimerPanel',
    'debug_toolbar.panels.settings.SettingsPanel',
    'debug_toolbar.panels.headers.HeadersPanel',
    'debug_toolbar.panels.request.RequestPanel',
    'debug_toolbar.panels.sql.SQLPanel',
    'debug_toolbar.panels.staticfiles.StaticFilesPanel',
    'debug_toolbar.panels.templates.TemplatesPanel',
    'debug_toolbar.panels.cache.CachePanel',
    'debug_toolbar.panels.signals.SignalsPanel',
```

(continues on next page)

(continued from previous page)

```
    'debug_toolbar.panels.logging.LoggingPanel',
    'debug_toolbar.panels.redirects.RedirectsPanel',
    # Additional
    'elastic_panel.panel.ElasticDebugPanel',
)
```

12.3.3.2 Debugging

Although (the unbeatable) Kibana is strongly recommended for data analyses, there are other good tools worth mentioning. One of them is elasticsearch-head Elasticsearch 2.x plugin or a correspondent Chrome extension of the same plugin. You may find it very useful for quick data preview or testing Elasticsearch queries.

12.4 Filter usage examples

Example usage of filtering backends.

Contents:

Table of Contents

- *Filter usage examples*
  - *Search*
    - *Search in all fields*
    - *Search a single term on specific field*
    - *Search for multiple terms*
    - *Search for multiple terms in specific fields*
  - *Filtering*
    - *Supported lookups*
      - *Native*
      - *term*
      - *terms*
      - *range*
      - *exists*
      - *prefix*
      - *wildcard*
      - *ids*
      - *Functional*
      - *contains*
      - *in*
      - *gt*

- *gte*
- *lt*
- *lte*
- *startswith*
- *endswith*
- *isnull*
- *exclude*

– *Usage examples*

12.4.1 Search

Query param name reserved for search is `search`. Make sure your models and documents do not have it as a field or attribute.

Multiple search terms are joined with `OR`.

Let's assume we have a number of Book items with fields `title`, `description` and `summary`.

12.4.1.1 Search in all fields

Search in all fields (`name`, `address`, `city`, `state_province` and `country`) for word "reilly".

```
http://127.0.0.1:8080/search/publisher/?search=reilly
```

12.4.1.2 Search a single term on specific field

In order to search in specific field (`name`) for term "reilly", add the field name separated with `:` to the search term.

```
http://127.0.0.1:8080/search/publisher/?search=name:reilly
```

12.4.1.3 Search for multiple terms

In order to search for multiple terms "reilly", "bloomsbury" add multiple `search` query params.

```
http://127.0.0.1:8080/search/publisher/?search=reilly&search=bloomsbury
```

12.4.1.4 Search for multiple terms in specific fields

In order to search for multiple terms "reilly", "bloomsbury" in specific fields add multiple `search` query params and field names separated with `:` to each of the search terms.

```
http://127.0.0.1:8080/search/publisher/?search=name:reilly&search=city:london
```

12.4.2 Filtering

12.4.2.1 Supported lookups

12.4.2.1.1 Native

The following native (to Elasticsearch) filters/lookups are implemented:

- *term*
- *terms*
- *range*
- *exists*
- *prefix*
- *wildcard*
- *regexp*
- *fuzzy*
- *type*
- *ids*

12.4.2.1.1.1 term

Find documents which contain the exact term specified in the field specified.

```
http://127.0.0.1:8080/search/books/?tags__term=education&tags__term=economy
```

12.4.2.1.1.2 terms

Find documents which contain any of the exact terms specified in the field specified. Note, that multiple values are separated with double underscores __.

```
http://localhost:8000/api/articles/?id=1&id=2&id=3
http://localhost:8000/api/articles/?id__terms=1__2__3
```

12.4.2.1.1.3 range

Find documents where the field specified contains values (dates, numbers, or strings) in the range specified.

From, to

```
http://localhost:8000/api/users/?age__range=16__67
```

From, to, boost

```
http://localhost:8000/api/users/?age__range=16__67__2.0
```

12.4.2.1.1.4 exists

Find documents where the field specified contains any non-null value.

```
http://localhost:8000/api/articles/?tags__exists=true
```

12.4.2.1.1.5 prefix

Find documents where the field specified contains terms which begin with the exact prefix specified.

```
http://localhost:8000/api/articles/?tags__prefix=bio
```

12.4.2.1.1.6 wildcard

Find documents where the field specified contains terms which match the pattern specified, where the pattern supports single character wildcards (?) and multi-character wildcards (*)

```
http://localhost:8000/api/articles/?title__wildcard=*elusional*
```

Should match: *delusional insanity*.

12.4.2.1.1.7 ids

Find documents with the specified type and IDs.

```
http://localhost:8000/api/articles/?ids=68__64__58
http://localhost:8000/api/articles/?ids=68&ids=64&ids=58
```

12.4.2.1.2 Functional

The following functional (non-native to Elasticsearch, but common in Django) filters/lookups are implemented:

- *contains*
- *in*
- *gt*
- *gte*
- *lt*
- *lte*
- *startswith*
- *endswith*
- *isnull*
- *exclude*

12.4.2.1.2.1 contains

Case-insensitive containment test.

```
http://localhost:8000/api/articles/?state__contains=lishe
```

Should match: *published*, *not published*, *needs polishing*.

12.4.2.1.2.2 in

In a given list.

```
http://localhost:8000/api/articles/?id__in=1__2__3
```

12.4.2.1.2.3 gt

Greater than.

```
http://localhost:8000/api/users/?id__gt=10
```

12.4.2.1.2.4 gte

Greater than or equal to.

```
http://localhost:8000/api/users/?id__gte=10
```

12.4.2.1.2.5 lt

Less than.

```
http://localhost:8000/api/users/?id__lt=10
```

12.4.2.1.2.6 lte

Less than or equal to.

```
http://localhost:8000/api/users/?id__lte=10
```

12.4.2.1.2.7 startswith

Case-sensitive starts-with.

http://localhost:8000/api/articles/?tags__startswith=bio

Should match: *biography*, *bio mechanics*

12.4.2.1.2.8 endswith

Case-sensitive ends-with.

```
http://localhost:8000/api/articles/?state__endswith=lished
```

Should match: *published*, *not published*.

12.4.2.1.2.9 isnull

Takes either True or False.

True

```
http://localhost:8000/api/articles/?null_field__isnull=true
```

False

```
http://localhost:8000/api/articles/?tags__isnull=false
```

12.4.2.1.2.10 exclude

Returns a new query set of containing objects that do not match the given lookup parameters.

```
http://localhost:8000/api/articles/?tags__exclude=children
http://localhost:8000/api/articles/?tags__exclude=children__python
```

12.4.3 Usage examples

See the example project for sample models/views/serializers.

- models
- documents
- serializers
- views

Additionally, see:

- Basic usage examples
- Advanced usage examples
- Misc usage examples

12.5 Search backends

12.5.1 Compound search filter backend

Compound search filter backend aims to replace old style *SearchFilterBackend*.

12.5.1.1 Sample view

```
from django_elasticsearch_dsl_drf.filter_backends import (
    DefaultOrderingFilterBackend,
    CompoundSearchFilterBackend,
    OrderingFilterBackend,
)
from django_elasticsearch_dsl_drf.viewsets import DocumentViewSet

from .documents import BookDocument
from .serializers import BookDocumentSerializer

class BookCompoundSearchBackendDocumentViewSet(DocumentViewSet):

    document = BookDocument
    serializer_class = BookDocumentSerializer
    lookup_field = 'id'

    filter_backends = [
        # ...
        OrderingFilterBackend,
        DefaultOrderingFilterBackend,
        CompoundSearchFilterBackend,
        # ...
    ]

    multi_match_search_fields = (
        'title',
        'description',
        'summary',
    )

    ordering = ('_score', 'id', 'title', 'price',)
```

12.5.1.2 Sample request

```
http://localhost:8000/search/books-compound-search-backend/?search=enim
```

12.5.1.3 Generated query

```
{
  "from": 0,
  "sort": [
    "id",
    "title",
    "price"
  ],
  "size": 23,
  "query": {
    "bool": {
      "should": [
        {
          "match": {
            "title": {
```

(continues on next page)

(continued from previous page)

```
                "query": "enim"
              }
            }
          },
          {
            "match": {
              "description": {
                "query": "enim"
              }
            }
          },
          {
            "match": {
              "summary": {
                "query": "enim"
              }
            }
          }
        ]
      }
    }
}
```

12.5.2 Multi match search filter backend

Document and serializer definition are trivial (there are lots of examples in other sections).

12.5.2.1 Sample view

```
from django_elasticsearch_dsl_drf.filter_backends import (
    DefaultOrderingFilterBackend,
    MultiMatchSearchFilterBackend,
    OrderingFilterBackend,
)
from django_elasticsearch_dsl_drf.viewsets import DocumentViewSet

from .documents import BookDocument
from .serializers import BookDocumentSerializer


class BookMultiMatchSearchFilterBackendDocumentViewSet(DocumentViewSet):

    document = BookDocument
    serializer_class = BookDocumentSerializer
    lookup_field = 'id'

    filter_backends = [
        # ...
        OrderingFilterBackend,
        DefaultOrderingFilterBackend,
        MultiMatchSearchFilterBackend,
        # ...
    ]
```

(continues on next page)

(continued from previous page)

```
    multi_match_search_fields = {
        'title': {'boost': 4},
        'summary': {'boost': 2},
        'description': None,
    }

    ordering = ('_score', 'id', 'title', 'price',)
```

12.5.2.2 Sample request

Note: Multiple search params (*search_multi_match*) are not supported. Even if you provide multiple search params, the first one would be picked, having the rest simply ignored.

```
http://localhost:8000/search/books-multi-match-search-backend/?search_multi_
↪match=debitis%20enim
```

12.5.2.3 Generated query

```
{
  "from": 0,
  "query": {
    "multi_match": {
      "query": "debitis enim",
      "fields": [
        "summary^2",
        "description",
        "title^4"
      ]
    }
  },
  "size": 38,
  "sort": [
    "_score",
    "id",
    "title",
    "price"
  ]
}
```

12.5.2.4 Options

All standard multi match query options are available/tunable with help of `multi_match_options` view property.

Selective list of available options:

- operator
- type
- analyzer

- tie_breaker

12.5.2.4.1 Type options

See the Elasticsearch docs for detailed explanation.

- best_fields
- most_fields
- cross_fields
- phrase
- phrase_prefix

Example

```
class BookMultiMatchSearchFilterBackendDocumentViewSet(DocumentViewSet):

    # ...

    multi_match_options = {
        'type': 'phrase'
    }
```

12.5.2.4.2 Operator options

Can be either `and` or `or`.

12.5.3 Simple query string filter backend

Document and serializer definition are trivial (there are lots of examples in other sections).

12.5.3.1 Sample view

```
from django_elasticsearch_dsl_drf.filter_backends import (
    DefaultOrderingFilterBackend,
    SimpleQueryStringSearchFilterBackend,
    OrderingFilterBackend,
)
from django_elasticsearch_dsl_drf.viewsets import DocumentViewSet

from .documents import BookDocument
from .serializers import BookDocumentSerializer


class BookSimpleQueryStringSearchFilterBackendDocumentViewSet(DocumentViewSet):

    document = BookDocument
    serializer_class = BookDocumentSerializer
    lookup_field = 'id'

    filter_backends = [
```

(continues on next page)

(continued from previous page)

```
        # ...
        OrderingFilterBackend,
        DefaultOrderingFilterBackend,
        SimpleQueryStringSearchFilterBackend,
        # ...
    ]

    simple_query_string_search_fields = {
        'title': {'boost': 4},
        'summary': {'boost': 2},
        'description': None,
    }

    ordering = ('_score', 'id', 'title', 'price',)
```

12.5.3.2 Sample request 1

Note: Multiple search params (*search_simple_query_string*) are not supported. Even if you provide multiple search params, the first one would be picked, having the rest simply ignored.

```
http://localhost:8000/search/books-simple-query-string-search-backend/?search_simple_
↪query_string="chapter%20II"%20%2Bfender
```

12.5.3.3 Generated query 1

```
{
  "query": {
    "simple_query_string": {
      "query": "\"chapter II\" +fender",
      "default_operator": "and",
      "fields": [
        "title",
        "description",
        "summary"
      ]
    }
  },
  "sort": [
    "_score",
    "id",
    "title",
    "price"
  ],
  "from": 0,
  "size": 1
}
```

12.5.3.4 Sample request 2

Note: Multiple search params (*search_simple_query_string*) are not supported. Even if you provide multiple search params, the first one would be picked, having the rest simply ignored.

```
http://localhost:8000/search/books-simple-query-string-search-backend/?search_simple_
↪query_string="chapter%20II"%20%2B(shutting%20|%20fender)
```

12.5.3.5 Generated query 2

```
{
  "query": {
    "simple_query_string": {
      "query": "\"chapter II\" +(shutting | fender)",
      "default_operator": "and",
      "fields": [
        "title",
        "description",
        "summary"
      ]
    }
  },
  "sort": [
    "_score",
    "id",
    "title",
    "price"
  ],
  "from": 0,
  "size": 2
}
```

12.5.3.6 Sample request 3

Note: Multiple search params (*search_simple_query_string*) are not supported. Even if you provide multiple search params, the first one would be picked, having the rest simply ignored.

```
http://localhost:8000/search/books-simple-query-string-search-backend/?search_simple_
↪query_string=%22Pool%20of%20Tears%22%20-considering
```

12.5.3.7 Generated query 3

```
{
  "query": {
    "simple_query_string": {
      "query": "\"Pool of Tears\" -considering",
      "default_operator": "and",
      "fields": [
        "title",
        "description",
```

(continues on next page)

(continued from previous page)

```
        "summary"
      ]
    }
  },
  "sort": [
    "_score",
    "id",
    "title",
    "price"
  ],
  "from": 0,
  "size": 1
}
```

12.5.3.8 Options

All standard multi match query options are available/tunable with help of `simple_query_string_options` view property.

Selective list of available options:

- default_operator

12.5.3.8.1 Default Operator options

Can be either `and` or `or`.

Example

```
class BookSimpleQueryStringSearchFilterBackendDocumentViewSet(DocumentViewSet):

    # ...

    simple_query_string_options = {
        "default_operator": "and",
    }
```

12.6 Basic usage examples

Basic Django REST framework integration example

See the example project for sample models/views/serializers.

- models
- documents
- serializers
- views

Contents:

Table of Contents

- *Basic usage examples*
  - *Example app*
    - *Sample models*
    - *Sample document*
    - *Sample serializer*
    - *Sample view*
    - *Usage example*
      - *Sample queries*
      - *Search*
      - *Filtering*
      - *Ordering*

12.6.1 Example app

12.6.1.1 Sample models

books/models/publisher.py

```
class Publisher(models.Model):
    """Publisher."""

    name = models.CharField(max_length=30)
    address = models.CharField(max_length=50)
    city = models.CharField(max_length=60)
    state_province = models.CharField(max_length=30)
    country = models.CharField(max_length=50)
    website = models.URLField()
    latitude = models.DecimalField(null=True,
                                   blank=True,
                                   decimal_places=15,
                                   max_digits=19,
                                   default=0)
    longitude = models.DecimalField(null=True,
                                    blank=True,
                                    decimal_places=15,
                                    max_digits=19,
                                    default=0)

    class Meta(object):
        """Meta options."""

        ordering = ["id"]

    def __str__(self):
        return self.name

    @property
```

(continues on next page)

(continued from previous page)

```
    def location_field_indexing(self):
        """Location for indexing.

        Used in Elasticsearch indexing/tests of `geo_distance` native filter.
        """
        return {
            'lat': self.latitude,
            'lon': self.longitude,
        }
```

12.6.1.2 Sample document

search_indexes/documents/publisher.py

```
from django_elasticsearch_dsl import Document, Index, fields
from elasticsearch_dsl import analyzer

from books.models import Publisher

# Name of the Elasticsearch index
PUBLISHER_INDEX = Index('publisher')
# See Elasticsearch Indices API reference for available settings
PUBLISHER_INDEX.settings(
    number_of_shards=1,
    number_of_replicas=1
)


@PUBLISHER_INDEX.doc_type
class PublisherDocument(Document):
    """Publisher Elasticsearch document."""

    id = fields.IntegerField(attr='id')

    name = fields.StringField(
        fields={
            'raw': fields.StringField(analyzer='keyword'),
        }
    )
    info = fields.StringField(
        fields={
            'raw': fields.StringField(analyzer='keyword'),
        }
    )
    address = fields.StringField(
        fields={
            'raw': fields.StringField(analyzer='keyword'),
        }
    )
    city = fields.StringField(
        fields={
            'raw': fields.StringField(analyzer='keyword'),
        }
    )
    state_province = fields.StringField(
```

(continues on next page)

(continued from previous page)

```
        fields={
            'raw': fields.StringField(analyzer='keyword'),
        }
    )
    country = fields.StringField(
        fields={
            'raw': fields.StringField(analyzer='keyword'),
        }
    )
    website = fields.StringField()

    # Location
    location = fields.GeoPointField(attr='location_field_indexing')

    class Meta(object):
        """Meta options."""

        model = Publisher  # The model associate with this Document
```

12.6.1.3 Sample serializer

search_indexes/serializers/book.py

```
import json

from django_elasticsearch_dsl_drf.serializers import DocumentSerializer

class PublisherDocumentSerializer(DocumentSerializer):
    """Serializer for Publisher document."""

    location = serializers.SerializerMethodField()

    class Meta(object):
        """Meta options."""

        # Note, that since we're using a dynamic serializer,
        # we only have to declare fields that we want to be shown. If
        # somehow, dynamic serializer doesn't work for you, either extend
        # or declare your serializer explicitly.
        fields = (
            'id',
            'name',
            'info',
            'address',
            'city',
            'state_province',
            'country',
            'website',
        )

    def get_location(self, obj):
    """Represent location value."""
    try:
        return obj.location.to_dict()
    except:
```

(continues on next page)

(continued from previous page)

```
        return {}
```

12.6.1.4 Sample view

search_indexes/views/publisher.py

```
from django_elasticsearch_dsl_drf.constants import (
    LOOKUP_FILTER_GEO_DISTANCE,
)
from django_elasticsearch_dsl_drf.filter_backends import (
    FilteringFilterBackend,
    OrderingFilterBackend,
    SearchFilterBackend,
)
from django_elasticsearch_dsl_drf.viewsets import DocumentViewSet

# Example app models
from search_indexes.documents.publisher import PublisherDocument
from search_indxes.serializers import PublisherDocumentSerializer

class PublisherDocumentView(DocumentViewSet):
    """The PublisherDocument view."""

    document = PublisherDocument
    serializer_class = PublisherDocumentSerializer
    lookup_field = 'id'
    filter_backends = [
        FilteringFilterBackend,
        OrderingFilterBackend,
        DefaultOrderingFilterBackend,
        SearchFilterBackend,
    ]
    # Define search fields
    search_fields = (
        'name',
        'info',
        'address',
        'city',
        'state_province',
        'country',
    )
    # Define filtering fields
    filter_fields = {
        'id': None,
        'name': 'name.raw',
        'city': 'city.raw',
        'state_province': 'state_province.raw',
        'country': 'country.raw',
    }
    # Define ordering fields
    ordering_fields = {
        'id': None,
        'name': None,
        'city': None,
        'country': None,
```

(continues on next page)

(continued from previous page)

```
    }
    # Specify default ordering
    ordering = ('id', 'name',)
    # Define geo-spatial filtering fields
    geo_spatial_filter_fields = {
        'location': {
            'lookups': [
                LOOKUP_FILTER_GEO_DISTANCE,
            ],
        },
    }
```

12.6.1.5 Usage example

Considering samples above, you should be able to perform the search, sorting and filtering actions described below.

12.6.1.5.1 Sample queries

12.6.1.5.1.1 Search

Query param name reserved for search is `search`. Make sure your models and documents do not have it as a field or attribute.

Multiple search terms are joined with `OR`.

Let's assume we have a number of Book items with fields `title`, `description` and `summary`.

Search in all fields

Search in all fields (`name`, `address`, `city`, `state_province` and `country`) for word "reilly".

```
http://127.0.0.1:8080/search/publisher/?search=reilly
```

Search a single term on specific field

In order to search in specific field (`name`) for term "reilly", add the field name separated with `:` to the search term.

```
http://127.0.0.1:8080/search/publisher/?search=name:reilly
```

Search for multiple terms

In order to search for multiple terms "reilly", "bloomsbury" add multiple `search` query params.

```
http://127.0.0.1:8080/search/publisher/?search=reilly&search=bloomsbury
```

Search for multiple terms in specific fields

In order to search for multiple terms "reilly", "bloomsbury" in specific fields add multiple `search` query params and field names separated with `:` to each of the search terms.

```
http://127.0.0.1:8080/search/publisher/?search=name:reilly&search=city:london
```

12.6.1.5.1.2 Filtering

Let's assume we have a number of Publisher documents with in cities (Yerevan, Groningen, Amsterdam, London).

Multiple filter terms are joined with `AND`.

Filter documents by single field

Filter documents by field (`city`) "yerevan".

```
http://127.0.0.1:8080/search/publisher/?city=yerevan
```

Filter documents by multiple fields

Filter documents by `city` "Yerevan" and "Groningen".

```
http://127.0.0.1:8080/search/publisher/?city__in=yerevan__groningen
```

Filter document by a single field

Filter documents by (field `country`) "Armenia".

```
http://127.0.0.1:8080/search/publisher/?country=armenia
```

Filter documents by multiple fields

Filter documents by multiple fields (field `city`) "Yerevan" and "Amsterdam" with use of functional `in` query filter.

```
http://127.0.0.1:8080/search/publisher/?city__in=yerevan__amsterdam
```

You can achieve the same effect by specifying multiple filters (`city`) "Yerevan" and "Amsterdam". Note, that in this case multiple filter terms are joined with `OR`.

```
http://127.0.0.1:8080/search/publisher/?city=yerevan&city=amsterdam
```

If you want the same as above, but joined with `AND`, add `__term` to each lookup.

```
http://127.0.0.1:8080/search/publisher/?city__term=education&city__term=economy
```

Filter documents by a word part of a single field

Filter documents by a part word part in single field (`city`) "ondon".

```
http://127.0.0.1:8080/search/publisher/?city__wildcard=*ondon
```

Geo-distance filtering

Filter documents by radius of 100000km from the given location.

```
http://127.0.0.1:8000/search/publishers/?location__geo_distance=100000km__12.04__-63.
↪93
```

12.6.1.5.1.3 Ordering

The − prefix means ordering should be descending.

Order documents by field (ascending)

Filter documents by field `city` (ascending).

```
http://127.0.0.1:8080/search/publisher/?search=country:armenia&ordering=city
```

Order documents by field (descending)

Filter documents by field `country` (descending).

```
http://127.0.0.1:8080/search/publisher/?ordering=-country
```

Order documents by multiple fields

If you want to order by multiple fields, use multiple ordering query params. In the example below, documents would be ordered first by field `country` (descending), then by field `city` (ascending).

```
http://127.0.0.1:8080/search/publisher/?ordering=-country&ordering=city
```

12.7 Advanced usage examples

Advanced Django REST framework integration examples.

See the example project for sample models/views/serializers.

- models
- documents
- serializers
- viewsets

Contents:

Table of Contents

- *Advanced usage examples*
  - *Example app*
    - *Sample models*
    - *Sample document*
      - *Index definition*
      - *Settings*
      - *Document index*
    - *Sample serializer*
    - *Sample view*
    - *Usage example*
      - *Search*
      - *Filtering*
      - *Ordering*
    - *Ids filter*
    - *Faceted search*

- *Post-filter*
  - *Sample view*
  - *Sample queries*
- *Geo-spatial features*
  - *Filtering*
  - *Ordering*
- *Suggestions*
  - *Completion suggesters*
  - *Document definition*
  - *Serializer definition*
  - *ViewSet definition*
  - *Sample requests/responses*
  - *Suggestions on Array/List field*
  - *Sample requests/responses*
  - *Context suggesters*
  - category *context*
  - geo *context*
  - *Term and Phrase suggestions*
  - *Document definition*
  - *ViewSet definition*
  - *Sample requests/responses*
  - *Completion*
  - *Term*
  - *Phrase*
- *Functional suggestions*
  - *Document definition*
  - *ViewSet definition*
- *Highlighting*
- *Pagination*
  - *Page number pagination*
  - *Limit/offset pagination*
  - *Customisations*

12.7.1 Example app

12.7.1.1 Sample models

books/models/publisher.py

```
import json

from django.conf import settings
from django.db import models
from django.utils.translation import ugettext, ugettext_lazy as _

from six import python_2_unicode_compatible

BOOK_PUBLISHING_STATUS_PUBLISHED = 'published'
BOOK_PUBLISHING_STATUS_NOT_PUBLISHED = 'not_published'
BOOK_PUBLISHING_STATUS_IN_PROGRESS = 'in_progress'
BOOK_PUBLISHING_STATUS_CANCELLED = 'cancelled'
BOOK_PUBLISHING_STATUS_REJECTED = 'rejected'
BOOK_PUBLISHING_STATUS_CHOICES = (
    (BOOK_PUBLISHING_STATUS_PUBLISHED, "Published"),
    (BOOK_PUBLISHING_STATUS_NOT_PUBLISHED, "Not published"),
    (BOOK_PUBLISHING_STATUS_IN_PROGRESS, "In progress"),
    (BOOK_PUBLISHING_STATUS_CANCELLED, "Cancelled"),
    (BOOK_PUBLISHING_STATUS_REJECTED, "Rejected"),
)
BOOK_PUBLISHING_STATUS_DEFAULT = BOOK_PUBLISHING_STATUS_PUBLISHED


@python_2_unicode_compatible
class Publisher(models.Model):
    """Publisher."""

    name = models.CharField(max_length=30)
    info = models.TextField(null=True, blank=True)
    address = models.CharField(max_length=50)
    city = models.CharField(max_length=60)
    state_province = models.CharField(max_length=30)
    country = models.CharField(max_length=50)
    website = models.URLField()
    latitude = models.DecimalField(null=True,
                                   blank=True,
                                   decimal_places=15,
                                   max_digits=19,
                                   default=0)
    longitude = models.DecimalField(null=True,
                                    blank=True,
                                    decimal_places=15,
                                    max_digits=19,
                                    default=0)

    class Meta(object):
        """Meta options."""

        ordering = ["id"]

    def __str__(self):
```

(continues on next page)

(continued from previous page)

```
        return self.name

    @property
    def location_field_indexing(self):
        """Location for indexing.

        Used in Elasticsearch indexing/tests of `geo_distance` native filter.
        """
        return {
            'lat': self.latitude,
            'lon': self.longitude,
        }
```

books/models/author.py

```
@python_2_unicode_compatible
class Author(models.Model):
    """Author."""

    salutation = models.CharField(max_length=10)
    name = models.CharField(max_length=200)
    email = models.EmailField()
    headshot = models.ImageField(upload_to='authors', null=True, blank=True)

    class Meta(object):
        """Meta options."""

        ordering = ["id"]

    def __str__(self):
        return self.name
```

books/models/tag.py

```
class Tag(models.Model):
    """Simple tag model."""

    title = models.CharField(max_length=255, unique=True)

    class Meta(object):
        """Meta options."""

        verbose_name = _("Tag")
        verbose_name_plural = _("Tags")

    def __str__(self):
        return self.title
```

books/models/book.py

```
@python_2_unicode_compatible
class Book(models.Model):
    """Book."""

    title = models.CharField(max_length=100)
    description = models.TextField(null=True, blank=True)
    summary = models.TextField(null=True, blank=True)
```

(continues on next page)

(continued from previous page)

```
    authors = models.ManyToManyField('books.Author', related_name='books')
    publisher = models.ForeignKey(Publisher, related_name='books')
    publication_date = models.DateField()
    state = models.CharField(max_length=100,
                             choices=BOOK_PUBLISHING_STATUS_CHOICES,
                             default=BOOK_PUBLISHING_STATUS_DEFAULT)
    isbn = models.CharField(max_length=100, unique=True)
    price = models.DecimalField(max_digits=10, decimal_places=2)
    pages = models.PositiveIntegerField(default=200)
    stock_count = models.PositiveIntegerField(default=30)
    tags = models.ManyToManyField('books.Tag',
                                  related_name='books',
                                  blank=True)

    class Meta(object):
        """Meta options."""

        ordering = ["isbn"]

    def __str__(self):
        return self.title

    @property
    def publisher_indexing(self):
        """Publisher for indexing.

        Used in Elasticsearch indexing.
        """
        if self.publisher is not None:
            return self.publisher.name

    @property
    def tags_indexing(self):
        """Tags for indexing.

        Used in Elasticsearch indexing.
        """
        return [tag.title for tag in self.tags.all()]
```

12.7.1.2 Sample document

12.7.1.2.1 Index definition

To separate dev/test/staging/production indexes, the following approach is recommended.

12.7.1.2.1.1 Settings

settings/base.py

```
# Name of the Elasticsearch index
ELASTICSEARCH_INDEX_NAMES = {
    'search_indexes.documents.book': 'book',
    'search_indexes.documents.publisher': 'publisher',
}
```

settings/testing.py

```
# Name of the Elasticsearch index
ELASTICSEARCH_INDEX_NAMES = {
    'search_indexes.documents.book': 'test_book',
    'search_indexes.documents.publisher': 'test_publisher',
}
```

settings/production.py

```
# Name of the Elasticsearch index
ELASTICSEARCH_INDEX_NAMES = {
    'search_indexes.documents.book': 'prod_book',
    'search_indexes.documents.publisher': 'prod_publisher',
}
```

12.7.1.2.1.2 Document index

search_indexes/documents/book.py

```
from django.conf import settings
from django_elasticsearch_dsl import Document, Index, fields
from elasticsearch_dsl import analyzer

from books.models import Book

# Name of the Elasticsearch index
INDEX = Index(settings.ELASTICSEARCH_INDEX_NAMES[__name__])

# See Elasticsearch Indices API reference for available settings
INDEX.settings(
    number_of_shards=1,
    number_of_replicas=1
)

html_strip = analyzer(
    'html_strip',
    tokenizer="standard",
    filter=["standard", "lowercase", "stop", "snowball"],
    char_filter=["html_strip"]
)


@INDEX.doc_type
class BookDocument(Document):
    """Book Elasticsearch document."""

    id = fields.IntegerField(attr='id')

    title = fields.StringField(
        analyzer=html_strip,
        fields={
            'raw': fields.StringField(analyzer='keyword'),
        }
    )
```

(continues on next page)

(continued from previous page)

```
    description = fields.StringField(
        analyzer=html_strip,
        fields={
            'raw': fields.StringField(analyzer='keyword'),
        }
    )

    summary = fields.StringField(
        analyzer=html_strip,
        fields={
            'raw': fields.StringField(analyzer='keyword'),
        }
    )

    publisher = fields.StringField(
        attr='publisher_indexing',
        analyzer=html_strip,
        fields={
            'raw': fields.StringField(analyzer='keyword'),
        }
    )

    publication_date = fields.DateField()

    state = fields.StringField(
        analyzer=html_strip,
        fields={
            'raw': fields.StringField(analyzer='keyword'),
        }
    )

    isbn = fields.StringField(
        analyzer=html_strip,
        fields={
            'raw': fields.StringField(analyzer='keyword'),
        }
    )

    price = fields.FloatField()

    pages = fields.IntegerField()

    stock_count = fields.IntegerField()

    tags = fields.StringField(
        attr='tags_indexing',
        analyzer=html_strip,
        fields={
            'raw': fields.StringField(analyzer='keyword', multi=True),
            'suggest': fields.CompletionField(multi=True),
        },
        multi=True
    )

    class Meta(object):
        """Meta options."""
```

(continues on next page)

(continued from previous page)

```
        model = Book  # The model associate with this Document
```

12.7.1.3 Sample serializer

search_indexes/serializers/tag.py

```
import json

from rest_framework import serializers

class TagSerializer(serializers.Serializer):
    """Helper serializer for the Tag field of the Book document."""

    title = serializers.CharField()

    class Meta(object):
        """Meta options."""

        fields = ('title',)
        read_only_fields = ('title',)
```

search_indexes/serializers/book.py

```
class BookDocumentSerializer(serializers.Serializer):
    """Serializer for the Book document."""

    id = serializers.SerializerMethodField()

    title = serializers.CharField(read_only=True)
    description = serializers.CharField(read_only=True)
    summary = serializers.CharField(read_only=True)

    publisher = serializers.CharField(read_only=True)
    publication_date = serializers.DateField(read_only=True)
    state = serializers.CharField(read_only=True)
    isbn = serializers.CharField(read_only=True)
    price = serializers.FloatField(read_only=True)
    pages = serializers.IntegerField(read_only=True)
    stock_count = serializers.IntegerField(read_only=True)
    tags = serializers.SerializerMethodField()

    class Meta(object):
        """Meta options."""

        fields = (
            'id',
            'title',
            'description',
            'summary',
            'publisher',
            'publication_date',
            'state',
            'isbn',
            'price',
            'pages',
```

(continues on next page)

(continued from previous page)

```
            'stock_count',
            'tags',
        )
        read_only_fields = fields

    def get_tags(self, obj):
        """Get tags."""
        if obj.tags:
            return list(obj.tags)
        else:
            return []
```

12.7.1.4 Sample view

search_indexes/viewsets/book.py

```
from django_elasticsearch_dsl_drf.constants import (
    LOOKUP_FILTER_TERMS,
    LOOKUP_FILTER_RANGE,
    LOOKUP_FILTER_PREFIX,
    LOOKUP_FILTER_WILDCARD,
    LOOKUP_QUERY_IN,
    LOOKUP_QUERY_EXCLUDE,
)
from django_elasticsearch_dsl_drf.filter_backends import (
    FilteringFilterBackend,
    OrderingFilterBackend,
    DefaultOrderingFilterBackend,
    SearchFilterBackend,
)
from django_elasticsearch_dsl_drf.viewsets import DocumentViewSet

# Example app models
from search_indexes.documents.book import BookDocument
from search_indxes.serializers import BookDocumentSerializer


class BookDocumentView(DocumentViewSet):
    """The BookDocument view."""

    document = BookDocument
    serializer_class = BookDocumentSerializer
    lookup_field = 'id'
    filter_backends = [
        FilteringFilterBackend,
        OrderingFilterBackend,
        DefaultOrderingFilterBackend,
        SearchFilterBackend,
    ]
    # Define search fields
    search_fields = (
        'title',
        'summary',
        'description',
    )
```

(continues on next page)

(continued from previous page)

```
    # Define filtering fields
    filter_fields = {
        'id': {
            'field': '_id',
            'lookups': [
                LOOKUP_FILTER_RANGE,
                LOOKUP_QUERY_IN,
            ],
        },
        'publisher': 'publisher.raw',
        'publication_date': 'publication_date',
        'isbn': 'isbn.raw',
        'tags': {
            'field': 'tags',
            'lookups': [
                LOOKUP_FILTER_TERMS,
                LOOKUP_FILTER_PREFIX,
                LOOKUP_FILTER_WILDCARD,
                LOOKUP_QUERY_IN,
                LOOKUP_QUERY_EXCLUDE,
            ],
        },
        'tags.raw': {
            'field': 'tags.raw',
            'lookups': [
                LOOKUP_FILTER_TERMS,
                LOOKUP_FILTER_PREFIX,
                LOOKUP_FILTER_WILDCARD,
                LOOKUP_QUERY_IN,
                LOOKUP_QUERY_EXCLUDE,
            ],
        },
    }
    # Define ordering fields
    ordering_fields = {
        'id': 'id',
        'title': 'title.raw',
        'price': 'price.raw',
        'state': 'state.raw',
        'publication_date': 'publication_date',
    }
    # Specify default ordering
    ordering = ('id', 'title',)
```

12.7.1.5 Usage example

Considering samples above, you should be able to perform the search, sorting and filtering actions described below.

12.7.1.5.1 Search

Query param name reserved for search is `search`. Make sure your models and documents do not have it as a field or attribute.

Multiple search terms are joined with `OR`.

Let's assume we have a number of Book items with fields `title`, `description` and `summary`.

Search in all fields

Search in all fields (`title`, `description` and `summary`) for word "education".

```
http://127.0.0.1:8080/search/books/?search=education
```

Search a single term on specific field

In order to search in specific field (`title`) for term "education", add the field name separated with `:` to the search term.

```
http://127.0.0.1:8080/search/books/?search=title:education
```

Search for multiple terms

In order to search for multiple terms "education", "technology" add multiple `search` query params.

```
http://127.0.0.1:8080/search/books/?search=education&search=technology
```

Search for multiple terms on specific fields

In order to search for multiple terms "education", "technology" in specific fields add multiple `search` query params and field names separated with `:` to each of the search terms.

```
http://127.0.0.1:8080/search/books/?search=title:education&search=summary:technology
```

Search with boosting

It's possible to boost search fields. In order to do that change the *search_fields* definition of the *DocumentViewSet* as follows:

```
class BookDocumentView(DocumentViewSet):
    """The BookDocument view."""

    # ...

    # Define search fields
    search_fields = {
        'title': {'boost': 4},
        'summary': {'boost': 2},
        'description': None,
    }

    # Order by `_score` first.
    ordering = ('_score', 'id', 'title', 'price',)

    # ...
```

Note, that we are ordering results by *_score* first.

12.7.1.5.2 Filtering

Let's assume we have a number of Book documents with the tags (education, politics, economy, biology, climate, environment, internet, technology).

Multiple filter terms are joined with `AND`.

Filter documents by field

Filter documents by field (`state`) "published".

```
http://127.0.0.1:8080/search/books/?state=published
```

Filter documents by multiple fields

Filter documents by field (`states`) "published" and "in_progress".

```
http://127.0.0.1:8080/search/books/?state__in=published__in_progress
```

Filter document by a single field

Filter documents by (field `tag`) "education".

```
http://127.0.0.1:8080/search/books/?tag=education
```

Filter documents by multiple fields

Filter documents by multiple fields (field `tags`) "education" and "economy" with use of functional `in` query filter.

```
http://127.0.0.1:8080/search/books/?tags__in=education__economy
```

You can achieve the same effect by specifying multiple fields (`tags`) "education" and "economy". Note, that in this case multiple filter terms are joined with `OR`.

```
http://127.0.0.1:8080/search/books/?tags=education&tags=economy
```

If you want the same as above, but joined with `AND`, add `__term` to each lookup.

```
http://127.0.0.1:8080/search/books/?tags__term=education&tags__term=economy
```

Filter documents by a word part of a single field

Filter documents by a part word part in single field (`tags`). Word part should match both "technology" and "biology".

```
http://127.0.0.1:8080/search/books/?tags__wildcard=*logy
```

12.7.1.5.3 Ordering

The − prefix means ordering should be descending.

Order documents by field (ascending)

Order documents by field `price` (ascending).

```
http://127.0.0.1:8080/search/books/?search=title:lorem&ordering=price
```

Order documents by field (descending)

Order documents by field `price` (descending).

```
http://127.0.0.1:8080/search/books/?search=title:lorem&ordering=-price
```

Order documents by multiple fields

If you want to order by multiple fields, use multiple ordering query params. In the example below, documents would be ordered first by field `publication_date` (descending), then by field `price` (ascending).

```
http://127.0.0.1:8080/search/books/?search=title:lorem&ordering=-publication_date&
↪ordering=price
```

12.7.1.6 Ids filter

Filters documents that only have the provided ids.

```
http://127.0.0.1:8000/api/articles/?ids=68__64__58
```

Or, alternatively:

```
http://127.0.0.1:8000/api/articles/?ids=68&ids=64&ids=58
```

12.7.1.7 Faceted search

In order to add faceted search support, we would have to extend our view set in the following way:

search_indexes/viewsets/book.py

```
# ...

from django_elasticsearch_dsl_drf.filter_backends import (
    # ...
    FacetedSearchFilterBackend,
)

# ...

from elasticsearch_dsl import (
    DateHistogramFacet,
    RangeFacet,
    TermsFacet,
)

# ...

class BookDocumentView(DocumentViewSet):
    """The BookDocument view."""

    # ...

    filter_backends = [
        # ...
        FacetedSearchFilterBackend,
    ]

    # ...

    faceted_search_fields = {
        'state': 'state.raw',  # By default, TermsFacet is used
        'publisher': {
            'field': 'publisher.raw',
            'facet': TermsFacet,  # But we can define it explicitly
            'enabled': True,
        },
```

(continues on next page)

(continued from previous page)

```
        'publication_date': {
            'field': 'publication_date',
            'facet': DateHistogramFacet,
            'options': {
                'interval': 'year',
            }
        },
        'pages_count': {
            'field': 'pages',
            'facet': RangeFacet,
            'options': {
                'ranges': [
                    ("<10", (None, 10)),
                    ("11-20", (11, 20)),
                    ("20-50", (20, 50)),
                    (">50", (50, None)),
                ]
            }
        },
    }

    # ...
```

Note, that none of the facets is enabled by default, unless you explicitly specify it to be enabled. That means, that you will have to add a query string *facet={facet_field_name}* for each of the facets you want to see in results.

In the example below, we show results with faceted `state` and `pages_count` facets.

```
http://127.0.0.1:8000/search/books/?facet=state&facet=pages_count
```

12.7.1.8 Post-filter

The *post_filter* is very similar to the common filter. The only difference is that it doesn't affect facets. So, whatever post-filters applied, the numbers in facets will remain intact.

12.7.1.8.1 Sample view

Note: Note the `PostFilterFilteringFilterBackend` and `post_filter_fields` usage.

search_indexes/viewsets/book.py

```
# ...

from django_elasticsearch_dsl_drf.filter_backends import (
    # ...
    PostFilterFilteringFilterBackend,
)

# ...

class BookDocumentView(DocumentViewSet):
    """The BookDocument view."""
```

(continues on next page)

(continued from previous page)

```
    document = BookDocument
    serializer_class = BookDocumentSerializer
    lookup_field = 'id'
    filter_backends = [
        FilteringFilterBackend,
        OrderingFilterBackend,
        DefaultOrderingFilterBackend,
        SearchFilterBackend,
        PostFilterFilteringFilterBackend,
    ]
    # Define search fields
    search_fields = (
        'title',
        'summary',
        'description',
    )
    # Define filtering fields
    filter_fields = {
        'id': {
            'field': '_id',
            'lookups': [
                LOOKUP_FILTER_RANGE,
                LOOKUP_QUERY_IN,
            ],
        },
        'publisher': 'publisher.raw',
        'publication_date': 'publication_date',
        'isbn': 'isbn.raw',
        'tags': {
            'field': 'tags',
            'lookups': [
                LOOKUP_FILTER_TERMS,
                LOOKUP_FILTER_PREFIX,
                LOOKUP_FILTER_WILDCARD,
                LOOKUP_QUERY_IN,
                LOOKUP_QUERY_EXCLUDE,
            ],
        },
        'tags.raw': {
            'field': 'tags.raw',
            'lookups': [
                LOOKUP_FILTER_TERMS,
                LOOKUP_FILTER_PREFIX,
                LOOKUP_FILTER_WILDCARD,
                LOOKUP_QUERY_IN,
                LOOKUP_QUERY_EXCLUDE,
            ],
        },
    }
    # Define post-filter filtering fields
    post_filter_fields = {
        'publisher_pf': 'publisher.raw',
        'isbn_pf': 'isbn.raw',
        'state_pf': 'state.raw',
        'tags_pf': {
            'field': 'tags',
```

(continues on next page)

(continued from previous page)

```
            'lookups': [
                LOOKUP_FILTER_TERMS,
                LOOKUP_FILTER_PREFIX,
                LOOKUP_FILTER_WILDCARD,
                LOOKUP_QUERY_IN,
                LOOKUP_QUERY_EXCLUDE,
            ],
        },
    }
    # Define ordering fields
    ordering_fields = {
        'id': 'id',
        'title': 'title.raw',
        'price': 'price.raw',
        'state': 'state.raw',
        'publication_date': 'publication_date',
    }
    # Specify default ordering
    ordering = ('id', 'title',)
```

12.7.1.8.2 Sample queries

Filter documents by field

Filter documents by field (`state`) "published".

```
http://127.0.0.1:8080/search/books/?state_pf=published
```

Filter documents by multiple fields

Filter documents by field (`states`) "published" and "in_progress".

```
http://127.0.0.1:8080/search/books/?state_pf__in=published__in_progress
```

12.7.1.9 Geo-spatial features

For testing the boundaries the following online services might be helpful:

- geojson.io
- Bounding Box Tool

12.7.1.9.1 Filtering

Geo-distance filtering

Filter documents by radius of 100000km from the given location.

```
http://localhost:8000/search/publishers/?location__geo_distance=100000km__12.04__-63.
↪93
```

Geo-polygon filtering

Filter documents that are located in the given polygon.

```
http://localhost:8000/search/publishers/?location__geo_polygon=40,-70__30,-80__20,-90
```

Geo-bounding-box filtering

Filter documents that are located in the given bounding box.

```
http://localhost:8000/search/publishers/?location__geo_bounding_box=44.87,40.07__43.
↪87,41.11
```

12.7.1.9.2 Ordering

Geo-distance ordering

```
http://localhost:8000/search/publishers/?ordering=location__48.85__2.30__km__plane
```

12.7.1.10 Suggestions

The suggest feature suggests similar looking terms based on a provided text by using a suggester.

Note: The `SuggesterFilterBackend` filter backend can be used in the `suggest` custom view action/route only. Usages outside of the are `suggest` action/route are restricted.

There are three options available here: `term`, `phrase` and `completion`.

Note: Suggestion functionality is exclusive. Once you have queried the `SuggesterFilterBackend`, the latter will transform your current search query into suggestion search query (which is very different). Therefore, always add it as the very last filter backend.

12.7.1.10.1 Completion suggesters

12.7.1.10.1.1 Document definition

To make use of suggestions, you should properly index relevant fields of your documents using `fields.CompletionField`.

search_indexes/documents/publisher.py

```
from django.conf import settings

from django_elasticsearch_dsl import Document, Index, fields

from books.models import Publisher

# Name of the Elasticsearch index
INDEX = Index(settings.ELASTICSEARCH_INDEX_NAMES[__name__])

# See Elasticsearch Indices API reference for available settings
INDEX.settings(
    number_of_shards=1,
```

(continues on next page)

(continued from previous page)

```
    number_of_replicas=1
)


@INDEX.doc_type
class PublisherDocument(Document):
    """Publisher Elasticsearch document."""

    id = fields.IntegerField(attr='id')

    name = fields.StringField(
        fields={
            'raw': fields.StringField(analyzer='keyword'),
            'suggest': fields.CompletionField(),
        }
    )

    info = fields.StringField()

    address = fields.StringField(
        fields={
            'raw': fields.StringField(analyzer='keyword')
        }
    )

    city = fields.StringField(
        fields={
            'raw': fields.StringField(analyzer='keyword'),
            'suggest': fields.CompletionField(),
        }
    )

    state_province = fields.StringField(
        fields={
            'raw': fields.StringField(analyzer='keyword'),
            'suggest': fields.CompletionField(),
        }
    )

    country = fields.StringField(
        fields={
            'raw': fields.StringField(analyzer='keyword'),
            'suggest': fields.CompletionField(),
        }
    )

    website = fields.StringField()

    # Location
    location = fields.GeoPointField(attr='location_field_indexing')

    class Meta(object):
        """Meta options."""

        model = Publisher  # The model associate with this Document
```

After that the `name.suggest`, `city.suggest`, `state_province.suggest` and `country.suggest`

fields would be available for suggestions feature.

12.7.1.10.1.2 Serializer definition

This is how publisher serializer would look like.

search_indexes/serializers/publisher.py

```
import json

from django_elasticsearch_dsl_drf.serializers import DocumentSerializer

class PublisherDocumentSerializer(DocumentSerializer):
    """Serializer for Publisher document."""

    class Meta(object):
        """Meta options."""

        # Note, that since we're using a dynamic serializer,
        # we only have to declare fields that we want to be shown. If
        # somehow, dynamic serializer doesn't work for you, either extend
        # or declare your serializer explicitly.
        fields = (
            'id',
            'name',
            'info',
            'address',
            'city',
            'state_province',
            'country',
            'website',
        )
```

12.7.1.10.1.3 ViewSet definition

In order to add suggestions support, we would have to extend our view set in the following way:

search_indexes/viewsets/publisher.py

```
# ...

from django_elasticsearch_dsl_drf.constants import SUGGESTER_COMPLETION
from django_elasticsearch_dsl_drf.filter_backends import (
    # ...
    SuggesterFilterBackend,
)

# ...

class PublisherDocumentViewSet(DocumentViewSet):
    """The PublisherDocument view."""

    document = PublisherDocument

    # ...
```

(continues on next page)

(continued from previous page)

```
filter_backends = [
    # ...
    SuggesterFilterBackend,
]

# ...

# Suggester fields
suggester_fields = {
    'name_suggest': {
        'field': 'name.suggest',
        'suggesters': [
            SUGGESTER_COMPLETION,
        ],
        'options': {
            'size': 20,  # Override default number of suggestions
        },
    },
    'city_suggest': {
        'field': 'city.suggest',
        'suggesters': [
            SUGGESTER_COMPLETION,
        ],
    },
    'state_province_suggest': {
        'field': 'state_province.suggest',
        'suggesters': [
            SUGGESTER_COMPLETION,
        ],
    },
    'country_suggest': {
        'field': 'country.suggest',
        'suggesters': [
            SUGGESTER_COMPLETION,
        ],
    },
}

# Geo-spatial filtering fields
geo_spatial_filter_fields = {
    'location': {
        'lookups': [
            LOOKUP_FILTER_GEO_DISTANCE,
        ],
    },
}
```

In the example below, we show suggestion results (auto-completion) for `country` field.

12.7.1.10.1.4 Sample requests/responses

Once you have extended your view set with `SuggesterFilterBackend` functionality, you can make use of the `suggest` custom action of your view set.

Request

```
GET http://127.0.0.1:8000/search/publishers/suggest/?country_suggest__completion=Ar
```

Response

```
{
    "_shards": {
        "failed": 0,
        "successful": 1,
        "total": 1
    },
    "country_suggest__completion": [
        {
            "options": [
                {
                    "score": 1.0,
                    "text": "Armenia"
                },
                {
                    "score": 1.0,
                    "text": "Argentina"
                }
            ],
            "offset": 0,
            "length": 2,
            "text": "Ar"
        }
    ]
}
```

You can also have multiple suggesters per request.

Request

```
GET http://127.0.0.1:8000/search/publishers/suggest/?name_suggest__completion=B&
↪country_suggest__completion=Ar
```

Response

```
{
    "_shards": {
        "successful": 1,
        "total": 1,
        "failed": 0
    },
    "country_suggest__completion": [
        {
            "text": "Ar",
            "options": [
                {
                    "score": 1.0,
                    "text": "Armenia"
                },
                {
                    "score": 1.0,
                    "text": "Argentina"
                }
            ],
            "offset": 0,
```

(continues on next page)

(continued from previous page)

```
            "length": 2
        }
    ],
    "name_suggest__completion": [
        {
            "text": "B",
            "options": [
                {
                    "score": 1.0,
                    "text": "Book Works"
                },
                {
                    "score": 1.0,
                    "text": "Brumleve LLC"
                },
                {
                    "score": 1.0,
                    "text": "Booktrope"
                },
                {
                    "score": 1.0,
                    "text": "Borman, Post and Wendt"
                },
                {
                    "score": 1.0,
                    "text": "Book League of America"
                }
            ],
            "offset": 0,
            "length": 1
        }
    ]
}
```

12.7.1.10.1.5 Suggestions on Array/List field

Suggestions on Array/List fields (typical use case - tags, where Tag model would be a many-to-many relation to a Book model) work almost the same.

Before checking the *Sample requests/responses*, do have in mind the following:

- `Book` (see the *Sample models*)
- `BookSerializer` (see the *Sample serializer*)
- `BookDocumentView` (see the **'Sample view'_**)

12.7.1.10.1.6 Sample requests/responses

Once you have extended your view set with `SuggesterFilterBackend` functionality, you can make use of the `suggest` custom action of your view set.

Request

```
GET http://127.0.0.1:8000/search/books/suggest/?tag_suggest__completion=bio
```

Response

```
{
    "_shards": {
        "failed": 0,
        "successful": 1,
        "total": 1
    },
    "country_suggest__completion": [
        {
            "options": [
                {
                    "score": 1.0,
                    "text": "Biography"
                },
                {
                    "score": 1.0,
                    "text": "Biology"
                }
            ],
            "offset": 0,
            "length": 2,
            "text": "bio"
        }
    ]
}
```

12.7.1.10.1.7 Context suggesters

Note, that context suggesters only work for *completion* (thus, not for *term* or *phrase*).

12.7.1.10.1.8 *category* context

The completion suggester considers all documents in the index, but it is often desirable to serve suggestions filtered and/or boosted by some criteria. For example, you want to suggest song titles filtered by certain artists or you want to boost song titles based on their genre.

In that case, the document definition should be altered as follows:

Document definition

```
class BookDocument(Document):

    # ...

    title = StringField(
        analyzer=html_strip,
        fields={
            'raw': KeywordField(),
            'suggest': fields.CompletionField(),
            'suggest_context': fields.CompletionField(
                contexts=[
                    {
                        "name": "tag",
                        "type": "category",
```

(continues on next page)

(continued from previous page)

```
                        # The `path` value shall be pointing to an
                        # existing field of current document, which shall
                        # be used for filtering.
                        "path": "tags.raw",
                    },
                ]
            ),
        }
    )

    # Tags
    tags = StringField(
        attr='tags_indexing',
        analyzer=html_strip,
        fields={
            'raw': KeywordField(multi=True),
            'suggest': fields.CompletionField(multi=True),
        },
        multi=True
    )

    # ...
```

ViewSet should altered as follows:

ViewSet definition

```
class BookFrontendDocumentViewSet(DocumentViewSet):

    # ...

    # Suggester fields
    suggester_fields = {
        'title_suggest_context': {
            'field': 'title.suggest_context',
            'default_suggester': SUGGESTER_COMPLETION,
            # We want to be able to filter the completion filter
            # results on the following params: tag, state and publisher.
            # We also want to provide the size value.
            # See the "https://www.elastic.co/guide/en/elasticsearch/
            # reference/6.1/suggester-context.html" for the reference.
            'completion_options': {
                'category_filters': {
                    # The `tag` has been defined as `name` value in the
                    # `suggest_context` of the `BookDocument`.
                    'title_suggest_tag': 'tag',
                },
            },
            'options': {
                'size': 10,  # By default, number of results is 5.
            },
        },
    }

    # ...
```

And finally we can narrow our suggestions as follows:

Sample request

In the example below we have filtered suggestions by tags "Art" and "Comics" having boosted "Comics" by 2.0.

```
GET http://localhost:8000/search/books-frontend/suggest/?title_suggest_context=M&
↪title_suggest_tag=Art&title_suggest_tag=Comics__2.0
```

12.7.1.10.1.9 *geo* context

Geo context allows to get suggestions within a certain distance from a specified geo location.

In that case, the document definition should be altered as follows:

Document definition

```
class AddressDocument(Document):

    # ...

    street = StringField(
        analyzer=html_strip,
        fields={
            'raw': KeywordField(),
            'suggest': fields.CompletionField(),
            'suggest_context': fields.CompletionField(
                contexts=[
                    {
                        "name": "loc",
                        "type": "geo",
                        "path": "location",
                        # You could also optionally add precision value.
                        # However, this is not required and can be
                        # specified in the query during runtime.
                        # "precision": "100km",
                    },
                ],
            ),
        }
    )

    location = fields.GeoPointField(
        attr='location_field_indexing',
    )

    # ...
```

ViewSet should altered as follows:

ViewSet definition

```
class BookFrontendDocumentViewSet(DocumentViewSet):

    # ...

    # Suggester fields
    suggester_fields = {
        'street_suggest_context': {
            'field': 'street.suggest_context',
```

(continues on next page)

(continued from previous page)

```
            'default_suggester': SUGGESTER_COMPLETION,
            # We want to be able to filter the completion filter
            # results on the following params: tag, state and publisher.
            # We also want to provide the size value.
            # See the "https://www.elastic.co/guide/en/elasticsearch/
            # reference/6.1/suggester-context.html" for the reference.
            'completion_options': {
                'geo_filters': {
                    'title_suggest_loc': 'loc',
                },
            },
            'options': {
                'size': 10,  # By default, number of results is 5.
            },
        },
    }

    # ...
```

And finally we can narrow our suggestions as follows:

Sample request

In the example below we have filtered suggestions within 8000km distance from geo-point (-30, -100).

```
GET http://localhost:8000/search/addresses-frontend/suggest/?street_suggest_context=L&
↪title_suggest_loc=-30__-100__8000km
```

Same query with boosting (boost value 2.0):

```
GET http://localhost:8000/search/addresses-frontend/suggest/?street_suggest_context=L&
↪title_suggest_loc=-30__-100__8000km__2.0
```

12.7.1.10.2 Term and Phrase suggestions

While for the `completion` suggesters to work the `CompletionField` shall be used, the `term` and `phrase` suggesters work on common text fields.

12.7.1.10.2.1 Document definition

search_indexes/documents/book.py

```
from django.conf import settings

from django_elasticsearch_dsl import Document, Index, fields

from books.models import Book

# Name of the Elasticsearch index
INDEX = Index(settings.ELASTICSEARCH_INDEX_NAMES[__name__])

# See Elasticsearch Indices API reference for available settings
INDEX.settings(
    number_of_shards=1,
```

(continues on next page)

(continued from previous page)

```
    number_of_replicas=1
)

@INDEX.doc_type
class BookDocument(Document):
    """Book Elasticsearch document."""
    # ID
    id = fields.IntegerField(attr='id')

    title = StringField(
        analyzer=html_strip,
        fields={
            'raw': KeywordField(),
            'suggest': fields.CompletionField(),
        }
    )

    description = StringField(
        analyzer=html_strip,
        fields={
            'raw': KeywordField(),
        }
    )

    summary = StringField(
        analyzer=html_strip,
        fields={
            'raw': KeywordField()
        }
    )

    # Publisher
    publisher = StringField(
        attr='publisher_indexing',
        analyzer=html_strip,
        fields={
            'raw': KeywordField(),
            'suggest': fields.CompletionField(),
        }
    )

    # Publication date
    publication_date = fields.DateField()

    # State
    state = StringField(
        analyzer=html_strip,
        fields={
            'raw': KeywordField(),
        }
    )

    # ISBN
    isbn = StringField(
        analyzer=html_strip,
        fields={
            'raw': KeywordField(),
```

(continues on next page)

(continued from previous page)

```
        }
    )

    # Price
    price = fields.FloatField()

    # Pages
    pages = fields.IntegerField()

    # Stock count
    stock_count = fields.IntegerField()

    # Tags
    tags = StringField(
        attr='tags_indexing',
        analyzer=html_strip,
        fields={
            'raw': KeywordField(multi=True),
            'suggest': fields.CompletionField(multi=True),
        },
        multi=True
    )

    null_field = fields.StringField(attr='null_field_indexing')

    class Meta(object):
        """Meta options."""

        model = Book  # The model associate with this Document
```

12.7.1.10.2.2 ViewSet definition

Note: The suggester filter backends shall come as last ones.

Suggesters for the view are configured in `suggester_fields` property.

In the example below, the `title_suggest` is the name of the GET query param which points to the `title.suggest` field of the `BookDocument` document. For the `title_suggest` the allowed suggesters are `SUGGESTER_COMPLETION`, `SUGGESTER_TERM` and `SUGGESTER_PHRASE`.

URL shall be constructed in the following way:

```
/search/books/suggest/?{QUERY_PARAM}__{SUGGESTER_NAME}={VALUE}
```

Example for `completion` suggester:

```
GET http://127.0.0.1:8000/search/books/suggest/?title_suggest__completion=temp
```

However, since we have `default_suggester` defined we can skip the `__{SUGGESTER_NAME}` part (if we want `completion` suggester functionality). Thus, it might be written as short as:

```
GET http://127.0.0.1:8000/search/books/suggest/?title_suggest=temp
```

Example for `term` suggester:

```
GET http://127.0.0.1:8000/search/books/suggest/?title_suggest__term=tmeporus
```

Example for `phrase` suggester:

```
GET http://127.0.0.1:8000/search/books/suggest/?title_suggest__phrase=tmeporus
```

search_indexes/viewsets/book.py

```
from django_elasticsearch_dsl_drf.constants import (
    LOOKUP_FILTER_PREFIX,
    LOOKUP_FILTER_RANGE,
    LOOKUP_FILTER_TERMS,
    LOOKUP_FILTER_WILDCARD,
    LOOKUP_QUERY_EXCLUDE,
    LOOKUP_QUERY_GT,
    LOOKUP_QUERY_GTE,
    LOOKUP_QUERY_IN,
    LOOKUP_QUERY_IN,
    LOOKUP_QUERY_ISNULL,
    LOOKUP_QUERY_LT,
    LOOKUP_QUERY_LTE,
    SUGGESTER_COMPLETION,
    SUGGESTER_PHRASE,
    SUGGESTER_TERM,
)
from django_elasticsearch_dsl_drf.filter_backends import (
    # ...
    SuggesterFilterBackend,
)

class BookDocumentViewSet(DocumentViewSet):
    """The BookDocument view."""

    document = BookDocument
    # serializer_class = BookDocumentSerializer
    serializer_class = BookDocumentSimpleSerializer
    lookup_field = 'id'
    filter_backends = [
        FilteringFilterBackend,
        OrderingFilterBackend,
        DefaultOrderingFilterBackend,
        SearchFilterBackend,
        SuggesterFilterBackend,  # This should be the last backend
    ]
    # Define search fields
    search_fields = (
        'title',
        'description',
        'summary',
    )
    # Define filter fields
    filter_fields = {
        'id': {
            'field': 'id',
            'lookups': [
                LOOKUP_FILTER_RANGE,
                LOOKUP_QUERY_IN,
```

(continues on next page)

(continued from previous page)

```
                LOOKUP_QUERY_GT,
                LOOKUP_QUERY_GTE,
                LOOKUP_QUERY_LT,
                LOOKUP_QUERY_LTE,
                LOOKUP_FILTER_TERMS,
            ],
        },
        'title': 'title.raw',
        'publisher': 'publisher.raw',
        'publication_date': 'publication_date',
        'state': 'state.raw',
        'isbn': 'isbn.raw',
        'price': {
            'field': 'price.raw',
            'lookups': [
                LOOKUP_FILTER_RANGE,
            ],
        },
        'pages': {
            'field': 'pages',
            'lookups': [
                LOOKUP_FILTER_RANGE,
                LOOKUP_QUERY_GT,
                LOOKUP_QUERY_GTE,
                LOOKUP_QUERY_LT,
                LOOKUP_QUERY_LTE,
            ],
        },
        'stock_count': {
            # 'field': 'stock_count',
            'lookups': [
                LOOKUP_FILTER_RANGE,
                LOOKUP_QUERY_GT,
                LOOKUP_QUERY_GTE,
                LOOKUP_QUERY_LT,
                LOOKUP_QUERY_LTE,
            ],
        },
        'tags': {
            'field': 'tags',
            'lookups': [
                LOOKUP_FILTER_TERMS,
                LOOKUP_FILTER_PREFIX,
                LOOKUP_FILTER_WILDCARD,
                LOOKUP_QUERY_IN,
                LOOKUP_QUERY_EXCLUDE,
                LOOKUP_QUERY_ISNULL,
            ],
        },
        'tags.raw': {
            'field': 'tags.raw',
            'lookups': [
                LOOKUP_FILTER_TERMS,
                LOOKUP_FILTER_PREFIX,
                LOOKUP_FILTER_WILDCARD,
                LOOKUP_QUERY_IN,
                LOOKUP_QUERY_EXCLUDE,
```

(continues on next page)

(continued from previous page)

```
            ],
        },
        # This has been added to test `exists` filter.
        'non_existent_field': 'non_existent_field',
        # This has been added to test `isnull` filter.
        'null_field': 'null_field',
    }
    # Define ordering fields
    ordering_fields = {
        'id': 'id',
        'title': 'title.raw',
        'price': 'price.raw',
        'state': 'state.raw',
        'publication_date': 'publication_date',
    }
    # Specify default ordering
    ordering = ('id', 'title', 'price',)

    # Suggester fields
    suggester_fields = {
        'title_suggest': {
            'field': 'title.suggest',
            'suggesters': [
                SUGGESTER_COMPLETION,
                SUGGESTER_TERM,
                SUGGESTER_PHRASE,
            ]
            'default_suggester': SUGGESTER_COMPLETION,
            'options': {
                'size': 10,  # Number of suggestions to retrieve.
            },
        },
        'publisher_suggest': 'publisher.suggest',
        'tag_suggest': 'tags.suggest',
        'summary_suggest': 'summary',
    }
```

Note, that by default the number of suggestions is limited to 5. If you need more suggestions, add ‘options‘ dictionary with *size* provided, as show above.

12.7.1.10.2.3 Sample requests/responses

Once you have extended your view set with `SuggesterFilterBackend` functionality, you can make use of the `suggest` custom action of your view set.

Let’s considering, that one of our books has the following text in the summary:

```
Twas brillig, and the slithy toves
Did gyre and gimble in the wabe.
All mimsy were the borogoves
And the mome raths outgrabe.

"Beware the Jabberwock, my son!
The jaws that bite, the claws that catch!
Beware the Jubjub bird, and shun
```

(continues on next page)

(continued from previous page)

```
The frumious Bandersnatch!"

He took his vorpal sword in his hand,
Long time the manxome foe he sought --
So rested he by the Tumtum tree,
And stood awhile in thought.
```

12.7.1.10.2.4 Completion

Request

```
GET http://127.0.0.1:8000/search/books/suggest/?title_suggest__completion=temp
```

Response


```
{
    "_shards": {
        "successful": 1,
        "total": 1,
        "failed": 0
    },
    "title_suggest": [
        {
            "length": 4,
            "text": "temp",
            "options": [
                {
                    "text": "Tempora voluptates distinctio facere ",
                    "_index": "book",
                    "_score": 1.0,
                    "_id": "1000087",
                    "_type": "book_document",
                    "_source": {
                        "description": null,
                        "summary": "Veniam dolores recusandae maxime laborum earum.",
                        "id": 1000087,
                        "state": "cancelled",
                        "authors": [
                            "Jayden van Luyssel",
                            "Yassin van Rooij",
                            "Florian van 't Erve",
                            "Mats van Nimwegen",
                            "Wessel Keltenie"
                        ],
                        "title": "Tempora voluptates distinctio facere."
                    }
                },
                {
                    "text": "Tempore sapiente repellat alias ad corrupti",
                    "_index": "book",
                    "_score": 1.0,
                    "_id": "29",
                    "_type": "book_document"
                    "_source": {
                        "description": null,
```


(continues on next page)

(continued from previous page)


```
                        "summary": "Dolores minus architecto iure fugit qui sed.",
                        "id": 29,
                        "state": "canelled",
                        "authors": [
                            "Wout van Northeim",
                            "Lenn van Vliet-Kuijpers",
                            "Tijs Mulder"
                        ],
                        "title": "Tempore sapiente repellat alias ad."
                    },

                },
                {
                    "text": "Temporibus exercitationem minus expedita",
                    "_index": "book",
                    "_score": 1.0,
                    "_id": "17",
                    "_type": "book_document",
                    "_source": {
                        "description": null,
                        "summary": "A laborum alias voluptates tenetur sapiente modi.
↪",
                        "id": 17,
                        "state": "canelled",
                        "authors": [
                            "Juliette Estey",
                            "Keano de Keijzer",
                            "Koen Scheffers",
                            "Florian van 't Erve",
                            "Tara Oversteeg",
                            "Mats van Nimwegen"
                        ],
                        "title": "Temporibus exercitationem minus expedita."
                    }
                }
            ],
            "offset": 0
        }
    ]
}
```


12.7.1.10.2.5 Term

Request

```
GET http://127.0.0.1:8000/search/books/suggest/?summary_suggest__term=tovse
```

Response


```
{
    "_shards": {
        "failed": 0,
        "total": 1,
        "successful": 1
    },
```


(continues on next page)

(continued from previous page)

```
    "summary_suggest__term": [
        {
            "text": "tovs",
            "offset": 0,
            "options": [
                {
                    "text": "tove",
                    "score": 0.75,
                    "freq": 1
                },
                {
                    "text": "took",
                    "score": 0.5,
                    "freq": 1
                },
                {
                    "text": "twas",
                    "score": 0.5,
                    "freq": 1
                }
            ],
            "length": 5
        }
    ]
}
```

12.7.1.10.2.6 Phrase

Request

```
GET http://127.0.0.1:8000/search/books/suggest/?summary_suggest__phrase=slith%20tovs
```

Response

```
{
    "summary_suggest__phrase": [
        {
            "text": "slith tovs",
            "offset": 0,
            "options": [
                {
                    "text": "slithi tov",
                    "score": 0.00083028956
                }
            ],
            "length": 10
        }
    ],
    "_shards": {
        "failed": 0,
        "total": 1,
        "successful": 1
    }
}
```

12.7.1.11 Functional suggestions

If native suggestions are not good enough for you, use functional suggesters.

Configuration is very similar to native suggesters.

12.7.1.11.1 Document definition

Obviously, different filters require different approaches. For instance, when using functional completion prefix filter, the best approach is to use keyword field of the Elasticsearch. While for match completion, Ngram fields work really well.

The following example indicates Ngram analyzer/filter usage.

search_indexes/documents/book.py

```
from django.conf import settings
from django_elasticsearch_dsl import Document, Index, fields

from elasticsearch_dsl import analyzer
from elasticsearch_dsl.analysis import token_filter

from books.models import Book

edge_ngram_completion_filter = token_filter(
    'edge_ngram_completion_filter',
    type="edge_ngram",
    min_gram=1,
    max_gram=20
)


edge_ngram_completion = analyzer(
    "edge_ngram_completion",
    tokenizer="standard",
    filter=["lowercase", edge_ngram_completion_filter]
)

INDEX = Index(settings.ELASTICSEARCH_INDEX_NAMES[__name__])

# See Elasticsearch Indices API reference for available settings
INDEX.settings(
    number_of_shards=1,
    number_of_replicas=1
)

@INDEX.doc_type
class BookDocument(Document):
    """Book Elasticsearch document."""

    # In different parts of the code different fields are used. There are
    # a couple of use cases: (1) more-like-this functionality, where `title`,
    # `description` and `summary` fields are used, (2) search and filtering
    # functionality where all of the fields are used.

    # ID
    id = fields.IntegerField(attr='id')
```

(continues on next page)

(continued from previous page)

```
    # ********************************************************************
    # ********************** Main data fields for search ****************
    # ********************************************************************

    title = StringField(
        analyzer=html_strip,
        fields={
            'raw': KeywordField(),
            'suggest': fields.CompletionField(),
            'edge_ngram_completion': StringField(
                analyzer=edge_ngram_completion
            ),
        }
    )

    # ...

    class Meta(object):
        """Meta options."""

        model = Book  # The model associate with this Document
```

12.7.1.11.2 ViewSet definition

Note: The suggester filter backends shall come as last ones.

Functional suggesters for the view are configured in `functional_suggester_fields` property.

In the example below, the `title_suggest` is the name of the GET query param which points to the `title.raw` field of the `BookDocument` document. For the `title_suggest` the allowed suggester is `FUNCTIONAL_SUGGESTER_COMPLETION_PREFIX`. For Ngram match we have the `title_suggest_match` field, which points to `title.edge_ngram_completion` field of the same document. For `title_suggest_match` the allowed suggester is `FUNCTIONAL_SUGGESTER_COMPLETION_MATCH`.

URL shall be constructed in the following way:

```
/search/books/functional_suggest/?{QUERY_PARAM}__{SUGGESTER_NAME}={VALUE}
```

Example for `completion_prefix` suggester:

```
GET http://localhost:8000/search/books/functional_suggest/?title_suggest_prefix__
↪completion_prefix=Temp
```

However, since we have `default_suggester` defined we can skip the `__{SUGGESTER_NAME}` part (if we want `completion_prefix` suggester functionality). Thus, it might be written as short as:

```
GET http://localhost:8000/search/books/functional_suggest/?title_suggest_prefix=Temp
```

Example for `completion_match` suggester:

```
GET http://localhost:8000/search/books/functional_suggest/?title_suggest_match__
↪completion_match=Temp
```

However, since we have `default_suggester` defined we can skip the `__{SUGGESTER_NAME}` part (if we want `completion_match` suggester functionality). Thus, it might be written as short as:

```
GET http://localhost:8000/search/books/functional_suggest/?title_suggest_match=Temp
```

search_indexes/viewsets/book.py

```
from django_elasticsearch_dsl_drf.constants import (
    # ...
    FUNCTIONAL_SUGGESTER_COMPLETION_PREFIX,
    FUNCTIONAL_SUGGESTER_COMPLETION_MATCH,
)
from django_elasticsearch_dsl_drf.filter_backends import (
    # ...
    SuggesterFilterBackend,
)

class BookDocumentViewSet(DocumentViewSet):
    """The BookDocument view."""

    document = BookDocument
    serializer_class = BookDocumentSerializer
    lookup_field = 'id'
    filter_backends = [
        FilteringFilterBackend,
        IdsFilterBackend,
        OrderingFilterBackend,
        DefaultOrderingFilterBackend,
        SearchFilterBackend,
        FacetedSearchFilterBackend,
        HighlightBackend,
        FunctionalSuggesterFilterBackend,  # This should come as last
    ]

    # ...

    # Functional suggester fields
    functional_suggester_fields = {
        'title_suggest': {
            'field': 'title.raw',
            'suggesters': [
                FUNCTIONAL_SUGGESTER_COMPLETION_PREFIX,
            ],
            'default_suggester': FUNCTIONAL_SUGGESTER_COMPLETION_PREFIX,
            'options': {
                'size': 25,
                'from': 0,
            }
        },
        'title_suggest_match': {
            'field': 'title.edge_ngram_completion',
            'suggesters': [FUNCTIONAL_SUGGESTER_COMPLETION_MATCH],
            'default_suggester': FUNCTIONAL_SUGGESTER_COMPLETION_MATCH,
        }
    }
```

Note: Note, that in `functional_suggester_fields['title_suggest']['options']` there are two

params: `size` and `from`. They control the query size and the offset of the generated functional suggest query.

12.7.1.12 Highlighting

Highlighters enable you to get highlighted snippets from one or more fields in your search results so you can show users where the query matches are.

ViewSet definition

```
from django_elasticsearch_dsl_drf.viewsets import DocumentViewSet
from django_elasticsearch_dsl_drf.filter_backends import (
    # ...
    HighlightBackend,
)

from ..documents import BookDocument
from ..serializers import BookDocumentSimpleSerializer


class BookDocumentViewSet(BaseDocumentViewSet):
"""The BookDocument view."""

    document = BookDocument
    # serializer_class = BookDocumentSerializer
    serializer_class = BookDocumentSimpleSerializer
    lookup_field = 'id'
    filter_backends = [
        # ...
        HighlightBackend,
    ]

    # ...

    # Define highlight fields
    highlight_fields = {
        'title': {
            'enabled': True,
            'options': {
                'pre_tags': ["<b>"],
                'post_tags': ["</b>"],
            }
        },
        'summary': {
            'options': {
                'fragment_size': 50,
                'number_of_fragments': 3
            }
        },
        'description': {},
    }

    # ...
```

Request

```
GET http://127.0.0.1:8000/search/books/?search=optimisation&highlight=title&
↪highlight=summary
```

(continues on next page)

(continued from previous page)

Response


```
{
    "count": 1,
    "next": null,
    "previous": null,
    "facets": {
        "_filter_publisher": {
            "publisher": {
                "buckets": [
                    {
                        "key": "Self published",
                        "doc_count": 1
                    }
                ],
                "doc_count_error_upper_bound": 0,
                "sum_other_doc_count": 0
            },
            "doc_count": 1
        }
    },
    "results": [
        {
            "id": 999999,
            "title": "Performance optimisation",
            "description": null,
            "summary": "Ad animi adipisci libero facilis iure totam
                        impedit. Facilis maiores quae qui magnam dolores.
                        Veritatis quia amet porro voluptates iure quod
                        impedit. Dolor voluptatibus maiores at libero
                        magnam.",
            "authors": [
                "Artur Barseghyan"
            ],
            "publisher": "Self published",
            "publication_date": "1981-04-29",
            "state": "cancelled",
            "isbn": "978-1-7372176-0-2",
            "price": 40.51,
            "pages": 162,
            "stock_count": 30,
            "tags": [
                "Guide",
                "Poetry",
                "Fantasy"
            ],
            "highlight": {
                "title": [
                    "Performance <b>optimisation</b>"
                ]
            },
            "null_field": null
        }
    ]
}
```

12.7.1.13 Pagination

12.7.1.13.1 Page number pagination

By default, the `PageNumberPagination` class is used on all view sets which inherit from `DocumentViewSet`.

Example:

```
http://127.0.0.1:8000/search/books/?page=4
http://127.0.0.1:8000/search/books/?page=4&page_size=100
```

12.7.1.13.2 Limit/offset pagination

In order to use a different `pagination_class`, for instance the `LimitOffsetPagination`, specify it explicitly in the view.

search_indexes/viewsets/book.py

```
# ...

from django_elasticsearch_dsl_drf.pagination import LimitOffsetPagination

# ...

class BookDocumentView(DocumentViewSet):
    """The BookDocument view."""

    # ...

    pagination_class = LimitOffsetPagination

    # ...
```

Example:

```
http://127.0.0.1:8000/search/books/?limit=100
http://127.0.0.1:8000/search/books/?offset=400&limit=100
```

12.7.1.13.3 Customisations

If you want to add additional data to the paginated response, for instance, the page size, subclass the correspondent pagination class and add your modifications in the `get_paginated_response_context` method as follows:

```
from django_elasticsearch_dsl_drf.pagination import PageNumberPagination


class CustomPageNumberPagination(PageNumberPagination):
    """Custom page number pagination."""

    def get_paginated_response_context(self, data):
        __data = super(
            CustomPageNumberPagination,
            self
        ).get_paginated_response_context(data)
```

(continues on next page)

(continued from previous page)

```
        __data.append(
            ('current_page', int(self.request.query_params.get('page', 1)))
        )
        __data.append(
            ('page_size', self.get_page_size(self.request))
        )

        return sorted(__data)
```

Same applies to the customisations of the `LimitOffsetPagination`.

12.8 Nested fields usage examples

Advanced Django REST framework integration examples with object/nested fields.

See the example project for sample models/views/serializers.

- models
- documents
- serializers
- viewsets

Contents:

Table of Contents

- *Nested fields usage examples*
  - *Example app*
    - *Sample models*
    - *Sample document*
      - *Index definition*
      - *Settings*
      - *Document index*
    - *Sample serializer*
    - *Sample view*
    - *Usage example*
      - *Sample queries*
      - *Search*
      - *Nested filtering*
      - *Nested search*
      - *Sample models*
      - *Sample document*

- *Sample view*
- *Sample request*
- *Filtering*
- *Ordering*

* *Suggestions*
* *Nested aggregations/facets*

12.8.1 Example app

12.8.1.1 Sample models

books/models/continent.py

```
from django.db import models

from six import python_2_unicode_compatible

@python_2_unicode_compatible
class Continent(models.Model):
    """Continent."""

    name = models.CharField(max_length=255)
    info = models.TextField(null=True, blank=True)
    latitude = models.DecimalField(
        null=True,
        blank=True,
        decimal_places=15,
        max_digits=19,
        default=0
    )
    longitude = models.DecimalField(
        null=True,
        blank=True,
        decimal_places=15,
        max_digits=19,
        default=0
    )

    class Meta(object):
        """Meta options."""

        ordering = ["id"]

    def __str__(self):
        return self.name

    @property
    def location_field_indexing(self):
        """Location for indexing.

        Used in Elasticsearch indexing/tests of `geo_distance` native filter.
        """
```

(continues on next page)

(continued from previous page)

```
        return {
            'lat': self.latitude,
            'lon': self.longitude,
        }
```

books/models/country.py

```
@python_2_unicode_compatible
class Country(models.Model):
    """Country."""

    name = models.CharField(max_length=255)
    info = models.TextField(null=True, blank=True)
    continent = models.ForeignKey(
        'books.Continent',
        on_delete=models.CASCADE
    )
    latitude = models.DecimalField(
        null=True,
        blank=True,
        decimal_places=15,
        max_digits=19,
        default=0
    )
    longitude = models.DecimalField(
        null=True,
        blank=True,
        decimal_places=15,
        max_digits=19,
        default=0
    )

    class Meta(object):
        """Meta options."""

        ordering = ["id"]

    def __str__(self):
        return self.name

    @property
    def location_field_indexing(self):
        """Location for indexing.

        Used in Elasticsearch indexing/tests of `geo_distance` native
        filter.
        """
        return {
            'lat': self.latitude,
            'lon': self.longitude,
        }
```

books/models/city.py

```
@python_2_unicode_compatible
class City(models.Model):
    """City."""
```

(continues on next page)

(continued from previous page)

```
    name = models.CharField(max_length=255)
    info = models.TextField(null=True, blank=True)
    country = models.ForeignKey('books.Country', on_delete=models.CASCADE)
    latitude = models.DecimalField(
        null=True,
        blank=True,
        decimal_places=15,
        max_digits=19,
        default=0
    )
    longitude = models.DecimalField(
        null=True,
        blank=True,
        decimal_places=15,
        max_digits=19,
        default=0
    )

    class Meta(object):
        """Meta options."""

        ordering = ["id"]

    def __str__(self):
        return self.name

    @property
    def location_field_indexing(self):
        """Location for indexing.

        Used in Elasticsearch indexing/tests of `geo_distance` native
        filter.
        """
        return {
            'lat': self.latitude,
            'lon': self.longitude,
        }
```

books/models/address.py

```
from django.db import models
from django_elasticsearch_dsl_drf.wrappers import dict_to_obj

from six import python_2_unicode_compatible

@python_2_unicode_compatible
class Address(models.Model):
    """Address."""

    street = models.CharField(max_length=255)
    house_number = models.CharField(max_length=60)
    appendix = models.CharField(max_length=30, null=True, blank=True)
    zip_code = models.CharField(max_length=60)
    city = models.ForeignKey('books.City', on_delete=models.CASCADE)
    latitude = models.DecimalField(
        null=True,
```

(continues on next page)

(continued from previous page)

```
        blank=True,
        decimal_places=15,
        max_digits=19,
        default=0
    )
    longitude = models.DecimalField(
        null=True,
        blank=True,
        decimal_places=15,
        max_digits=19,
        default=0
    )

    class Meta(object):
        """Meta options."""

        ordering = ["id"]

    def __str__(self):
        return "{} {} {} {}".format(
            self.street,
            self.house_number,
            self.appendix,
            self.zip_code
        )

    @property
    def location_field_indexing(self):
        """Location for indexing.

        Used in Elasticsearch indexing/tests of `geo_distance` native
        filter.
        """
        return {
            'lat': self.latitude,
            'lon': self.longitude,
        }

    @property
    def country_indexing(self):
        """Country data (nested) for indexing.

        Example:

        >>> mapping = {
        >>>     'country': {
        >>>         'name': 'Netherlands',
        >>>         'city': {
        >>>             'name': 'Amsterdam',
        >>>         }
        >>>     }
        >>> }

        :return:
        """
        wrapper = dict_to_obj({
            'name': self.city.country.name,
```

(continues on next page)

(continued from previous page)

```
            'city': {
                'name': self.city.name
            }
        })

        return wrapper

    @property
    def continent_indexing(self):
        """Continent data (nested) for indexing.

        Example:

        >>> mapping = {
        >>>     'continent': {
        >>>         'name': 'Asia',
        >>>         'country': {
        >>>             'name': 'Netherlands',
        >>>             'city': {
        >>>                 'name': 'Amsterdam',
        >>>             }
        >>>         }
        >>>     }
        >>> }

        :return:
        """
        wrapper = dict_to_obj({
            'name': self.city.country.continent.name,
            'country': {
                'name': self.city.country.name,
                'city': {
                    'name': self.city.name,
                }
            }
        })

        return wrapper
```

12.8.1.2 Sample document

12.8.1.2.1 Index definition

To separate dev/test/staging/production indexes, the following approach is recommended.

12.8.1.2.1.1 Settings

settings/base.py

```
# Name of the Elasticsearch index
ELASTICSEARCH_INDEX_NAMES = {
    'search_indexes.documents.address': 'address',
}
```

settings/testing.py

```
# Name of the Elasticsearch index
ELASTICSEARCH_INDEX_NAMES = {
    'search_indexes.documents.address': 'test_address',
}
```

settings/production.py

```
# Name of the Elasticsearch index
ELASTICSEARCH_INDEX_NAMES = {
    'search_indexes.documents.address': 'prod_address',
}
```

12.8.1.2.1.2 Document index

search_indexes/documents/address.py

```
from django.conf import settings

from django_elasticsearch_dsl import Document, Index, fields
from django_elasticsearch_dsl_drf.compat import KeywordField, StringField

from books.models import Address

from .analyzers import html_strip


INDEX = Index(settings.ELASTICSEARCH_INDEX_NAMES[__name__])

# See Elasticsearch Indices API reference for available settings
INDEX.settings(
    number_of_shards=1,
    number_of_replicas=1
)

@INDEX.doc_type
class AddressDocument(Document):
    """Address Elasticsearch document."""

    # In different parts of the code different fields are used. There are
    # a couple of use cases: (1) more-like-this functionality, where `title`,
    # `description` and `summary` fields are used, (2) search and filtering
    # functionality where all of the fields are used.

    # ID
    id = fields.IntegerField(attr='id')

    # ********************************************************************
    # ********************** Main data fields for search ****************
    # ********************************************************************

    street = StringField(
        analyzer=html_strip,
        fields={
            'raw': KeywordField(),
```

(continues on next page)

(continued from previous page)

```
            'suggest': fields.CompletionField(),
        }
    )

    house_number = StringField(analyzer=html_strip)

    appendix = StringField(analyzer=html_strip)

    zip_code = StringField(
        analyzer=html_strip,
        fields={
            'raw': KeywordField(),
            'suggest': fields.CompletionField(),
        }
    )

    # ********************************************************************
    # ********** Additional fields for search and filtering **************
    # ********************************************************************

    # City object
    city = fields.ObjectField(
        properties={
            'name': StringField(
                analyzer=html_strip,
                fields={
                    'raw': KeywordField(),
                    'suggest': fields.CompletionField(),
                }
            ),
            'info': StringField(analyzer=html_strip),
            'location': fields.GeoPointField(attr='location_field_indexing'),
            'country': fields.ObjectField(
                properties={
                    'name': StringField(
                        analyzer=html_strip,
                        fields={
                            'raw': KeywordField(),
                            'suggest': fields.CompletionField(),
                        }
                    ),
                    'info': StringField(analyzer=html_strip),
                    'location': fields.GeoPointField(
                        attr='location_field_indexing'
                    )
                }
            )
        }
    )

    # Country object
    country = fields.NestedField(
        attr='country_indexing',
        properties={
            'name': StringField(
                analyzer=html_strip,
                fields={
```

(continues on next page)

(continued from previous page)

```
                    'raw': KeywordField(),
                    'suggest': fields.CompletionField(),
                }
            ),
            'city': fields.ObjectField(
                properties={
                    'name': StringField(
                        analyzer=html_strip,
                        fields={
                            'raw': KeywordField(),
                        },
                    ),
                },
            ),
        },
    )

    # Continent object
    continent = fields.NestedField(
        attr='continent_indexing',
        properties={
            'name': StringField(
                analyzer=html_strip,
                fields={
                    'raw': KeywordField(),
                    'suggest': fields.CompletionField(),
                }
            ),
            'country': fields.NestedField(
                properties={
                    'name': StringField(
                        analyzer=html_strip,
                        fields={
                            'raw': KeywordField(),
                        }
                    ),
                    'city': fields.NestedField(
                        properties={
                            'name': StringField(
                                analyzer=html_strip,
                                fields={
                                    'raw': KeywordField(),
                                }
                            )
                        }
                    )
                }
            )
        }
    )

    location = fields.GeoPointField(attr='location_field_indexing')

    class Meta(object):
        """Meta options."""

        model = Address  # The model associate with this Document
```

12.8.1.3 Sample serializer

search_indexes/serializers/address.py

```
from django_elasticsearch_dsl_drf.serializers import DocumentSerializer

from ..documents import AddressDocument


class AddressDocumentSerializer(DocumentSerializer):
    """Serializer for address document."""

    class Meta(object):
        """Meta options."""

        document = AddressDocument
        fields = (
            'id',
            'street',
            'house_number',
            'appendix',
            'zip_code',
            'city',
            'country',
            'continent',
            'location',
        )
```

12.8.1.4 Sample view

search_indexes/viewsets/address.py

```
from django_elasticsearch_dsl_drf.constants import (
    LOOKUP_FILTER_GEO_DISTANCE,
    LOOKUP_FILTER_GEO_POLYGON,
    LOOKUP_FILTER_GEO_BOUNDING_BOX,
    SUGGESTER_COMPLETION,
)
from django_elasticsearch_dsl_drf.filter_backends import (
    DefaultOrderingFilterBackend,
    FacetedSearchFilterBackend,
    FilteringFilterBackend,
    GeoSpatialFilteringFilterBackend,
    GeoSpatialOrderingFilterBackend,
    NestedFilteringFilterBackend,
    OrderingFilterBackend,
    SearchFilterBackend,
    SuggesterFilterBackend,
)
from django_elasticsearch_dsl_drf.pagination import LimitOffsetPagination
from django_elasticsearch_dsl_drf.viewsets import DocumentViewSet

from ..documents import AddressDocument
from ..serializers import AddressDocumentSerializer

class AddressDocumentViewSet(DocumentViewSet):
```

(continues on next page)

(continued from previous page)

```
    """The AddressDocument view."""

    document = AddressDocument
    serializer_class = AddressDocumentSerializer
    lookup_field = 'id'
    filter_backends = [
        FacetedSearchFilterBackend,
        FilteringFilterBackend,
        OrderingFilterBackend,
        SearchFilterBackend,
        GeoSpatialFilteringFilterBackend,
        GeoSpatialOrderingFilterBackend,
        NestedFilteringFilterBackend,
        DefaultOrderingFilterBackend,
        SuggesterFilterBackend,
    ]
    pagination_class = LimitOffsetPagination
    # Define search fields
    search_fields = (
        'street',
        'zip_code',
        'city.name',
        'city.country.name',
    )
    # Define filtering fields
    filter_fields = {
        'id': None,
        'city': 'city.name.raw',
    }
    # Nested filtering fields
    nested_filter_fields = {
        'continent_country': {
            'field': 'continent.country.name.raw',
            'path': 'continent.country',
        },
        'continent_country_city': {
            'field': 'continent.country.city.name.raw',
            'path': 'continent.country.city',
        },
    }
    # Define geo-spatial filtering fields
    geo_spatial_filter_fields = {
        'location': {
            'lookups': [
                LOOKUP_FILTER_GEO_BOUNDING_BOX,
                LOOKUP_FILTER_GEO_DISTANCE,
                LOOKUP_FILTER_GEO_POLYGON,

            ],
        },
    }
    # Define ordering fields
    ordering_fields = {
        'id': None,
        'street': None,
        'city': 'city.name.raw',
        'country': 'city.country.name.raw',
```

(continues on next page)

(continued from previous page)

```
        'zip_code': None,
    }
    # Define ordering fields
    geo_spatial_ordering_fields = {
        'location': None,
    }
    # Specify default ordering
    ordering = (
        'id',
        'street.raw',
        'city.name.raw',
    )
    # Suggester fields
    suggester_fields = {
        'street_suggest': {
            'field': 'street.suggest',
            'suggesters': [
                SUGGESTER_COMPLETION,
            ],
        },
        'city_suggest': {
            'field': 'city.name.suggest',
            'suggesters': [
                SUGGESTER_COMPLETION,
            ],
        },
        'country_suggest': {
            'field': 'city.country.name.suggest',
            'suggesters': [
                SUGGESTER_COMPLETION,
            ],
        }
    }

    # Facets
    faceted_search_fields = {
        'city': {
            'field': 'city.name.raw',
            'enabled': True,
        },
        'country': {
            'field': 'city.country.name.raw',
            'enabled': True,
        },
    }
```

12.8.1.5 Usage example

Considering samples above, you should be able to perform the search, sorting and filtering actions described below.

12.8.1.5.1 Sample queries

12.8.1.5.1.1 Search

Just a couple of examples, because searching in nested fields doesn't differ from searching in simple fields.

Search in all fields

Search in all fields (`street`, `zip_code` and `city`, `country`) for word "Picadilly".

```
http://127.0.0.1:8000/search/addresses/?search=Piccadilly
```

Search a single term on specific field

In order to search in specific field (`country`) for term "Armenia", add the field name separated with `|` to the search term.

```
http://127.0.0.1:8000/search/addresses/?search=city.country.name:Armenia
```

12.8.1.5.1.2 Nested filtering

Filter documents by nested field

Filter documents by field (`continent.country`) "Armenia".

```
http://127.0.0.1:8000/search/addresses/?continent_country=Armenia
```

Filter documents by field (`continent.country.city`) "Amsterdam".

```
http://127.0.0.1:8000/search/addresses/?continent_country_city=Amsterdam
```

12.8.1.5.1.3 Nested search

For nested search, let's have another example.

12.8.1.5.1.4 Sample models

books/models/city.py

```
from django.db import models
from six import python_2_unicode_compatible

@python_2_unicode_compatible
class City(models.Model):
    """City."""

    name = models.CharField(max_length=255)
    info = models.TextField(null=True, blank=True)
    country = models.ForeignKey('books.Country')
    latitude = models.DecimalField(null=True,
                                   blank=True,
                                   decimal_places=15,
                                   max_digits=19,
```

(continues on next page)

(continued from previous page)

```
                                    default=0)
    longitude = models.DecimalField(null=True,
                                     blank=True,
                                     decimal_places=15,
                                     max_digits=19,
                                     default=0)
```

books/models/country.py

```
from django.db import models
from six import python_2_unicode_compatible

@python_2_unicode_compatible
class Country(models.Model):
    """Country."""

    name = models.CharField(max_length=255)
    info = models.TextField(null=True, blank=True)
    latitude = models.DecimalField(null=True,
                                    blank=True,
                                    decimal_places=15,
                                    max_digits=19,
                                    default=0)
    longitude = models.DecimalField(null=True,
                                     blank=True,
                                     decimal_places=15,
                                     max_digits=19,
                                     default=0)
```

12.8.1.5.1.5 Sample document

documents/city.py

```
from django.conf import settings

from django_elasticsearch_dsl import Document, Index, fields
from django_elasticsearch_dsl_drf.compat import KeywordField, StringField

from books.models import City

from .analyzers import html_strip

INDEX = Index(settings.ELASTICSEARCH_INDEX_NAMES[__name__])

# See Elasticsearch Indices API reference for available settings
INDEX.settings(
    number_of_shards=1,
    number_of_replicas=1
)


@INDEX.doc_type
class CityDocument(Document):
    """City Elasticsearch document.
```

(continues on next page)

(continued from previous page)

```
    This document has been created purely for testing out complex fields.
    """

    # ID
    id = fields.IntegerField(attr='id')

    # ********************************************************************
    # ********************** Main data fields for search *****************
    # ********************************************************************

    name = StringField(
        analyzer=html_strip,
        fields={
            'raw': KeywordField(),
            'suggest': fields.CompletionField(),
        }
    )

    info = StringField(analyzer=html_strip)

    # ********************************************************************
    # ************** Nested fields for search and filtering **************
    # ********************************************************************

    # City object
    country = fields.NestedField(
        properties={
            'name': StringField(
                analyzer=html_strip,
                fields={
                    'raw': KeywordField(),
                    'suggest': fields.CompletionField(),
                }
            ),
            'info': StringField(analyzer=html_strip),
            'location': fields.GeoPointField(attr='location_field_indexing'),
        }
    )

    location = fields.GeoPointField(attr='location_field_indexing')

    # ********************************************************************
    # ********** Other complex fields for search and filtering ***********
    # ********************************************************************

    boolean_list = fields.ListField(
        StringField(attr='boolean_list_indexing')
    )

    datetime_list = fields.ListField(
        StringField(attr='datetime_list_indexing')
    )
    float_list = fields.ListField(
        StringField(attr='float_list_indexing')
    )
    integer_list = fields.ListField(
        StringField(attr='integer_list_indexing')
```

(continues on next page)

(continued from previous page)

```
    )

    class Meta(object):
        """Meta options."""

        model = City  # The model associate with this Document
```

12.8.1.5.1.6 Sample view

viewsets/city.py

```
from django_elasticsearch_dsl_drf.constants import (
    LOOKUP_FILTER_GEO_DISTANCE,
    LOOKUP_FILTER_GEO_POLYGON,
    LOOKUP_FILTER_GEO_BOUNDING_BOX,
    SUGGESTER_COMPLETION,
)
from django_elasticsearch_dsl_drf.filter_backends import (
    FilteringFilterBackend,
    DefaultOrderingFilterBackend,
    OrderingFilterBackend,
    SearchFilterBackend,
    SuggesterFilterBackend,
    GeoSpatialFilteringFilterBackend,
    GeoSpatialOrderingFilterBackend,
)
from django_elasticsearch_dsl_drf.pagination import LimitOffsetPagination
from django_elasticsearch_dsl_drf.viewsets import DocumentViewSet

from ..documents import CityDocument
from ..serializers import CityDocumentSerializer

class CityDocumentViewSet(BaseDocumentViewSet):
    """The CityDocument view."""

    document = CityDocument
    serializer_class = CityDocumentSerializer
    lookup_field = 'id'
    filter_backends = [
        FilteringFilterBackend,
        OrderingFilterBackend,
        SearchFilterBackend,
        GeoSpatialFilteringFilterBackend,
        GeoSpatialOrderingFilterBackend,
        DefaultOrderingFilterBackend,
        SuggesterFilterBackend,
    ]
    pagination_class = LimitOffsetPagination
    # Define search fields
    search_fields = (
        'name',
        'info',
    )

    search_nested_fields = {
```

(continues on next page)

(continued from previous page)

```
        'country': {
            'path': 'country',
            'fields': ['name'],
        }
    }

    # Define filtering fields
    filter_fields = {
        'id': None,
        'name': 'name.raw',
        'country': 'country.name.raw',
    }
    # Define geo-spatial filtering fields
    geo_spatial_filter_fields = {
        'location': {
            'lookups': [
                LOOKUP_FILTER_GEO_BOUNDING_BOX,
                LOOKUP_FILTER_GEO_DISTANCE,
                LOOKUP_FILTER_GEO_POLYGON,

            ],
        },
    }
    # Define ordering fields
    ordering_fields = {
        'id': None,
        'name': None,
        'country': 'country.name.raw',
    }
    # Define ordering fields
    geo_spatial_ordering_fields = {
        'location': None,
    }
    # Specify default ordering
    ordering = (
        'id',
        'name.raw',
        'country.name.raw',
    )

    # Suggester fields
    suggester_fields = {
        'name_suggest': {
            'field': 'name.suggest',
            'suggesters': [
                SUGGESTER_COMPLETION,
            ],
        },
        'country_suggest': {
            'field': 'country.name.suggest',
            'suggesters': [
                SUGGESTER_COMPLETION,
            ],
        }
    }
```

12.8.1.5.1.7 Sample request

Request

```
GET http://127.0.0.1:8000/search/cities/?search=Switzerland
```

12.8.1.5.1.8 Filtering

Filter documents by field

Filter documents by field (`city`) "Dublin".

```
http://127.0.0.1:8000/search/addresses/?city=Dublin
```

Filter documents by multiple fields

Filter documents by field (`states`) "published" and "in_progress".

```
http://127.0.0.1:8000/search/addresses/?city__in=Yerevan__Dublin
```

12.8.1.5.1.9 Ordering

The − prefix means ordering should be descending.

Order documents by field (descending)

Order documents by field `country` (ascending).

```
http://127.0.0.1:8000/search/addresses/?ordering=-country
```

12.8.1.6 Suggestions

The suggest feature suggests similar looking terms based on a provided text by using a suggester.

Note: The `SuggesterFilterBackend` filter backend can be used in the `suggest` custom view action/route only. Usages outside of the are `suggest` action/route are restricted.

There are three options available here: `term`, `phrase` and `completion`.

Note: Suggestion functionality is exclusive. Once you have queried the `SuggesterFilterBackend`, the latter will transform your current search query into suggestion search query (which is very different). Therefore, always add it as the very last filter backend.

Suggest completion for field `country`.

```
http://127.0.0.1:8000/search/addresses/suggest/?country_suggest__completion=Ar
```

Suggest completion for field `city`.

```
http://127.0.0.1:8000/search/addresses/suggest/?city_suggest__completion=Ye
```

12.8.1.7 Nested aggregations/facets

At the moment, nested aggregations/facets are not supported out of the box. Out of the box support will surely land in the package one day, but for now, there's a simple and convenient way of implementing nested aggregations/facets with minimal efforts. Consider the following example.

search_indexes/backends/nested_continents.py

```
from django_elasticsearch_dsl_drf.filter_backends.mixins import (
    FilterBackendMixin,
)
from rest_framework.filters import BaseFilterBackend

class NestedContinentsBackend(BaseFilterBackend, FilterBackendMixin):
    """Adds nesting to continents."""

    faceted_search_param = 'nested_facet'

    def get_faceted_search_query_params(self, request):
        """Get faceted search query params.

        :param request: Django REST framework request.
        :type request: rest_framework.request.Request
        :return: List of search query params.
        :rtype: list
        """
        query_params = request.query_params.copy()
        return query_params.getlist(self.faceted_search_param, [])

    def filter_queryset(self, request, queryset, view):
        """Filter the queryset.
        :param request: Django REST framework request.
        :param queryset: Base queryset.
        :param view: View.
        :type request: rest_framework.request.Request
        :type queryset: elasticsearch_dsl.search.Search
        :type view: rest_framework.viewsets.ReadOnlyModelViewSet
        :return: Updated queryset.
        :rtype: elasticsearch_dsl.search.Search
        """
        facets = self.get_faceted_search_query_params(request)

        if 'continent' in facets:
            queryset \
                .aggs\
                .bucket('continents',
                        'nested',
                        path='continent') \
                .bucket('continent_name',
                        'terms',
                        field='continent.name.raw',
                        size=10) \
                .bucket('counties',
                        'nested',
                        path='continent.country') \
                .bucket('country_name',
                        'terms',
                        field='continent.country.name.raw',
```

(continues on next page)

(continued from previous page)

```
                        size=10) \
                .bucket('city',
                        'nested',
                        path='continent.country.city') \
                .bucket('city_name',
                        'terms',
                        field='continent.country.city.name.raw',
                        size=10)

        return queryset
```

The view will look as follows:

search_indexes/viewsets/address.py

```
from django_elasticsearch_dsl_drf.constants import (
    LOOKUP_FILTER_GEO_DISTANCE,
    LOOKUP_FILTER_GEO_POLYGON,
    LOOKUP_FILTER_GEO_BOUNDING_BOX,
    SUGGESTER_COMPLETION,
)
from django_elasticsearch_dsl_drf.filter_backends import (
    DefaultOrderingFilterBackend,
    FacetedSearchFilterBackend,
    FilteringFilterBackend,
    GeoSpatialFilteringFilterBackend,
    GeoSpatialOrderingFilterBackend,
    NestedFilteringFilterBackend,
    OrderingFilterBackend,
    SearchFilterBackend,
    SuggesterFilterBackend,
)
from django_elasticsearch_dsl_drf.pagination import LimitOffsetPagination
from django_elasticsearch_dsl_drf.viewsets import DocumentViewSet

from ..backends import NestedContinentsBackend
from ..documents import AddressDocument
from ..serializers import AddressDocumentSerializer

class AddressDocumentViewSet(DocumentViewSet):
    """The AddressDocument view."""

    document = AddressDocument
    serializer_class = AddressDocumentSerializer
    lookup_field = 'id'
    filter_backends = [
        FacetedSearchFilterBackend,
        FilteringFilterBackend,
        OrderingFilterBackend,
        SearchFilterBackend,
        GeoSpatialFilteringFilterBackend,
        GeoSpatialOrderingFilterBackend,
        NestedContinentsBackend,
        NestedFilteringFilterBackend,
        DefaultOrderingFilterBackend,
        SuggesterFilterBackend,
    ]
```

(continues on next page)

(continued from previous page)

```
    pagination_class = LimitOffsetPagination
    # Define search fields
    search_fields = (
        'street',
        'zip_code',
        'city.name',
        'city.country.name',
    )
    # Define filtering fields
    filter_fields = {
        'id': None,
        'city': 'city.name.raw',
    }
    # Nested filtering fields
    nested_filter_fields = {
        'continent_country': {
            'field': 'continent.country.name.raw',
            'path': 'continent.country',
        },
        'continent_country_city': {
            'field': 'continent.country.city.name.raw',
            'path': 'continent.country.city',
        },
    }
    # Define geo-spatial filtering fields
    geo_spatial_filter_fields = {
        'location': {
            'lookups': [
                LOOKUP_FILTER_GEO_BOUNDING_BOX,
                LOOKUP_FILTER_GEO_DISTANCE,
                LOOKUP_FILTER_GEO_POLYGON,

            ],
        },
    }
    # Define ordering fields
    ordering_fields = {
        'id': None,
        'street': None,
        'city': 'city.name.raw',
        'country': 'city.country.name.raw',
        'zip_code': None,
    }
    # Define ordering fields
    geo_spatial_ordering_fields = {
        'location': None,
    }
    # Specify default ordering
    ordering = (
        'id',
        'street.raw',
        'city.name.raw',
    )
    # Suggester fields
    suggester_fields = {
        'street_suggest': {
            'field': 'street.suggest',
```

(continues on next page)

(continued from previous page)

```
            'suggesters': [
                SUGGESTER_COMPLETION,
            ],
        },
        'city_suggest': {
            'field': 'city.name.suggest',
            'suggesters': [
                SUGGESTER_COMPLETION,
            ],
        },
        'country_suggest': {
            'field': 'city.country.name.suggest',
            'suggesters': [
                SUGGESTER_COMPLETION,
            ],
        }
    }

    # Facets
    faceted_search_fields = {
        'city': {
            'field': 'city.name.raw',
            'enabled': True,
        },
        'country': {
            'field': 'city.country.name.raw',
            'enabled': True,
        },
    }
```

12.9 More like this

More like this functionality.

12.9.1 Usage example

12.9.1.1 Sample document

```
from django.conf import settings

from django_elasticsearch_dsl import Document, Index, fields
from django_elasticsearch_dsl_drf.compat import KeywordField, StringField
from django_elasticsearch_dsl_drf.analyzers import edge_ngram_completion

from books.models import Book

from .analyzers import html_strip

INDEX = Index(settings.ELASTICSEARCH_INDEX_NAMES[__name__])

# See Elasticsearch Indices API reference for available settings
INDEX.settings(
```

(continues on next page)

(continued from previous page)

```
    number_of_shards=1,
    number_of_replicas=1,
    blocks={'read_only_allow_delete': False}
)


@INDEX.doc_type
class BookDocument(Document):

    # ID
    id = fields.IntegerField(attr='id')

    title = StringField(
        analyzer=html_strip,
        fields={
            'raw': KeywordField(),
            'suggest': fields.CompletionField(),
            'edge_ngram_completion': StringField(
                analyzer=edge_ngram_completion
            ),
            'mlt': StringField(analyzer='english'),
        }
    )

    description = StringField(
        analyzer=html_strip,
        fields={
            'raw': KeywordField(),
            'mlt': StringField(analyzer='english'),
        }
    )

    summary = StringField(
        analyzer=html_strip,
        fields={
            'raw': KeywordField(),
            'mlt': StringField(analyzer='english'),
        }
    )

    # ...

    class Meta(object):
        """Meta options."""

        model = Book  # The model associate with this Document

    def prepare_summary(self, instance):
        """Prepare summary."""
        return instance.summary[:32766]
```

12.9.1.2 Sample view

```
from django_elasticsearch_dsl_drf.filter_backends import (
    FilteringFilterBackend,
```

(continues on next page)

(continued from previous page)

```
    IdsFilterBackend,
    OrderingFilterBackend,
    PostFilterFilteringFilterBackend,
    SearchFilterBackend,
)
from django_elasticsearch_dsl_drf.viewsets import (
    DocumentViewSet,
    MoreLikeThisMixin,
)

from .serializers import BookDocumentSerializer

class BookMoreLikeThisDocumentViewSet(DocumentViewSet,
                                      MoreLikeThisMixin):
    """Same as BookDocumentViewSet, with more-like-this and no facets."""

    # ...

    document = BookDocument
    lookup_field = 'id'
    serializer_class = BookDocumentSerializer

    # ...

    filter_backends = [
        # ...
        FilteringFilterBackend,
        PostFilterFilteringFilterBackend,
        IdsFilterBackend,
        OrderingFilterBackend,
        SearchFilterBackend,
        # ...
    ]

    # More-like-this options
    more_like_this_options = {
        'fields': (
            'title.mlt',
            'summary.mlt',
            'description.mlt',
        )
    }
```

12.9.1.3 Sample request

```
http://localhost:8000/search/books-more-like-this-no-options/1007587/more_like_this/
```

12.9.1.4 Generated query

```
{
  "query": {
    "more_like_this": {
      "fields": [
```

(continues on next page)

(continued from previous page)

```
        "title.mlt",
        "summary.mlt",
        "description.mlt"
      ],
      "like": {
        "_index": "book",
        "_id": "1007587",
        "_type": "book_document"
      }
    }
  },
  "from": 0,
  "size": 14,
  "sort": [
    "_score"
  ]
}
```

12.9.1.5 Options

Pretty much all Elasticsearch more-like-this options available. You might be particularly interested in the following:

- min_term_freq
- max_query_terms
- unlike
- stop_words

12.10 Global aggregations

Global aggregations (facets) are regular aggregations, which are not influenced by the search query/filter. They deliver results similar to *post_filter*.

12.10.1 Sample view

```
from django_elasticsearch_dsl_drf.filter_backends import (
    CompoundSearchFilterBackend,
    DefaultOrderingFilterBackend,
    FacetedSearchFilterBackend,
    OrderingFilterBackend,
)
from django_elasticsearch_dsl_drf.viewsets import DocumentViewSet

from .documents import BookDocument
from .serializers import BookDocumentSerializer

class BookCompoundSearchBackendDocumentViewSet(DocumentViewSet):

    document = BookDocument
    serializer_class = BookDocumentSerializer
    lookup_field = 'id'
```

(continues on next page)

(continued from previous page)

```
    filter_backends = [
        # ...
        OrderingFilterBackend,
        DefaultOrderingFilterBackend,
        CompoundSearchFilterBackend,
        FacetedSearchFilterBackend,
        # ...
    ]

    faceted_search_fields = {
        'state_global': {
            'field': 'state.raw',
            'enabled': True,
            'global': True,  # This makes the aggregation global
        },
    }
```

12.10.2 Sample request

```
http://localhost:8000/search/books/?facet=state_global&state=rejected
```

12.10.3 Generated query

```
{
   "from":0,
   "query":{
      "bool":{
         "filter":[
            {
               "terms":{
                  "state.raw":[
                     "rejected"
                  ]
               }
            }
         ]
      }
   },
   "size":25,
   "aggs":{
      "_filter_state_global":{
         "aggs":{
            "state_global":{
               "terms":{
                  "field":"state.raw"
               }
            }
         },
         "global":{

         }
```

(continues on next page)

(continued from previous page)

```
        }
    },
    "sort":[
        "id",
        "title",
        "price"
    ]
}
```

12.10.4 Sample response

```
{
    "count": 25,
    "next": null,
    "previous": null,
    "facets": {
        "_filter_state_global": {
            "state_global": {
                "buckets": [
                    {
                        "doc_count": 29,
                        "key": "not_published"
                    },
                    {
                        "doc_count": 25,
                        "key": "in_progress"
                    },
                    {
                        "doc_count": 25,
                        "key": "rejected"
                    },
                    {
                        "doc_count": 21,
                        "key": "cancelled"
                    },
                    {
                        "doc_count": 17,
                        "key": "published"
                    }
                ],
                "sum_other_doc_count": 0,
                "doc_count_error_upper_bound": 0
            },
            "doc_count": 117
        }
    },
    "results": [
        {
            "id": 1007489,
            "title": "Cupiditate qui nulla itaque maxime impedit.",
            "description": null,
            "summary": "Aut recusandae architecto incidunt quaerat odio .",
            "authors": [
                "Evy Vermeulen",
                "Tycho Weijland",
```

(continues on next page)

(continued from previous page)

```
                "Rik Zeldenrust"
            ],
            "publisher": "Overdijk Inc",
            "publication_date": "2014-02-28",
            "state": "rejected",
            "isbn": "978-0-15-184366-4",
            "price": 6.53,
            "pages": 82,
            "stock_count": 30,
            "tags": [
                "Trilogy"
            ],
            "highlight": {},
            "null_field": null,
            "score": null
        },
        # ...
    ]
}
```

12.11 Configuration tweaks

12.11.1 Ignore certain Elasticsearch exceptions

```
class BookIgnoreIndexErrorsDocumentViewSet(DocumentViewSet):

    # ...
    ignore = [404]
    # ...
```

12.12 Source filtering backend

Allows to control how the *_source* field is returned with every hit.

By default operations return the contents of the _source field unless you have used the *stored_fields* parameter or if the *_source* field is disabled.

You can turn off *_source* retrieval by using the *source* parameter:

```
from django_elasticsearch_dsl_drf.filter_backends import (
    SourceBackend
)
from django_elasticsearch_dsl_drf.viewsets import (
    BaseDocumentViewSet,
)

# Local article document definition
from .documents import ArticleDocument

# Local article document serializer
from .serializers import ArticleDocumentSerializer
```

(continues on next page)

(continued from previous page)

```
class ArticleDocumentView(BaseDocumentViewSet):

    document = ArticleDocument
    serializer_class = ArticleDocumentSerializer
    filter_backends = [SourceBackend,]
    source = ["title"]
```

To disable *_source* retrieval set to False:

```
# ...
source = False
# ...
```

The *source* also accepts one or more wildcard patterns to control what parts of the *_source* should be returned:

```
# ...
source = ["title", "author.*"]
# ...
```

Finally, for complete control, you can specify both *includes* and *excludes* patterns:

```
# ...
source = {
    "includes": ["title", "author.*"],
    "excludes": [ "*.description" ]
}
# ...
```

Note: Source can make queries lighter. However, it can break current functionality. Use it with caution.

12.13 Indexing troubleshooting

When indexing lots of data (millions of records), you might get timeout exceptions.

A couple of possible solutions (complementary) are listed below. All of them are independent and not strictly related to each other. Thus, you may just use one or a couple or all of them. It's totally up to you.

If you want to test what works best for you, use this test dataset (Postgres) containing 1.8 million location records for *search_indexes.documents.location.LocationDocument* document.

12.13.1 Timeout

For re-indexing, you might want to increase the timeout to avoid time-out exceptions.

To do that, make a new settings file (*indexing*) and add the following:

settings/indexing.py

```
from .base import *  # Import from your main/production settings.

# Override the elasticsearch configuration and provide a custom timeout
```

(continues on next page)

(continued from previous page)

```
ELASTICSEARCH_DSL = {
    'default': {
        'hosts': 'localhost:9200',
        'timeout': 60,  # Custom timeout
    },
}
```

Then rebuild your search index specifying the indexing settings:

```
./manage.py search_index --rebuild -f --settings=settings.indexing
```

Note, that you may as well specify the timeout in your global settings. However, if you're happy with how things work in production (except for the indexing part), you may do as suggested (separate indexing settings).

12.13.2 Chunk size

Note, that this feature is (yet) *only available in the forked version* barseghyanartur/django-elasticsearch-dsl.

Install it as follows:

```
pip install https://github.com/barseghyanartur/django-elasticsearch-dsl/archive/mjl-
↪index-speedup-2-additions.zip
```

Specify the *chunk_size* param as follows (we set chunk_size to 50 in this case):

```
./manage.py search_index --rebuild -f --chunk-size=50
```

12.13.3 Use parallel indexing

Parallel indexing speeds things up (drastically). In my tests I got a speedup boost of 66 percent on 1.8 million records.

Note, that this feature is (yet) *only available in the forked versions* barseghyanartur/django-elasticsearch-dsl. or mjl/django-elasticsearch-dsl.

Install it as follows:

barseghyanartur/django-elasticsearch-dsl fork

```
pip install https://github.com/barseghyanartur/django-elasticsearch-dsl/archive/mjl-
↪index-speedup-2-additions.zip
```

mjl/django-elasticsearch-dsl fork

```
pip install https://github.com/mjl/django-elasticsearch-dsl/archive/mjl-index-speedup.
↪zip
```

In order to make use of it, define set *parallel_indexing* to True on the document meta.

yourapp/documents.py

```
class LocationDocument(Document):

    # ...

    class Meta(object):
```

(continues on next page)

(continued from previous page)

```
        """Meta options."""

        model = Location
        parallel_indexing = True
```

12.13.4 Limit the number of items indexed at once

This is very close to the *chunk_size* shown above, but might work better on heavy querysets. Instead of processing entire queryset at once, it's sliced instead. So, if you have 2 million records in your queryset and you wish to index them by chunks of 20 thousands at once, specify the *queryset_pagination* on the document meta:

yourapp/documents.py

```
class LocationDocument(Document):

    # ...

    class Meta(object):
        """Meta options."""

        model = Location
        queryset_pagination = 50
```

You may even make it dynamic based on the settings loaded. So, for instance, you may have it set to None in production (if you were happy with how things were) and provide a certain value for it in the dedicated indexing settings (as already has been mentioned above).

settings/base.py

```
# Main/production settings
ELASTICSEARCH_DSL_QUERYSET_PAGINATION = None
```

settings/indexing.py

```
# Indexing only settings
ELASTICSEARCH_DSL_QUERYSET_PAGINATION = 1000
```

yourapp/documents.py

```
from django.conf import settings

# ...

class LocationDocument(Document):

    # ...

    class Meta(object):
        """Meta options."""

        model = Location
        queryset_pagination = settings.ELASTICSEARCH_DSL_QUERYSET_PAGINATION
```

12.14 FAQ

You will find a lot of useful information in the documentation.

Additionally, all raised issues that were questions have been marked as *question*, so you could take a look at the closed (question) issues.

12.14.1 Questions and answers

Question

- Is it possible to search sub string in word?
- How to implement partial/fuzzy search?

Answer

Yes. There are many ways doing this in Elasticsearch.

To mention a couple:

- You could use partial matching using NGrams. Partially shown here. The basic idea.
- Use contains functional filter.

Question

Can we use Django REST Framework `serializers.ModelSerializer` directly?

Answer

No, but you could use `serializers.Serializer`. Read the docs.

Question

How can I order search results overall relevance

Answer

That's `_score`. See the following example.

```
ordering = ('_score', 'id', 'title', 'price',)
```

In the given example, results are sorted by the `score` (which is relevance), then by `id`, `title` and `price`.

Question

How can I separate my development/production/acceptance/test indexes?

Answer

It's documented here.

Question

How can I sync my database with Elasticsearch indexes.

Answer

It's documented here.

Question

I keep getting `[FORBIDDEN/12/index read-only / allow delete (api)]` error when saving models despite having `blocks={'read_only_allow_delete': None}`, in settings.

Answer

Once of the possible reasons for the mentioned symptom might be low disk space.

12.15 Demo

12.15.1 Run demo locally

In order to be able to quickly evaluate the `django-elasticsearch-dsl-drf`, a demo app (with a quick installer) has been created (works on Ubuntu/Debian, may work on other Linux systems as well, although not guaranteed). Follow the instructions below for having the demo running within a minute.

12.15.2 Prerequisites

- Python 3
- Docker

Grab and run Elasticsearch:

```
docker pull docker.elastic.co/elasticsearch/elasticsearch:5.5.3
docker run -p 9200:9200 -e "discovery.type=single-node" -e "xpack.security.
↪enabled=false" docker.elastic.co/elasticsearch/elasticsearch:5.5.3
```

Grab and run the latest `django_elasticsearch_dsl_drf_demo_installer.sh`:

```
wget -O - https://raw.github.com/barseghyanartur/django-elasticsearch-dsl-drf/stable/
↪examples/django_elasticsearch_dsl_drf_demo_installer.sh | bash
```

Open your browser and test the app.

- URL: http://127.0.0.1:8001/search/

12.16 frontend demo for django-elasticsearch-dsl-drf

Frontend demo for django-elasticsearch-dsl-drf

Based on Book model, BookDocument and BookFrontendDocumentViewSet viewset.

12.16.1 Quick start

From the project root directory.

12.16.1.1 Install the django requirements

Since project supports Django versions from 1.8 to 2.1, you may install any version you want.

To install latest LTS version, do:

```
pip install -r examples/requirements/django_1_11.txt
```

12.16.1.2 Install Elasticsearch requirements

Since project supports Elasticsearch versions from 2.x to 6.x, you may install any version you want.

To install requirements for 6.x, do:

```
pip install -r examples/requirements/elastic_6x.txt
```

12.16.1.3 Run Elasticsearch

It's really easy using Docker.

To run 6.3.2 using Docker, do:

```
docker pull docker.elastic.co/elasticsearch/elasticsearch:6.3.2
docker run -p 9200:9200 -e "discovery.type=single-node" -e "xpack.security.
↪enabled=false" docker.elastic.co/elasticsearch/elasticsearch:6.3.2
```

12.16.1.4 Build Elasticsearch index

First, create some test data:

```
./scripts/create_test_data.sh
```

Then build Elasticsearch index:

```
./scripts/rebuild_index.sh
```

12.16.1.5 Install React requirements

Note, that you should be using NodeJS > 7.5.

Typically, you would first do:

```
nvm use 9
```

Then run the installer:

```
./scripts/yarn_install.sh
```

12.16.1.6 Run Django

The following script would run the Django server which is used by the demo app.

```
./scripts/runserver.sh
```

12.16.1.7 Run React demo app

Finally, run the React demo app:

```
./scripts/frontend.sh
```

Open http://localhost:3000 to view the frontend in the browser.

12.17 Release history and notes

Sequence based identifiers are used for versioning (schema follows below):

```
major.minor[.revision]
```

- It's always safe to upgrade within the same minor version (for example, from 0.3 to 0.3.4).
- Minor version changes might be backwards incompatible. Read the release notes carefully before upgrading (for example, when upgrading from 0.3.4 to 0.4).
- All backwards incompatible changes are mentioned in this document.

12.17.1 0.20.4

2019-12-25

- Tested against Django 3.0.
- Tested against Python 3.8.
- Tested against Django REST Framework 3.11.
- Minor fixes.
- Test optimisations.

12.17.2 0.20.3

2019-09-20

- Testing the auxiliary versions module.

12.17.3 0.20.2

2019-08-30

- Minor improvements in test coverage.

12.17.4 0.20.1

2019-08-18

- Minor Elasticsearch 7.x compatibility fixes.

12.17.5 0.20

2019-08-17

- Adding Elasticsearch 7.x support.

12.17.6 0.19

2019-08-06

Note: Dropping support for Elasticsearch versions prior 6.x. This is unfortunate, but this project depends on the upstream `django-elasticsearch-dsl` where as of version 6.4.x the support for older Elasticsearch versions was dropped. Use `django-elasticsearch-dsl-drf` version 0.18 if you need to work with 5.x or 2.x.

- Dropping support for Elasticsearch versions prior to 6.x.

12.17.7 0.18

2019-06-26

Note: Support for Django versions prior 1.11 has been dropped. Support for Django REST Framework prior 3.9 has been dropped.

- Dropping support for Django versions prior 1.11.
- Dropping support for Django REST Framework versions prior 3.9.
- Fix Django REST Framework deprecations.

12.17.8 0.17.7

2019-05-30

Note: Support for Django 1.8, 1.9 and 1.10 will be dropped in the next release. As usual, compatibility shims won't be removed directly. The change will affect the test matrix only first.

- Prevent unicode errors in tests on Python 2.7.
- Fixes in occasionally failing search test (`test_search` and `test_filtering_geo_spatial`).
- Working travis.
- Fixed issue with errors on empty `ids` filter.

12.17.9 0.17.6

2019-04-08

- Minor fixes.
- Additions to the docs.

12.17.10 0.17.5

2019-04-03

Note: Dropping support for Python 3.4. As of this version everything works, but no longer tested.

- Minor fixes.
- Dropping Python 3.4 support.
- Django 2.2 support.

12.17.11 0.17.4

2019-03-13

- Source backend.

12.17.12 0.17.3

2019-02-08

- Obey object permissions.

12.17.13 0.17.2

2019-01-07

- Add nested ordering.

12.17.14 0.17.1

2018-12-12

- Skipping the new context suggester tests for Elasticsearch 2.x and a number of other 2.x related fixes in tests.
- A number of 5.x fixes in tests.

12.17.15 0.17

2018-12-12

Note: Release supported by whythawk.

- Added support for context suggesters (*category* and *geo*). Note, that this functionality is available for Elasticsearch 5.x and 6.x (thus, not for Elasticsearch 2.x).
- Added support for *size* attribute on suggesters.

12.17.16 0.16.3

2018-10-31

Note: Release dedicated to Charles Aznavour.

- Make it possible to ignore certain Elastic exceptions by providing the appropriate `ignore` argument (on the view level). Default behaviour is intact. Set it to a list of integers (error codes) if you need it so.

12.17.17 0.16.2

2018-09-21

- Tested yet untested `pip_helpers` module.
- More tests.

12.17.18 0.16.1

2018-09-18

- Make it possible to control the size of the functional suggester queries.

12.17.19 0.16

2018-09-10

Note: This release contains minor backwards incompatible changes. You might need to update your code if you have been making use of nested search.

Old way of declaring nested search fields

```
search_nested_fields = {
    'country': ['name'],
    'country.city': ['name'],
}
```

New way of declaring nested search fields

```
search_nested_fields = {
    'country': {
        'path': 'country',
        'fields': ['name'],
    },
    'city': {
        'path': 'country.city',
```

(continues on next page)

(continued from previous page)

```
        'fields': ['name'],
    },
}
```

- Changes in nested search. This affects usage of both historical `SearchFilterBackend` and `CompoundSearchFilterBackend`. Update your code accordingly.
- Take meta property `using` of the document `Meta` into consideration.

12.17.20 0.15.1

2018-08-22

- More tests.
- Fixes in docs.

12.17.21 0.15

2018-08-10

- Global aggregations.

12.17.22 0.14

2018-08-06

- More like this support through detail action.

12.17.23 0.13.2

2018-08-03

- Successfully tested against Python 3.7 and Django 2.1.
- Unified the base `BaseSearchFilterBackend` class.
- Minor clean up and fixes in docs.
- Upgrading test suite to modern versions (`pytest`, `tox`, `factory_boy`, `Faker`). Removing unused dependencies from requirements (`drf-extensions`).
- Fixed missing PDF generation in offline documentation (non ReadTheDocs). The `rst2pdf` package (which does not support Python 3) has been replaced with `rinohtype` package (which does support Python 3).

12.17.24 0.13.1

2018-07-26

- Minor fix in suggesters on Elasticsearch 6.x.

12.17.25 0.13

2018-07-23

Note: Release dedicated to Guido van Rossum, the former Python BDFL, who resigned from his BDFL position recently. Guido knew it better than we all do. His charisma, talent and leadership will be certainly missed a lot by the community. Thumbs up again for the best BDFL ever.

- The `SimpleQueryStringSearchFilterBackend` backend has been implemented.
- Minor fixes in the `MultiMatchSearchFilterBackend` backend.

12.17.26 0.12

2018-07-21

- New-style Search Filter Backends. Old style `SearchFilterBackend` is still supported (until at least version 0.16), but is deprecated. Migrate to `CompoundSearchFilterBackend`. `MultiMatchSearchFilterBackend` introduced (the name speaks for itself).
- From now on, your views would also work with model- and object-level permissions of the Django REST Framework (such as `DjangoModelPermissions`, `DjangoModelPermissionsOrAnonReadOnly` and `DjangoObjectPermissions`). Correspondent model or object would be used for that. If you find it incorrect in your case, write custom permissions and declare the explicitly in your view-sets.
- Fixed geo-spatial `geo_distance` ordering for Elastic 5.x. and 6.x.
- Fixes occasionally failing tests.

12.17.27 0.11

2018-07-15

Note: This release contains backwards incompatible changes. You should update your Django code and front-end parts of your applications that were relying on the complex queries using `|` and `:` chars in the GET params.

Note: If you have used custom filter backends using `SEPARATOR_LOOKUP_VALUE`, `SEPARATOR_LOOKUP_COMPLEX_VALUE` or `SEPARATOR_LOOKUP_COMPLEX_MULTIPLE_VALUE` constants or `split_lookup_complex_value` helper method of the `FilterBackendMixin`, you most likely want to run your functional tests to see if everything still works.

Note: Do not keep things as they were in your own fork, since new search backends will use the `|` and `:` symbols differently.

Examples of old API requests vs new API requests

Note: Note, that `|` and `:` chars were mostly replaced with `__` and `,`.

Old API requests

```
http://127.0.0.1:8080/search/publisher/?search=name|reilly&search=city|london
http://127.0.0.1:8000/search/publishers/?location__geo_distance=100000km|12.04|-63.93
http://localhost:8000/api/articles/?id__terms=1|2|3
http://localhost:8000/api/users/?age__range=16|67|2.0
http://localhost:8000/api/articles/?id__in=1|2|3
http://localhost:8000/api/articles/?location__geo_polygon=40,-70|30,-80|20,-90|_
↪name:myname|validation_method:IGNORE_MALFORMED
```

New API requests

```
http://127.0.0.1:8080/search/publisher/?search=name:reilly&search=city:london
http://127.0.0.1:8000/search/publishers/?location__geo_distance=100000km__12.04__-63.
↪93
http://localhost:8000/api/articles/?id__terms=1__2__3
http://localhost:8000/api/users/?age__range=16__67__2.0
http://localhost:8000/api/articles/?id__in=1__2__3
http://localhost:8000/api/articles/?location__geo_polygon=40,-70__30,-80__20,-90___
↪name,myname__validation_method,IGNORE_MALFORMED
```

- `SEPARATOR_LOOKUP_VALUE` has been removed. Use `SEPARATOR_LOOKUP_COMPLEX_VALUE` and `SEPARATOR_LOOKUP_COMPLEX_MULTIPLE_VALUE` instead.
- `SEPARATOR_LOOKUP_NAME` has been added.
- The method `split_lookup_complex_value` has been removed. Use `split_lookup_complex_value` instead.
- Default filter lookup option is added. In past, if no specific lookup was provided and there were multiple values for a single field to filter on, by default `terms` filter was used. The `term` lookup was used by default in similar situation for a single value to filter on. It's now possible to declare default lookup which will be used when no lookup is given.
- Removed deprecated `views` module. Import from `viewsets` instead.
- Removed undocumented `get_count` helper from `helpers` module.

12.17.28 0.10

2018-07-06

- Elasticsearch 6.x support.
- Minor fixes.

12.17.29 0.9

2018-07-04

- Introduced `post_filter` support.
- Generalised the `FilteringFilterBackend` backend. Both `PostFilterFilteringFilterBackend` and `NestedFilteringFilterBackend` backends are now primarily based on it.
- Reduced Elastic queries from 3 to 2 when using `LimitOffsetPagination`.

12.17.30 0.8.4

2018-06-27

Note: Release supported by Goldmund, Wyldebeast & Wunderliebe.

- Added `NestedFilteringFilterBackend` backend.
- Documentation updated with examples of implementing a nested aggregations/facets.

12.17.31 0.8.3

2018-06-25

- It's possible to retrieve original dictionary from `DictionaryProxy` object.
- Added helper wrappers and helper functions as a temporary fix for issues in the `django-elasticsearch-dsl`.

12.17.32 0.8.2

2018-06-05

- Minor fixes.

12.17.33 0.8.1

2018-06-05

- Fixed wrong filter name in functional suggesters results into an error on Django 1.10 (and prior).
- Documentation improvements.

12.17.34 0.8

2018-06-01

Note: Release supported by Goldmund, Wyldebeast & Wunderliebe.

Note: This release contain minor backwards incompatible changes. You should update your code.

- (1) `BaseDocumentViewSet` (which from now on does not contain `suggest` functionality) has been renamed to `DocumentViewSet` (which does contain `suggest` functionality).
- (2) You should no longer import from `django_elasticsearch_dsl_drf.views`. Instead, import from `django_elasticsearch_dsl_drf.viewsets`.

- Deprecated `django_elasticsearch_dsl_drf.views` in favour of `django_elasticsearch_dsl_drf.viewsets`.
- Suggest action/method has been moved to `SuggestMixin` class.

- `FunctionalSuggestMixin` class introduced which resembled functionality of the `SuggestMixin` with several improvements/additions, such as advanced filtering and context-aware suggestions.
- You can now define a default suggester in `suggester_fields` which will be used if you do not provide suffix for the filter name.

12.17.35 0.7.2

2018-05-09

Note: Release dedicated to the Victory Day, the victims of the Second World War and Liberation of Shushi.

- Django REST framework 3.8.x support.

12.17.36 0.7.1

2018-04-04

Note: Release supported by Goldmund, Wyldebeast & Wunderliebe.

- Add query *boost* support for search fields.

12.17.37 0.7

2018-03-08

Note: Dear ladies, congratulations on International Women's Day

- CoreAPI/CoreSchema support.

12.17.38 0.6.4

2018-03-05

- Minor fix: explicitly use DocType in the ViewSets.

12.17.39 0.6.3

2018-01-03

- Minor fix in the search backend.
- Update the year in the license and code.

12.17.40 0.6.2

2017-12-29

- Update example project (and the tests that are dependant on the example project) to work with Django 2.0.
- Set minimal requirement for `django-elasticsearch-dsl` to 3.0.

12.17.41 0.6.1

2017-11-28

- Documentation fixes.

12.17.42 0.6

2017-11-28

- Added highlight backend.
- Added nested search functionality.

12.17.43 0.5.1

2017-10-18

- Fixed serialization of complex nested structures (lists of nested objects).
- Documentation fixes.

12.17.44 0.5

2017-10-05

Note: This release contains changes that might be backwards incompatible for your project. If you have used dynamic document serializer `django_elasticsearch_dsl_drf.serializers.DocumentSerializer` with customisations (with use of `serializers.SerializerMethodField`, having the value parsed to JSON), just remove the custom parts.

- Support for `ObjectField`, `NestedField`, `GeoPointField`, `ListField`, `GeoShapeField` (and in general, nesting fields either as a dictionary or list should not be a problem at all).
- Dynamic serializer has been made less strict.
- Added `get_paginated_response_context` methods to both `PageNumberPagination` and `LimitOffsetPagination` pagination classes to simplify customisations.

12.17.45 0.4.4

2017-10-02

- Documentation improvements (Elasticsearch suggestions).
- More tests (term and phrase suggestions).

- Code style fixes.

12.17.46 0.4.3

2017-09-28

- Documentation fixes.
- Fixes in tests.
- Improved factories.

12.17.47 0.4.2

2017-09-28

- Added `geo_bounding_box` query support to the geo-spatial features.

12.17.48 0.4.1

2017-09-26

- Fixes in docs.

12.17.49 0.4

2017-09-26

Note: This release contains changes that might be backwards incompatible for your project. Make sure to add the `DefaultOrderingFilterBackend` everywhere you have used the `OrderingFilterBackend`, right after the latter.

- `GeoSpatialFilteringFilterBackend` filtering backend, supporting `geo_distance` and `geo_polygon` geo-spatial queries.
- `GeoSpatialOrderingFilterBackend` ordering backend, supporting ordering of results for `geo_distance` filter.
- `OrderingFilterBackend` no longer provides defaults when no ordering is given. In order to take care of the defaults include the `DefaultOrderingFilterBackend` in the list of `filter_backends` (after all other ordering backends).

12.17.50 0.3.12

2017-09-21

- Added `geo_distance` filter. Note, that although functionally the filter would not change its' behaviour, it is likely to be moved to a separate backend (`geo_spatial`). For now use as is.
- Minor fixes.

12.17.51 0.3.11

2017-09-21

- Added `query` argument to `more_like_this` helper.

12.17.52 0.3.10

2017-09-20

- Minor fixes.
- Simplified Elasticsearch version check.

12.17.53 0.3.9

2017-09-12

- Python 2.x compatibility fix.

12.17.54 0.3.8

2017-09-12

- Fixes tests on some environments.

12.17.55 0.3.7

2017-09-07

- Docs fixes.

12.17.56 0.3.6

2017-09-07

- Fixed suggestions test for Elasticsearch 5.x.
- Added *compat* module for painless testing of Elastic 2.x to Elastic 5.x transition.

12.17.57 0.3.5

2017-08-24

- Minor fixes in the ordering backend.
- Improved tests and coverage.

12.17.58 0.3.4

2017-08-23

- Minor fixes in the ordering backend.

12.17.59 0.3.3

2017-07-13

- Minor fixes and improvements.

12.17.60 0.3.2

2017-07-12

- Minor fixes and improvements.

12.17.61 0.3.1

2017-07-12

- Minor Python2 fixes.
- Minor documentation fixes.

12.17.62 0.3

2017-07-11

- Add suggestions support (`term`, `phrase` and `completion`).

12.17.63 0.2.6

2017-07-11

- Minor fixes.
- Fixes in documentation.

12.17.64 0.2.5

2017-07-11

- Fixes in documentation.

12.17.65 0.2.4

2017-07-11

- Fixes in documentation.

12.17.66 0.2.3

2017-07-11

- Fixes in documentation.

12.17.67 0.2.2

2017-07-11

- Fixes in documentation.

12.17.68 0.2.1

2017-07-11

- Fixes in documentation.

12.17.69 0.2

2017-07-11

- Initial faceted search support.
- Pagination support.

12.17.70 0.1.8

2017-06-26

- Python2 fixes.
- Documentation and example project improvements.

12.17.71 0.1.7

2017-06-25

- Dynamic serializer for Documents.
- Major improvements in documentation.

12.17.72 0.1.6

2017-06-23

- Implemented `gt`, `gte`, `lt` and `lte` functional query lookups.
- Implemented `ids` native filter lookup.

12.17.73 0.1.5

2017-06-22

- Implemented `endswith` and `contains` functional filters.
- Added tests for `wildcard`, `exists`, `exclude` and `isnull` filters. Improved `range` filter tests.
- Improve `more_like_this` helper test.
- Improve ordering tests.

- Two additional arguments added to the `more_like_this` helper: `min_doc_freq` and `max_doc_freq`.
- Minor documentation improvements.

12.17.74 0.1.4

2017-06-22

- Added tests for `in`, `term` and `terms` filters.
- Minor documentation fixes.

12.17.75 0.1.3

2017-06-21

- Added tests for `more_like_this` helper, `range` and `prefix` filters.
- Minor documentation improvements.

12.17.76 0.1.2

2017-06-20

- Minor fixes in tests.

12.17.77 0.1.1

2017-06-20

- Fixes in `more_like_this` helper.
- Tiny documentation improvements.

12.17.78 0.1

2017-06-19

- Initial beta release.

12.18 django_elasticsearch_dsl_drf package

12.18.1 Subpackages

12.18.1.1 django_elasticsearch_dsl_drf.fields package

12.18.1.1.1 Submodules

12.18.1.1.2 django_elasticsearch_dsl_drf.fields.common module

Common fields.

class `django_elasticsearch_dsl_drf.fields.common.`**`BooleanField`**(*read_only=False, write_only=False, required=None, default=<class 'rest_framework.fields.empty'>, initial=<class 'rest_framework.fields.empty'>, source=None, label=None, help_text=None, style=None, error_messages=None, validators=None, allow_null=False*)

Bases: `rest_framework.fields.BooleanField`

Object field.

`get_value`(*dictionary*)

Get value.

`to_representation`(*value*)

To representation.

class `django_elasticsearch_dsl_drf.fields.common.`**`CharField`**(***kwargs*)

Bases: `rest_framework.fields.CharField`

Object field.

`get_value`(*dictionary*)

Get value.

`to_representation`(*value*)

To representation.

class `django_elasticsearch_dsl_drf.fields.common.`**`DateField`**(*format=<class 'rest_framework.fields.empty'>, input_formats=None, *args, **kwargs*)

Bases: `rest_framework.fields.DateField`

Object field.

`get_value`(*dictionary*)

Get value.

`to_representation`(*value*)

To representation.

class `django_elasticsearch_dsl_drf.fields.common.`**`FloatField`**(***kwargs*)

Bases: `rest_framework.fields.FloatField`

Object field.

`get_value`(*dictionary*)

Get value.

`to_representation`(*value*)

To representation.

class `django_elasticsearch_dsl_drf.fields.common.`**`IntegerField`**(***kwargs*)

Bases: `rest_framework.fields.IntegerField`

Object field.

`get_value`(*dictionary*)

Get value.

`to_representation`(*value*)

To representation.

class `django_elasticsearch_dsl_drf.fields.common.`**`IPAddressField`**(*protocol='both', **kwargs*)

Bases: `rest_framework.fields.IPAddressField`

Object field.

`get_value`(*dictionary*)

Get value.

`to_representation`(*value*)

To representation.

12.18.1.1.3 django_elasticsearch_dsl_drf.fields.helpers module

Helpers.

`django_elasticsearch_dsl_drf.fields.helpers.`**`to_representation`**(*value*)

To representation.

12.18.1.1.4 django_elasticsearch_dsl_drf.fields.nested_fields module

Nested fields.

class `django_elasticsearch_dsl_drf.fields.nested_fields.`**`GeoPointField`**(*read_only=False, write_only=False, required=None, default=<class 'rest_framework.fields.empty'>, initial=<class 'rest_framework.fields.empty'>, source=None, label=None, help_text=None, style=None, error_messages=None, validators=None, allow_null=False*)

Bases: *`django_elasticsearch_dsl_drf.fields.nested_fields.ObjectField`*

Geo point field.

class `django_elasticsearch_dsl_drf.fields.nested_fields.`**`GeoShapeField`**(*read_only=False, write_only=False, required=None, default=<class 'rest_framework.fields.empty'>, initial=<class 'rest_framework.fields.empty'>, source=None, label=None, help_text=None, style=None, error_messages=None, validators=None, allow_null=False*)

Bases: `django_elasticsearch_dsl_drf.fields.nested_fields.ObjectField`

Geo shape field.

class `django_elasticsearch_dsl_drf.fields.nested_fields.`**`NestedField`**(*read_only=False, write_only=False, required=None, default=<class 'rest_framework.fields.empty'>, initial=<class 'rest_framework.fields.empty'>, source=None, label=None, help_text=None, style=None, error_messages=None, validators=None, allow_null=False*)

Bases: `django_elasticsearch_dsl_drf.fields.nested_fields.ObjectField`

Nested field.

class `django_elasticsearch_dsl_drf.fields.nested_fields.`**`ObjectField`**(*read_only=False, write_only=False, required=None, default=<class 'rest_framework.fields.empty'>, initial=<class 'rest_framework.fields.empty'>, source=None, label=None, help_text=None, style=None, error_messages=None, validators=None, allow_null=False*)

Bases: `rest_framework.fields.Field`

Object field.

`get_value`(*dictionary*)

Get value.

`to_internal_value`(*data*)

To internal value.

`to_representation`(*value*)

To representation.

class `django_elasticsearch_dsl_drf.fields.nested_fields.`**`ListField`**(*read_only=False, write_only=False, required=None, default=<class 'rest_framework.fields.empty'>, initial=<class 'rest_framework.fields.empty'>, source=None, label=None, help_text=None, style=None, error_messages=None, validators=None, allow_null=False*)

Bases: `rest_framework.fields.Field`

List field.

get_value(*dictionary*)
Get value.

to_internal_value(*data*)
To internal value.

to_representation(*value*)
To representation.

12.18.1.1.5 Module contents

Fields.

class `django_elasticsearch_dsl_drf.fields.`**BooleanField**(*read_only=False, write_only=False, required=None, default=<class 'rest_framework.fields.empty'>, initial=<class 'rest_framework.fields.empty'>, source=None, label=None, help_text=None, style=None, error_messages=None, validators=None, allow_null=False*)

Bases: `rest_framework.fields.BooleanField`

Object field.

get_value(*dictionary*)
Get value.

to_representation(*value*)
To representation.

class `django_elasticsearch_dsl_drf.fields.`**CharField**(***kwargs*)

Bases: `rest_framework.fields.CharField`

Object field.

get_value(*dictionary*)
Get value.

to_representation(*value*)
To representation.

class `django_elasticsearch_dsl_drf.fields.`**DateField**(*format=<class 'rest_framework.fields.empty'>, input_formats=None, *args, **kwargs*)

Bases: `rest_framework.fields.DateField`

Object field.

get_value(*dictionary*)
Get value.

to_representation(*value*)
To representation.

class `django_elasticsearch_dsl_drf.fields.`**FloatField**(***kwargs*)
Bases: `rest_framework.fields.FloatField`

Object field.

get_value(*dictionary*)
Get value.

to_representation(*value*)
To representation.

class `django_elasticsearch_dsl_drf.fields.`**GeoPointField**(*read_only=False, write_only=False, required=None, default=<class 'rest_framework.fields.empty'>, initial=<class 'rest_framework.fields.empty'>, source=None, label=None, help_text=None, style=None, error_messages=None, validators=None, allow_null=False*)
Bases: `django_elasticsearch_dsl_drf.fields.nested_fields.ObjectField`

Geo point field.

class `django_elasticsearch_dsl_drf.fields.`**GeoShapeField**(*read_only=False, write_only=False, required=None, default=<class 'rest_framework.fields.empty'>, initial=<class 'rest_framework.fields.empty'>, source=None, label=None, help_text=None, style=None, error_messages=None, validators=None, allow_null=False*)
Bases: `django_elasticsearch_dsl_drf.fields.nested_fields.ObjectField`

Geo shape field.

class `django_elasticsearch_dsl_drf.fields.`**IntegerField**(***kwargs*)
Bases: `rest_framework.fields.IntegerField`

Object field.

get_value(*dictionary*)
Get value.

to_representation(*value*)
To representation.

class `django_elasticsearch_dsl_drf.fields.`**`IPAddressField`**(*protocol='both', **kwargs*)

Bases: `rest_framework.fields.IPAddressField`

Object field.

`get_value`(*dictionary*)
Get value.

`to_representation`(*value*)
To representation.

class `django_elasticsearch_dsl_drf.fields.`**`ListField`**(*read_only=False, write_only=False, required=None, default=<class 'rest_framework.fields.empty'>, initial=<class 'rest_framework.fields.empty'>, source=None, label=None, help_text=None, style=None, error_messages=None, validators=None, allow_null=False*)

Bases: `rest_framework.fields.Field`

List field.

`get_value`(*dictionary*)
Get value.

`to_internal_value`(*data*)
To internal value.

`to_representation`(*value*)
To representation.

class `django_elasticsearch_dsl_drf.fields.`**`NestedField`**(*read_only=False, write_only=False, required=None, default=<class 'rest_framework.fields.empty'>, initial=<class 'rest_framework.fields.empty'>, source=None, label=None, help_text=None, style=None, error_messages=None, validators=None, allow_null=False*)

Bases: `django_elasticsearch_dsl_drf.fields.nested_fields.ObjectField`

Nested field.

class `django_elasticsearch_dsl_drf.fields.`**`ObjectField`**(*read_only=False, write_only=False, required=None, default=<class 'rest_framework.fields.empty'>, initial=<class 'rest_framework.fields.empty'>, source=None, label=None, help_text=None, style=None, error_messages=None, validators=None, allow_null=False*)

Bases: `rest_framework.fields.Field`

Object field.

`get_value`(*dictionary*)
Get value.

`to_internal_value`(*data*)
To internal value.

`to_representation`(*value*)
To representation.

12.18.1.2 django_elasticsearch_dsl_drf.filter_backends package

12.18.1.2.1 Subpackages

12.18.1.2.1.1 django_elasticsearch_dsl_drf.filter_backends.aggregations package

12.18.1.2.1.2 Submodules

12.18.1.2.1.3 django_elasticsearch_dsl_drf.filter_backends.aggregations.bucket_aggregations module

12.18.1.2.1.4 django_elasticsearch_dsl_drf.filter_backends.aggregations.metrics_aggregations module

12.18.1.2.1.5 django_elasticsearch_dsl_drf.filter_backends.aggregations.pipeline_aggregations module

12.18.1.2.1.6 Module contents

12.18.1.2.1.7 django_elasticsearch_dsl_drf.filter_backends.filtering package

12.18.1.2.1.8 Submodules

12.18.1.2.1.9 django_elasticsearch_dsl_drf.filter_backends.filtering.common module

Common filtering backend.

class `django_elasticsearch_dsl_drf.filter_backends.filtering.common.`**`FilteringFilterBackend`**

Bases: `rest_framework.filters.BaseFilterBackend`, *`django_elasticsearch_dsl_drf.filter_backends.mixins.FilterBackendMixin`*

Filtering filter backend for Elasticsearch.

Example:

```
>>> from django_elasticsearch_dsl_drf.constants import (
>>>     LOOKUP_FILTER_PREFIX,
>>>     LOOKUP_FILTER_WILDCARD,
>>>     LOOKUP_QUERY_EXCLUDE,
>>>     LOOKUP_QUERY_ISNULL,
>>> )
>>> from django_elasticsearch_dsl_drf.filter_backends import (
>>>     FilteringFilterBackend
>>> )
>>> from django_elasticsearch_dsl_drf.viewsets import (
>>>     BaseDocumentViewSet,
>>> )
>>>
>>> # Local article document definition
>>> from .documents import ArticleDocument
>>>
>>> # Local article document serializer
>>> from .serializers import ArticleDocumentSerializer
>>>
>>> class ArticleDocumentView(BaseDocumentViewSet):
>>>
>>>     document = ArticleDocument
>>>     serializer_class = ArticleDocumentSerializer
>>>     filter_backends = [FilteringFilterBackend,]
>>>     filter_fields = {
>>>         'title': 'title.raw',
>>>         'state': {
>>>             'field': 'state.raw',
>>>             'lookups': [
>>>                 LOOKUP_FILTER_PREFIX,
>>>                 LOOKUP_FILTER_WILDCARD,
>>>                 LOOKUP_QUERY_EXCLUDE,
>>>                 LOOKUP_QUERY_ISNULL,
>>>             ],
>>>             'default_lookup': LOOKUP_FILTER_WILDCARD,
>>>         }
>>> }
```

classmethod **`apply_filter_prefix`**(*queryset*, *options*, *value*)

Apply *prefix* filter.

Syntax:

/endpoint/?field_name__prefix={value}

Example:

http://localhost:8000/api/articles/?tags__prefix=bio

Parameters

- **`queryset`** (*`elasticsearch_dsl.search.Search`*) – Original queryset.

- **options** (*dict*) – Filter options.
- **value** (*str*) – value to filter on.

Returns Modified queryset.

Return type elasticsearch_dsl.search.Search

classmethod apply_filter_range(*queryset*, *options*, *value*)

Apply *range* filter.

Syntax:

/endpoint/?field_name__range={lower}__{upper}__{boost} /endpoint/?field_name__range={lower}__{upper}

Example:

http://localhost:8000/api/users/?age__range=16__67__2.0 http://localhost:8000/api/users/?age__range=16__67 http://localhost:8000/api/users/?age__range=16

Parameters

- **queryset** (*elasticsearch_dsl.search.Search*) – Original queryset.
- **options** (*dict*) – Filter options.
- **value** (*str*) – value to filter on.

Returns Modified queryset.

Return type elasticsearch_dsl.search.Search

classmethod apply_filter_term(*queryset*, *options*, *value*)

Apply *term* filter.

Syntax:

/endpoint/?field_name={value}

Example:

http://localhost:8000/api/articles/?tags=children

Parameters

- **queryset** (*elasticsearch_dsl.search.Search*) – Original queryset.
- **options** (*dict*) – Filter options.
- **value** (*str*) – value to filter on.

Returns Modified queryset.

Return type elasticsearch_dsl.search.Search

classmethod apply_filter_terms(*queryset*, *options*, *value*)

Apply *terms* filter.

Syntax:

/endpoint/?field_name__terms={value1}__{value2} /endpoint/?field_name__terms={value1}

Note, that number of values is not limited.

Example:

http://localhost:8000/api/articles/?tags__terms=children__python http://localhost:8000/api/articles/?tags__terms=children

Parameters

- **queryset** (*elasticsearch_dsl.search.Search*) – Original queryset.
- **options** (*dict*) – Filter options.
- **value** (*mixed: either str or iterable (list, tuple)*) – value to filter on.

Returns Modified queryset.

Return type elasticsearch_dsl.search.Search

classmethod apply_query_contains(*queryset*, *options*, *value*)

Apply *contains* filter.

Syntax:

/endpoint/?field_name__contains={value}

Example:

http://localhost:8000/api/articles/?state__contains=lis

Parameters

- **queryset** (*elasticsearch_dsl.search.Search*) – Original queryset.
- **options** (*dict*) – Filter options.
- **value** (*str*) – value to filter on.

Returns Modified queryset.

Return type elasticsearch_dsl.search.Search

classmethod apply_query_endswith(*queryset*, *options*, *value*)

Apply *endswith* filter.

Syntax:

/endpoint/?field_name__endswith={value}

Example:

http://localhost:8000/api/articles/?tags__endswith=dren

Parameters

- **queryset** (*elasticsearch_dsl.search.Search*) – Original queryset.
- **options** (*dict*) – Filter options.
- **value** (*str*) – value to filter on.

Returns Modified queryset.

Return type elasticsearch_dsl.search.Search

classmethod apply_query_exclude(*queryset*, *options*, *value*)

Apply *exclude* functional query.

Syntax:

/endpoint/?field_name__isnull={value1}__{value2} /endpoint/?field_name__exclude={valu1}

Note, that number of values is not limited.

Example:

http://localhost:8000/api/articles/?tags__exclude=children__python http://localhost:8000/api/articles/?tags__exclude=children

Parameters

- **queryset** (*elasticsearch_dsl.search.Search*) – Original queryset.
- **options** (*dict*) – Filter options.
- **value** (*str*) – value to filter on.

Returns Modified queryset.

Return type elasticsearch_dsl.search.Search

classmethod apply_query_exists(*queryset*, *options*, *value*)

Apply *exists* filter.

Syntax:

/endpoint/?field_name__exists=true /endpoint/?field_name__exists=false

Example:

http://localhost:8000/api/articles/?tags__exists=true http://localhost:8000/api/articles/?tags__exists=false

Parameters

- **queryset** (*elasticsearch_dsl.search.Search*) – Original queryset.
- **options** (*dict*) – Filter options.
- **value** (*str*) – value to filter on.

Returns Modified queryset.

Return type elasticsearch_dsl.search.Search

classmethod apply_query_gt(*queryset*, *options*, *value*)

Apply *gt* functional query.

Syntax:

/endpoint/?field_name__gt={value}__{boost} /endpoint/?field_name__gt={value}

Example:

http://localhost:8000/api/articles/?id__gt=1__2.0 http://localhost:8000/api/articles/?id__gt=1

Parameters

- **queryset** (*elasticsearch_dsl.search.Search*) – Original queryset.
- **options** (*dict*) – Filter options.
- **value** (*str*) – value to filter on.

Returns Modified queryset.

Return type elasticsearch_dsl.search.Search

classmethod apply_query_gte(*queryset*, *options*, *value*)

Apply *gte* functional query.

Syntax:

/endpoint/?field_name__gte={value}__{boost} /endpoint/?field_name__gte={value}

Example:

http://localhost:8000/api/articles/?id__gte=1__2.0 http://localhost:8000/api/articles/?id__gte=1

Parameters

- **queryset** (*elasticsearch_dsl.search.Search*) – Original queryset.
- **options** (*dict*) – Filter options.
- **value** (*str*) – value to filter on.

Returns Modified queryset.

Return type elasticsearch_dsl.search.Search

classmethod apply_query_in(*queryset*, *options*, *value*)

Apply *in* functional query.

Syntax:

/endpoint/?field_name__in={value1}__{value2} /endpoint/?field_name__in={value1}

Note, that number of values is not limited.

Example:

http://localhost:8000/api/articles/?tags__in=children__python

Parameters

- **queryset** (*elasticsearch_dsl.search.Search*) – Original queryset.
- **options** (*dict*) – Filter options.
- **value** (*str*) – value to filter on.

Returns Modified queryset.

Return type elasticsearch_dsl.search.Search

classmethod apply_query_isnull(*queryset*, *options*, *value*)

Apply *isnull* functional query.

Syntax:

/endpoint/?field_name__isnull=true /endpoint/?field_name__isnull=false

Example:

http://localhost:8000/api/articles/?tags__isnull=true http://localhost:8000/api/articles/?tags__isnull=false

Parameters

- **queryset** (*elasticsearch_dsl.search.Search*) – Original queryset.
- **options** (*dict*) – Filter options.
- **value** (*str*) – value to filter on.

Returns Modified queryset.

Return type elasticsearch_dsl.search.Search

classmethod apply_query_lt(*queryset*, *options*, *value*)

Apply *lt* functional query.

Syntax:

/endpoint/?field_name__lt={value}__{boost} /endpoint/?field_name__lt={value}

Example:

http://localhost:8000/api/articles/?id__lt=1__2.0 http://localhost:8000/api/articles/?id__lt=1

Parameters

- **queryset** (*elasticsearch_dsl.search.Search*) – Original queryset.
- **options** (*dict*) – Filter options.
- **value** (*str*) – value to filter on.

Returns Modified queryset.

Return type elasticsearch_dsl.search.Search

classmethod apply_query_lte(*queryset*, *options*, *value*)

Apply *lte* functional query.

Syntax:

/endpoint/?field_name__lte={value}__{boost} /endpoint/?field_name__lte={value}

Example:

http://localhost:8000/api/articles/?id__lte=1__2.0 http://localhost:8000/api/articles/?id__lte=1

Parameters

- **queryset** (*elasticsearch_dsl.search.Search*) – Original queryset.
- **options** (*dict*) – Filter options.
- **value** (*str*) – value to filter on.

Returns Modified queryset.

Return type elasticsearch_dsl.search.Search

classmethod apply_query_wildcard(*queryset*, *options*, *value*)

Apply *wildcard* filter.

Syntax:

/endpoint/?field_name__wildcard={value}* /endpoint/?field_name__wildcard=*{value} /endpoint/?field_name__wildcard=*{value}*

Example:

http://localhost:8000/api/articles/?tags__wildcard=child*

Parameters

- **queryset** (*elasticsearch_dsl.search.Search*) – Original queryset.

- **options** (*dict*) – Filter options.
- **value** (*str*) – value to filter on.

Returns Modified queryset.

Return type elasticsearch_dsl.search.Search

filter_queryset (*request*, *queryset*, *view*)

Filter the queryset.

Parameters

- **request** (*rest_framework.request.Request*) – Django REST framework request.
- **queryset** (*elasticsearch_dsl.search.Search*) – Base queryset.
- **view** (*rest_framework.viewsets.ReadOnlyModelViewSet*) – View.

Returns Updated queryset.

Return type elasticsearch_dsl.search.Search

get_coreschema_field (*field*)

get_filter_query_params (*request*, *view*)

Get query params to be filtered on.

Parameters

- **request** (*rest_framework.request.Request*) – Django REST framework request.
- **view** (*rest_framework.viewsets.ReadOnlyModelViewSet*) – View.

Returns Request query params to filter on.

Return type dict

classmethod get_gte_lte_params (*value*, *lookup*)

Get params for *gte*, *gt*, *lte* and *lt* query.

Syntax:

/endpoint/?field_name__gt={lower}__{boost} /endpoint/?field_name__gt={lower}

Example:

http://localhost:8000/api/articles/?id__gt=1 http://localhost:8000/api/articles/?id__gt=1__2.0

Parameters

- **value** (*str*) –
- **lookup** (*str*) –

Returns Params to be used in *range* query.

Return type dict

classmethod get_range_params (*value*)

Get params for *range* query.

Syntax:

/endpoint/?field_name__range={lower}__{upper}__{boost} /endpoint/?field_name__range={lower}__{upper}

Example:

http://localhost:8000/api/users/?age__range=16__67__2.0 http://localhost:8000/api/users/?age__range=16__67 http://localhost:8000/api/users/?age__range=16

Parameters **value** –

Type str

Returns Params to be used in *range* query.

Return type dict

get_schema_fields(*view*)

classmethod prepare_filter_fields(*view*)

Prepare filter fields.

Parameters **view** (*rest_framework.viewsets.ReadOnlyModelViewSet*) –

Returns Filtering options.

Return type dict

12.18.1.2.1.10 django_elasticsearch_dsl_drf.filter_backends.filtering.geo_spatial module

Geo spatial filtering backend.

Elasticsearch supports two types of geo data:

- geo_point fields which support lat/lon pairs
- geo_shape fields, which support points, lines, circles, polygons, multi-polygons etc.

The queries in this group are:

- geo_shape query: Find document with geo-shapes which either intersect, are contained by, or do not intersect with the specified geo-shape.
- geo_bounding_box query: Finds documents with geo-points that fall into the specified rectangle.
- geo_distance query: Finds document with geo-points within the specified distance of a central point.
- geo_distance_range query: Like the geo_distance query, but the range starts at a specified distance from the central point. Note, that this one is deprecated and this isn't implemented.
- geo_polygon query: Find documents with geo-points within the specified polygon.

class `django_elasticsearch_dsl_drf.filter_backends.filtering.geo_spatial.`**GeoSpatialFilteri**

Bases: `rest_framework.filters.BaseFilterBackend`, *`django_elasticsearch_dsl_drf.filter_backends.mixins.FilterBackendMixin`*

Geo-spatial filtering filter backend for Elasticsearch.

Example:

```
>>> from django_elasticsearch_dsl_drf.constants import (
>>>     LOOKUP_FILTER_GEO_DISTANCE,
>>> )
>>> from django_elasticsearch_dsl_drf.filter_backends import (
```

(continues on next page)

(continued from previous page)

```
>>>     GeoSpatialFilteringFilterBackend
>>> )
>>> from django_elasticsearch_dsl_drf.viewsets import (
>>>     BaseDocumentViewSet,
>>> )
>>>
>>> # Local article document definition
>>> from .documents import ArticleDocument
>>>
>>> # Local article document serializer
>>> from .serializers import ArticleDocumentSerializer
>>>
>>> class ArticleDocumentView(BaseDocumentViewSet):
>>>
>>>     document = ArticleDocument
>>>     serializer_class = ArticleDocumentSerializer
>>>     filter_backends = [GeoSpatialFilteringFilterBackend,]
>>>     geo_spatial_filter_fields = {
>>>         'loc': 'location',
>>>         'location': {
>>>             'field': 'location',
>>>             'lookups': [
>>>                 LOOKUP_FILTER_GEO_DISTANCE,
>>>             ],
>>>         }
>>> }
```

classmethod apply_query_geo_bounding_box(*queryset*, *options*, *value*)

Apply *geo_bounding_box* query.

Parameters

- **queryset** (*elasticsearch_dsl.search.Search*) – Original queryset.
- **options** (*dict*) – Filter options.
- **value** (*str*) – value to filter on.

Returns Modified queryset.

Return type elasticsearch_dsl.search.Search

classmethod apply_query_geo_distance(*queryset*, *options*, *value*)

Apply *geo_distance* query.

Parameters

- **queryset** (*elasticsearch_dsl.search.Search*) – Original queryset.
- **options** (*dict*) – Filter options.
- **value** (*str*) – value to filter on.

Returns Modified queryset.

Return type elasticsearch_dsl.search.Search

classmethod apply_query_geo_polygon(*queryset*, *options*, *value*)

Apply *geo_polygon* query.

Parameters

- **queryset** (*elasticsearch_dsl.search.Search*) – Original queryset.

- **options** (*dict*) – Filter options.
- **value** (*str*) – value to filter on.

Returns Modified queryset.

Return type elasticsearch_dsl.search.Search

filter_queryset (*request*, *queryset*, *view*)

Filter the queryset.

Parameters

- **request** (*rest_framework.request.Request*) – Django REST framework request.
- **queryset** (*elasticsearch_dsl.search.Search*) – Base queryset.
- **view** (*rest_framework.viewsets.ReadOnlyModelViewSet*) – View.

Returns Updated queryset.

Return type elasticsearch_dsl.search.Search

get_filter_query_params (*request*, *view*)

Get query params to be filtered on.

Parameters

- **request** (*rest_framework.request.Request*) – Django REST framework request.
- **view** (*rest_framework.viewsets.ReadOnlyModelViewSet*) – View.

Returns Request query params to filter on.

Return type dict

classmethod get_geo_bounding_box_params (*value*, *field*)

Get params for *geo_bounding_box* query.

Example:

/api/articles/?location__geo_bounding_box=40.73,-74.1__40.01,-71.12

Example:

/api/articles/?location__geo_polygon=40.73,-74.1 __40.01,-71.12 ___name,myname __validation_method,IGNORE_MALFORMED __type,indexed

Elasticsearch:

{

"query": {

"bool" [{]

"must" [{] "match_all" : {}

}, "filter" : {

"geo_bounding_box" [{]

"person.location" [{]

"top_left" [{] "lat" : 40.73, "lon" : -74.1

}, "bottom_right" : {

"lat" : 40.01, "lon" : -71.12

}

}

}

}

}

}

}

Parameters

- **value** (*str*) –
- **field** –

Returns Params to be used in *geo_bounding_box* query.

Return type dict

classmethod get_geo_distance_params(*value*, *field*)

Get params for *geo_distance* query.

Example:

/api/articles/?location__geo_distance=2km__43.53__-12.23

Parameters

- **value** (*str*) –
- **field** –

Returns Params to be used in *geo_distance* query.

Return type dict

classmethod get_geo_polygon_params(*value*, *field*)

Get params for *geo_polygon* query.

Example:

/api/articles/?location__geo_polygon=40,-70__30,-80__20,-90

Example:

/api/articles/?location__geo_polygon=40,-70 __30,-80 __20,-90 ___name,myname __validation_method,IGNORE_MALFORMED

Elasticsearch:

{

"query": {

"bool" [{]

"must" [{] "match_all" : {}

}, "filter" : {

"geo_polygon" [{]

"person.location" [{]

"points" [[] {"lat" : 40, "lon" : -70}, {"lat" : 30, "lon" : -80}, {"lat" : 20, "lon" : -90}

]

}

}

}

}

}

}

Parameters

- **value** (*str*) –
- **field** –

Returns Params to be used in *geo_distance* query.

Return type dict

classmethod prepare_filter_fields(*view*)

Prepare filter fields.

Parameters **view** (*rest_framework.viewsets.ReadOnlyModelViewSet*) –

Returns Filtering options.

Return type dict

12.18.1.2.1.11 django_elasticsearch_dsl_drf.filter_backends.filtering.ids module

Ids filtering backend.

Filters documents that only have the provided ids. Note, this query uses the *_uid* field.

Elastic query:

{

"query": {

"ids": { "type": "book_document", "values": ["68", "64", "58"]

}

}

}

REST framework request equivalent:

- http://localhost:8000/api/articles/?ids=68__64__58
- http://localhost:8000/api/articles/?ids=68&ids=64&ids=58

Official Elastic docs:

- https://www.elastic.co/guide/en/elasticsearch/reference/current/ query-dsl-ids-query.html

class `django_elasticsearch_dsl_drf.filter_backends.filtering.ids.`**IdsFilterBackend**

Bases: `rest_framework.filters.BaseFilterBackend`, *`django_elasticsearch_dsl_drf.filter_backends.mixins.FilterBackendMixin`*

Ids filter backend for Elasticsearch.

Example:

```
>>> from django_elasticsearch_dsl_drf.filter_backends import (
>>>     IdsFilterBackend
>>> )
>>> from django_elasticsearch_dsl_drf.viewsets import (
>>>     BaseDocumentViewSet,
>>> )
>>>
>>> # Local article document definition
>>> from .documents import ArticleDocument
>>>
>>> # Local article document serializer
>>> from .serializers import ArticleDocumentSerializer
>>>
>>> class ArticleDocumentView(BaseDocumentViewSet):
>>>
>>>     document = ArticleDocument
>>>     serializer_class = ArticleDocumentSerializer
>>>     filter_backends = [IdsFilterBackend]
```

filter_queryset (*request*, *queryset*, *view*)

Filter the queryset.

Parameters

- **request** (*rest_framework.request.Request*) – Django REST framework request.
- **queryset** (*elasticsearch_dsl.search.Search*) – Base queryset.
- **view** (*rest_framework.viewsets.ReadOnlyModelViewSet*) – View.

Returns Updated queryset.

Return type elasticsearch_dsl.search.Search

get_ids_query_params (*request*)

Get search query params.

Parameters **request** (*rest_framework.request.Request*) – Django REST framework request.

Returns List of search query params.

Return type list

get_ids_values (*request*, *view*)

Get ids values for query.

Parameters

- **request** (*rest_framework.request.Request*) – Django REST framework request.
- **queryset** (*elasticsearch_dsl.search.Search*) – Base queryset.
- **view** (*rest_framework.viewsets.ReadOnlyModelViewSet*) – View.

Returns Updated queryset.

Return type elasticsearch_dsl.search.Search

ids_query_param = 'ids'

12.18.1.2.1.12 django_elasticsearch_dsl_drf.filter_backends.filtering.nested module

Nested filtering backend.

class `django_elasticsearch_dsl_drf.filter_backends.filtering.nested.`**`NestedFilteringFilterBa`**

Bases: *`django_elasticsearch_dsl_drf.filter_backends.filtering.common.FilteringFilterBackend`*

Nested filter backend.

Example:

```
>>> from django_elasticsearch_dsl_drf.constants import (
>>>     LOOKUP_FILTER_TERM,
>>>     LOOKUP_FILTER_PREFIX,
>>>     LOOKUP_FILTER_WILDCARD,
>>>     LOOKUP_QUERY_EXCLUDE,
>>>     LOOKUP_QUERY_ISNULL,
>>> )
>>> from django_elasticsearch_dsl_drf.filter_backends import (
>>>     NestedFilteringFilterBackend
>>> )
>>> from django_elasticsearch_dsl_drf.viewsets import (
>>>     BaseDocumentViewSet,
>>> )
>>>
>>> # Local article document definition
>>> from .documents import ArticleDocument
>>>
>>> # Local article document serializer
>>> from .serializers import ArticleDocumentSerializer
>>>
>>> class ArticleDocumentView(BaseDocumentViewSet):
>>>
>>>     document = ArticleDocument
>>>     serializer_class = ArticleDocumentSerializer
>>>     filter_backends = [NestedFilteringFilterBackend,]
>>>     nested_filter_fields = {
>>>         'country': {
>>>             'field': 'continent.country.name.raw',
>>>             'path': 'continent.country',
>>>             'lookups': [
>>>                 LOOKUP_FILTER_TERM,
>>>                 LOOKUP_FILTER_TERMS,
>>>                 LOOKUP_FILTER_PREFIX,
>>>                 LOOKUP_FILTER_WILDCARD,
>>>                 LOOKUP_QUERY_EXCLUDE,
>>>                 LOOKUP_QUERY_ISNULL,
>>>             ],
>>>         }
>>> }
```

classmethod apply_filter(*queryset*, *options=None*, *args=None*, *kwargs=None*)

Apply filter.

Parameters

- **queryset** –
- **options** –

- **args** –
- **kwargs** –

Returns

classmethod apply_query(*queryset*, *options=None*, *args=None*, *kwargs=None*)

Apply query.

Parameters

- **queryset** –
- **options** –
- **args** –
- **kwargs** –

Returns

get_coreschema_field(*field*)

get_filter_field_nested_path(*filter_fields*, *field_name*)

Get filter field path to be used in nested query.

Parameters

- **filter_fields** –
- **field_name** –

Returns

get_filter_query_params(*request*, *view*)

Get query params to be filtered on.

Parameters

- **request** (*rest_framework.request.Request*) – Django REST framework request.
- **view** (*rest_framework.viewsets.ReadOnlyModelViewSet*) – View.

Returns Request query params to filter on.

Return type dict

get_schema_fields(*view*)

classmethod prepare_filter_fields(*view*)

Prepare filter fields.

Parameters **view** (*rest_framework.viewsets.ReadOnlyModelViewSet*) –

Returns Filtering options.

Return type dict

12.18.1.2.1.13 django_elasticsearch_dsl_drf.filter_backends.filtering.post_filter module

The `post_filter` filtering backend.

class `django_elasticsearch_dsl_drf.filter_backends.filtering.post_filter.`**PostFilterFilteri**

Bases: *`django_elasticsearch_dsl_drf.filter_backends.filtering.common.FilteringFilterBackend`*

The `post_filter` filtering filter backend for Elasticsearch.

Example:

```
>>> from django_elasticsearch_dsl_drf.constants import (
>>>     LOOKUP_FILTER_PREFIX,
>>>     LOOKUP_FILTER_WILDCARD,
>>>     LOOKUP_QUERY_EXCLUDE,
>>>     LOOKUP_QUERY_ISNULL,
>>> )
>>> from django_elasticsearch_dsl_drf.filter_backends import (
>>>     PostFilterFilteringFilterBackend
>>> )
>>> from django_elasticsearch_dsl_drf.viewsets import (
>>>     BaseDocumentViewSet,
>>> )
>>>
>>> # Local article document definition
>>> from .documents import ArticleDocument
>>>
>>> # Local article document serializer
>>> from .serializers import ArticleDocumentSerializer
>>>
>>> class ArticleDocumentView(BaseDocumentViewSet):
>>>
>>>     document = ArticleDocument
>>>     serializer_class = ArticleDocumentSerializer
>>>     filter_backends = [PostFilterFilteringFilterBackend,]
>>>     post_filter_fields = {
>>>         'title': 'title.raw',
>>>         'state': {
>>>             'field': 'state.raw',
>>>             'lookups': [
>>>                 LOOKUP_FILTER_PREFIX,
>>>                 LOOKUP_FILTER_WILDCARD,
>>>                 LOOKUP_QUERY_EXCLUDE,
>>>                 LOOKUP_QUERY_ISNULL,
>>>             ],
>>>         }
>>> }
```

classmethod apply_filter(*queryset*, *options=None*, *args=None*, *kwargs=None*)

Apply filter.

Parameters

- **queryset** –
- **options** –
- **args** –
- **kwargs** –

Returns

classmethod apply_query(*queryset*, *options=None*, *args=None*, *kwargs=None*)

Apply query.

Parameters

- **queryset** –
- **options** –
- **args** –
- **kwargs** –

Returns

get_coreschema_field(*field*)

get_schema_fields(*view*)

classmethod prepare_filter_fields(*view*)

Prepare filter fields.

Parameters **view**(*rest_framework.viewsets.ReadOnlyModelViewSet*) –

Returns Filtering options.

Return type dict

12.18.1.2.1.14 Module contents

Term level filtering and `post_filter` backends.

class `django_elasticsearch_dsl_drf.filter_backends.filtering.`**FilteringFilterBackend**

Bases: `rest_framework.filters.BaseFilterBackend`, *`django_elasticsearch_dsl_drf.filter_backends.mixins.FilterBackendMixin`*

Filtering filter backend for Elasticsearch.

Example:

```
>>> from django_elasticsearch_dsl_drf.constants import (
>>>     LOOKUP_FILTER_PREFIX,
>>>     LOOKUP_FILTER_WILDCARD,
>>>     LOOKUP_QUERY_EXCLUDE,
>>>     LOOKUP_QUERY_ISNULL,
>>> )
>>> from django_elasticsearch_dsl_drf.filter_backends import (
>>>     FilteringFilterBackend
>>> )
>>> from django_elasticsearch_dsl_drf.viewsets import (
>>>     BaseDocumentViewSet,
>>> )
>>>
>>> # Local article document definition
>>> from .documents import ArticleDocument
>>>
>>> # Local article document serializer
>>> from .serializers import ArticleDocumentSerializer
>>>
>>> class ArticleDocumentView(BaseDocumentViewSet):
>>>
>>>     document = ArticleDocument
>>>     serializer_class = ArticleDocumentSerializer
>>>     filter_backends = [FilteringFilterBackend,]
>>>     filter_fields = {
>>>         'title': 'title.raw',
>>>         'state': {
>>>             'field': 'state.raw',
>>>             'lookups': [
>>>                 LOOKUP_FILTER_PREFIX,
>>>                 LOOKUP_FILTER_WILDCARD,
>>>                 LOOKUP_QUERY_EXCLUDE,
>>>                 LOOKUP_QUERY_ISNULL,
>>>             ],
```

(continues on next page)

(continued from previous page)

```
>>>             'default_lookup': LOOKUP_FILTER_WILDCARD,
>>>         }
>>> }
```

classmethod apply_filter_prefix(*queryset*, *options*, *value*)

Apply *prefix* filter.

Syntax:

/endpoint/?field_name__prefix={value}

Example:

http://localhost:8000/api/articles/?tags__prefix=bio

Parameters

- **queryset** (*elasticsearch_dsl.search.Search*) – Original queryset.
- **options** (*dict*) – Filter options.
- **value** (*str*) – value to filter on.

Returns Modified queryset.

Return type elasticsearch_dsl.search.Search

classmethod apply_filter_range(*queryset*, *options*, *value*)

Apply *range* filter.

Syntax:

/endpoint/?field_name__range={lower}__{upper}__{boost} /endpoint/?field_name__range={lower}__{upper}

Example:

http://localhost:8000/api/users/?age__range=16__67__2.0 http://localhost:8000/api/users/?age__range=16__67 http://localhost:8000/api/users/?age__range=16

Parameters

- **queryset** (*elasticsearch_dsl.search.Search*) – Original queryset.
- **options** (*dict*) – Filter options.
- **value** (*str*) – value to filter on.

Returns Modified queryset.

Return type elasticsearch_dsl.search.Search

classmethod apply_filter_term(*queryset*, *options*, *value*)

Apply *term* filter.

Syntax:

/endpoint/?field_name={value}

Example:

http://localhost:8000/api/articles/?tags=children

Parameters

- **queryset** (*elasticsearch_dsl.search.Search*) – Original queryset.
- **options** (*dict*) – Filter options.
- **value** (*str*) – value to filter on.

Returns Modified queryset.

Return type elasticsearch_dsl.search.Search

classmethod apply_filter_terms(*queryset*, *options*, *value*)

Apply *terms* filter.

Syntax:

/endpoint/?field_name__terms={value1}__{value2} /endpoint/?field_name__terms={value1}

Note, that number of values is not limited.

Example:

http://localhost:8000/api/articles/?tags__terms=children__python http://localhost:8000/api/articles/?tags__terms=children

Parameters

- **queryset** (*elasticsearch_dsl.search.Search*) – Original queryset.
- **options** (*dict*) – Filter options.
- **value** (*mixed: either str or iterable (list, tuple)*) – value to filter on.

Returns Modified queryset.

Return type elasticsearch_dsl.search.Search

classmethod apply_query_contains(*queryset*, *options*, *value*)

Apply *contains* filter.

Syntax:

/endpoint/?field_name__contains={value}

Example:

http://localhost:8000/api/articles/?state__contains=lis

Parameters

- **queryset** (*elasticsearch_dsl.search.Search*) – Original queryset.
- **options** (*dict*) – Filter options.
- **value** (*str*) – value to filter on.

Returns Modified queryset.

Return type elasticsearch_dsl.search.Search

classmethod apply_query_endswith(*queryset*, *options*, *value*)

Apply *endswith* filter.

Syntax:

/endpoint/?field_name__endswith={value}

Example:

http://localhost:8000/api/articles/?tags__endswith=dren

Parameters

- **queryset** (*elasticsearch_dsl.search.Search*) – Original queryset.
- **options** (*dict*) – Filter options.
- **value** (*str*) – value to filter on.

Returns Modified queryset.

Return type elasticsearch_dsl.search.Search

classmethod apply_query_exclude(*queryset*, *options*, *value*)

Apply *exclude* functional query.

Syntax:
/endpoint/?field_name__isnull={value1}__{value2} /endpoint/?field_name__exclude={valu1}
Note, that number of values is not limited.

Example:
http://localhost:8000/api/articles/?tags__exclude=children__python http://localhost:8000/api/articles/?tags__exclude=children

Parameters

- **queryset** (*elasticsearch_dsl.search.Search*) – Original queryset.
- **options** (*dict*) – Filter options.
- **value** (*str*) – value to filter on.

Returns Modified queryset.
Return type elasticsearch_dsl.search.Search

classmethod apply_query_exists(*queryset*, *options*, *value*)

Apply *exists* filter.

Syntax:
/endpoint/?field_name__exists=true /endpoint/?field_name__exists=false
Example:
http://localhost:8000/api/articles/?tags__exists=true http://localhost:8000/api/articles/?tags__exists=false

Parameters

- **queryset** (*elasticsearch_dsl.search.Search*) – Original queryset.
- **options** (*dict*) – Filter options.
- **value** (*str*) – value to filter on.

Returns Modified queryset.
Return type elasticsearch_dsl.search.Search

classmethod apply_query_gt(*queryset*, *options*, *value*)

Apply *gt* functional query.

Syntax:
/endpoint/?field_name__gt={value}__{boost} /endpoint/?field_name__gt={value}
Example:
http://localhost:8000/api/articles/?id__gt=1__2.0 http://localhost:8000/api/articles/?id__gt=1

Parameters

- **queryset** (*elasticsearch_dsl.search.Search*) – Original queryset.
- **options** (*dict*) – Filter options.
- **value** (*str*) – value to filter on.

Returns Modified queryset.
Return type elasticsearch_dsl.search.Search

classmethod apply_query_gte(*queryset*, *options*, *value*)

Apply *gte* functional query.

Syntax:

/endpoint/?field_name__gte={value}__{boost} /endpoint/?field_name__gte={value}

Example:

http://localhost:8000/api/articles/?id__gte=1__2.0 http://localhost:8000/api/articles/?id__gte=1

Parameters

- **queryset** (*elasticsearch_dsl.search.Search*) – Original queryset.
- **options** (*dict*) – Filter options.
- **value** (*str*) – value to filter on.

Returns Modified queryset.

Return type elasticsearch_dsl.search.Search

classmethod apply_query_in(*queryset*, *options*, *value*)

Apply *in* functional query.

Syntax:

/endpoint/?field_name__in={value1}__{value2} /endpoint/?field_name__in={value1}

Note, that number of values is not limited.

Example:

http://localhost:8000/api/articles/?tags__in=children__python

Parameters

- **queryset** (*elasticsearch_dsl.search.Search*) – Original queryset.
- **options** (*dict*) – Filter options.
- **value** (*str*) – value to filter on.

Returns Modified queryset.

Return type elasticsearch_dsl.search.Search

classmethod apply_query_isnull(*queryset*, *options*, *value*)

Apply *isnull* functional query.

Syntax:

/endpoint/?field_name__isnull=true /endpoint/?field_name__isnull=false

Example:

http://localhost:8000/api/articles/?tags__isnull=true http://localhost:8000/api/articles/?tags__isnull=false

Parameters

- **queryset** (*elasticsearch_dsl.search.Search*) – Original queryset.
- **options** (*dict*) – Filter options.
- **value** (*str*) – value to filter on.

Returns Modified queryset.

Return type elasticsearch_dsl.search.Search

classmethod apply_query_lt(*queryset*, *options*, *value*)

Apply *lt* functional query.

Syntax:

/endpoint/?field_name__lt={value}__{boost} /endpoint/?field_name__lt={value}

Example:

http://localhost:8000/api/articles/?id__lt=1__2.0 http://localhost:8000/api/articles/?id__lt=1

Parameters

- **queryset** (*elasticsearch_dsl.search.Search*) – Original queryset.
- **options** (*dict*) – Filter options.
- **value** (*str*) – value to filter on.

Returns Modified queryset.
Return type elasticsearch_dsl.search.Search

classmethod apply_query_lte(*queryset*, *options*, *value*)

Apply *lte* functional query.

Syntax:
/endpoint/?field_name__lte={value}__{boost} /endpoint/?field_name__lte={value}

Example:
http://localhost:8000/api/articles/?id__lte=1__2.0 http://localhost:8000/api/articles/?id__lte=1

Parameters

- **queryset** (*elasticsearch_dsl.search.Search*) – Original queryset.
- **options** (*dict*) – Filter options.
- **value** (*str*) – value to filter on.

Returns Modified queryset.
Return type elasticsearch_dsl.search.Search

classmethod apply_query_wildcard(*queryset*, *options*, *value*)

Apply *wildcard* filter.

Syntax:
/endpoint/?field_name__wildcard={value}* /endpoint/?field_name__wildcard=*{value} /endpoint/?field_name__wildcard=*{value}*

Example:
http://localhost:8000/api/articles/?tags__wildcard=child*

Parameters

- **queryset** (*elasticsearch_dsl.search.Search*) – Original queryset.
- **options** (*dict*) – Filter options.
- **value** (*str*) – value to filter on.

Returns Modified queryset.
Return type elasticsearch_dsl.search.Search

filter_queryset(*request*, *queryset*, *view*)

Filter the queryset.

Parameters

- **request** (*rest_framework.request.Request*) – Django REST framework request.
- **queryset** (*elasticsearch_dsl.search.Search*) – Base queryset.
- **view** (*rest_framework.viewsets.ReadOnlyModelViewSet*) – View.

Returns Updated queryset.
Return type elasticsearch_dsl.search.Search

get_coreschema_field(*field*)

get_filter_query_params(*request*, *view*)
Get query params to be filtered on.
Parameters
- **request** (*rest_framework.request.Request*) – Django REST framework request.
- **view** (*rest_framework.viewsets.ReadOnlyModelViewSet*) – View.

Returns Request query params to filter on.
Return type dict

classmethod get_gte_lte_params(*value*, *lookup*)
Get params for *gte*, *gt*, *lte* and *lt* query.

Syntax:
/endpoint/?field_name__gt={lower}__{boost} /endpoint/?field_name__gt={lower}
Example:
http://localhost:8000/api/articles/?id__gt=1 http://localhost:8000/api/articles/?id__gt=1__2.0

Parameters
- **value** (*str*) –
- **lookup** (*str*) –

Returns Params to be used in *range* query.
Return type dict

classmethod get_range_params(*value*)
Get params for *range* query.

Syntax:
/endpoint/?field_name__range={lower}__{upper}__{boost} /endpoint/?field_name__range={lower}__{upper}
Example:
http://localhost:8000/api/users/?age__range=16__67__2.0 http://localhost:8000/api/users/?age__range=16__67 http://localhost:8000/api/users/?age__range=16

Parameters **value** –
Type str
Returns Params to be used in *range* query.
Return type dict

get_schema_fields(*view*)

classmethod prepare_filter_fields(*view*)
Prepare filter fields.
Parameters **view** (*rest_framework.viewsets.ReadOnlyModelViewSet*) –
Returns Filtering options.
Return type dict

class django_elasticsearch_dsl_drf.filter_backends.filtering.**GeoSpatialFilteringFilterBacke**
Bases: rest_framework.filters.BaseFilterBackend, *django_elasticsearch_dsl_drf.filter_backends.mixins.FilterBackendMixin*

Geo-spatial filtering filter backend for Elasticsearch.

Example:

```
>>> from django_elasticsearch_dsl_drf.constants import (
>>>     LOOKUP_FILTER_GEO_DISTANCE,
>>> )
>>> from django_elasticsearch_dsl_drf.filter_backends import (
>>>     GeoSpatialFilteringFilterBackend
>>> )
>>> from django_elasticsearch_dsl_drf.viewsets import (
>>>     BaseDocumentViewSet,
>>> )
>>>
>>> # Local article document definition
>>> from .documents import ArticleDocument
>>>
>>> # Local article document serializer
>>> from .serializers import ArticleDocumentSerializer
>>>
>>> class ArticleDocumentView(BaseDocumentViewSet):
>>>
>>>     document = ArticleDocument
>>>     serializer_class = ArticleDocumentSerializer
>>>     filter_backends = [GeoSpatialFilteringFilterBackend,]
>>>     geo_spatial_filter_fields = {
>>>         'loc': 'location',
>>>         'location': {
>>>             'field': 'location',
>>>             'lookups': [
>>>                 LOOKUP_FILTER_GEO_DISTANCE,
>>>             ],
>>>         }
>>> }
```

classmethod apply_query_geo_bounding_box(*queryset*, *options*, *value*)

Apply *geo_bounding_box* query.

Parameters

- **queryset** (*elasticsearch_dsl.search.Search*) – Original queryset.
- **options** (*dict*) – Filter options.
- **value** (*str*) – value to filter on.

Returns Modified queryset.

Return type elasticsearch_dsl.search.Search

classmethod apply_query_geo_distance(*queryset*, *options*, *value*)

Apply *geo_distance* query.

Parameters

- **queryset** (*elasticsearch_dsl.search.Search*) – Original queryset.
- **options** (*dict*) – Filter options.
- **value** (*str*) – value to filter on.

Returns Modified queryset.

Return type elasticsearch_dsl.search.Search

classmethod apply_query_geo_polygon(*queryset*, *options*, *value*)

Apply *geo_polygon* query.

Parameters

- **queryset** (*elasticsearch_dsl.search.Search*) – Original queryset.
- **options** (*dict*) – Filter options.
- **value** (*str*) – value to filter on.

Returns Modified queryset.
Return type elasticsearch_dsl.search.Search

filter_queryset (*request*, *queryset*, *view*)

Filter the queryset.

Parameters

- **request** (*rest_framework.request.Request*) – Django REST framework request.
- **queryset** (*elasticsearch_dsl.search.Search*) – Base queryset.
- **view** (*rest_framework.viewsets.ReadOnlyModelViewSet*) – View.

Returns Updated queryset.
Return type elasticsearch_dsl.search.Search

get_filter_query_params (*request*, *view*)

Get query params to be filtered on.

Parameters

- **request** (*rest_framework.request.Request*) – Django REST framework request.
- **view** (*rest_framework.viewsets.ReadOnlyModelViewSet*) – View.

Returns Request query params to filter on.
Return type dict

classmethod get_geo_bounding_box_params (*value*, *field*)

Get params for *geo_bounding_box* query.

Example:
/api/articles/?location__geo_bounding_box=40.73,-74.1__40.01,-71.12

Example:
/api/articles/?location__geo_polygon=40.73,-74.1 __40.01,-71.12 ___name,myname __validation_method,IGNORE_MALFORMED __type,indexed

Elasticsearch:

{

"query": {

"bool" [{]

"must" [{] "match_all" : {}

}, "filter" : {

"geo_bounding_box" [{]

"person.location" [{]

"top_left" [{] "lat" : 40.73, "lon" : -74.1

}, "bottom_right" : {

"lat" : 40.01, "lon" : -71.12

}

}

}

}

}

}

}

Parameters

- **value** (*str*) –
- **field** –

Returns Params to be used in *geo_bounding_box* query.

Return type dict

classmethod get_geo_distance_params(*value*, *field*)

Get params for *geo_distance* query.

Example:

/api/articles/?location__geo_distance=2km__43.53__-12.23

Parameters

- **value** (*str*) –
- **field** –

Returns Params to be used in *geo_distance* query.

Return type dict

classmethod get_geo_polygon_params(*value*, *field*)

Get params for *geo_polygon* query.

Example:

/api/articles/?location__geo_polygon=40,-70__30,-80__20,-90

Example:

/api/articles/?location__geo_polygon=40,-70 __30,-80 __20,-90 ___name,myname __validation_method,IGNORE_MALFORMED

Elasticsearch:

{

"query": {

"bool" [{]

"must" [{] "match_all" : {}

}, "filter" : {

"geo_polygon" [{]

"person.location" [{]

"points" [[] {"lat" : 40, "lon" : -70}, {"lat" : 30, "lon" : -80}, {"lat" : 20, "lon" : -90}

]

```
                                    }
                                }
                            }
                        }
                    }
                }
```

Parameters

- **value** (*str*) –
- **field** –

Returns Params to be used in *geo_distance* query.

Return type dict

classmethod prepare_filter_fields(*view*)

Prepare filter fields.

Parameters **view** (*rest_framework.viewsets.ReadOnlyModelViewSet*) –

Returns Filtering options.

Return type dict

class django_elasticsearch_dsl_drf.filter_backends.filtering.**IdsFilterBackend**

Bases: rest_framework.filters.BaseFilterBackend, *django_elasticsearch_dsl_drf.filter_backends.mixins.FilterBackendMixin*

Ids filter backend for Elasticsearch.

Example:

```
>>> from django_elasticsearch_dsl_drf.filter_backends import (
>>>     IdsFilterBackend
>>> )
>>> from django_elasticsearch_dsl_drf.viewsets import (
>>>     BaseDocumentViewSet,
>>> )
>>>
>>> # Local article document definition
>>> from .documents import ArticleDocument
>>>
>>> # Local article document serializer
>>> from .serializers import ArticleDocumentSerializer
>>>
>>> class ArticleDocumentView(BaseDocumentViewSet):
>>>
>>>     document = ArticleDocument
>>>     serializer_class = ArticleDocumentSerializer
>>>     filter_backends = [IdsFilterBackend]
```

filter_queryset(*request*, *queryset*, *view*)

Filter the queryset.

Parameters

- **request** (*rest_framework.request.Request*) – Django REST framework request.
- **queryset** (*elasticsearch_dsl.search.Search*) – Base queryset.

- **view** (*rest_framework.viewsets.ReadOnlyModelViewSet*) – View.

Returns Updated queryset.
Return type elasticsearch_dsl.search.Search

get_ids_query_params(*request*)

Get search query params.

Parameters **request** (*rest_framework.request.Request*) – Django REST framework request.
Returns List of search query params.
Return type list

get_ids_values(*request*, *view*)

Get ids values for query.

Parameters

- **request** (*rest_framework.request.Request*) – Django REST framework request.
- **queryset** (*elasticsearch_dsl.search.Search*) – Base queryset.
- **view** (*rest_framework.viewsets.ReadOnlyModelViewSet*) – View.

Returns Updated queryset.
Return type elasticsearch_dsl.search.Search

ids_query_param = 'ids'

class django_elasticsearch_dsl_drf.filter_backends.filtering.**NestedFilteringFilterBackend**

Bases: *django_elasticsearch_dsl_drf.filter_backends.filtering.common.FilteringFilterBackend*

Nested filter backend.

Example:

```
>>> from django_elasticsearch_dsl_drf.constants import (
>>>     LOOKUP_FILTER_TERM,
>>>     LOOKUP_FILTER_PREFIX,
>>>     LOOKUP_FILTER_WILDCARD,
>>>     LOOKUP_QUERY_EXCLUDE,
>>>     LOOKUP_QUERY_ISNULL,
>>> )
>>> from django_elasticsearch_dsl_drf.filter_backends import (
>>>     NestedFilteringFilterBackend
>>> )
>>> from django_elasticsearch_dsl_drf.viewsets import (
>>>     BaseDocumentViewSet,
>>> )
>>>
>>> # Local article document definition
>>> from .documents import ArticleDocument
>>>
>>> # Local article document serializer
>>> from .serializers import ArticleDocumentSerializer
>>>
>>> class ArticleDocumentView(BaseDocumentViewSet):
>>>
>>>     document = ArticleDocument
>>>     serializer_class = ArticleDocumentSerializer
```

(continues on next page)

(continued from previous page)

```
>>>     filter_backends = [NestedFilteringFilterBackend,]
>>>     nested_filter_fields = {
>>>         'country': {
>>>             'field': 'continent.country.name.raw',
>>>             'path': 'continent.country',
>>>             'lookups': [
>>>                 LOOKUP_FILTER_TERM,
>>>                 LOOKUP_FILTER_TERMS,
>>>                 LOOKUP_FILTER_PREFIX,
>>>                 LOOKUP_FILTER_WILDCARD,
>>>                 LOOKUP_QUERY_EXCLUDE,
>>>                 LOOKUP_QUERY_ISNULL,
>>>             ],
>>>         }
>>> }
```

classmethod apply_filter(*queryset*, *options=None*, *args=None*, *kwargs=None*)

Apply filter.

Parameters

- **queryset** –
- **options** –
- **args** –
- **kwargs** –

Returns

classmethod apply_query(*queryset*, *options=None*, *args=None*, *kwargs=None*)

Apply query.

Parameters

- **queryset** –
- **options** –
- **args** –
- **kwargs** –

Returns

get_coreschema_field(*field*)

get_filter_field_nested_path(*filter_fields*, *field_name*)

Get filter field path to be used in nested query.

Parameters

- **filter_fields** –
- **field_name** –

Returns

get_filter_query_params(*request*, *view*)

Get query params to be filtered on.

Parameters

- **request** (*rest_framework.request.Request*) – Django REST framework request.
- **view** (*rest_framework.viewsets.ReadOnlyModelViewSet*) – View.

Returns Request query params to filter on.
Return type dict

get_schema_fields(*view*)

classmethod prepare_filter_fields(*view*)
Prepare filter fields.
Parameters view(*rest_framework.viewsets.ReadOnlyModelViewSet*) –
Returns Filtering options.
Return type dict

class django_elasticsearch_dsl_drf.filter_backends.filtering.**PostFilterFilteringFilterBacke**
Bases: *django_elasticsearch_dsl_drf.filter_backends.filtering.common.FilteringFilterBackend*

The `post_filter` filtering filter backend for Elasticsearch.

Example:

```
>>> from django_elasticsearch_dsl_drf.constants import (
>>>     LOOKUP_FILTER_PREFIX,
>>>     LOOKUP_FILTER_WILDCARD,
>>>     LOOKUP_QUERY_EXCLUDE,
>>>     LOOKUP_QUERY_ISNULL,
>>> )
>>> from django_elasticsearch_dsl_drf.filter_backends import (
>>>     PostFilterFilteringFilterBackend
>>> )
>>> from django_elasticsearch_dsl_drf.viewsets import (
>>>     BaseDocumentViewSet,
>>> )
>>>
>>> # Local article document definition
>>> from .documents import ArticleDocument
>>>
>>> # Local article document serializer
>>> from .serializers import ArticleDocumentSerializer
>>>
>>> class ArticleDocumentView(BaseDocumentViewSet):
>>>
>>>     document = ArticleDocument
>>>     serializer_class = ArticleDocumentSerializer
>>>     filter_backends = [PostFilterFilteringFilterBackend,]
>>>     post_filter_fields = {
>>>         'title': 'title.raw',
>>>         'state': {
>>>             'field': 'state.raw',
>>>             'lookups': [
>>>                 LOOKUP_FILTER_PREFIX,
>>>                 LOOKUP_FILTER_WILDCARD,
>>>                 LOOKUP_QUERY_EXCLUDE,
>>>                 LOOKUP_QUERY_ISNULL,
>>>             ],
>>>         }
>>> }
```

classmethod apply_filter(*queryset*, *options=None*, *args=None*, *kwargs=None*)
Apply filter.
Parameters

- **queryset** –
- **options** –
- **args** –
- **kwargs** –

Returns

classmethod apply_query(*queryset*, *options=None*, *args=None*, *kwargs=None*)

Apply query.

Parameters

- **queryset** –
- **options** –
- **args** –
- **kwargs** –

Returns

get_coreschema_field(*field*)

get_schema_fields(*view*)

classmethod prepare_filter_fields(*view*)

Prepare filter fields.

Parameters **view** (*rest_framework.viewsets.ReadOnlyModelViewSet*) –

Returns Filtering options.

Return type dict

12.18.1.2.1.15 django_elasticsearch_dsl_drf.filter_backends.ordering package

12.18.1.2.1.16 Submodules

12.18.1.2.1.17 django_elasticsearch_dsl_drf.filter_backends.ordering.common module

Ordering backend.

class `django_elasticsearch_dsl_drf.filter_backends.ordering.common.`**DefaultOrderingFilterBac**

Bases: `rest_framework.filters.BaseFilterBackend`, `django_elasticsearch_dsl_drf.filter_backends.ordering.common.OrderingMixin`

Default ordering filter backend for Elasticsearch.

Make sure this is your last ordering backend.

Example:

```
>>> from django_elasticsearch_dsl_drf.filter_backends import (
>>>     DefaultOrderingFilterBackend,
>>>     OrderingFilterBackend
>>> )
>>> from django_elasticsearch_dsl_drf.viewsets import (
>>>     BaseDocumentViewSet,
>>> )
>>>
>>> # Local article document definition
>>> from .documents import ArticleDocument
```

(continues on next page)

(continued from previous page)

```
>>>
>>> # Local article document serializer
>>> from .serializers import ArticleDocumentSerializer
>>>
>>> class ArticleDocumentView(BaseDocumentViewSet):
>>>
>>>     document = ArticleDocument
>>>     serializer_class = ArticleDocumentSerializer
>>>     filter_backends = [
>>>         DefaultOrderingFilterBackend,
>>>         OrderingFilterBackend,
>>>     ]
>>>     ordering_fields = {
>>>         'id': None,
>>>         'title': 'title.raw',
>>>         'date_submitted': 'date_submitted',
>>>         'continent': {
>>>             'field': 'continent.name.raw',
>>>             'path': 'continent',
>>>         }
>>>         'country': {
>>>             'field': 'continent.country.name.raw',
>>>             'path': 'continent.country',
>>>         }
>>>         'city': {
>>>             'field': 'continent.country.city.name.raw',
>>>             'path': 'continent.country.city',
>>>         }
>>>     }
>>>     ordering = 'city'
```

filter_queryset(*request*, *queryset*, *view*)

Filter the queryset.

Parameters

- **request** (*rest_framework.request.Request*) – Django REST framework request.
- **queryset** (*elasticsearch_dsl.search.Search*) – Base queryset.
- **view** (*rest_framework.viewsets.ReadOnlyModelViewSet*) – View.

Returns Updated queryset.

Return type elasticsearch_dsl.search.Search

classmethod get_default_ordering_params(*view*)

Get the default ordering params for the view.

Parameters **view** (*rest_framework.viewsets.ReadOnlyModelViewSet*) – View.

Returns Ordering params to be used for ordering.

Return type list

get_ordering_query_params(*request*, *view*)

Get ordering query params.

Parameters

- **request** (*rest_framework.request.Request*) – Django REST framework request.

- **view** (*rest_framework.viewsets.ReadOnlyModelViewSet*) – View.

Returns Ordering params to be used for ordering.

Return type list

ordering_param = 'ordering'

class `django_elasticsearch_dsl_drf.filter_backends.ordering.common.`**OrderingFilterBackend**

Bases: `rest_framework.filters.BaseFilterBackend`, `django_elasticsearch_dsl_drf.filter_backends.ordering.common.OrderingMixin`

Ordering filter backend for Elasticsearch.

Example:

```
>>> from django_elasticsearch_dsl_drf.filter_backends import (
>>>     OrderingFilterBackend
>>> )
>>> from django_elasticsearch_dsl_drf.viewsets import (
>>>     BaseDocumentViewSet,
>>> )
>>>
>>> # Local article document definition
>>> from .documents import ArticleDocument
>>>
>>> # Local article document serializer
>>> from .serializers import ArticleDocumentSerializer
>>>
>>> class ArticleDocumentView(BaseDocumentViewSet):
>>>
>>>     document = ArticleDocument
>>>     serializer_class = ArticleDocumentSerializer
>>>     filter_backends = [OrderingFilterBackend,]
>>>     ordering_fields = {
>>>         'id': None,
>>>         'title': 'title.raw',
>>>         'date_submitted': 'date_submitted',
>>>         'continent': {
>>>             'field': 'continent.name.raw',
>>>             'path': 'continent',
>>>         }
>>>         'country': {
>>>             'field': 'continent.country.name.raw',
>>>             'path': 'continent.country',
>>>         }
>>>         'city': {
>>>             'field': 'continent.country.city.name.raw',
>>>             'path': 'continent.country.city',
>>>         }
>>>     }
>>>     ordering = ('id', 'title',)
```

filter_queryset(*request*, *queryset*, *view*)

Filter the queryset.

Parameters

- **request** (*rest_framework.request.Request*) – Django REST framework request.
- **queryset** (*elasticsearch_dsl.search.Search*) – Base queryset.

- **view** (*rest_framework.viewsets.ReadOnlyModelViewSet*) – View.

Returns Updated queryset.
Return type elasticsearch_dsl.search.Search

get_ordering_query_params(*request*, *view*)
Get ordering query params.

Parameters

- **request** (*rest_framework.request.Request*) – Django REST framework request.
- **view** (*rest_framework.viewsets.ReadOnlyModelViewSet*) – View.

Returns Ordering params to be used for ordering.
Return type list

get_schema_fields(*view*)

ordering_param = 'ordering'

12.18.1.2.1.18 django_elasticsearch_dsl_drf.filter_backends.ordering.geo_spatial module

Geo-spatial ordering backend.

class `django_elasticsearch_dsl_drf.filter_backends.ordering.geo_spatial.`**GeoSpatialOrderingF**
Bases: `rest_framework.filters.BaseFilterBackend`, *`django_elasticsearch_dsl_drf.filter_backends.mixins.FilterBackendMixin`*

Geo-spatial ordering filter backend for Elasticsearch.

Example:

```
>>> from django_elasticsearch_dsl_drf.filter_backends import (
>>>     GeoSpatialOrderingFilterBackend
>>> )
>>> from django_elasticsearch_dsl_drf.viewsets import (
>>>     BaseDocumentViewSet,
>>> )
>>>
>>> # Local article document definition
>>> from .documents import ArticleDocument
>>>
>>> # Local article document serializer
>>> from .serializers import ArticleDocumentSerializer
>>>
>>> class ArticleDocumentView(BaseDocumentViewSet):
>>>
>>>     document = ArticleDocument
>>>     serializer_class = ArticleDocumentSerializer
>>>     filter_backends = [GeoSpatialOrderingFilterBackend,]
>>>     geo_spatial_ordering_fields = {
>>>         'location': {
>>>             'field': 'location',
>>>         }
>>>     }
```

filter_queryset(*request*, *queryset*, *view*)
Filter the queryset.

Parameters

- **request** (*rest_framework.request.Request*) – Django REST framework request.
- **queryset** (*elasticsearch_dsl.search.Search*) – Base queryset.
- **view** (*rest_framework.viewsets.ReadOnlyModelViewSet*) – View.

Returns Updated queryset.
Return type elasticsearch_dsl.search.Search

classmethod get_geo_distance_params(*value*, *field*)

Get params for *geo_distance* ordering.

Example:
/api/articles/?ordering=-location__45.3214__-34.3421__km__planes

Parameters

- **value** (*str*) –
- **field** –

Returns Params to be used in *geo_distance* query.
Return type dict

get_geo_spatial_field_name(*request*, *view*, *name*)

Get geo-spatial field name.

We have to deal with a couple of situations here:

Example 1:

```
>>> geo_spatial_ordering_fields = {
>>>     'location': None,
>>> }
```

Example 2:

```
>>> geo_spatial_ordering_fields = {
>>>     'location': 'location',
>>> }
```

Example 3:

```
>>> geo_spatial_ordering_fields = {
>>>     'location': {
>>>         'field': 'location'
>>>     },
>>> }
```

Parameters

- **request** –
- **view** –
- **name** –

Returns

get_ordering_query_params(*request*, *view*)

Get ordering query params.

Parameters

- **request** (*rest_framework.request.Request*) – Django REST framework request.
- **view** (*rest_framework.viewsets.ReadOnlyModelViewSet*) – View.

Returns Ordering params to be used for ordering.
Return type list

ordering_param = 'ordering'

12.18.1.2.1.19 Module contents

Ordering backends.

class `django_elasticsearch_dsl_drf.filter_backends.ordering.`**DefaultOrderingFilterBackend**

Bases: `rest_framework.filters.BaseFilterBackend`, `django_elasticsearch_dsl_drf.filter_backends.ordering.common.OrderingMixin`

Default ordering filter backend for Elasticsearch.

Make sure this is your last ordering backend.

Example:

```
>>> from django_elasticsearch_dsl_drf.filter_backends import (
>>>     DefaultOrderingFilterBackend,
>>>     OrderingFilterBackend
>>> )
>>> from django_elasticsearch_dsl_drf.viewsets import (
>>>     BaseDocumentViewSet,
>>> )
>>>
>>> # Local article document definition
>>> from .documents import ArticleDocument
>>>
>>> # Local article document serializer
>>> from .serializers import ArticleDocumentSerializer
>>>
>>> class ArticleDocumentView(BaseDocumentViewSet):
>>>
>>>     document = ArticleDocument
>>>     serializer_class = ArticleDocumentSerializer
>>>     filter_backends = [
>>>         DefaultOrderingFilterBackend,
>>>         OrderingFilterBackend,
>>>     ]
>>>     ordering_fields = {
>>>         'id': None,
>>>         'title': 'title.raw',
>>>         'date_submitted': 'date_submitted',
>>>         'continent': {
>>>             'field': 'continent.name.raw',
>>>             'path': 'continent',
>>>         }
>>>         'country': {
>>>             'field': 'continent.country.name.raw',
>>>             'path': 'continent.country',
>>>         }
```

(continues on next page)

(continued from previous page)

```
>>>         'city': {
>>>             'field': 'continent.country.city.name.raw',
>>>             'path': 'continent.country.city',
>>>         }
>>>     }
>>>     ordering = 'city'
```

filter_queryset(*request*, *queryset*, *view*)

Filter the queryset.

Parameters

- **request** (*rest_framework.request.Request*) – Django REST framework request.
- **queryset** (*elasticsearch_dsl.search.Search*) – Base queryset.
- **view** (*rest_framework.viewsets.ReadOnlyModelViewSet*) – View.

Returns Updated queryset.

Return type elasticsearch_dsl.search.Search

classmethod get_default_ordering_params(*view*)

Get the default ordering params for the view.

Parameters **view** (*rest_framework.viewsets.ReadOnlyModelViewSet*) – View.

Returns Ordering params to be used for ordering.

Return type list

get_ordering_query_params(*request*, *view*)

Get ordering query params.

Parameters

- **request** (*rest_framework.request.Request*) – Django REST framework request.
- **view** (*rest_framework.viewsets.ReadOnlyModelViewSet*) – View.

Returns Ordering params to be used for ordering.

Return type list

ordering_param = 'ordering'

class django_elasticsearch_dsl_drf.filter_backends.ordering.**GeoSpatialOrderingFilterBacken**

Bases: rest_framework.filters.BaseFilterBackend, *django_elasticsearch_dsl_drf.filter_backends.mixins.FilterBackendMixin*

Geo-spatial ordering filter backend for Elasticsearch.

Example:

```
>>> from django_elasticsearch_dsl_drf.filter_backends import (
>>>     GeoSpatialOrderingFilterBackend
>>> )
>>> from django_elasticsearch_dsl_drf.viewsets import (
>>>     BaseDocumentViewSet,
>>> )
>>>
>>> # Local article document definition
>>> from .documents import ArticleDocument
```

(continues on next page)

(continued from previous page)

```
>>>
>>> # Local article document serializer
>>> from .serializers import ArticleDocumentSerializer
>>>
>>> class ArticleDocumentView(BaseDocumentViewSet):
>>>
>>>     document = ArticleDocument
>>>     serializer_class = ArticleDocumentSerializer
>>>     filter_backends = [GeoSpatialOrderingFilterBackend,]
>>>     geo_spatial_ordering_fields = {
>>>         'location': {
>>>             'field': 'location',
>>>         }
>>>     }
```

filter_queryset(*request*, *queryset*, *view*)

Filter the queryset.

Parameters

- **request** (*rest_framework.request.Request*) – Django REST framework request.
- **queryset** (*elasticsearch_dsl.search.Search*) – Base queryset.
- **view** (*rest_framework.viewsets.ReadOnlyModelViewSet*) – View.

Returns Updated queryset.

Return type elasticsearch_dsl.search.Search

classmethod get_geo_distance_params(*value*, *field*)

Get params for *geo_distance* ordering.

Example:

/api/articles/?ordering=-location__45.3214__-34.3421__km__planes

Parameters

- **value** (*str*) –
- **field** –

Returns Params to be used in *geo_distance* query.

Return type dict

get_geo_spatial_field_name(*request*, *view*, *name*)

Get geo-spatial field name.

We have to deal with a couple of situations here:

Example 1:

```
>>> geo_spatial_ordering_fields = {
>>>     'location': None,
>>> }
```

Example 2:

```
>>> geo_spatial_ordering_fields = {
>>>     'location': 'location',
>>> }
```

Example 3:

```
>>> geo_spatial_ordering_fields = {
>>>     'location': {
>>>         'field': 'location'
>>>     },
>>> }
```

Parameters

- **request** –
- **view** –
- **name** –

Returns

get_ordering_query_params(*request*, *view*)

Get ordering query params.

Parameters

- **request** (*rest_framework.request.Request*) – Django REST framework request.
- **view** (*rest_framework.viewsets.ReadOnlyModelViewSet*) – View.

Returns Ordering params to be used for ordering.

Return type list

ordering_param = 'ordering'

class django_elasticsearch_dsl_drf.filter_backends.ordering.**OrderingFilterBackend**

Bases: rest_framework.filters.BaseFilterBackend, django_elasticsearch_dsl_drf.filter_backends.ordering.common.OrderingMixin

Ordering filter backend for Elasticsearch.

Example:

```
>>> from django_elasticsearch_dsl_drf.filter_backends import (
>>>     OrderingFilterBackend
>>> )
>>> from django_elasticsearch_dsl_drf.viewsets import (
>>>     BaseDocumentViewSet,
>>> )
>>>
>>> # Local article document definition
>>> from .documents import ArticleDocument
>>>
>>> # Local article document serializer
>>> from .serializers import ArticleDocumentSerializer
>>>
>>> class ArticleDocumentView(BaseDocumentViewSet):
>>>
>>>     document = ArticleDocument
>>>     serializer_class = ArticleDocumentSerializer
>>>     filter_backends = [OrderingFilterBackend,]
>>>     ordering_fields = {
>>>         'id': None,
>>>         'title': 'title.raw',
>>>         'date_submitted': 'date_submitted',
```

(continues on next page)

(continued from previous page)

```
>>>         'continent': {
>>>             'field': 'continent.name.raw',
>>>             'path': 'continent',
>>>         }
>>>         'country': {
>>>             'field': 'continent.country.name.raw',
>>>             'path': 'continent.country',
>>>         }
>>>         'city': {
>>>             'field': 'continent.country.city.name.raw',
>>>             'path': 'continent.country.city',
>>>         }
>>>     }
>>>     ordering = ('id', 'title',)
```

filter_queryset (*request*, *queryset*, *view*)

Filter the queryset.

Parameters

- **request** (*rest_framework.request.Request*) – Django REST framework request.
- **queryset** (*elasticsearch_dsl.search.Search*) – Base queryset.
- **view** (*rest_framework.viewsets.ReadOnlyModelViewSet*) – View.

Returns Updated queryset.

Return type elasticsearch_dsl.search.Search

get_ordering_query_params (*request*, *view*)

Get ordering query params.

Parameters

- **request** (*rest_framework.request.Request*) – Django REST framework request.
- **view** (*rest_framework.viewsets.ReadOnlyModelViewSet*) – View.

Returns Ordering params to be used for ordering.

Return type list

get_schema_fields (*view*)

ordering_param = 'ordering'

12.18.1.2.1.20 django_elasticsearch_dsl_drf.filter_backends.search package

12.18.1.2.1.21 Subpackages

12.18.1.2.1.22 django_elasticsearch_dsl_drf.filter_backends.search.query_backends package

12.18.1.2.1.23 Submodules

12.18.1.2.1.24 django_elasticsearch_dsl_drf.filter_backends.search.query_backends.base module

class `django_elasticsearch_dsl_drf.filter_backends.search.query_backends.base.`**BaseSearchQue**

Bases: `object`

Search query backend.

classmethod construct_search(*request*, *view*, *search_backend*)

Construct search.

Parameters

- **request** –
- **view** –
- **search_backend** –

Returns

12.18.1.2.1.25 django_elasticsearch_dsl_drf.filter_backends.search.query_backends.match module

class `django_elasticsearch_dsl_drf.filter_backends.search.query_backends.match.`**MatchQueryBa**

Bases: *`django_elasticsearch_dsl_drf.filter_backends.search.query_backends.base.BaseSearchQueryBackend`*

Match query backend.

classmethod construct_search(*request*, *view*, *search_backend*)

Construct search.

Parameters

- **request** –
- **view** –
- **search_backend** –

Returns

query_type = 'match'

12.18.1.2.1.26 django_elasticsearch_dsl_drf.filter_backends.search.query_backends.match_phrase module

class `django_elasticsearch_dsl_drf.filter_backends.search.query_backends.match_phrase.`**Match**

Bases: *`django_elasticsearch_dsl_drf.filter_backends.search.query_backends.base.BaseSearchQueryBackend`*

Match phrase query backend.

classmethod construct_search(*request*, *view*, *search_backend*)

Construct search.

Parameters

- **request** –
- **view** –
- **search_backend** –

Returns

query_type = 'match_phrase'

12.18.1.2.1.27 django_elasticsearch_dsl_drf.filter_backends.search.query_backends.match_phrase_prefix module

class `django_elasticsearch_dsl_drf.filter_backends.search.query_backends.match_phrase_pref`

Bases: *`django_elasticsearch_dsl_drf.filter_backends.search.query_backends.base.BaseSearchQueryBackend`*

Match phrase prefix query backend.

classmethod construct_search(*request*, *view*, *search_backend*)

Construct search.

Parameters

- **request** –
- **view** –
- **search_backend** –

Returns

query_type = 'match_phrase_prefix'

12.18.1.2.1.28 django_elasticsearch_dsl_drf.filter_backends.search.query_backends.multi_match module

class `django_elasticsearch_dsl_drf.filter_backends.search.query_backends.multi_match.MultiM`

Bases: *`django_elasticsearch_dsl_drf.filter_backends.search.query_backends.base.BaseSearchQueryBackend`*

Multi match query backend.

classmethod construct_search(*request*, *view*, *search_backend*)

Construct search.

In case of multi match, we always look in a group of fields. Thus, matching per field is no longer valid use case here. However, we might want to have multiple fields enabled for multi match per view set, and only search in some of them in specific request.

Example:

/search/books/?search_multi_match=lorem ipsum /search/books/?search_multi_match=title,summary:lorem ipsum

Note, that multiple searches are not supported (would not raise an exception, but would simply take only the first):

/search/books/?search_multi_match=title,summary:lorem ipsum
&search_multi_match=author,publisher=o'reily

In the view-set fields shall be defined in a very simple way. The only accepted argument would be boost (per field).

Example 1 (complex):

multi_match_search_fields = { 'title': {'field': 'title.english', 'boost': 4}, 'summary': {'boost': 2}, 'description': None,

}

Example 2 (simple list):

multi_match_search_fields = ('title', 'summary', 'description',

)

Parameters

- **request** –
- **view** –
- **search_backend** –

Returns

classmethod get_field(*field*, *options*)

Get field.

Parameters

- **field** –
- **options** –

Returns

classmethod get_query_options(*request*, *view*, *search_backend*)

query_type = 'multi_match'

12.18.1.2.1.29 django_elasticsearch_dsl_drf.filter_backends.search.query_backends.nested module

class `django_elasticsearch_dsl_drf.filter_backends.search.query_backends.nested.`**NestedQuery**

Bases: *`django_elasticsearch_dsl_drf.filter_backends.search.query_backends.base.BaseSearchQueryBackend`*

Nested query backend.

classmethod construct_search(*request*, *view*, *search_backend*)

Construct search.

Dictionary key is the GET param name. The path option stands for the path in Elasticsearch.

Type 1:

search_nested_fields = {

'country': { 'path': 'country', 'fields': ['name'],

}, 'city': {

'path': 'country.city', 'fields': ['name'],

},

}

Type 2:

search_nested_fields = {

'country': { 'path': 'country', 'fields': [{'name': {'boost': 2}}]

}, 'city': {

'path': 'country.city', 'fields': [{'name': {'boost': 2}}]

},

}

Parameters

- **request** –
- **view** –
- **search_backend** –

Returns

query_type = 'nested'

12.18.1.2.1.30 django_elasticsearch_dsl_drf.filter_backends.search.query_backends.simple_query_string module

class `django_elasticsearch_dsl_drf.filter_backends.search.query_backends.simple_query_strin`

Bases: *`django_elasticsearch_dsl_drf.filter_backends.search.query_backends.base.BaseSearchQueryBackend`*

Simple query string query backend.

classmethod construct_search(*request*, *view*, *search_backend*)

Construct search.

In case of multi match, we always look in a group of fields. Thus, matching per field is no longer valid use case here. However, we might want to have multiple fields enabled for multi match per view set, and only search in some of them in specific request.

Example:

/search/books/?search_simple_query_string= "fried eggs" %2B(eggplant | potato) -frittata

/search/books/?search_simple_query_string= title,summary:"fried eggs" +(eggplant | potato) -frittata

Note, that multiple searches are not supported (would not raise an exception, but would simply take only the first):

/search/books/?search_simple_query_string= title,summary:"fried eggs" +(eggplant | potato) -frittata &search_simple_query_string= author,publisher="fried eggs" +(eggplant | potato) -frittata

In the view-set fields shall be defined in a very simple way. The only accepted argument would be boost (per field).

Example 1 (complex):

simple_query_string_search_fields = { 'title': {'field': 'title.english', 'boost': 4}, 'summary': {'boost': 2}, 'description': None,

}

Example 2 (simple list):

simple_query_string_search_fields = ('title', 'summary', 'description',

)

Query examples:

http://localhost:8000/search /books-simple-query-string-search-backend /?search_simple_query_string=%22Pool%20of%20Tears%22
http://localhost:8000/search /books-simple-query-string-search-backend /?search_simple_query_string=%22Pool%20of%20Tears%22 -considering

Parameters

- **request** –
- **view** –
- **search_backend** –

Returns

classmethod get_field(*field*, *options*)

Get field.

Parameters

- **field** –
- **options** –

Returns

classmethod get_query_options(*request*, *view*, *search_backend*)

query_type = 'simple_query_string'

12.18.1.2.1.31 Module contents

Search query backends.

class `django_elasticsearch_dsl_drf.filter_backends.search.query_backends.`**BaseSearchQueryBa**

Bases: `object`

Search query backend.

classmethod construct_search(*request*, *view*, *search_backend*)

Construct search.

Parameters

- **request** –
- **view** –
- **search_backend** –

Returns

class `django_elasticsearch_dsl_drf.filter_backends.search.query_backends.`**MatchQueryBackend**

Bases: *`django_elasticsearch_dsl_drf.filter_backends.search.query_backends.base.BaseSearchQueryBackend`*

Match query backend.

classmethod construct_search(*request*, *view*, *search_backend*)

Construct search.

Parameters

- **request** –
- **view** –
- **search_backend** –

Returns

query_type = 'match'

class `django_elasticsearch_dsl_drf.filter_backends.search.query_backends.`**MatchPhraseQueryBa**

Bases: *`django_elasticsearch_dsl_drf.filter_backends.search.query_backends.base.BaseSearchQueryBackend`*

Match phrase query backend.

classmethod construct_search(*request*, *view*, *search_backend*)

Construct search.

Parameters

- **request** –
- **view** –
- **search_backend** –

Returns

query_type = 'match_phrase'

class `django_elasticsearch_dsl_drf.filter_backends.search.query_backends.`**MatchPhrasePrefixQ**

Bases: *`django_elasticsearch_dsl_drf.filter_backends.search.query_backends.base.BaseSearchQueryBackend`*

Match phrase prefix query backend.

classmethod construct_search(*request*, *view*, *search_backend*)

Construct search.

Parameters

- **request** –
- **view** –
- **search_backend** –

Returns

query_type = 'match_phrase_prefix'

class `django_elasticsearch_dsl_drf.filter_backends.search.query_backends.`**MultiMatchQueryBac**

Bases: *`django_elasticsearch_dsl_drf.filter_backends.search.query_backends.base.BaseSearchQueryBackend`*

Multi match query backend.

classmethod construct_search(*request*, *view*, *search_backend*)

Construct search.

In case of multi match, we always look in a group of fields. Thus, matching per field is no longer valid use case here. However, we might want to have multiple fields enabled for multi match per view set, and only search in some of them in specific request.

Example:

/search/books/?search_multi_match=lorem ipsum /search/books/?search_multi_match=title,summary:lorem ipsum

Note, that multiple searches are not supported (would not raise an exception, but would simply take only the first):

/search/books/?search_multi_match=title,summary:lorem ipsum
&search_multi_match=author,publisher=o'reily

In the view-set fields shall be defined in a very simple way. The only accepted argument would be boost (per field).

Example 1 (complex):

multi_match_search_fields = { 'title': {'field': 'title.english', 'boost': 4}, 'summary': {'boost': 2}, 'description': None,

}

Example 2 (simple list):

multi_match_search_fields = ('title', 'summary', 'description',

)

Parameters

- **request** –
- **view** –
- **search_backend** –

Returns

classmethod get_field(*field*, *options*)

Get field.

Parameters

- **field** –
- **options** –

Returns

classmethod get_query_options(*request*, *view*, *search_backend*)

query_type = 'multi_match'

class `django_elasticsearch_dsl_drf.filter_backends.search.query_backends.`**NestedQueryBacken**

Bases: *`django_elasticsearch_dsl_drf.filter_backends.search.query_backends.base.BaseSearchQueryBackend`*

Nested query backend.

classmethod construct_search(*request*, *view*, *search_backend*)

Construct search.

Dictionary key is the GET param name. The path option stands for the path in Elasticsearch.

Type 1:

search_nested_fields = {

'country': { 'path': 'country', 'fields': ['name'],

}, 'city': {

'path': 'country.city', 'fields': ['name'],

},

}

Type 2:

search_nested_fields = {

'country': { 'path': 'country', 'fields': [{'name': {'boost': 2}}]

}, 'city': {

'path': 'country.city', 'fields': [{'name': {'boost': 2}}]

},

}

Parameters

- **request** –
- **view** –
- **search_backend** –

Returns

query_type = 'nested'

class `django_elasticsearch_dsl_drf.filter_backends.search.query_backends.`**SimpleQueryString**

Bases: *django_elasticsearch_dsl_drf.filter_backends.search.query_backends.base.BaseSearchQueryBackend*

Simple query string query backend.

classmethod construct_search(*request*, *view*, *search_backend*)

Construct search.

In case of multi match, we always look in a group of fields. Thus, matching per field is no longer valid use case here. However, we might want to have multiple fields enabled for multi match per view set, and only search in some of them in specific request.

Example:

/search/books/?search_simple_query_string= "fried eggs" %2B(eggplant | potato) -frittata

/search/books/?search_simple_query_string= title,summary:"fried eggs" +(eggplant | potato) -frittata

Note, that multiple searches are not supported (would not raise an exception, but would simply take only the first):

/search/books/?search_simple_query_string= title,summary:"fried eggs" +(eggplant | potato) -frittata &search_simple_query_string= author,publisher="fried eggs" +(eggplant | potato) -frittata

In the view-set fields shall be defined in a very simple way. The only accepted argument would be boost (per field).

Example 1 (complex):

simple_query_string_search_fields = { 'title': {'field': 'title.english', 'boost': 4}, 'summary': {'boost': 2}, 'description': None,

}

Example 2 (simple list):

simple_query_string_search_fields = ('title', 'summary', 'description',

)

Query examples:

http://localhost:8000/search /books-simple-query-string-search-backend /?search_simple_query_string=%22Pool%20of%20Tears%22

http://localhost:8000/search /books-simple-query-string-search-backend /?search_simple_query_string=%22Pool%20of%20Tears%22 -considering

Parameters

- **request** –
- **view** –
- **search_backend** –

Returns

classmethod get_field(*field*, *options*)

Get field.

Parameters

- **field** –
- **options** –

Returns

classmethod get_query_options(*request*, *view*, *search_backend*)

query_type = 'simple_query_string'

12.18.1.2.1.32 Submodules

12.18.1.2.1.33 django_elasticsearch_dsl_drf.filter_backends.search.base module

Base search backend.

class `django_elasticsearch_dsl_drf.filter_backends.search.base.`**BaseSearchFilterBackend**

Bases: `rest_framework.filters.BaseFilterBackend`, *`django_elasticsearch_dsl_drf.filter_backends.mixins.FilterBackendMixin`*

Base search filter backend.

filter_queryset(*request*, *queryset*, *view*)

Filter the queryset.

Parameters

- **request** (*`rest_framework.request.Request`*) – Django REST framework request.
- **queryset** (*`elasticsearch_dsl.search.Search`*) – Base queryset.
- **view** (*`rest_framework.viewsets.ReadOnlyModelViewSet`*) – View.

Returns Updated queryset.

Return type elasticsearch_dsl.search.Search

get_coreschema_field(*field*)

get_query_backends(*request*, *view*)

Get query backends.

Returns

get_schema_fields(*view*)

get_search_query_params(*request*)

Get search query params.

Parameters **request** (*`rest_framework.request.Request`*) – Django REST framework request.

Returns List of search query params.

Return type list

matching = 'should'

query_backends = []

search_param = 'search'

12.18.1.2.1.34 django_elasticsearch_dsl_drf.filter_backends.search.compound module

Compound search backend.

class `django_elasticsearch_dsl_drf.filter_backends.search.compound.`**CompoundSearchFilterBac**

Bases: *`django_elasticsearch_dsl_drf.filter_backends.search.base.BaseSearchFilterBackend`*

Compound search backend.

query_backends = [<class 'django_elasticsearch_dsl_drf.filter_backends.search.query_ba

12.18.1.2.1.35 django_elasticsearch_dsl_drf.filter_backends.search.historical module

Search backend. Most likely to be deprecated soon.

class `django_elasticsearch_dsl_drf.filter_backends.search.historical.`**SearchFilterBackend**

Bases: `rest_framework.filters.BaseFilterBackend`, *`django_elasticsearch_dsl_drf.filter_backends.mixins.FilterBackendMixin`*

Search filter backend for Elasticsearch.

Example:

```
>>> from django_elasticsearch_dsl_drf.filter_backends import (
>>>     SearchFilterBackend
>>> )
>>> from django_elasticsearch_dsl_drf.viewsets import (
>>>     BaseDocumentViewSet,
>>> )
>>>
>>> # Local article document definition
>>> from .documents import ArticleDocument
>>>
>>> # Local article document serializer
>>> from .serializers import ArticleDocumentSerializer
>>>
>>> class ArticleDocumentView(BaseDocumentViewSet):
>>>
>>>     document = ArticleDocument
>>>     serializer_class = ArticleDocumentSerializer
>>>     filter_backends = [SearchFilterBackend,]
>>>     search_fields = (
>>>         'title',
>>>         'content',
>>>     )
>>>     search_nested_fields = {
>>>         'state': ['name'],
>>>         'documents.author': ['title', 'description'],
>>>     }
```

construct_nested_search(*request*, *view*)

Construct nested search.

We have to deal with two types of structures:

Type 1:

```
>>> search_nested_fields = {
>>>     'country': {
>>>         'path': 'country',
>>>         'fields': ['name'],
>>>     },
>>>     'city': {
>>>         'path': 'country.city',
>>>         'fields': ['name'],
>>>     },
>>> }
```

Type 2:

```
>>> search_nested_fields = {
>>>     'country': {
>>>         'path': 'country',
>>>         'fields': [{'name': {'boost': 2}}]
>>>     },
>>>     'city': {
>>>         'path': 'country.city',
>>>         'fields': [{'name': {'boost': 2}}]
>>>     },
>>> }
```

Parameters

- **request** (*rest_framework.request.Request*) – Django REST framework request.
- **queryset** (*elasticsearch_dsl.search.Search*) – Base queryset.
- **view** (*rest_framework.viewsets.ReadOnlyModelViewSet*) – View.

Returns Updated queryset.

Return type elasticsearch_dsl.search.Search

construct_search(*request*, *view*)

Construct search.

We have to deal with two types of structures:

Type 1:

```
>>> search_fields = (
>>>     'title',
>>>     'description',
>>>     'summary',
>>> )
```

Type 2:

```
>>> search_fields = {
>>>     'title': {'boost': 2},
>>>     'description': None,
>>>     'summary': None,
>>> }
```

Parameters

- **request** (*rest_framework.request.Request*) – Django REST framework request.
- **queryset** (*elasticsearch_dsl.search.Search*) – Base queryset.
- **view** (*rest_framework.viewsets.ReadOnlyModelViewSet*) – View.

Returns Updated queryset.
Return type elasticsearch_dsl.search.Search

filter_queryset(*request*, *queryset*, *view*)
Filter the queryset.
Parameters

- **request** (*rest_framework.request.Request*) – Django REST framework request.
- **queryset** (*elasticsearch_dsl.search.Search*) – Base queryset.
- **view** (*rest_framework.viewsets.ReadOnlyModelViewSet*) – View.

Returns Updated queryset.
Return type elasticsearch_dsl.search.Search

get_coreschema_field(*field*)

get_schema_fields(*view*)

get_search_query_params(*request*)
Get search query params.
Parameters **request** (*rest_framework.request.Request*) – Django REST framework request.
Returns List of search query params.
Return type list

search_param = 'search'

12.18.1.2.1.36 django_elasticsearch_dsl_drf.filter_backends.search.multi_match module

Multi match search filter backend.

class django_elasticsearch_dsl_drf.filter_backends.search.multi_match.**MultiMatchSearchFilte**
Bases: *django_elasticsearch_dsl_drf.filter_backends.search.base.BaseSearchFilterBackend*

Multi match search filter backend.

matching = 'must'

query_backends = [<class 'django_elasticsearch_dsl_drf.filter_backends.search.query_ba

search_param = 'search_multi_match'

12.18.1.2.1.37 django_elasticsearch_dsl_drf.filter_backends.search.query_string module

12.18.1.2.1.38 django_elasticsearch_dsl_drf.filter_backends.search.simple_query_string module

Simple query string search filter backend.

class `django_elasticsearch_dsl_drf.filter_backends.search.simple_query_string.`**SimpleQuerySt**

Bases: *`django_elasticsearch_dsl_drf.filter_backends.search.base.BaseSearchFilterBackend`*

Simple query string search filter backend.

matching = 'must'

query_backends = [<class 'django_elasticsearch_dsl_drf.filter_backends.search.query_ba

search_param = 'search_simple_query_string'

12.18.1.2.1.39 Module contents

Search filter backends.

class `django_elasticsearch_dsl_drf.filter_backends.search.`**BaseSearchFilterBackend**

Bases: `rest_framework.filters.BaseFilterBackend`, *`django_elasticsearch_dsl_drf.filter_backends.mixins.FilterBackendMixin`*

Base search filter backend.

filter_queryset(*request*, *queryset*, *view*)

Filter the queryset.

Parameters

- **request** (*`rest_framework.request.Request`*) – Django REST framework request.
- **queryset** (*`elasticsearch_dsl.search.Search`*) – Base queryset.
- **view** (*`rest_framework.viewsets.ReadOnlyModelViewSet`*) – View.

Returns Updated queryset.

Return type elasticsearch_dsl.search.Search

get_coreschema_field(*field*)

get_query_backends(*request*, *view*)

Get query backends.

Returns

get_schema_fields(*view*)

get_search_query_params(*request*)

Get search query params.

Parameters **request** (*`rest_framework.request.Request`*) – Django REST framework request.

Returns List of search query params.

Return type list

matching = 'should'

query_backends = []

search_param = 'search'

class `django_elasticsearch_dsl_drf.filter_backends.search.`**CompoundSearchFilterBackend**

Bases: *`django_elasticsearch_dsl_drf.filter_backends.search.base.BaseSearchFilterBackend`*

Compound search backend.

query_backends = [<class 'django_elasticsearch_dsl_drf.filter_backends.search.query_ba

class django_elasticsearch_dsl_drf.filter_backends.search.**MultiMatchSearchFilterBackend**

Bases: *django_elasticsearch_dsl_drf.filter_backends.search.base.BaseSearchFilterBackend*

Multi match search filter backend.

matching = 'must'

query_backends = [<class 'django_elasticsearch_dsl_drf.filter_backends.search.query_ba

search_param = 'search_multi_match'

class django_elasticsearch_dsl_drf.filter_backends.search.**SearchFilterBackend**

Bases: rest_framework.filters.BaseFilterBackend, *django_elasticsearch_dsl_drf.filter_backends.mixins.FilterBackendMixin*

Search filter backend for Elasticsearch.

Example:

```
>>> from django_elasticsearch_dsl_drf.filter_backends import (
>>>     SearchFilterBackend
>>> )
>>> from django_elasticsearch_dsl_drf.viewsets import (
>>>     BaseDocumentViewSet,
>>> )
>>>
>>> # Local article document definition
>>> from .documents import ArticleDocument
>>>
>>> # Local article document serializer
>>> from .serializers import ArticleDocumentSerializer
>>>
>>> class ArticleDocumentView(BaseDocumentViewSet):
>>>
>>>     document = ArticleDocument
>>>     serializer_class = ArticleDocumentSerializer
>>>     filter_backends = [SearchFilterBackend,]
>>>     search_fields = (
>>>         'title',
>>>         'content',
>>>     )
>>>     search_nested_fields = {
>>>         'state': ['name'],
>>>         'documents.author': ['title', 'description'],
>>>     }
```

construct_nested_search(*request*, *view*)

Construct nested search.

We have to deal with two types of structures:

Type 1:

```
>>> search_nested_fields = {
>>>     'country': {
>>>         'path': 'country',
>>>         'fields': ['name'],
>>>     },
```

(continues on next page)

(continued from previous page)

```
>>>     'city': {
>>>         'path': 'country.city',
>>>         'fields': ['name'],
>>>     },
>>> }
```

Type 2:

```
>>> search_nested_fields = {
>>>     'country': {
>>>         'path': 'country',
>>>         'fields': [{'name': {'boost': 2}}]
>>>     },
>>>     'city': {
>>>         'path': 'country.city',
>>>         'fields': [{'name': {'boost': 2}}]
>>>     },
>>> }
```

Parameters

- **request** (*rest_framework.request.Request*) – Django REST framework request.
- **queryset** (*elasticsearch_dsl.search.Search*) – Base queryset.
- **view** (*rest_framework.viewsets.ReadOnlyModelViewSet*) – View.

Returns Updated queryset.

Return type elasticsearch_dsl.search.Search

construct_search(*request*, *view*)

Construct search.

We have to deal with two types of structures:

Type 1:

```
>>> search_fields = (
>>>     'title',
>>>     'description',
>>>     'summary',
>>> )
```

Type 2:

```
>>> search_fields = {
>>>     'title': {'boost': 2},
>>>     'description': None,
>>>     'summary': None,
>>> }
```

Parameters

- **request** (*rest_framework.request.Request*) – Django REST framework request.
- **queryset** (*elasticsearch_dsl.search.Search*) – Base queryset.

- **view** (*rest_framework.viewsets.ReadOnlyModelViewSet*) – View.

Returns Updated queryset.
Return type elasticsearch_dsl.search.Search

filter_queryset(*request*, *queryset*, *view*)
Filter the queryset.
Parameters

- **request** (*rest_framework.request.Request*) – Django REST framework request.
- **queryset** (*elasticsearch_dsl.search.Search*) – Base queryset.
- **view** (*rest_framework.viewsets.ReadOnlyModelViewSet*) – View.

Returns Updated queryset.
Return type elasticsearch_dsl.search.Search

get_coreschema_field(*field*)

get_schema_fields(*view*)

get_search_query_params(*request*)
Get search query params.
Parameters **request** (*rest_framework.request.Request*) – Django REST framework request.
Returns List of search query params.
Return type list

search_param = 'search'

class django_elasticsearch_dsl_drf.filter_backends.search.**SimpleQueryStringSearchFilterBac**
Bases: *django_elasticsearch_dsl_drf.filter_backends.search.base.BaseSearchFilterBackend*

Simple query string search filter backend.

matching = 'must'

query_backends = [<class 'django_elasticsearch_dsl_drf.filter_backends.search.query_ba

search_param = 'search_simple_query_string'

12.18.1.2.1.40 django_elasticsearch_dsl_drf.filter_backends.suggester package

12.18.1.2.1.41 Submodules

12.18.1.2.1.42 django_elasticsearch_dsl_drf.filter_backends.suggester.functional module

Functional suggesters backend.

It's assumed, that fields you're planning to query suggestions for have been properly indexed using `fields.CompletionField`.

Example:

```
>>> from django_elasticsearch_dsl import Document, Index, fields
>>>
>>> from books.models import Publisher
>>>
>>> # Name of the Elasticsearch index
>>> PUBLISHER_INDEX = Index(PUBLISHER_INDEX_NAME)
>>> # See Elasticsearch Indices API reference for available settings
>>> PUBLISHER_INDEX.settings(
>>>     number_of_shards=1,
>>>     number_of_replicas=1
>>> )
>>>
>>> @PUBLISHER_INDEX.doc_type
>>> class PublisherDocument(Document):
>>>     "Publisher Elasticsearch document."
>>>
>>>     id = fields.IntegerField(attr='id')
>>>
>>>     name = fields.StringField(
>>>         fields={
>>>             'raw': fields.StringField(analyzer='keyword'),
>>>             'suggest': fields.CompletionField(),
>>>         }
>>>     )
>>>
>>>     info = fields.StringField()
>>>
>>>     address = fields.StringField(
>>>         fields={
>>>             'raw': fields.StringField(analyzer='keyword')
>>>         }
>>>     )
>>>
>>>     city = fields.StringField(
>>>         fields={
>>>             'raw': fields.StringField(analyzer='keyword'),
>>>             'suggest': fields.CompletionField(),
>>>         }
>>>     )
>>>
>>>     state_province = fields.StringField(
>>>         fields={
>>>             'raw': fields.StringField(analyzer='keyword'),
>>>             'suggest': fields.CompletionField(),
>>>         }
>>>     )
>>>
>>>     country = fields.StringField(
>>>         fields={
>>>             'raw': fields.StringField(analyzer='keyword'),
>>>             'suggest': fields.CompletionField(),
>>>         }
>>>     )
>>>
>>>     website = fields.StringField()
>>>
>>>     class Meta(object):
```

(continues on next page)

(continued from previous page)

```
>>>         "Meta options."
>>>
>>>         model = Publisher  # The model associate with this Document
```

class `django_elasticsearch_dsl_drf.filter_backends.suggester.functional.`**`FunctionalSuggester`**

Bases: `rest_framework.filters.BaseFilterBackend`, *`django_elasticsearch_dsl_drf.filter_backends.mixins.FilterBackendMixin`*

Suggester filter backend for Elasticsearch.

Suggestion functionality is exclusive. Once you have queried the `FunctionalSuggesterFilterBackend`, the latter will transform your current search query into another search query (altered). Therefore, always add it as the very last filter backend.

Example:

```
>>> from django_elasticsearch_dsl_drf.constants import (
>>>     FUNCTIONAL_SUGGESTER_COMPLETION_MATCH,
>>>     FUNCTIONAL_SUGGESTER_COMPLETION_PREFIX,
>>>     FUNCTIONAL_SUGGESTER_PHRASE_MATCH,
>>>     FUNCTIONAL_SUGGESTER_PHRASE_MATCH,
>>>     FUNCTIONAL_SUGGESTER_TERM_MATCH,
>>> )
>>> from django_elasticsearch_dsl_drf.filter_backends import (
>>>     FunctionalSuggesterFilterBackend
>>> )
>>> from django_elasticsearch_dsl_drf.viewsets import DocumentViewSet
>>>
>>> # Local PublisherDocument definition
>>> from .documents import PublisherDocument
>>>
>>> # Local PublisherDocument serializer
>>> from .serializers import PublisherDocumentSerializer
>>>
>>> class PublisherDocumentView(DocumentViewSet):
>>>
>>>     document = PublisherDocument
>>>     serializer_class = PublisherDocumentSerializer
>>>     filter_backends = [
>>>         # ...
>>>         FunctionalSuggesterFilterBackend,
>>>     ]
>>>     # Suggester fields
>>>     functional_suggester_fields = {
>>>         'name_suggest': {
>>>             'field': 'name.suggest',
>>>             'suggesters': [
>>>                 FUNCTIONAL_SUGGESTER_COMPLETION_MATCH,
>>>                 FUNCTIONAL_SUGGESTER_COMPLETION_PREFIX,
>>>             ],
>>>         },
>>>         'city_suggest': {
>>>             'field': 'city.suggest',
>>>             'suggesters': [
>>>                 FUNCTIONAL_SUGGESTER_COMPLETION_PREFIX,
>>>             ],
>>>         },
```

(continues on next page)

(continued from previous page)

```
>>>         'state_province_suggest': {
>>>             'field': 'state_province.suggest',
>>>             'suggesters': [
>>>                 FUNCTIONAL_SUGGESTER_COMPLETION_MATCH,
>>>             ],
>>>         },
>>>         'country_suggest': {
>>>             'field': 'country.suggest',
>>>             'suggesters': [
>>>                 FUNCTIONAL_SUGGESTER_COMPLETION_PREFIX,
>>>             ],
>>>         },
>>>     }
```

classmethod apply_query_size(*queryset*, *options*)

Apply query size.

Parameters

- **queryset** –
- **options** –

Returns

classmethod apply_suggester_completion_match(*suggester_name*, *queryset*, *options*, *value*)

Apply *completion* suggester match.

This is effective when used with Ngram fields.

Parameters

- **suggester_name** (*str*) –
- **queryset** (*elasticsearch_dsl.search.Search*) – Original queryset.
- **options** (*dict*) – Filter options.
- **value** (*str*) – value to filter on.

Returns Modified queryset.

Return type elasticsearch_dsl.search.Search

classmethod apply_suggester_completion_prefix(*suggester_name*, *queryset*, *options*, *value*)

Apply *completion* suggester prefix.

This is effective when used with Keyword fields.

Parameters

- **suggester_name** (*str*) –
- **queryset** (*elasticsearch_dsl.search.Search*) – Original queryset.
- **options** (*dict*) – Filter options.
- **value** (*str*) – value to filter on.

Returns Modified queryset.

Return type elasticsearch_dsl.search.Search

clean_queryset(*queryset*)

Clean the queryset.

- Remove aggregations.

- Remove highlight.
- Remove sorting options.

Parameters **queryset** –
Returns

extract_field_name(*field_name*)

Extract field name.

For instance, "name.suggest" or "name.raw" becomes "name".

Parameters **field_name** –
Returns
Return type str

filter_queryset(*request*, *queryset*, *view*)

Filter the queryset.

Parameters

- **request** (*rest_framework.request.Request*) – Django REST framework request.
- **queryset** (*elasticsearch_dsl.search.Search*) – Base queryset.
- **view** (*rest_framework.viewsets.ReadOnlyModelViewSet*) – View.

Returns Updated queryset.
Return type elasticsearch_dsl.search.Search

get_suggester_query_params(*request*, *view*)

Get query params to be for suggestions.

Parameters

- **request** (*rest_framework.request.Request*) – Django REST framework request.
- **view** (*rest_framework.viewsets.ReadOnlyModelViewSet*) – View.

Returns Request query params to filter on.
Return type dict

classmethod prepare_suggester_fields(*view*)

Prepare filter fields.

Parameters **view** (*rest_framework.viewsets.ReadOnlyModelViewSet*) –
Returns Filtering options.
Return type dict

serialize_queryset(*queryset*, *suggester_name*, *value*, *serializer_field*)

Serialize queryset.

This shall be done here, since we don't want to delegate it to pagination.

Parameters

- **queryset** –
- **suggester_name** –
- **value** –
- **serializer_field** –

Returns

12.18.1.2.1.43 django_elasticsearch_dsl_drf.filter_backends.suggester.native module

Suggesters backend.

It's assumed, that fields you're planning to query suggestions for have been properly indexed using `fields.CompletionField`.

Example:

```
>>> from django_elasticsearch_dsl import Document, Index, fields
>>>
>>> from books.models import Publisher
>>>
>>> # Name of the Elasticsearch index
>>> PUBLISHER_INDEX = Index(PUBLISHER_INDEX_NAME)
>>> # See Elasticsearch Indices API reference for available settings
>>> PUBLISHER_INDEX.settings(
>>>     number_of_shards=1,
>>>     number_of_replicas=1
>>> )
>>>
>>> @PUBLISHER_INDEX.doc_type
>>> class PublisherDocument(Document):
>>>     "Publisher Elasticsearch document."
>>>
>>>     id = fields.IntegerField(attr='id')
>>>
>>>     name = fields.StringField(
>>>         fields={
>>>             'raw': fields.StringField(analyzer='keyword'),
>>>             'suggest': fields.CompletionField(),
>>>         }
>>>     )
>>>
>>>     info = fields.StringField()
>>>
>>>     address = fields.StringField(
>>>         fields={
>>>             'raw': fields.StringField(analyzer='keyword')
>>>         }
>>>     )
>>>
>>>     city = fields.StringField(
>>>         fields={
>>>             'raw': fields.StringField(analyzer='keyword'),
>>>             'suggest': fields.CompletionField(),
>>>         }
>>>     )
>>>
>>>     state_province = fields.StringField(
>>>         fields={
>>>             'raw': fields.StringField(analyzer='keyword'),
>>>             'suggest': fields.CompletionField(),
>>>         }
>>>     )
>>>
>>>     country = fields.StringField(
>>>         fields={
```

(continues on next page)

(continued from previous page)

```
>>>             'raw': fields.StringField(analyzer='keyword'),
>>>             'suggest': fields.CompletionField(),
>>>         }
>>>     )
>>>
>>>     website = fields.StringField()
>>>
>>>     class Meta(object):
>>>         "Meta options."
>>>
>>>         model = Publisher  # The model associate with this Document
```

class `django_elasticsearch_dsl_drf.filter_backends.suggester.native.`**`SuggesterFilterBackend`**

Bases: `rest_framework.filters.BaseFilterBackend`, *`django_elasticsearch_dsl_drf.filter_backends.mixins.FilterBackendMixin`*

Suggester filter backend for Elasticsearch.

Suggestion functionality is exclusive. Once you have queried the `SuggesterFilterBackend`, the latter will transform your current search query into suggestion search query (which is very different). Therefore, always add it as the very last filter backend.

Example:

```
>>> from django_elasticsearch_dsl_drf.constants import (
>>>     SUGGESTER_TERM,
>>>     SUGGESTER_PHRASE,
>>>     SUGGESTER_COMPLETION,
>>> )
>>> from django_elasticsearch_dsl_drf.filter_backends import (
>>>     SuggesterFilterBackend
>>> )
>>> from django_elasticsearch_dsl_drf.viewsets import DocumentViewSet
>>>
>>> # Local PublisherDocument definition
>>> from .documents import PublisherDocument
>>>
>>> # Local PublisherDocument serializer
>>> from .serializers import PublisherDocumentSerializer
>>>
>>> class PublisherDocumentView(BaseDocumentViewSet):
>>>
>>>     document = PublisherDocument
>>>     serializer_class = PublisherDocumentSerializer
>>>     filter_backends = [
>>>         # ...
>>>         SuggesterFilterBackend,
>>>     ]
>>>     # Suggester fields
>>>     suggester_fields = {
>>>         'name_suggest': {
>>>             'field': 'name.suggest',
>>>             'suggesters': [
>>>                 SUGGESTER_TERM,
>>>                 SUGGESTER_PHRASE,
>>>                 SUGGESTER_COMPLETION,
>>>             ],
```

(continues on next page)

(continued from previous page)

```
>>>         },
>>>         'city_suggest': {
>>>             'field': 'city.suggest',
>>>             'suggesters': [
>>>                 SUGGESTER_COMPLETION,
>>>             ],
>>>         },
>>>         'state_province_suggest': {
>>>             'field': 'state_province.suggest',
>>>             'suggesters': [
>>>                 SUGGESTER_COMPLETION,
>>>             ],
>>>         },
>>>         'country_suggest': {
>>>             'field': 'country.suggest',
>>>             'suggesters': [
>>>                 SUGGESTER_COMPLETION,
>>>             ],
>>>         },
>>>     }
```

classmethod apply_suggester_completion(*suggester_name*, *queryset*, *options*, *value*)

Apply *completion* suggester.

Parameters

- **suggester_name** (*str*) –
- **queryset** (*elasticsearch_dsl.search.Search*) – Original queryset.
- **options** (*dict*) – Filter options.
- **value** (*str*) – value to filter on.

Returns Modified queryset.

Return type elasticsearch_dsl.search.Search

classmethod apply_suggester_phrase(*suggester_name*, *queryset*, *options*, *value*)

Apply *phrase* suggester.

Parameters

- **suggester_name** (*str*) –
- **queryset** (*elasticsearch_dsl.search.Search*) – Original queryset.
- **options** (*dict*) – Filter options.
- **value** (*str*) – value to filter on.

Returns Modified queryset.

Return type elasticsearch_dsl.search.Search

classmethod apply_suggester_term(*suggester_name*, *queryset*, *options*, *value*)

Apply *term* suggester.

Parameters

- **suggester_name** (*str*) –
- **queryset** (*elasticsearch_dsl.search.Search*) – Original queryset.
- **options** (*dict*) – Filter options.

- **value** (*str*) – value to filter on.

Returns Modified queryset.

Return type elasticsearch_dsl.search.Search

filter_queryset(*request*, *queryset*, *view*)

Filter the queryset.

Parameters

- **request** (*rest_framework.request.Request*) – Django REST framework request.
- **queryset** (*elasticsearch_dsl.search.Search*) – Base queryset.
- **view** (*rest_framework.viewsets.ReadOnlyModelViewSet*) – View.

Returns Updated queryset.

Return type elasticsearch_dsl.search.Search

classmethod get_suggester_context(*field*, *suggester_name*, *request*, *view*)

Get suggester context.

Given the following definition (in ViewSets):

```
>>> # Suggester fields
>>> suggester_fields = {
>>>     'title_suggest': {
>>>         'field': 'title.suggest',
>>>         'default_suggester': SUGGESTER_COMPLETION,
>>>     },
>>>     'title_suggest_context': {
>>>         'field': 'title.suggest_context',
>>>         'default_suggester': SUGGESTER_COMPLETION,
>>>         'completion_options': {
>>>             'filters': {
>>>                 'title_suggest_tag': 'tag',
>>>                 'title_suggest_state': 'state',
>>>                 'title_suggest_publisher': 'publisher',
>>>             },
>>>             'size': 10,
>>>         }
>>>     },
>>> }
```

http://localhost:8000/search/books-frontend/suggest/?title_suggest_context=M

When talking about the queries made, we have the following. Multiple values per field are combined with OR:

```
>>> completion={
>>>     'field': options['field'],
>>>     'size': 10,
>>>     'contexts': {
>>>         'tag': ['History', 'Drama'],
>>>     }
>>> }
```

The following works with OR as well, so it seems we have OR only. However, the following construction is more handy, since it allows us to play with boosting nicely. Also, it allows to provide *prefix* param (which in case of the example given below means that suggestions shall match both categories with "Child", "Children", "Childrend's"). Simply put it's treated as *prefix*, rather than *term*.

```
>>> completion={
>>>     'field': options['field'],
>>>     'size': 10,
>>>     'contexts': {
>>>         'tag': [
>>>             {'context': 'History'},
>>>             {'context': 'Drama', 'boost': 2},
>>>             {'context': 'Children', 'prefix': True},
>>>         ],
>>>     },
>>> }
```

Sample query for *category* filter:

/search/books-frontend/suggest/ ?title_suggest_context=M &title_suggest_tag=Art__2.0 &title_suggest_tag=Documentary__2.0__prefix &title_suggest_publisher=Apress

The query params would be:

query_params: <QueryDict: {
'title_suggest_context': ['M'], 'title_suggest_tag': ['Art__2.0', 'Documentary__2.0__prefix'], 'title_suggest_publisher': ['Apress']
}>

Sample query for *geo* filter:

/search/address/suggest/ ?street_suggest_context=M &street_suggest_loc=43.66__-79.22__2.0__10000km

The query params would be:

query_params: <QueryDict: {
'street_suggest_context': ['M'], 'street_suggest_loc': ['Art__43.66__-79.22__2.0__10000km'],
}>

Returns

get_suggester_query_params(*request*, *view*)

Get query params to be for suggestions.

Parameters

- **request** (*rest_framework.request.Request*) – Django REST framework request.
- **view** (*rest_framework.viewsets.ReadOnlyModelViewSet*) – View.

Returns Request query params to filter on.

Return type dict

classmethod prepare_suggester_fields(*view*)

Prepare filter fields.

Parameters **view**(*rest_framework.viewsets.ReadOnlyModelViewSet*) –

Returns Filtering options.

Return type dict

12.18.1.2.1.44 Module contents

Suggester filtering backends.

class `django_elasticsearch_dsl_drf.filter_backends.suggester.`**SuggesterFilterBackend**

Bases: `rest_framework.filters.BaseFilterBackend`, *`django_elasticsearch_dsl_drf.filter_backends.mixins.FilterBackendMixin`*

Suggester filter backend for Elasticsearch.

Suggestion functionality is exclusive. Once you have queried the `SuggesterFilterBackend`, the latter will transform your current search query into suggestion search query (which is very different). Therefore, always add it as the very last filter backend.

Example:

```
>>> from django_elasticsearch_dsl_drf.constants import (
>>>     SUGGESTER_TERM,
>>>     SUGGESTER_PHRASE,
>>>     SUGGESTER_COMPLETION,
>>> )
>>> from django_elasticsearch_dsl_drf.filter_backends import (
>>>     SuggesterFilterBackend
>>> )
>>> from django_elasticsearch_dsl_drf.viewsets import DocumentViewSet
>>>
>>> # Local PublisherDocument definition
>>> from .documents import PublisherDocument
>>>
>>> # Local PublisherDocument serializer
>>> from .serializers import PublisherDocumentSerializer
>>>
>>> class PublisherDocumentView(BaseDocumentViewSet):
>>>
>>>     document = PublisherDocument
>>>     serializer_class = PublisherDocumentSerializer
>>>     filter_backends = [
>>>         # ...
>>>         SuggesterFilterBackend,
>>>     ]
>>>     # Suggester fields
>>>     suggester_fields = {
>>>         'name_suggest': {
>>>             'field': 'name.suggest',
>>>             'suggesters': [
>>>                 SUGGESTER_TERM,
>>>                 SUGGESTER_PHRASE,
>>>                 SUGGESTER_COMPLETION,
>>>             ],
>>>         },
>>>         'city_suggest': {
>>>             'field': 'city.suggest',
>>>             'suggesters': [
>>>                 SUGGESTER_COMPLETION,
>>>             ],
>>>         },
>>>         'state_province_suggest': {
>>>             'field': 'state_province.suggest',
>>>             'suggesters': [
>>>                 SUGGESTER_COMPLETION,
>>>             ],
>>>         },
>>>         'country_suggest': {
>>>             'field': 'country.suggest',
>>>             'suggesters': [
>>>                 SUGGESTER_COMPLETION,
>>>             ],
```

(continues on next page)

(continued from previous page)

```
>>>         },
>>>     }
```

classmethod apply_suggester_completion(*suggester_name*, *queryset*, *options*, *value*)

Apply *completion* suggester.

Parameters

- **suggester_name** (*str*) –
- **queryset** (*elasticsearch_dsl.search.Search*) – Original queryset.
- **options** (*dict*) – Filter options.
- **value** (*str*) – value to filter on.

Returns Modified queryset.

Return type elasticsearch_dsl.search.Search

classmethod apply_suggester_phrase(*suggester_name*, *queryset*, *options*, *value*)

Apply *phrase* suggester.

Parameters

- **suggester_name** (*str*) –
- **queryset** (*elasticsearch_dsl.search.Search*) – Original queryset.
- **options** (*dict*) – Filter options.
- **value** (*str*) – value to filter on.

Returns Modified queryset.

Return type elasticsearch_dsl.search.Search

classmethod apply_suggester_term(*suggester_name*, *queryset*, *options*, *value*)

Apply *term* suggester.

Parameters

- **suggester_name** (*str*) –
- **queryset** (*elasticsearch_dsl.search.Search*) – Original queryset.
- **options** (*dict*) – Filter options.
- **value** (*str*) – value to filter on.

Returns Modified queryset.

Return type elasticsearch_dsl.search.Search

filter_queryset(*request*, *queryset*, *view*)

Filter the queryset.

Parameters

- **request** (*rest_framework.request.Request*) – Django REST framework request.
- **queryset** (*elasticsearch_dsl.search.Search*) – Base queryset.
- **view** (*rest_framework.viewsets.ReadOnlyModelViewSet*) – View.

Returns Updated queryset.

Return type elasticsearch_dsl.search.Search

classmethod get_suggester_context (*field*, *suggester_name*, *request*, *view*)

Get suggester context.

Given the following definition (in ViewSets):

```
>>> # Suggester fields
>>> suggester_fields = {
>>>     'title_suggest': {
>>>         'field': 'title.suggest',
>>>         'default_suggester': SUGGESTER_COMPLETION,
>>>     },
>>>     'title_suggest_context': {
>>>         'field': 'title.suggest_context',
>>>         'default_suggester': SUGGESTER_COMPLETION,
>>>         'completion_options': {
>>>             'filters': {
>>>                 'title_suggest_tag': 'tag',
>>>                 'title_suggest_state': 'state',
>>>                 'title_suggest_publisher': 'publisher',
>>>             },
>>>             'size': 10,
>>>         }
>>>     },
>>> }
```

http://localhost:8000/search/books-frontend/suggest/?title_suggest_context=M

When talking about the queries made, we have the following. Multiple values per field are combined with OR:

```
>>> completion={
>>>     'field': options['field'],
>>>     'size': 10,
>>>     'contexts': {
>>>         'tag': ['History', 'Drama'],
>>>     }
>>> }
```

The following works with OR as well, so it seems we have OR only. However, the following construction is more handy, since it allows us to play with boosting nicely. Also, it allows to provide *prefix* param (which in case of the example given below means that suggestions shall match both categories with "Child", "Children", "Childrend's"). Simply put it's treated as *prefix*, rather than *term*.

```
>>> completion={
>>>     'field': options['field'],
>>>     'size': 10,
>>>     'contexts': {
>>>         'tag': [
>>>             {'context': 'History'},
>>>             {'context': 'Drama', 'boost': 2},
>>>             {'context': 'Children', 'prefix': True},
>>>         ],
>>>     },
>>> }
```

Sample query for *category* filter:

/search/books-frontend/suggest/ ?title_suggest_context=M &title_suggest_tag=Art__2.0 &title_suggest_tag=Documentary__2.0__prefix &title_suggest_publisher=Apress

The query params would be:

query_params: <QueryDict: {
'title_suggest_context': ['M'], 'title_suggest_tag': ['Art__2.0', 'Documentary__2.0__prefix'], 'title_suggest_publisher': ['Apress']
}>

Sample query for *geo* filter:

/search/address/suggest/?street_suggest_context=M&street_suggest_loc=43.66__-79.22__2.0__10000km

The query params would be:

query_params: <QueryDict: {
'street_suggest_context': ['M'], 'street_suggest_loc': ['Art__43.66__-79.22__2.0__10000km'],
}>

Returns

get_suggester_query_params(*request*, *view*)

Get query params to be for suggestions.

Parameters

- **request** (*rest_framework.request.Request*) – Django REST framework request.
- **view** (*rest_framework.viewsets.ReadOnlyModelViewSet*) – View.

Returns Request query params to filter on.

Return type dict

classmethod prepare_suggester_fields(*view*)

Prepare filter fields.

Parameters **view** (*rest_framework.viewsets.ReadOnlyModelViewSet*) –

Returns Filtering options.

Return type dict

class django_elasticsearch_dsl_drf.filter_backends.suggester.**FunctionalSuggesterFilterBacke**

Bases: rest_framework.filters.BaseFilterBackend, *django_elasticsearch_dsl_drf.filter_backends.mixins.FilterBackendMixin*

Suggester filter backend for Elasticsearch.

Suggestion functionality is exclusive. Once you have queried the FunctionalSuggesterFilterBackend, the latter will transform your current search query into another search query (altered). Therefore, always add it as the very last filter backend.

Example:

```
>>> from django_elasticsearch_dsl_drf.constants import (
>>>     FUNCTIONAL_SUGGESTER_COMPLETION_MATCH,
>>>     FUNCTIONAL_SUGGESTER_COMPLETION_PREFIX,
>>>     FUNCTIONAL_SUGGESTER_PHRASE_MATCH,
>>>     FUNCTIONAL_SUGGESTER_PHRASE_MATCH,
>>>     FUNCTIONAL_SUGGESTER_TERM_MATCH,
>>> )
>>> from django_elasticsearch_dsl_drf.filter_backends import (
>>>     FunctionalSuggesterFilterBackend
>>> )
>>> from django_elasticsearch_dsl_drf.viewsets import DocumentViewSet
>>>
>>> # Local PublisherDocument definition
>>> from .documents import PublisherDocument
```

(continues on next page)

(continued from previous page)

```
>>>
>>> # Local PublisherDocument serializer
>>> from .serializers import PublisherDocumentSerializer
>>>
>>> class PublisherDocumentView(DocumentViewSet):
>>>
>>>     document = PublisherDocument
>>>     serializer_class = PublisherDocumentSerializer
>>>     filter_backends = [
>>>         # ...
>>>         FunctionalSuggesterFilterBackend,
>>>     ]
>>>     # Suggester fields
>>>     functional_suggester_fields = {
>>>         'name_suggest': {
>>>             'field': 'name.suggest',
>>>             'suggesters': [
>>>                 FUNCTIONAL_SUGGESTER_COMPLETION_MATCH,
>>>                 FUNCTIONAL_SUGGESTER_COMPLETION_PREFIX,
>>>             ],
>>>         },
>>>         'city_suggest': {
>>>             'field': 'city.suggest',
>>>             'suggesters': [
>>>                 FUNCTIONAL_SUGGESTER_COMPLETION_PREFIX,
>>>             ],
>>>         },
>>>         'state_province_suggest': {
>>>             'field': 'state_province.suggest',
>>>             'suggesters': [
>>>                 FUNCTIONAL_SUGGESTER_COMPLETION_MATCH,
>>>             ],
>>>         },
>>>         'country_suggest': {
>>>             'field': 'country.suggest',
>>>             'suggesters': [
>>>                 FUNCTIONAL_SUGGESTER_COMPLETION_PREFIX,
>>>             ],
>>>         },
>>>     }
```

classmethod apply_query_size(*queryset*, *options*)

Apply query size.

Parameters

- **queryset** –
- **options** –

Returns

classmethod apply_suggester_completion_match(*suggester_name*, *queryset*, *options*, *value*)

Apply *completion* suggester match.

This is effective when used with Ngram fields.

Parameters

- **suggester_name** (*str*) –

- **queryset** (*elasticsearch_dsl.search.Search*) – Original queryset.
- **options** (*dict*) – Filter options.
- **value** (*str*) – value to filter on.

Returns Modified queryset.
Return type elasticsearch_dsl.search.Search

classmethod apply_suggester_completion_prefix(*suggester_name*, *queryset*, *options*, *value*)

Apply *completion* suggester prefix.

This is effective when used with Keyword fields.

Parameters

- **suggester_name** (*str*) –
- **queryset** (*elasticsearch_dsl.search.Search*) – Original queryset.
- **options** (*dict*) – Filter options.
- **value** (*str*) – value to filter on.

Returns Modified queryset.
Return type elasticsearch_dsl.search.Search

clean_queryset(*queryset*)

Clean the queryset.

- Remove aggregations.
- Remove highlight.
- Remove sorting options.

Parameters **queryset** –
Returns

extract_field_name(*field_name*)

Extract field name.

For instance, "name.suggest" or "name.raw" becomes "name".

Parameters **field_name** –
Returns
Return type str

filter_queryset(*request*, *queryset*, *view*)

Filter the queryset.

Parameters

- **request** (*rest_framework.request.Request*) – Django REST framework request.
- **queryset** (*elasticsearch_dsl.search.Search*) – Base queryset.
- **view** (*rest_framework.viewsets.ReadOnlyModelViewSet*) – View.

Returns Updated queryset.
Return type elasticsearch_dsl.search.Search

get_suggester_query_params(*request*, *view*)

Get query params to be for suggestions.

Parameters

- **request** (*rest_framework.request.Request*) – Django REST framework request.
- **view** (*rest_framework.viewsets.ReadOnlyModelViewSet*) – View.

Returns Request query params to filter on.
Return type dict

classmethod prepare_suggester_fields(*view*)

Prepare filter fields.

Parameters **view** (*rest_framework.viewsets.ReadOnlyModelViewSet*) –
Returns Filtering options.
Return type dict

serialize_queryset(*queryset*, *suggester_name*, *value*, *serializer_field*)

Serialize queryset.

This shall be done here, since we don't want to delegate it to pagination.

Parameters

- **queryset** –
- **suggester_name** –
- **value** –
- **serializer_field** –

Returns

12.18.1.2.2 Submodules

12.18.1.2.3 django_elasticsearch_dsl_drf.filter_backends.faceted_search module

Faceted search backend.

class django_elasticsearch_dsl_drf.filter_backends.faceted_search.**FacetedSearchFilterBacke**

Bases: rest_framework.filters.BaseFilterBackend

Faceted search backend.

Example:

```
>>> from django_elasticsearch_dsl_drf.filter_backends import (
>>>     FacetedSearchFilterBackend
>>> )
>>> from elasticsearch_dsl import TermsFacet, DateHistogramFacet
>>> from django_elasticsearch_dsl_drf.viewsets import (
>>>     BaseDocumentViewSet,
>>> )
>>>
>>> # Local article document definition
>>> from .documents import ArticleDocument
>>>
>>> # Local article document serializer
>>> from .serializers import ArticleDocumentSerializer
>>>
>>> class ArticleDocumentView(BaseDocumentViewSet):
>>>
>>>     document = ArticleDocument
```

(continues on next page)

(continued from previous page)

```
>>>     serializer_class = ArticleDocumentSerializer
>>>     filter_backends = [FacetedSearchFilterBackend,]
>>>     faceted_search_fields = {
>>>         'title': 'title.raw',  # Uses `TermsFacet` by default
>>>         'state': {
>>>             'field': 'state.raw',
>>>             'facet': TermsFacet,
>>>         },
>>>         'publisher': {
>>>             'field': 'publisher.raw',
>>>             'facet': TermsFacet,
>>>             'enabled': False,
>>>         },
>>>         'date_published': {
>>>             'field': 'date_published.raw',
>>>             'facet': DateHistogramFacet,
>>>             'options': {
>>>                 'interval': 'month',
>>>             },
>>>             'enabled': True,
>>>         },
>>>
>>>     }
```

Facets make queries to be more heavy. That's why by default all facets are disabled and enabled only explicitly either in the filter options (*enabled* set to True) or via query params *?facet=state&facet=date_published*.

aggregate (*request*, *queryset*, *view*)

Aggregate.

Parameters

- **request** –
- **queryset** –
- **view** –

Returns

construct_facets (*request*, *view*)

Construct facets.

Turns the following structure:

```
>>> {
>>>     'publisher': {
>>>         'field': 'publisher.raw',
>>>         'facet': TermsFacet,
>>>         'enabled': False,
>>>     }
>>>     'date_published': {
>>>         'field': 'date_published',
>>>         'facet': DateHistogramFacet,
>>>         'options': {
>>>             'interval': 'month',
>>>         },
>>>         'enabled': True,
>>>     },
>>> }
```

Into the following structure:

```
>>> {
>>>     'publisher': TermsFacet(field='publisher.raw'),
>>>     'publishing_frequency': DateHistogramFacet(
>>>         field='date_published.raw',
>>>         interval='month'
>>>     ),
>>> }
```

faceted_search_param = 'facet'

filter_queryset(*request*, *queryset*, *view*)

Filter the queryset.

Parameters

- **request** (*rest_framework.request.Request*) – Django REST framework request.
- **queryset** (*elasticsearch_dsl.search.Search*) – Base queryset.
- **view** (*rest_framework.viewsets.ReadOnlyModelViewSet*) – View.

Returns Updated queryset.

Return type elasticsearch_dsl.search.Search

get_faceted_search_query_params(*request*)

Get faceted search query params.

Parameters **request** (*rest_framework.request.Request*) – Django REST framework request.

Returns List of search query params.

Return type list

classmethod prepare_faceted_search_fields(*view*)

Prepare faceted search fields.

Prepares the following structure:

```
>>> {
>>>     'publisher': {
>>>         'field': 'publisher.raw',
>>>         'facet': TermsFacet,
>>>         'enabled': False,
>>>     }
>>>     'date_published': {
>>>         'field': 'date_published.raw',
>>>         'facet': DateHistogramFacet,
>>>         'options': {
>>>             'interval': 'month',
>>>         },
>>>         'enabled': True,
>>>     },
>>> }
```

Parameters **view** (*rest_framework.viewsets.ReadOnlyModelViewSet*) –

Returns Faceted search fields options.

Return type dict

12.18.1.2.4 django_elasticsearch_dsl_drf.filter_backends.highlight module

Highlight backend.

class `django_elasticsearch_dsl_drf.filter_backends.highlight.`**`HighlightBackend`**

Bases: `rest_framework.filters.BaseFilterBackend`

Highlight backend.

Example:

```
>>> from django_elasticsearch_dsl_drf.filter_backends import (
>>>     HighlightBackend
>>> )
>>> from django_elasticsearch_dsl_drf.viewsets import (
>>>     BaseDocumentViewSet,
>>> )
>>>
>>> # Local article document definition
>>> from .documents import ArticleDocument
>>>
>>> # Local article document serializer
>>> from .serializers import ArticleDocumentSerializer
>>>
>>> class ArticleDocumentView(BaseDocumentViewSet):
>>>
>>>     document = ArticleDocument
>>>     serializer_class = ArticleDocumentSerializer
>>>     filter_backends = [HighlightBackend,]
>>>     highlight_fields = {
>>>         'author.name': {
>>>             'enabled': False,
>>>             'options': {
>>>                 'fragment_size': 150,
>>>                 'number_of_fragments': 3
>>>             }
>>>         }
>>>         'title': {
>>>             'options': {
>>>                 'pre_tags' : ["<em>"],
>>>                 'post_tags' : ["</em>"]
>>>             },
>>>             'enabled': True,
>>>         },
>>>     }
```

Highlight make queries to be more heavy. That's why by default all highlights are disabled and enabled only explicitly either in the filter options (*enabled* set to True) or via query params *?highlight=author.name&highlight=title*.

`filter_queryset`(*request*, *queryset*, *view*)

Filter the queryset.

Parameters

- **`request`** (*`rest_framework.request.Request`*) – Django REST framework request.
- **`queryset`** (*`elasticsearch_dsl.search.Search`*) – Base queryset.

- **view** (*rest_framework.viewsets.ReadOnlyModelViewSet*) – View.

Returns Updated queryset.
Return type elasticsearch_dsl.search.Search

get_highlight_query_params(*request*)
Get highlight query params.
Parameters **request** (*rest_framework.request.Request*) – Django REST framework request.
Returns List of search query params.
Return type list

highlight_param = 'highlight'

classmethod prepare_highlight_fields(*view*)
Prepare faceted search fields.

Prepares the following structure:

```
>>> {
>>>     'author.name': {
>>>         'enabled': False,
>>>         'options': {
>>>             'fragment_size': 150,
>>>             'number_of_fragments': 3
>>>         }
>>>     }
>>>     'title': {
>>>         'options': {
>>>             'pre_tags' : ["<em>"],
>>>             'post_tags' : ["</em>"]
>>>         },
>>>         'enabled': True,
>>>     },
>>> }
```

Parameters **view** (*rest_framework.viewsets.ReadOnlyModelViewSet*) –
Returns Highlight fields options.
Return type dict

12.18.1.2.5 django_elasticsearch_dsl_drf.filter_backends.mixins module

Mixins.

class django_elasticsearch_dsl_drf.filter_backends.mixins.**FilterBackendMixin**
Bases: object

Filter backend mixin.

classmethod apply_filter(*queryset*, *options=None*, *args=None*, *kwargs=None*)
Apply filter.
Parameters

- **queryset** –
- **options** –
- **args** –
- **kwargs** –

Returns

classmethod apply_query(*queryset*, *options=None*, *args=None*, *kwargs=None*)

Apply query.

Parameters

- **queryset** –
- **options** –
- **args** –
- **kwargs** –

Returns

classmethod split_lookup_complex_multiple_value(*value*, *maxsplit=-1*)

Split lookup complex multiple value.

Parameters

- **value** (*str*) – Value to split.
- **maxsplit** (*int*) – The *maxsplit* option of *string.split*.

Returns Lookup filter split into a list.

Return type list

classmethod split_lookup_complex_value(*value*, *maxsplit=-1*)

Split lookup complex value.

Parameters

- **value** (*str*) – Value to split.
- **maxsplit** (*int*) – The *maxsplit* option of *string.split*.

Returns Lookup filter split into a list.

Return type list

classmethod split_lookup_filter(*value*, *maxsplit=-1*)

Split lookup filter.

Parameters

- **value** (*str*) – Value to split.
- **maxsplit** (*int*) – The *maxsplit* option of *string.split*.

Returns Lookup filter split into a list.

Return type list

classmethod split_lookup_name(*value*, *maxsplit=-1*)

Split lookup value.

Parameters

- **value** (*str*) – Value to split.
- **maxsplit** (*int*) – The *maxsplit* option of *string.split*.

Returns Lookup value split into a list.

Return type list

12.18.1.2.6 Module contents

All filter backends.

12.18.1.3 django_elasticsearch_dsl_drf.tests package

12.18.1.3.1 Submodules

12.18.1.3.2 django_elasticsearch_dsl_drf.tests.base module

Base tests.

class `django_elasticsearch_dsl_drf.tests.base.`**`BaseRestFrameworkTestCase`**(*methodName='runTest'*)

Bases: `django.test.testcases.TransactionTestCase`

Base REST framework test case.

`authenticate`()

Helper for logging in Genre Coordinator user.

Returns

`pytestmark = [Mark(name='django_db', args=(), kwargs={}), Mark(name='django_db', args=`

`classmethod setUpClass`()

Set up class.

class `django_elasticsearch_dsl_drf.tests.base.`**`BaseTestCase`**(*methodName='runTest'*)

Bases: `django.test.testcases.TransactionTestCase`

Base test case.

`pytestmark = [Mark(name='django_db', args=(), kwargs={}), Mark(name='django_db', args=`

`classmethod setUpClass`()

Set up class.

12.18.1.3.3 django_elasticsearch_dsl_drf.tests.data_mixins module

Data mixins.

class `django_elasticsearch_dsl_drf.tests.data_mixins.`**`AddressesMixin`**

Bases: `object`

Addresses mixin.

`classmethod created_addresses`()

Create addresses.

Returns

class `django_elasticsearch_dsl_drf.tests.data_mixins.`**`BooksMixin`**

Bases: `object`

Books mixin.

`classmethod create_books`()

Create books.

Returns

12.18.1.3.4 django_elasticsearch_dsl_drf.tests.test_faceted_search module

Test faceted search backend.

class `django_elasticsearch_dsl_drf.tests.test_faceted_search.`**`TestFacetedSearch`**(*methodName='r*

Bases: *`django_elasticsearch_dsl_drf.tests.base.BaseRestFrameworkTestCase`*

Test faceted search.

`pytestmark = [Mark(name='django_db', args=(), kwargs={}), Mark(name='django_db', args=`

`classmethod setUpClass`()

Set up class.

`test_list_results_with_facets`()

Test list results with facets.

12.18.1.3.5 django_elasticsearch_dsl_drf.tests.test_filtering_common module

Test filtering backend.

class `django_elasticsearch_dsl_drf.tests.test_filtering_common.`**`TestFilteringCommon`**(*methodNa*

Bases: *`django_elasticsearch_dsl_drf.tests.base.BaseRestFrameworkTestCase`*, *`django_elasticsearch_dsl_drf.tests.data_mixins.AddressesMixin`*, *`django_elasticsearch_dsl_drf.tests.data_mixins.BooksMixin`*

Test filtering common.

`pytestmark = [Mark(name='django_db', args=(), kwargs={}), Mark(name='django_db', args=`

`classmethod setUpClass`()

Set up.

`test_default_filter_lookup`()

Test default filter lookup.

Example:

http://localhost:8000/search/books-default-filter-lookup/ ?authors=Robin&authors=Luc

`test_field_filter_contains`()

Test filter contains.

Example:

http://localhost:8000/api/articles/?state__contains=lishe

`test_field_filter_endswith`()

Test filter endswith.

Example:

http://localhost:8000/api/articles/?state__endswith=lished

`test_field_filter_exclude`()

Test filter exclude.

Example:

http://localhost:8000/api/articles/?tags__exclude=children

`test_field_filter_exists_false`()

Test filter exists.

Example:

http://localhost:8000/api/articles/?non_existent__exists=false

`test_field_filter_exists_true`()

Test filter exists true.

Example:

http://localhost:8000/api/articles/?tags__exists=true

test_field_filter_gt()

Field filter gt.

Example:

http://localhost:8000/api/users/?id__gt=10

Returns

test_field_filter_gt_with_boost()

Field filter gt with boost.

Example:

http://localhost:8000/api/users/?id__gt=10__2.0

Returns

test_field_filter_gte()

Field filter gte.

Example:

http://localhost:8000/api/users/?id__gte=10

Returns

test_field_filter_in()

Test filter in.

Example:

http://localhost:8000/api/articles/?id__in=1__2__3

test_field_filter_isnull_false()

Test filter isnull true.

Example:

http://localhost:8000/api/articles/?tags__isnull=false

test_field_filter_isnull_true()

Test filter isnull true.

Example:

http://localhost:8000/api/articles/?null_field__isnull=true

test_field_filter_lt()

Field filter lt.

Example:

http://localhost:8000/api/users/?id__lt=10

Returns

test_field_filter_lt_with_boost()

Field filter lt with boost.

Example:

http://localhost:8000/api/users/?id__lt=10__2.0

Returns

test_field_filter_lte()

Field filter lte.

Example:

http://localhost:8000/api/users/?id__lte=10

Returns

test_field_filter_prefix()

Test filter prefix.

Example:
http://localhost:8000/api/articles/?tags__prefix=bio

test_field_filter_range()

Field filter range.

Example:
http://localhost:8000/api/users/?age__range=16__67

test_field_filter_range_with_boost()

Field filter range.

Example:
http://localhost:8000/api/users/?age__range=16__67__2.0

test_field_filter_term()

Field filter term.

test_field_filter_term_explicit()

Field filter term.

test_field_filter_terms_list()

Test filter terms.

test_field_filter_terms_string()

Test filter terms.

Example:
http://localhost:8000/api/articles/?id__terms=1__2__3

test_field_filter_wildcard()

Test filter wildcard.

Example:
http://localhost:8000/api/articles/?title__wildcard=*elusional*

test_ids_empty_filter()

Test ids filter with empty value. This should not fail.

Example:
http://localhost:8000/api/articles/?ids=

test_ids_filter()

Test ids filter.

Example:
http://localhost:8000/api/articles/?ids=68__64__58 http://localhost:8000/api/articles/?ids=68&ids=64&ids=58

test_nested_field_filter_term()

Nested field filter term.

test_schema_field_not_required()

Test schema fields always not required

test_schema_fields_with_filter_fields_list()

Test schema field generator

test_various_complex_fields()
Test various complex fields.
Returns

12.18.1.3.6 django_elasticsearch_dsl_drf.tests.test_filtering_geo_spatial module

Test geo-spatial filtering backend.

class `django_elasticsearch_dsl_drf.tests.test_filtering_geo_spatial.`**TestFilteringGeoSpatial**
Bases: *`django_elasticsearch_dsl_drf.tests.base.BaseRestFrameworkTestCase`*

Test filtering geo-spatial.

pytestmark = [Mark(name='django_db', args=(), kwargs={}), Mark(name='django_db', args=

classmethod setUpClass()
Set up.

test_field_filter_geo_bounding_box()
Test field filter geo-bounding-box.
Returns

test_field_filter_geo_bounding_box_fail_test()
Test field filter geo-bounding-box (fail test).
Returns

test_field_filter_geo_distance()
Field filter geo-distance.

Example:
http://localhost:8000 /api/publisher/?location__geo_distance=1km__48.8549__2.3000

Returns

test_field_filter_geo_distance_distance_type_arc()
Field filter geo-distance.

Example:
http://localhost:8000 /api/publisher/?location__geo_distance=1km__48.8549__2.3000__arc

Returns

test_field_filter_geo_distance_not_enough_args_fail()
Field filter geo-distance. Fail test on not enough args.

Example:
http://localhost:8000 /api/publisher/?location__geo_distance=1km__48.8549

Returns

test_field_filter_geo_polygon()
Test field filter geo-polygon.
Returns

test_field_filter_geo_polygon_fail_test()
Test field filter geo-polygon (fail test).
Returns

test_field_filter_geo_polygon_string_options()
Test field filter geo-polygon.
Returns

test_field_filter_geo_polygon_string_options_fail_test()
Test field filter geo-polygon (fail test).
Returns

12.18.1.3.7 django_elasticsearch_dsl_drf.tests.test_filtering_global_aggregations module

Test filtering *post_filter* backend.

class django_elasticsearch_dsl_drf.tests.test_filtering_global_aggregations.**TestFilteringG**
Bases: *django_elasticsearch_dsl_drf.tests.base.BaseRestFrameworkTestCase*, *django_elasticsearch_dsl_drf.tests.data_mixins.AddressesMixin*, *django_elasticsearch_dsl_drf.tests.data_mixins.BooksMixin*

Test filtering with global aggregations.

pytestmark = [Mark(name='django_db', args=(), kwargs={}), Mark(name='django_db', args=

classmethod setUpClass()
Set up.

test_list_results_with_facets()
Test list results with facets.

12.18.1.3.8 django_elasticsearch_dsl_drf.tests.test_filtering_nested module

Test nested filtering backend.

class django_elasticsearch_dsl_drf.tests.test_filtering_nested.**TestFilteringNested**(*methodNa*
Bases: *django_elasticsearch_dsl_drf.tests.base.BaseRestFrameworkTestCase*, *django_elasticsearch_dsl_drf.tests.data_mixins.AddressesMixin*

Test filtering nested.

base_url

pytestmark = [Mark(name='django_db', args=(), kwargs={}), Mark(name='django_db', args=

classmethod setUpClass()
Set up.

test_field_filter_contains()
Test filter contains.

Example:
http://localhost:8000/api/articles/?state__contains=lishe

test_field_filter_endswith()
Test filter endswith.

Example:
http://localhost:8000/api/articles/?state__endswith=lished

test_field_filter_exclude()
Test filter exclude.

Example:
http://localhost:8000/api/articles/?tags__exclude=children

test_field_filter_exists_false()
Test filter exists.

Example:
http://localhost:8000/api/articles/?non_existent__exists=false

test_field_filter_exists_true()
Test filter exists true.

Example:
http://localhost:8000/api/articles/?tags__exists=true

test_field_filter_in()
Test filter in.

Example:
http://localhost:8000/api/articles/?id__in=1__2__3

test_field_filter_prefix()
Test filter prefix.

Example:
http://localhost:8000/api/articles/?tags__prefix=bio

test_field_filter_range()
Field filter range.

Example:
http://localhost:8000/api/users/?age__range=16__67

test_field_filter_range_with_boost()
Field filter range.

Example:
http://localhost:8000/api/users/?age__range=16__67__2.0

test_field_filter_term()
Field filter term.

test_field_filter_term_explicit()
Field filter term.

test_field_filter_terms_list()
Test filter terms.

test_field_filter_terms_string()
Test filter terms.

Example:
http://localhost:8000/api/articles/?id__terms=1__2__3

test_field_filter_wildcard()
Test filter wildcard.

Example:
http://localhost:8000/api/articles/?title__wildcard=*elusional*

test_schema_field_not_required()
Test schema fields always not required

test_schema_fields_with_filter_fields_list()
Test schema field generator

12.18.1.3.9 django_elasticsearch_dsl_drf.tests.test_filtering_post_filter module

Test filtering *post_filter* backend.

class `django_elasticsearch_dsl_drf.tests.test_filtering_post_filter.`**TestFilteringPostFilte**

Bases: *`django_elasticsearch_dsl_drf.tests.base.BaseRestFrameworkTestCase`*, *`django_elasticsearch_dsl_drf.tests.data_mixins.AddressesMixin`*, *`django_elasticsearch_dsl_drf.tests.data_mixins.BooksMixin`*

Test filtering *post_filter*.

pytestmark = [Mark(name='django_db', args=(), kwargs={}), Mark(name='django_db', args=

classmethod setUpClass()

Set up.

test_field_filter_contains()

Test filter contains.

Example:

http://localhost:8000/api/articles/?state__contains=lishe

test_field_filter_endswith()

Test filter endswith.

Example:

http://localhost:8000/api/articles/?state__endswith=lished

test_field_filter_exclude()

Test filter exclude.

Example:

http://localhost:8000/api/articles/?tags__exclude=children

test_field_filter_exists_false()

Test filter exists.

Example:

http://localhost:8000/api/articles/?non_existent__exists=false

test_field_filter_exists_true()

Test filter exists true.

Example:

http://localhost:8000/api/articles/?tags__exists=true

test_field_filter_gt()

Field filter gt.

Example:

http://localhost:8000/api/users/?id__gt=10

Returns

test_field_filter_gt_with_boost()

Field filter gt with boost.

Example:

http://localhost:8000/api/users/?id__gt=10;2.0

Returns

test_field_filter_gte()

Field filter gte.

Example:
http://localhost:8000/api/users/?id__gte=10

Returns

test_field_filter_in()
Test filter in.

Example:
http://localhost:8000/api/articles/?id__in=1;2;3

test_field_filter_isnull_false()
Test filter isnull true.

Example:
http://localhost:8000/api/articles/?tags__isnull=false

test_field_filter_isnull_true()
Test filter isnull true.

Example:
http://localhost:8000/api/articles/?null_field__isnull=true

test_field_filter_lt()
Field filter lt.

Example:
http://localhost:8000/api/users/?id__lt=10

Returns

test_field_filter_lt_with_boost()
Field filter lt with boost.

Example:
http://localhost:8000/api/users/?id__lt=10;2.0

Returns

test_field_filter_lte()
Field filter lte.

Example:
http://localhost:8000/api/users/?id__lte=10

Returns

test_field_filter_prefix()
Test filter prefix.

Example:
http://localhost:8000/api/articles/?tags__prefix=bio

test_field_filter_range()
Field filter range.

Example:
http://localhost:8000/api/users/?age__range=16;67

test_field_filter_range_with_boost()
Field filter range.

Example:
http://localhost:8000/api/users/?age__range=16;67;2.0

test_field_filter_term()
Field filter term.

test_field_filter_term_explicit()
Field filter term.

test_field_filter_terms_list()
Test filter terms.

test_field_filter_terms_string()
Test filter terms.

Example:
http://localhost:8000/api/articles/?id__terms=1;2;3

test_field_filter_wildcard()
Test filter wildcard.

Example:
http://localhost:8000/api/articles/?title__wildcard=*elusional*

test_ids_filter()
Test ids filter.

Example:
http://localhost:8000/api/articles/?ids=68;64;58 http://localhost:8000/api/articles/?ids=68&ids=64&ids=58

test_list_results_with_facets()
Test list results with facets.

test_schema_field_not_required()
Test schema fields always not required

test_schema_fields_with_filter_fields_list()
Test schema field generator

test_various_complex_fields()
Test various complex fields.
Returns

12.18.1.3.10 django_elasticsearch_dsl_drf.tests.test_functional_suggesters module

Test functional suggestions backend.

class `django_elasticsearch_dsl_drf.tests.test_functional_suggesters.`**TestFunctionalSuggester**
Bases: *`django_elasticsearch_dsl_drf.tests.base.BaseRestFrameworkTestCase`*, *`django_elasticsearch_dsl_drf.tests.data_mixins.AddressesMixin`*

Test functional suggesters.

pytestmark = [Mark(name='django_db', args=(), kwargs={}), Mark(name='django_db', args=

classmethod setUpClass()
Set up class.

test_suggesters_completion()
Test suggesters completion.

test_suggesters_completion_no_args_provided()
Test suggesters completion with no args provided.

12.18.1.3.11 django_elasticsearch_dsl_drf.tests.test_helpers module

Test helpers.

class `django_elasticsearch_dsl_drf.tests.test_helpers.`**`TestHelpers`**(*methodName='runTest'*)

Bases: *`django_elasticsearch_dsl_drf.tests.base.BaseTestCase`*

Test helpers.

`pytestmark = [Mark(name='django_db', args=(), kwargs={}), Mark(name='django_db', args=`

`classmethod setUpClass`()

Set up class.

`test_filter_by_field`()

Filter by field.

12.18.1.3.12 django_elasticsearch_dsl_drf.tests.test_highlight module

Test highlight backend.

class `django_elasticsearch_dsl_drf.tests.test_highlight.`**`TestHighlight`**(*methodName='runTest'*)

Bases: *`django_elasticsearch_dsl_drf.tests.base.BaseRestFrameworkTestCase`*

Test highlight.

`pytestmark = [Mark(name='django_db', args=(), kwargs={}), Mark(name='django_db', args=`

`classmethod setUpClass`()

Set up class.

`test_list_results_with_highlights`()

Test list results with facets.

12.18.1.3.13 django_elasticsearch_dsl_drf.tests.test_more_like_this module

Test more-like-this functionality.

class `django_elasticsearch_dsl_drf.tests.test_more_like_this.`**`TestMoreLikeThis`**(*methodName='run*

Bases: *`django_elasticsearch_dsl_drf.tests.base.BaseRestFrameworkTestCase`*

Test suggesters.

`pytestmark = [Mark(name='django_db', args=(), kwargs={}), Mark(name='django_db', args=`

`classmethod setUpClass`()

Set up class.

`test_more_like_this`()

Test more-like-this.

12.18.1.3.14 django_elasticsearch_dsl_drf.tests.test_ordering_common module

Test ordering backend.

class `django_elasticsearch_dsl_drf.tests.test_ordering_common.`**`TestOrdering`**(*methodName='runTest*

Bases: *`django_elasticsearch_dsl_drf.tests.base.BaseRestFrameworkTestCase`*

Test ordering.

static deep_get(*dic*, *keys*, *default=None*)

Returns value at period separated keys in dictionary or default

From https://stackoverflow.com/a/46890853

Parameters

- **dic** (*dict*) – Dictionary to retrieve value from.
- **keys** (*str*) – Period separated path of keys
- **default** (*str*) – Default value to return if keys not found

Returns Value at keys or default

pytestmark = [Mark(name='django_db', args=(), kwargs={}), Mark(name='django_db', args=

classmethod setUpClass()

Set up class.

test_address_default_nested_order_by()

test_address_default_order_by()

Test if default ordering on addresses is correct (asc).

test_address_order_by_nested_field_continent_ascending()

Order by field *continent.country.name.raw* ascending.

test_address_order_by_nested_field_continent_descending()

Order by field *continent.country.name.raw* descending.

test_address_order_by_nested_field_country_ascending()

Order by field *continent.country.name.raw* ascending.

test_address_order_by_nested_field_country_descending()

Order by field *continent.country.name.raw* descending.

test_author_default_order_by()

Author order by default.

test_author_order_by_field_id_ascending()

Order by field *name* ascending.

test_author_order_by_field_id_descending()

Order by field *id* descending.

test_author_order_by_field_name_ascending()

Order by field *name* ascending.

test_author_order_by_field_name_descending()

Order by field *name* descending.

test_book_default_order_by()

Book order by default.

test_book_order_by_field_id_ascending()

Order by field *id* ascending.

test_book_order_by_field_id_descending()

Order by field *id* descending.

test_book_order_by_field_title_ascending()

Order by field *title* ascending.

test_book_order_by_field_title_descending()

Order by field *title* descending.

test_book_order_by_non_existent_field()
Order by non-existent field.

test_schema_field_not_required()
Test schema fields always not required

test_schema_fields_with_filter_fields_list()
Test schema field generator

12.18.1.3.15 django_elasticsearch_dsl_drf.tests.test_ordering_geo_spatial module

Test geo-spatial ordering filter backend.

class `django_elasticsearch_dsl_drf.tests.test_ordering_geo_spatial.`**TestOrderingGeoSpatial**(
Bases: *`django_elasticsearch_dsl_drf.tests.base.BaseRestFrameworkTestCase`*

Test ordering geo-spatial.

pytestmark = [Mark(name='django_db', args=(), kwargs={}), Mark(name='django_db', args=

classmethod setUpClass()
Set up.

test_field_filter_geo_distance()
Field filter geo_distance.

Example:
http://localhost:8000 /api/publisher/?ordering=location;48.85;2.30;km;plane

12.18.1.3.16 django_elasticsearch_dsl_drf.tests.test_pagination module

Test pagination.

class `django_elasticsearch_dsl_drf.tests.test_pagination.`**TestPagination**(*methodName='runTest'*)
Bases: *`django_elasticsearch_dsl_drf.tests.base.BaseRestFrameworkTestCase`*

Test pagination.

pytestmark = [Mark(name='django_db', args=(), kwargs={}), Mark(name='django_db', args=

classmethod setUpClass()
Set up class.

test_pagination()
Test pagination.

12.18.1.3.17 django_elasticsearch_dsl_drf.tests.test_pip_helpers module

Test pip_helpers.

class `django_elasticsearch_dsl_drf.tests.test_pip_helpers.`**TestPipHelpers**(*methodName='runTest'*)
Bases: `unittest.case.TestCase`

Test pip_helpers.

pytestmark = [Mark(name='django_db', args=(), kwargs={})]

classmethod setUpClass()
Hook method for setting up class fixture before running tests in the class.

test_check_if_installed()
Test *check_if_installed*.
Returns

test_get_installed_packages()
Test *get_installed_packages*.
Returns

test_get_installed_packages_with_versions()
Test *get_installed_packages*.
Returns

12.18.1.3.18 django_elasticsearch_dsl_drf.tests.test_search module

Test search backend.

class django_elasticsearch_dsl_drf.tests.test_search.**TestSearch**(*methodName='runTest'*)
Bases: *django_elasticsearch_dsl_drf.tests.base.BaseRestFrameworkTestCase*

Test search.

pytestmark = [Mark(name='django_db', args=(), kwargs={}), Mark(name='django_db', args=

classmethod setUpClass()
Set up class.

test_compound_search_boost_by_field()

test_compound_search_by_field()

test_compound_search_by_field_multi_terms()

test_compound_search_by_nested_field()

test_schema_field_not_required()
Test schema fields always not required

test_schema_fields_with_filter_fields_list()
Test schema field generator

test_search_boost(*url=None*, *search_field='search'*)
Search boost.
Returns

test_search_boost_compound(*search_field='search'*)

test_search_by_field(*url=None*, *search_field='search'*)
Search by field.

test_search_by_field_multi_terms(*url=None*, *search_field='search'*)
Search by field, multiple terms.

test_search_by_nested_field(*url=None*)
Search by field.

class django_elasticsearch_dsl_drf.tests.test_search.**TestSearchCustomCases**(*methodName='runTest*
Bases: *django_elasticsearch_dsl_drf.tests.base.BaseRestFrameworkTestCase*

Test search.

pytestmark = [Mark(name='django_db', args=(), kwargs={}), Mark(name='django_db', args=

test_search_any_word_in_indexed_fields()
Test search any word in indexed fields.
Returns

12.18.1.3.19 django_elasticsearch_dsl_drf.tests.test_search_multi_match module

Test multi match search filter backend.

class `django_elasticsearch_dsl_drf.tests.test_search_multi_match.`**TestMultiMatchSearch**(*metho*
Bases: *`django_elasticsearch_dsl_drf.tests.base.BaseRestFrameworkTestCase`*

Test multi match search.

pytestmark = [Mark(name='django_db', args=(), kwargs={}), Mark(name='django_db', args=

classmethod setUpClass()
Set up class.

test_schema_field_not_required()
Test schema fields always not required

test_schema_fields_with_filter_fields_list()
Test schema field generator

test_search(*url=None*)
Search.

test_search_boost(*url=None*)
Search boost.
Returns

test_search_boost_selected_fields(*url=None*)
Search boost.
Returns

test_search_selected_fields(*url=None*)
Search boost.
Returns

12.18.1.3.20 django_elasticsearch_dsl_drf.tests.test_search_simple_query_string module

Test multi match search filter backend.

class `django_elasticsearch_dsl_drf.tests.test_search_simple_query_string.`**TestSimpleQueryStr**
Bases: *`django_elasticsearch_dsl_drf.tests.base.BaseRestFrameworkTestCase`*

Test simple query string search.

pytestmark = [Mark(name='django_db', args=(), kwargs={}), Mark(name='django_db', args=

classmethod setUpClass()
Set up class.

test_schema_field_not_required()
Test schema fields always not required

test_schema_fields_with_filter_fields_list()
Test schema field generator

test_search_boost_selected_fields(*url=None*)
Search boost.
Returns

test_search_selected_fields(*url=None*)
Search boost.
Returns

test_search_with_quotes(*url=None*)
Search with quotes.

test_search_with_quotes_alternative()
Test search by field.
Parameters **url** –
Returns

test_search_with_quotes_boost(*url=None*)
Search boost.
Returns

test_search_with_quotes_boost_alternative()
Search boost.
Returns

test_search_without_quotes(*url=None*)
Test search without quotes. This does not work on Elasticsearch 6.x.
Parameters **url** –
Returns

test_search_without_quotes_boost(*url=None*)
Search boost without quotes. Does not work on Elasticsearch 6.x.
Returns

12.18.1.3.21 django_elasticsearch_dsl_drf.tests.test_serializers module

Test serializers.

class `django_elasticsearch_dsl_drf.tests.test_serializers.`**TestSerializers**(*methodName='runTest'*)
Bases: *`django_elasticsearch_dsl_drf.tests.base.BaseRestFrameworkTestCase`*

Test serializers.

pytestmark = [Mark(name='django_db', args=(), kwargs={}), Mark(name='django_db', args=

test_serializer_document_equals_to_none()
Test serializer no document specified.

test_serializer_fields_and_exclude()
Test serializer fields and exclude.

test_serializer_meta_del_attr()
Test serializer set attr.

test_serializer_meta_set_attr()
Test serializer set attr.

test_serializer_no_document_specified()
Test serializer no document specified.

12.18.1.3.22 django_elasticsearch_dsl_drf.tests.test_suggesters module

Test suggestions backend.

class `django_elasticsearch_dsl_drf.tests.test_suggesters.`**TestContextSuggesters**(*methodName='ru*

Bases: *django_elasticsearch_dsl_drf.tests.base.BaseRestFrameworkTestCase*, *django_elasticsearch_dsl_drf.tests.data_mixins.AddressesMixin*

Test context suggesters.

pytestmark = [Mark(name='django_db', args=(), kwargs={}), Mark(name='django_db', args=

classmethod setUpClass()

Set up class.

test_suggesters_completion_context()

Test suggesters completion context.

class `django_elasticsearch_dsl_drf.tests.test_suggesters.`**TestSuggesters**(*methodName='runTest'*)

Bases: *django_elasticsearch_dsl_drf.tests.base.BaseRestFrameworkTestCase*, *django_elasticsearch_dsl_drf.tests.data_mixins.AddressesMixin*

Test suggesters.

pytestmark = [Mark(name='django_db', args=(), kwargs={}), Mark(name='django_db', args=

classmethod setUpClass()

Set up class.

test_nested_fields_suggesters_completion()

Test suggesters completion for nested fields.

test_suggesters_completion()

Test suggesters completion.

test_suggesters_completion_no_args_provided()

Test suggesters completion with no args provided.

test_suggesters_phrase()

Test suggesters phrase.

test_suggesters_term()

Test suggesters term.

class `django_elasticsearch_dsl_drf.tests.test_suggesters.`**TestSuggestersEmptyIndex**(*methodNam*

Bases: *django_elasticsearch_dsl_drf.tests.base.BaseRestFrameworkTestCase*, *django_elasticsearch_dsl_drf.tests.data_mixins.AddressesMixin*

Test suggesters on empty index.

pytestmark = [Mark(name='django_db', args=(), kwargs={}), Mark(name='django_db', args=

classmethod setUpClass()

Set up class.

test_suggesters_on_empty_index()

Test suggesters phrase.

12.18.1.3.23 django_elasticsearch_dsl_drf.tests.test_views module

Test views.

class `django_elasticsearch_dsl_drf.tests.test_views.`**TestViews**(*methodName='runTest'*)

Bases: *`django_elasticsearch_dsl_drf.tests.base.BaseRestFrameworkTestCase`*

Test views.

pytestmark = [Mark(name='django_db', args=(), kwargs={}), Mark(name='django_db', args=

classmethod setUpClass()

Set up class.

test_detail_view()

Test detail view.

test_detail_view_with_custom_lookup()

Test detail view with a custom lookup field.

test_listing_view()

Test listing view.

12.18.1.3.24 django_elasticsearch_dsl_drf.tests.test_wrappers module

Test wrappers.

class `django_elasticsearch_dsl_drf.tests.test_wrappers.`**TestWrappers**(*methodName='runTest'*)

Bases: `unittest.case.TestCase`

Test wrappers.

pytestmark = [Mark(name='django_db', args=(), kwargs={})]

classmethod setUpClass()

Hook method for setting up class fixture before running tests in the class.

test_dict_to_obj()

Test *dict_to_obj*.

Returns

test_obj_to_dict()

Test *obj_to_dict*.

Returns

test_wrapper_as_json()

Test **:Wrapper:'as_json'** property.

12.18.1.3.25 Module contents

Tests.

class `django_elasticsearch_dsl_drf.tests.`**TestFacetedSearch**(*methodName='runTest'*)

Bases: *`django_elasticsearch_dsl_drf.tests.base.BaseRestFrameworkTestCase`*

Test faceted search.

pytestmark = [Mark(name='django_db', args=(), kwargs={}), Mark(name='django_db', args=

classmethod setUpClass()

Set up class.

test_list_results_with_facets()

Test list results with facets.

class `django_elasticsearch_dsl_drf.tests.`**`TestFilteringCommon`**(*methodName='runTest'*)

Bases: *`django_elasticsearch_dsl_drf.tests.base.BaseRestFrameworkTestCase`*, *`django_elasticsearch_dsl_drf.tests.data_mixins.AddressesMixin`*, *`django_elasticsearch_dsl_drf.tests.data_mixins.BooksMixin`*

Test filtering common.

`pytestmark = [Mark(name='django_db', args=(), kwargs={}), Mark(name='django_db', args=`

classmethod `setUpClass`()

Set up.

`test_default_filter_lookup`()

Test default filter lookup.

Example:

http://localhost:8000/search/books-default-filter-lookup/ ?authors=Robin&authors=Luc

`test_field_filter_contains`()

Test filter contains.

Example:

http://localhost:8000/api/articles/?state__contains=lishe

`test_field_filter_endswith`()

Test filter endswith.

Example:

http://localhost:8000/api/articles/?state__endswith=lished

`test_field_filter_exclude`()

Test filter exclude.

Example:

http://localhost:8000/api/articles/?tags__exclude=children

`test_field_filter_exists_false`()

Test filter exists.

Example:

http://localhost:8000/api/articles/?non_existent__exists=false

`test_field_filter_exists_true`()

Test filter exists true.

Example:

http://localhost:8000/api/articles/?tags__exists=true

`test_field_filter_gt`()

Field filter gt.

Example:

http://localhost:8000/api/users/?id__gt=10

Returns

`test_field_filter_gt_with_boost`()

Field filter gt with boost.

Example:

http://localhost:8000/api/users/?id__gt=10__2.0

Returns

test_field_filter_gte()

Field filter gte.

Example:

http://localhost:8000/api/users/?id__gte=10

Returns

test_field_filter_in()

Test filter in.

Example:

http://localhost:8000/api/articles/?id__in=1__2__3

test_field_filter_isnull_false()

Test filter isnull true.

Example:

http://localhost:8000/api/articles/?tags__isnull=false

test_field_filter_isnull_true()

Test filter isnull true.

Example:

http://localhost:8000/api/articles/?null_field__isnull=true

test_field_filter_lt()

Field filter lt.

Example:

http://localhost:8000/api/users/?id__lt=10

Returns

test_field_filter_lt_with_boost()

Field filter lt with boost.

Example:

http://localhost:8000/api/users/?id__lt=10__2.0

Returns

test_field_filter_lte()

Field filter lte.

Example:

http://localhost:8000/api/users/?id__lte=10

Returns

test_field_filter_prefix()

Test filter prefix.

Example:

http://localhost:8000/api/articles/?tags__prefix=bio

test_field_filter_range()

Field filter range.

Example:

http://localhost:8000/api/users/?age__range=16__67

test_field_filter_range_with_boost()

Field filter range.

Example:
http://localhost:8000/api/users/?age__range=16__67__2.0

test_field_filter_term()
Field filter term.

test_field_filter_term_explicit()
Field filter term.

test_field_filter_terms_list()
Test filter terms.

test_field_filter_terms_string()
Test filter terms.

Example:
http://localhost:8000/api/articles/?id__terms=1__2__3

test_field_filter_wildcard()
Test filter wildcard.

Example:
http://localhost:8000/api/articles/?title__wildcard=*elusional*

test_ids_empty_filter()
Test ids filter with empty value. This should not fail.

Example:
http://localhost:8000/api/articles/?ids=

test_ids_filter()
Test ids filter.

Example:
http://localhost:8000/api/articles/?ids=68__64__58 http://localhost:8000/api/articles/?ids=68&ids=64&ids=58

test_nested_field_filter_term()
Nested field filter term.

test_schema_field_not_required()
Test schema fields always not required

test_schema_fields_with_filter_fields_list()
Test schema field generator

test_various_complex_fields()
Test various complex fields.

Returns

class `django_elasticsearch_dsl_drf.tests.`**TestFilteringGeoSpatial**(*methodName='runTest'*)
Bases: *`django_elasticsearch_dsl_drf.tests.base.BaseRestFrameworkTestCase`*

Test filtering geo-spatial.

pytestmark = [Mark(name='django_db', args=(), kwargs={}), Mark(name='django_db', args=

classmethod setUpClass()
Set up.

test_field_filter_geo_bounding_box()
Test field filter geo-bounding-box.

Returns

test_field_filter_geo_bounding_box_fail_test()
Test field filter geo-bounding-box (fail test).
Returns

test_field_filter_geo_distance()
Field filter geo-distance.

Example:
http://localhost:8000 /api/publisher/?location__geo_distance=1km__48.8549__2.3000

Returns

test_field_filter_geo_distance_distance_type_arc()
Field filter geo-distance.

Example:
http://localhost:8000 /api/publisher/?location__geo_distance=1km__48.8549__2.3000__arc

Returns

test_field_filter_geo_distance_not_enough_args_fail()
Field filter geo-distance. Fail test on not enough args.

Example:
http://localhost:8000 /api/publisher/?location__geo_distance=1km__48.8549

Returns

test_field_filter_geo_polygon()
Test field filter geo-polygon.
Returns

test_field_filter_geo_polygon_fail_test()
Test field filter geo-polygon (fail test).
Returns

test_field_filter_geo_polygon_string_options()
Test field filter geo-polygon.
Returns

test_field_filter_geo_polygon_string_options_fail_test()
Test field filter geo-polygon (fail test).
Returns

class django_elasticsearch_dsl_drf.tests.**TestFilteringGlobalAggregations**(*methodName='runTest'*)
Bases: *django_elasticsearch_dsl_drf.tests.base.BaseRestFrameworkTestCase*, *django_elasticsearch_dsl_drf.tests.data_mixins.AddressesMixin*, *django_elasticsearch_dsl_drf.tests.data_mixins.BooksMixin*

Test filtering with global aggregations.

pytestmark = [Mark(name='django_db', args=(), kwargs={}), Mark(name='django_db', args=

classmethod setUpClass()
Set up.

test_list_results_with_facets()
Test list results with facets.

class django_elasticsearch_dsl_drf.tests.**TestFilteringNested**(*methodName='runTest'*)
Bases: *django_elasticsearch_dsl_drf.tests.base.BaseRestFrameworkTestCase*, *django_elasticsearch_dsl_drf.tests.data_mixins.AddressesMixin*

Test filtering nested.

base_url

pytestmark = [Mark(name='django_db', args=(), kwargs={}), Mark(name='django_db', args=

classmethod setUpClass()

Set up.

test_field_filter_contains()

Test filter contains.

Example:

http://localhost:8000/api/articles/?state__contains=lishe

test_field_filter_endswith()

Test filter endswith.

Example:

http://localhost:8000/api/articles/?state__endswith=lished

test_field_filter_exclude()

Test filter exclude.

Example:

http://localhost:8000/api/articles/?tags__exclude=children

test_field_filter_exists_false()

Test filter exists.

Example:

http://localhost:8000/api/articles/?non_existent__exists=false

test_field_filter_exists_true()

Test filter exists true.

Example:

http://localhost:8000/api/articles/?tags__exists=true

test_field_filter_in()

Test filter in.

Example:

http://localhost:8000/api/articles/?id__in=1__2__3

test_field_filter_prefix()

Test filter prefix.

Example:

http://localhost:8000/api/articles/?tags__prefix=bio

test_field_filter_range()

Field filter range.

Example:

http://localhost:8000/api/users/?age__range=16__67

test_field_filter_range_with_boost()

Field filter range.

Example:

http://localhost:8000/api/users/?age__range=16__67__2.0

test_field_filter_term()

Field filter term.

test_field_filter_term_explicit()
Field filter term.

test_field_filter_terms_list()
Test filter terms.

test_field_filter_terms_string()
Test filter terms.

Example:
http://localhost:8000/api/articles/?id__terms=1__2__3

test_field_filter_wildcard()
Test filter wildcard.

Example:
http://localhost:8000/api/articles/?title__wildcard=*elusional*

test_schema_field_not_required()
Test schema fields always not required

test_schema_fields_with_filter_fields_list()
Test schema field generator

class django_elasticsearch_dsl_drf.tests.**TestFilteringPostFilter**(*methodName='runTest'*)
Bases: *django_elasticsearch_dsl_drf.tests.base.BaseRestFrameworkTestCase*, *django_elasticsearch_dsl_drf.tests.data_mixins.AddressesMixin*, *django_elasticsearch_dsl_drf.tests.data_mixins.BooksMixin*

Test filtering *post_filter*.

pytestmark = [Mark(name='django_db', args=(), kwargs={}), Mark(name='django_db', args=

classmethod setUpClass()
Set up.

test_field_filter_contains()
Test filter contains.

Example:
http://localhost:8000/api/articles/?state__contains=lishe

test_field_filter_endswith()
Test filter endswith.

Example:
http://localhost:8000/api/articles/?state__endswith=lished

test_field_filter_exclude()
Test filter exclude.

Example:
http://localhost:8000/api/articles/?tags__exclude=children

test_field_filter_exists_false()
Test filter exists.

Example:
http://localhost:8000/api/articles/?non_existent__exists=false

test_field_filter_exists_true()
Test filter exists true.

Example:

http://localhost:8000/api/articles/?tags__exists=true

test_field_filter_gt()

Field filter gt.

Example:

http://localhost:8000/api/users/?id__gt=10

Returns

test_field_filter_gt_with_boost()

Field filter gt with boost.

Example:

http://localhost:8000/api/users/?id__gt=10;2.0

Returns

test_field_filter_gte()

Field filter gte.

Example:

http://localhost:8000/api/users/?id__gte=10

Returns

test_field_filter_in()

Test filter in.

Example:

http://localhost:8000/api/articles/?id__in=1;2;3

test_field_filter_isnull_false()

Test filter isnull true.

Example:

http://localhost:8000/api/articles/?tags__isnull=false

test_field_filter_isnull_true()

Test filter isnull true.

Example:

http://localhost:8000/api/articles/?null_field__isnull=true

test_field_filter_lt()

Field filter lt.

Example:

http://localhost:8000/api/users/?id__lt=10

Returns

test_field_filter_lt_with_boost()

Field filter lt with boost.

Example:

http://localhost:8000/api/users/?id__lt=10;2.0

Returns

test_field_filter_lte()

Field filter lte.

Example:

http://localhost:8000/api/users/?id__lte=10

Returns

test_field_filter_prefix()
Test filter prefix.

Example:
http://localhost:8000/api/articles/?tags__prefix=bio

test_field_filter_range()
Field filter range.

Example:
http://localhost:8000/api/users/?age__range=16;67

test_field_filter_range_with_boost()
Field filter range.

Example:
http://localhost:8000/api/users/?age__range=16;67;2.0

test_field_filter_term()
Field filter term.

test_field_filter_term_explicit()
Field filter term.

test_field_filter_terms_list()
Test filter terms.

test_field_filter_terms_string()
Test filter terms.

Example:
http://localhost:8000/api/articles/?id__terms=1;2;3

test_field_filter_wildcard()
Test filter wildcard.

Example:
http://localhost:8000/api/articles/?title__wildcard=*elusional*

test_ids_filter()
Test ids filter.

Example:
http://localhost:8000/api/articles/?ids=68;64;58 http://localhost:8000/api/articles/?ids=68&ids=64&ids=58

test_list_results_with_facets()
Test list results with facets.

test_schema_field_not_required()
Test schema fields always not required

test_schema_fields_with_filter_fields_list()
Test schema field generator

test_various_complex_fields()
Test various complex fields.

Returns

class django_elasticsearch_dsl_drf.tests.**TestFunctionalSuggesters**(*methodName='runTest'*)
Bases: *django_elasticsearch_dsl_drf.tests.base.BaseRestFrameworkTestCase*, *django_elasticsearch_dsl_drf.tests.data_mixins.AddressesMixin*

Test functional suggesters.

pytestmark = [Mark(name='django_db', args=(), kwargs={}), Mark(name='django_db', args=

classmethod setUpClass()
Set up class.

test_suggesters_completion()
Test suggesters completion.

test_suggesters_completion_no_args_provided()
Test suggesters completion with no args provided.

class `django_elasticsearch_dsl_drf.tests.`**TestHelpers**(*methodName='runTest'*)
Bases: *`django_elasticsearch_dsl_drf.tests.base.BaseTestCase`*

Test helpers.

pytestmark = [Mark(name='django_db', args=(), kwargs={}), Mark(name='django_db', args=

classmethod setUpClass()
Set up class.

test_filter_by_field()
Filter by field.

class `django_elasticsearch_dsl_drf.tests.`**TestHighlight**(*methodName='runTest'*)
Bases: *`django_elasticsearch_dsl_drf.tests.base.BaseRestFrameworkTestCase`*

Test highlight.

pytestmark = [Mark(name='django_db', args=(), kwargs={}), Mark(name='django_db', args=

classmethod setUpClass()
Set up class.

test_list_results_with_highlights()
Test list results with facets.

class `django_elasticsearch_dsl_drf.tests.`**TestMultiMatchSearch**(*methodName='runTest'*)
Bases: *`django_elasticsearch_dsl_drf.tests.base.BaseRestFrameworkTestCase`*

Test multi match search.

pytestmark = [Mark(name='django_db', args=(), kwargs={}), Mark(name='django_db', args=

classmethod setUpClass()
Set up class.

test_schema_field_not_required()
Test schema fields always not required

test_schema_fields_with_filter_fields_list()
Test schema field generator

test_search(*url=None*)
Search.

test_search_boost(*url=None*)
Search boost.
Returns

test_search_boost_selected_fields(*url=None*)
Search boost.
Returns

test_search_selected_fields(*url=None*)
Search boost.
Returns

class django_elasticsearch_dsl_drf.tests.**TestSimpleQueryStringSearch**(*methodName='runTest'*)
Bases: *django_elasticsearch_dsl_drf.tests.base.BaseRestFrameworkTestCase*

Test simple query string search.

pytestmark = [Mark(name='django_db', args=(), kwargs={}), Mark(name='django_db', args=

classmethod setUpClass()
Set up class.

test_schema_field_not_required()
Test schema fields always not required

test_schema_fields_with_filter_fields_list()
Test schema field generator

test_search_boost_selected_fields(*url=None*)
Search boost.
Returns

test_search_selected_fields(*url=None*)
Search boost.
Returns

test_search_with_quotes(*url=None*)
Search with quotes.

test_search_with_quotes_alternative()
Test search by field.
Parameters **url** –
Returns

test_search_with_quotes_boost(*url=None*)
Search boost.
Returns

test_search_with_quotes_boost_alternative()
Search boost.
Returns

test_search_without_quotes(*url=None*)
Test search without quotes. This does not work on Elasticsearch 6.x.
Parameters **url** –
Returns

test_search_without_quotes_boost(*url=None*)
Search boost without quotes. Does not work on Elasticsearch 6.x.
Returns

class django_elasticsearch_dsl_drf.tests.**TestOrdering**(*methodName='runTest'*)
Bases: *django_elasticsearch_dsl_drf.tests.base.BaseRestFrameworkTestCase*

Test ordering.

static deep_get(*dic*, *keys*, *default=None*)
Returns value at period separated keys in dictionary or default

From https://stackoverflow.com/a/46890853
Parameters

- **dic** (*dict*) – Dictionary to retrieve value from.
- **keys** (*str*) – Period separated path of keys
- **default** (*str*) – Default value to return if keys not found

Returns Value at keys or default

pytestmark = [Mark(name='django_db', args=(), kwargs={}), Mark(name='django_db', args=

classmethod setUpClass()
Set up class.

test_address_default_nested_order_by()

test_address_default_order_by()
Test if default ordering on addresses is correct (asc).

test_address_order_by_nested_field_continent_ascending()
Order by field *continent.country.name.raw* ascending.

test_address_order_by_nested_field_continent_descending()
Order by field *continent.country.name.raw* descending.

test_address_order_by_nested_field_country_ascending()
Order by field *continent.country.name.raw* ascending.

test_address_order_by_nested_field_country_descending()
Order by field *continent.country.name.raw* descending.

test_author_default_order_by()
Author order by default.

test_author_order_by_field_id_ascending()
Order by field *name* ascending.

test_author_order_by_field_id_descending()
Order by field *id* descending.

test_author_order_by_field_name_ascending()
Order by field *name* ascending.

test_author_order_by_field_name_descending()
Order by field *name* descending.

test_book_default_order_by()
Book order by default.

test_book_order_by_field_id_ascending()
Order by field *id* ascending.

test_book_order_by_field_id_descending()
Order by field *id* descending.

test_book_order_by_field_title_ascending()
Order by field *title* ascending.

test_book_order_by_field_title_descending()
Order by field *title* descending.

test_book_order_by_non_existent_field()
Order by non-existent field.

test_schema_field_not_required()
Test schema fields always not required

test_schema_fields_with_filter_fields_list()
Test schema field generator

class django_elasticsearch_dsl_drf.tests.**TestOrderingGeoSpatial**(*methodName='runTest'*)
Bases: *django_elasticsearch_dsl_drf.tests.base.BaseRestFrameworkTestCase*

Test ordering geo-spatial.

pytestmark = [Mark(name='django_db', args=(), kwargs={}), Mark(name='django_db', args=

classmethod setUpClass()
Set up.

test_field_filter_geo_distance()
Field filter geo_distance.

Example:
http://localhost:8000 /api/publisher/?ordering=location;48.85;2.30;km;plane

class django_elasticsearch_dsl_drf.tests.**TestPagination**(*methodName='runTest'*)
Bases: *django_elasticsearch_dsl_drf.tests.base.BaseRestFrameworkTestCase*

Test pagination.

pytestmark = [Mark(name='django_db', args=(), kwargs={}), Mark(name='django_db', args=

classmethod setUpClass()
Set up class.

test_pagination()
Test pagination.

class django_elasticsearch_dsl_drf.tests.**TestPipHelpers**(*methodName='runTest'*)
Bases: unittest.case.TestCase

Test pip_helpers.

pytestmark = [Mark(name='django_db', args=(), kwargs={})]

classmethod setUpClass()
Hook method for setting up class fixture before running tests in the class.

test_check_if_installed()
Test *check_if_installed*.
Returns

test_get_installed_packages()
Test *get_installed_packages*.
Returns

test_get_installed_packages_with_versions()
Test *get_installed_packages*.
Returns

class django_elasticsearch_dsl_drf.tests.**TestSearch**(*methodName='runTest'*)
Bases: *django_elasticsearch_dsl_drf.tests.base.BaseRestFrameworkTestCase*

Test search.

pytestmark = [Mark(name='django_db', args=(), kwargs={}), Mark(name='django_db', args=

classmethod setUpClass()
Set up class.

test_compound_search_boost_by_field()

test_compound_search_by_field()

test_compound_search_by_field_multi_terms()

test_compound_search_by_nested_field()

test_schema_field_not_required()
Test schema fields always not required

test_schema_fields_with_filter_fields_list()
Test schema field generator

test_search_boost(*url=None*, *search_field='search'*)
Search boost.
Returns

test_search_boost_compound(*search_field='search'*)

test_search_by_field(*url=None*, *search_field='search'*)
Search by field.

test_search_by_field_multi_terms(*url=None*, *search_field='search'*)
Search by field, multiple terms.

test_search_by_nested_field(*url=None*)
Search by field.

class django_elasticsearch_dsl_drf.tests.**TestSerializers**(*methodName='runTest'*)
Bases: *django_elasticsearch_dsl_drf.tests.base.BaseRestFrameworkTestCase*

Test serializers.

pytestmark = [Mark(name='django_db', args=(), kwargs={}), Mark(name='django_db', args=

test_serializer_document_equals_to_none()
Test serializer no document specified.

test_serializer_fields_and_exclude()
Test serializer fields and exclude.

test_serializer_meta_del_attr()
Test serializer set attr.

test_serializer_meta_set_attr()
Test serializer set attr.

test_serializer_no_document_specified()
Test serializer no document specified.

class django_elasticsearch_dsl_drf.tests.**TestSuggesters**(*methodName='runTest'*)
Bases: *django_elasticsearch_dsl_drf.tests.base.BaseRestFrameworkTestCase*, *django_elasticsearch_dsl_drf.tests.data_mixins.AddressesMixin*

Test suggesters.

pytestmark = [Mark(name='django_db', args=(), kwargs={}), Mark(name='django_db', args=

classmethod setUpClass()
Set up class.

test_nested_fields_suggesters_completion()
Test suggesters completion for nested fields.

test_suggesters_completion()
Test suggesters completion.

test_suggesters_completion_no_args_provided()
Test suggesters completion with no args provided.

test_suggesters_phrase()
Test suggesters phrase.

test_suggesters_term()
Test suggesters term.

class `django_elasticsearch_dsl_drf.tests.`**TestViews**(*methodName='runTest'*)
Bases: *`django_elasticsearch_dsl_drf.tests.base.BaseRestFrameworkTestCase`*

Test views.

pytestmark = [Mark(name='django_db', args=(), kwargs={}), Mark(name='django_db', args=

classmethod setUpClass()
Set up class.

test_detail_view()
Test detail view.

test_detail_view_with_custom_lookup()
Test detail view with a custom lookup field.

test_listing_view()
Test listing view.

class `django_elasticsearch_dsl_drf.tests.`**TestWrappers**(*methodName='runTest'*)
Bases: `unittest.case.TestCase`

Test wrappers.

pytestmark = [Mark(name='django_db', args=(), kwargs={})]

classmethod setUpClass()
Hook method for setting up class fixture before running tests in the class.

test_dict_to_obj()
Test *dict_to_obj*.
Returns

test_obj_to_dict()
Test *obj_to_dict*.
Returns

test_wrapper_as_json()
Test **:Wrapper:'as_json'** property.

12.18.2 Submodules

12.18.3 django_elasticsearch_dsl_drf.analyzers module

Analyzers.

12.18.4 django_elasticsearch_dsl_drf.apps module

Apps.

class `django_elasticsearch_dsl_drf.apps.`**`Config`**(*app_name*, *app_module*)

Bases: `django.apps.config.AppConfig`

Config.

`label = 'django_elasticsearch_dsl_drf'`

`name = 'django_elasticsearch_dsl_drf'`

12.18.5 django_elasticsearch_dsl_drf.compat module

Transitional compatibility module. Contains various field wrappers and helpers for painless (testing of) Elastic 2.x to Elastic 5.x transition. This module is not supposed to solve all transition issues for you. Better move to Elastic 5.x as soon as possible.

`django_elasticsearch_dsl_drf.compat.`**`KeywordField`**(***kwargs*)

Keyword field.

Parameters **`kwargs`** –

Returns

`django_elasticsearch_dsl_drf.compat.`**`StringField`**(***kwargs*)

String field.

Parameters **`kwargs`** –

Returns

12.18.6 django_elasticsearch_dsl_drf.constants module

Constants module. Contains Elasticsearch constants, lookup constants, functional constants, suggesters, etc.

12.18.7 django_elasticsearch_dsl_drf.helpers module

Helpers.

`django_elasticsearch_dsl_drf.helpers.`**`get_document_for_model`**(*model*)

Get document for model given.

Parameters **`model`** (Subclass of *django.db.models.Model*.) – Model to get document index for.

Returns Document index for the given model.

Return type Subclass of *django_elasticsearch_dsl.Document*.

`django_elasticsearch_dsl_drf.helpers.`**`get_index_and_mapping_for_model`**(*model*)

Get index and mapping for model.

Parameters **`model`** (Subclass of *django.db.models.Model*.) – Django model for which to get index and mapping for.

Returns Index and mapping values.

Return type tuple.

`django_elasticsearch_dsl_drf.helpers.`**`more_like_this`**(*obj*, *fields*, *max_query_terms=25*, *min_term_freq=2*, *min_doc_freq=5*, *max_doc_freq=0*, *query=None*)

More like this.

https://www.elastic.co/guide/en/elasticsearch/reference/current/ query-dsl-mlt-query.html

Parameters

- **obj** (Instance of *django.db.models.Model* (sub-classed) model.) – Django model instance for which similar objects shall be found.
- **fields** (*list*) – Fields to search in.
- **max_query_terms** (*int*) –
- **min_term_freq** (*int*) –
- **min_doc_freq** (*int*) –
- **max_doc_freq** (*int*) –
- **query** (*elasticsearch_dsl.query.Q*) – Q query

Returns List of objects.

Return type elasticsearch_dsl.search.Search

Example:

```
>>> from django_elasticsearch_dsl_drf.helpers import more_like_this
>>> from books.models import Book
>>> book = Book.objects.first()
>>> similar_books = more_like_this(
>>>     book,
>>>     ['title', 'description', 'summary']
>>> )
```

`django_elasticsearch_dsl_drf.helpers.`**`sort_by_list`**(*unsorted_dict*, *sorted_keys*)

Sort an OrderedDict by list of sorted keys.

Parameters

- **unsorted_dict** (*collections.OrderedDict*) – Source dictionary.
- **sorted_keys** (*list*) – Keys to sort on.

Returns Sorted dictionary.

Return type collections.OrderedDict

12.18.8 django_elasticsearch_dsl_drf.pagination module

Pagination.

class `django_elasticsearch_dsl_drf.pagination.`**`LimitOffsetPagination`**(**args*, ***kwargs*)

Bases: `rest_framework.pagination.LimitOffsetPagination`

A limit/offset pagination.

Example:

http://api.example.org/accounts/?limit=100 http://api.example.org/accounts/?offset=400&limit=100

get_count(*es_response*)

Determine an object count, supporting either querysets or regular lists.

get_facets(*facets=None*)

Get facets.

Parameters **facets** –

Returns

get_paginated_response(*data*)

Get paginated response.

Parameters **data** –

Returns

get_paginated_response_context(*data*)

Get paginated response data.

Parameters **data** –

Returns

paginate_queryset(*queryset*, *request*, *view=None*)

class `django_elasticsearch_dsl_drf.pagination.`**Page**(*object_list*, *number*, *paginator*, *facets*)

Bases: `django.core.paginator.Page`

Page for Elasticsearch.

class `django_elasticsearch_dsl_drf.pagination.`**PageNumberPagination**(**args*, ***kwargs*)

Bases: `rest_framework.pagination.PageNumberPagination`

Page number pagination.

A simple page number based style that supports page numbers as query parameters.

Example:
http://api.example.org/accounts/?page=4 http://api.example.org/accounts/?page=4&page_size=100

django_paginator_class
alias of `Paginator`

get_count(*es_response*)

get_facets(*page=None*)
Get facets.
Parameters **page** –
Returns

get_paginated_response(*data*)
Get paginated response.
Parameters **data** –
Returns

get_paginated_response_context(*data*)
Get paginated response data.
Parameters **data** –
Returns

paginate_queryset(*queryset*, *request*, *view=None*)
Paginate a queryset.

Paginate a queryset if required, either returning a page object, or *None* if pagination is not configured for this view.
Parameters

- **queryset** –
- **request** –
- **view** –

Returns

class `django_elasticsearch_dsl_drf.pagination.`**Paginator**(*object_list*, *per_page*, *orphans=0*, *allow_empty_first_page=True*)

Bases: `django.core.paginator.Paginator`

Paginator for Elasticsearch.

page(*number*)
Returns a Page object for the given 1-based page number.

Parameters **number** –
Returns

12.18.9 django_elasticsearch_dsl_drf.pip_helpers module

Pip helpers module.

`django_elasticsearch_dsl_drf.pip_helpers.`**`check_if_installed`**(*package*, *installed_packages=None*)

Check if package is installed.

Parameters

- **package** (*str*) –
- **installed_packages** (*iterable*) –

Returns
Return type bool

`django_elasticsearch_dsl_drf.pip_helpers.`**`get_installed_packages`**(*with_versions=False*)

Get installed packages.

Parameters **with_versions** (*bool*) – If set to True, returned with versions.
Returns
Return type list

12.18.10 django_elasticsearch_dsl_drf.serializers module

Serializers.

class `django_elasticsearch_dsl_drf.serializers.`**`DocumentSerializer`**(*instance=None*, *data=<class 'rest_framework.fields.empty'>*, ***kwargs*)

Bases: `rest_framework.serializers.Serializer`

A dynamic DocumentSerializer class.

`create`(*validated_data*)

Create.

Do nothing.

Parameters **validated_data** –
Returns

`get_fields`()

Get the required fields for serializing the result.

`update`(*instance*, *validated_data*)

Update.

Do nothing.

Parameters

- **instance** –
- **validated_data** –

Returns

class `django_elasticsearch_dsl_drf.serializers.`**`DocumentSerializerMeta`**

Bases: `rest_framework.serializers.SerializerMetaclass`

Metaclass for the DocumentSerializer.

Ensures that all declared subclasses implemented a Meta.

class `django_elasticsearch_dsl_drf.serializers.`**`Meta`**

Bases: `type`

Template for the DocumentSerializerMeta.Meta class.

`exclude = ()`

`field_aliases = {}`

`field_options = {}`

`fields = ()`

`ignore_fields = ()`

`index_aliases = {}`

`index_classes = ()`

`search_fields = ()`

`serializers = ()`

12.18.11 django_elasticsearch_dsl_drf.utils module

Utils.

class `django_elasticsearch_dsl_drf.utils.`**`DictionaryProxy`**(*mapping*)

Bases: `object`

Dictionary proxy.

`to_dict`()

To dict.

Returns

class `django_elasticsearch_dsl_drf.utils.`**`EmptySearch`**(**args*, ***kwargs*)

Bases: `object`

Empty Search.

`execute`(**args*, ***kwargs*)

`highlight`(**args*, ***kwargs*)

`sort`(**args*, ***kwargs*)

`to_dict`(**args*, ***kwargs*)

12.18.12 django_elasticsearch_dsl_drf.versions module

Contains information about the current Elasticsearch version in use, including (LTE and GTE).

`django_elasticsearch_dsl_drf.versions.`**`get_elasticsearch_version`**(*default=(2, 0, 0)*)

Get Elasticsearch version.

Parameters **`default`** (`tuple`) – Default value. Mainly added for building the docs when Elasticsearch is not running.

Returns

Return type list

12.18.13 django_elasticsearch_dsl_drf.viewsets module

Base ViewSets.

class `django_elasticsearch_dsl_drf.viewsets.`**`BaseDocumentViewSet`**(**args*, ***kwargs*)

Bases: `rest_framework.viewsets.ReadOnlyModelViewSet`

Base document ViewSet.

`document = None`

`document_uid_field = 'id'`

`get_object`()
Get object.

`get_queryset`()
Get queryset.

`ignore = []`

`pagination_class`
alias of *`django_elasticsearch_dsl_drf.pagination.PageNumberPagination`*

class `django_elasticsearch_dsl_drf.viewsets.`**`DocumentViewSet`**(**args*, ***kwargs*)

Bases: *`django_elasticsearch_dsl_drf.viewsets.BaseDocumentViewSet`*, *`django_elasticsearch_dsl_drf.viewsets.SuggestMixin`*, *`django_elasticsearch_dsl_drf.viewsets.FunctionalSuggestMixin`*

DocumentViewSet with suggest and functional-suggest mix-ins.

class `django_elasticsearch_dsl_drf.viewsets.`**`FunctionalSuggestMixin`**

Bases: `object`

Functional suggest mixin.

`functional_suggest`(*request*)
Functional suggest functionality.
Parameters **`request`** –
Returns

class `django_elasticsearch_dsl_drf.viewsets.`**`MoreLikeThisMixin`**

Bases: `object`

More-like-this mixin.

`more_like_this`(*request*, *pk=None*, *id=None*)
More-like-this functionality detail view.
Parameters **`request`** –
Returns

class `django_elasticsearch_dsl_drf.viewsets.`**`SuggestMixin`**

Bases: `object`

Suggest mixin.

`suggest`(*request*)
Suggest functionality.

12.18.14 django_elasticsearch_dsl_drf.wrappers module

`django_elasticsearch_dsl_drf.wrappers.`**`dict_to_obj`**(*mapping*)

dict to obj mapping.

Parameters **mapping** (*dict*) –

Returns

Return type *Wrapper*

`django_elasticsearch_dsl_drf.wrappers.`**`obj_to_dict`**(*obj*)

Wrapper to dict.

Parameters **obj** (**'obj':Wrapper:**) –

Returns

Return type dict

class `django_elasticsearch_dsl_drf.wrappers.`**`Wrapper`**

Bases: `object`

Wrapper.

Example: >>> from django_elasticsearch_dsl_drf.wrappers import dict_to_obj >>> >>> mapping = { >>> 'country': { >>> 'name': 'Netherlands', >>> 'province': { >>> 'name': 'North Holland', >>> 'city': { >>> 'name': 'Amsterdam', >>> } >>> } >>> } >>> } >>> >>> wrapper = dict_to_obj(mapping) >>> wrapper.country.name >>> "Netherlands" >>> wrapper.country.province.name >>> "North Holland" >>> wrapper.country.province.city.name >>> "Amsterdam" >>> wrapper.as_dict >>> { >>> 'country': { >>> 'name': 'Netherlands', >>> 'province': { >>> 'name': 'North Holland', >>> 'city': { >>> 'name': 'Amsterdam', >>> } >>> } >>> } >>> } >>> str(wrapper) >>> "Netherlands"

`as_dict`

As dict.

Returns

Return type dict

`as_json`

As JSON.

Returns

Return type str

12.18.15 Module contents

Integrate Elasticsearch DSL with Django REST framework.

CHAPTER 13

Indices and tables

- genindex
- modindex
- search

Python Module Index

d

`django_elasticsearch_dsl_drf`, 278
`django_elasticsearch_dsl_drf.analyzers`, 271
`django_elasticsearch_dsl_drf.apps`, 271
`django_elasticsearch_dsl_drf.compat`, 272
`django_elasticsearch_dsl_drf.constants`, 272
`django_elasticsearch_dsl_drf.fields`, 159
`django_elasticsearch_dsl_drf.fields.common`, 154
`django_elasticsearch_dsl_drf.fields.helpers`, 156
`django_elasticsearch_dsl_drf.fields.nested_fields`, 156
`django_elasticsearch_dsl_drf.filter_backends`, 239
`django_elasticsearch_dsl_drf.filter_backends.aggregations`, 162
`django_elasticsearch_dsl_drf.filter_backends.aggregations.bucket_aggregations`, 162
`django_elasticsearch_dsl_drf.filter_backends.aggregations.metrics_aggregations`, 162
`django_elasticsearch_dsl_drf.filter_backends.aggregations.pipeline_aggregations`, 162
`django_elasticsearch_dsl_drf.filter_backends.faceted_search`, 234
`django_elasticsearch_dsl_drf.filter_backends.filtering`, 179
`django_elasticsearch_dsl_drf.filter_backends.filtering.common`, 162
`django_elasticsearch_dsl_drf.filter_backends.filtering.geo_spatial`, 170
`django_elasticsearch_dsl_drf.filter_backends.filtering.ids`, 174
`django_elasticsearch_dsl_drf.filter_backends.filtering.nested`, 176
`django_elasticsearch_dsl_drf.filter_backends.filtering.post_filter`, 177
`django_elasticsearch_dsl_drf.filter_backends.highli`
237
`django_elasticsearch_dsl_drf.filter_backends.mixins`
238
`django_elasticsearch_dsl_drf.filter_backends.orderi`
198
`django_elasticsearch_dsl_drf.filter_backends.orderi`
193
`django_elasticsearch_dsl_drf.filter_backends.orderi`
196
`django_elasticsearch_dsl_drf.filter_backends.search`
215
`django_elasticsearch_dsl_drf.filter_backends.search`
211
`django_elasticsearch_dsl_drf.filter_backends.search`
212
`django_elasticsearch_dsl_drf.filter_backends.search`
212
`django_elasticsearch_dsl_drf.filter_backends.search`
214
`django_elasticsearch_dsl_drf.filter_backends.search`
207
`django_elasticsearch_dsl_drf.filter_backends.search`
203
`django_elasticsearch_dsl_drf.filter_backends.search`
203
`django_elasticsearch_dsl_drf.filter_backends.search`
203
`django_elasticsearch_dsl_drf.filter_backends.search`
204
`django_elasticsearch_dsl_drf.filter_backends.search`
204
`django_elasticsearch_dsl_drf.filter_backends.search`
205
`django_elasticsearch_dsl_drf.filter_backends.search`
206
`django_elasticsearch_dsl_drf.filter_backends.search`
214
`django_elasticsearch_dsl_drf.filter_backends.search`
214

```
django_elasticsearch_dsl_drf.filter_backends.suggester,
    227
django_elasticsearch_dsl_drf.filter_backends.suggester.functional,
    218
django_elasticsearch_dsl_drf.filter_backends.suggester.native,
    223
django_elasticsearch_dsl_drf.helpers,
    272
django_elasticsearch_dsl_drf.pagination,
    273
django_elasticsearch_dsl_drf.pip_helpers,
    275
django_elasticsearch_dsl_drf.serializers,
    275
django_elasticsearch_dsl_drf.tests, 257
django_elasticsearch_dsl_drf.tests.base,
    240
django_elasticsearch_dsl_drf.tests.data_mixins,
    240
django_elasticsearch_dsl_drf.tests.test_faceted_search,
    240
django_elasticsearch_dsl_drf.tests.test_filtering_common,
    241
django_elasticsearch_dsl_drf.tests.test_filtering_geo_spatial,
    244
django_elasticsearch_dsl_drf.tests.test_filtering_global_aggregations,
    245
django_elasticsearch_dsl_drf.tests.test_filtering_nested,
    245
django_elasticsearch_dsl_drf.tests.test_filtering_post_filter,
    247
django_elasticsearch_dsl_drf.tests.test_functional_suggesters,
    249
django_elasticsearch_dsl_drf.tests.test_helpers,
    250
django_elasticsearch_dsl_drf.tests.test_highlight,
    250
django_elasticsearch_dsl_drf.tests.test_more_like_this,
    250
django_elasticsearch_dsl_drf.tests.test_ordering_common,
    250
django_elasticsearch_dsl_drf.tests.test_ordering_geo_spatial,
    252
django_elasticsearch_dsl_drf.tests.test_pagination,
    252
django_elasticsearch_dsl_drf.tests.test_pip_helpers,
    252
django_elasticsearch_dsl_drf.tests.test_search,
    253
django_elasticsearch_dsl_drf.tests.test_search_multi_match,
    254
django_elasticsearch_dsl_drf.tests.test_search_simple_query_string,
    254
django_elasticsearch_dsl_drf.tests.test_serializers,
    255
    256
    256
    257
    276
    277
    278
```

Index

A

AddressesMixin (*class in django_elasticsearch_dsl_drf.tests.data_mixins*), 240
aggregate() (*django_elasticsearch_dsl_drf.filter_backends.faceted_search.FacetedSearchFilterBackend method*), 235
apply_filter() (*django_elasticsearch_dsl_drf.filter_backends.filtering.nested.NestedFilteringFilterBackend class method*), 176
apply_filter() (*django_elasticsearch_dsl_drf.filter_backends.filtering.NestedFilteringFilterBackend class method*), 191
apply_filter() (*django_elasticsearch_dsl_drf.filter_backends.filtering.post_filter.PostFilterFilteringFilterBackend class method*), 178
apply_filter() (*django_elasticsearch_dsl_drf.filter_backends.filtering.PostFilterFilteringFilterBackend class method*), 192
apply_filter() (*django_elasticsearch_dsl_drf.filter_backends.mixins.FilterBackendMixin class method*), 238
apply_filter_prefix() (*django_elasticsearch_dsl_drf.filter_backends.filtering.common.FilteringFilterBackend class method*), 163
apply_filter_prefix() (*django_elasticsearch_dsl_drf.filter_backends.filtering.FilteringFilterBackend class method*), 180
apply_filter_range() (*django_elasticsearch_dsl_drf.filter_backends.filtering.common.FilteringFilterBackend class method*), 164
apply_filter_range() (*django_elasticsearch_dsl_drf.filter_backends.filtering.FilteringFilterBackend class method*), 180
apply_filter_term() (*django_elasticsearch_dsl_drf.filter_backends.filtering.common.FilteringFilterBackend class method*), 164
apply_filter_term() (*django_elasticsearch_dsl_drf.filter_backends.filtering.FilteringFilterBackend class method*), 180
apply_filter_terms() (*django_elasticsearch_dsl_drf.filter_backends.filtering.common.FilteringFilterBackend class method*), 164
apply_filter_terms() (*django_elasticsearch_dsl_drf.filter_backends.filtering.FilteringFilterBackend class method*), 180
apply_query() (*django_elasticsearch_dsl_drf.filter_backends.filtering.n class method*), 177
apply_query() (*django_elasticsearch_dsl_drf.filter_backends.filtering. class method*), 191
apply_query() (*django_elasticsearch_dsl_drf.filter_backends.filtering.p class method*), 178
apply_query() (*django_elasticsearch_dsl_drf.filter_backends.filtering. class method*), 193
apply_query() (*django_elasticsearch_dsl_drf.filter_backends.mixins.F class method*), 239
apply_query_contains() (*django_elasticsearch_dsl_drf.filter_backends.filtering.common.F class method*), 165
apply_query_contains() (*django_elasticsearch_dsl_drf.filter_backends.filtering.FilteringF class method*), 181
apply_query_endswith() (*django_elasticsearch_dsl_drf.filter_backends.filtering.common.F class method*), 165
apply_query_endswith() (*django_elasticsearch_dsl_drf.filter_backends.filtering.FilteringF class method*), 181
apply_query_exclude() (*django_elasticsearch_dsl_drf.filter_backends.filtering.common.F class method*), 165
apply_query_exclude() (*django_elasticsearch_dsl_drf.filter_backends.filtering.FilteringF class method*), 181
apply_query_exists() (*django_elasticsearch_dsl_drf.filter_backends.filtering.common.F class method*), 166
apply_query_exists() (*django_elasticsearch_dsl_drf.filter_backends.filtering.FilteringF class method*), 182
apply_query_geo_bounding_box() (*django_elasticsearch_dsl_drf.filter_backends.filtering.geo_spatia class method*), 171
apply_query_geo_bounding_box() (*django_elasticsearch_dsl_drf.filter_backends.filtering.GeoSpatia*

class method), 186
apply_query_geo_distance() (*django_elasticsearch_dsl_drf.filter_backends.filtering.geo_spatial.GeoSpatialFilteringFilterBackend*) *class method*), 171
apply_query_geo_distance() (*django_elasticsearch_dsl_drf.filter_backends.filtering.GeoSpatialFilteringFilterBackend*) *class method*), 186
apply_query_geo_polygon() (*django_elasticsearch_dsl_drf.filter_backends.filtering.geo_spatial.GeoSpatialFilteringFilterBackend*) *class method*), 171
apply_query_geo_polygon() (*django_elasticsearch_dsl_drf.filter_backends.filtering.GeoSpatialFilteringFilterBackend*) *class method*), 186
apply_query_gt() (*django_elasticsearch_dsl_drf.filter_backends.filtering.common.FilteringFilterBackend*) *class method*), 166
apply_query_gt() (*django_elasticsearch_dsl_drf.filter_backends.filtering.FilteringFilterBackend*) *class method*), 182
apply_query_gte() (*django_elasticsearch_dsl_drf.filter_backends.filtering.common.FilteringFilterBackend*) *class method*), 167
apply_query_gte() (*django_elasticsearch_dsl_drf.filter_backends.filtering.FilteringFilterBackend*) *class method*), 182
apply_query_in() (*django_elasticsearch_dsl_drf.filter_backends.filtering.common.FilteringFilterBackend*) *class method*), 167
apply_query_in() (*django_elasticsearch_dsl_drf.filter_backends.filtering.FilteringFilterBackend*) *class method*), 183
apply_query_isnull() (*django_elasticsearch_dsl_drf.filter_backends.filtering.common.FilteringFilterBackend*) *class method*), 167
apply_query_isnull() (*django_elasticsearch_dsl_drf.filter_backends.filtering.FilteringFilterBackend*) *class method*), 183
apply_query_lt() (*django_elasticsearch_dsl_drf.filter_backends.filtering.common.FilteringFilterBackend*) *class method*), 168
apply_query_lt() (*django_elasticsearch_dsl_drf.filter_backends.filtering.FilteringFilterBackend*) *class method*), 183
apply_query_lte() (*django_elasticsearch_dsl_drf.filter_backends.filtering.common.FilteringFilterBackend*) *class method*), 168
apply_query_lte() (*django_elasticsearch_dsl_drf.filter_backends.filtering.FilteringFilterBackend*) *class method*), 184
apply_query_size() (*django_elasticsearch_dsl_drf.filter_backends.suggester.functional.FunctionalSuggesterFilterBackend*) *class method*), 221
apply_query_size() (*django_elasticsearch_dsl_drf.filter_backends.suggester.FunctionalSuggesterFilterBackend*) *class method*), 232
apply_query_wildcard() (*django_elasticsearch_dsl_drf.filter_backends.filtering.common.FilteringFilterBackend*) *class method*), 168
apply_query_wildcard() (*django_elasticsearch_dsl_drf.filter_backends.filtering.FilteringFilterBackend*) *class method*), 184
apply_suggester_completion() (*django_elasticsearch_dsl_drf.filter_backends.suggester.native.SuggesterFilterBackend*) *class method*), 225
apply_suggester_completion() (*django_elasticsearch_dsl_drf.filter_backends.suggester.SuggesterFilterBackend*) *class method*), 229
apply_suggester_completion_match() (*django_elasticsearch_dsl_drf.filter_backends.suggester.functional.FunctionalSuggesterFilterBackend*) *class method*), 221
apply_suggester_completion_match() (*django_elasticsearch_dsl_drf.filter_backends.suggester.FunctionalSuggesterFilterBackend*) *class method*), 232
apply_suggester_completion_prefix() (*django_elasticsearch_dsl_drf.filter_backends.suggester.FunctionalSuggesterFilterBackend*) *class method*), 221
apply_suggester_completion_prefix() (*django_elasticsearch_dsl_drf.filter_backends.suggester.FunctionalSuggesterFilterBackend*) *class method*), 233
apply_suggester_phrase() (*django_elasticsearch_dsl_drf.filter_backends.suggester.native.SuggesterFilterBackend*) *class method*), 225
apply_suggester_phrase() (*django_elasticsearch_dsl_drf.filter_backends.suggester.SuggesterFilterBackend*) *class method*), 229
apply_suggester_phrase() (*django_elasticsearch_dsl_drf.filter_backends.suggester.native.SuggesterFilterBackend*) *class method*), 225
apply_suggester_phrase() (*django_elasticsearch_dsl_drf.filter_backends.suggester.SuggesterFilterBackend*) *class method*), 229
arg_filter (*django_elasticsearch_dsl_drf.wrappers.Wrapper attribute*), 278
arg_kwds (*django_elasticsearch_dsl_drf.wrappers.Wrapper attribute*), 278
arg_kwds (*django_elasticsearch_dsl_drf.tests.base.BaseRestFrameworkTestCase*) *method*), 240

B

base_url (*django_elasticsearch_dsl_drf.tests.test_filtering_nested.TestFilteringNested attribute*), 245
base_url (*django_elasticsearch_dsl_drf.tests.TestFilteringNested attribute*), 261
BaseDocumentViewSet (*class in django_elasticsearch_dsl_drf.viewsets*), 277
BaseRestFrameworkTestCase (*class in django_elasticsearch_dsl_drf.tests.base*), 240
BaseSearchFilterBackend (*class in django_elasticsearch_dsl_drf.filter_backends.search*), 215
BaseSearchFilterBackend (*class in django_elasticsearch_dsl_drf.filter_backends.search.base*), 215

BaseSearchQueryBackend (*class in django_elasticsearch_dsl_drf.filter_backends.search.query_backends*), 207

BaseSearchQueryBackend (*class in django_elasticsearch_dsl_drf.filter_backends.search.query_backends.base*), 203

BaseTestCase (*class in django_elasticsearch_dsl_drf.tests.base*), 240

BooksMixin (*class in django_elasticsearch_dsl_drf.tests.data_mixins*), 240

BooleanField (*class in django_elasticsearch_dsl_drf.fields*), 159

BooleanField (*class in django_elasticsearch_dsl_drf.fields.common*), 154

C

CharField (*class in django_elasticsearch_dsl_drf.fields*), 159

CharField (*class in django_elasticsearch_dsl_drf.fields.common*), 155

check_if_installed() (*in module django_elasticsearch_dsl_drf.pip_helpers*), 275

clean_queryset() (*django_elasticsearch_dsl_drf.filter_backends.suggester.functional.FunctionalSuggesterFilterBackend method*), 221

clean_queryset() (*django_elasticsearch_dsl_drf.filter_backends.suggester.common.SuggesterFilterBackend method*), 233

CompoundSearchFilterBackend (*class in django_elasticsearch_dsl_drf.filter_backends.search*), 215

CompoundSearchFilterBackend (*class in django_elasticsearch_dsl_drf.filter_backends.search.compound*), 212

Config (*class in django_elasticsearch_dsl_drf.apps*), 271

construct_facets() (*django_elasticsearch_dsl_drf.filter_backends.faceted_search.FacetedSearchFilterBackend method*), 235

construct_nested_search() (*django_elasticsearch_dsl_drf.filter_backends.search.historical.SearchFilterBackend method*), 212

construct_nested_search() (*django_elasticsearch_dsl_drf.filter_backends.search.SearchFilterBackend method*), 216

construct_search() (*django_elasticsearch_dsl_drf.filter_backends.search.historical.SearchFilterBackend method*), 213

construct_search() (*django_elasticsearch_dsl_drf.filter_backends.search.query_backends.BaseSearchQueryBackend class method*), 203

construct_search() (*django_elasticsearch_dsl_drf.filter_backends.search.query_backends.base.BaseSearchQueryBackend class method*), 203

construct_search() (*django_elasticsearch_dsl_drf.filter_backends.search.query_backends.BaseSearchQueryBackend class method*), 203

construct_search() (*django_elasticsearch_dsl_drf.filter_backends.search.query_backends.BaseSearchQueryBackend class method*), 204

construct_search() (*django_elasticsearch_dsl_drf.filter_backends.search.query_backends.BaseSearchQueryBackend class method*), 208

construct_search() (*django_elasticsearch_dsl_drf.filter_backends.search.query_backends.BaseSearchQueryBackend class method*), 208

construct_search() (*django_elasticsearch_dsl_drf.filter_backends.search.query_backends.BaseSearchQueryBackend class method*), 207

construct_search() (*django_elasticsearch_dsl_drf.filter_backends.search.query_backends.BaseSearchQueryBackend class method*), 204

construct_search() (*django_elasticsearch_dsl_drf.filter_backends.search.query_backends.BaseSearchQueryBackend class method*), 208

construct_search() (*django_elasticsearch_dsl_drf.filter_backends.suggester.functional.FunctionalSuggesterFilterBackend class method*), 205

construct_search() (*django_elasticsearch_dsl_drf.filter_backends.search.query_backends.BaseSearchQueryBackend class method*), 209

construct_search() (*django_elasticsearch_dsl_drf.filter_backends.search.query_backends.BaseSearchQueryBackend class method*), 206

construct_search() (*django_elasticsearch_dsl_drf.filter_backends.search.query_backends.BaseSearchQueryBackend class method*), 210

construct_search() (*django_elasticsearch_dsl_drf.filter_backends.search.SearchFilterBackend method*), 217

create() (*django_elasticsearch_dsl_drf.serializers.DocumentSerializer method*), 275

create_books() (*django_elasticsearch_dsl_drf.tests.data_mixins.BooksMixin class method*), 240

create_addresses() (*django_elasticsearch_dsl_drf.tests.data_mixins.AddressesMixin class method*), 240

D

DateField (*class in django_elasticsearch_dsl_drf.fields*), 159

DateField (*class in*

django_elasticsearch_dsl_drf.fields.common), 155

deep_get() (*django_elasticsearch_dsl_drf.tests.test_ordering_common.TestOrdering static method*), 250

deep_get() (*django_elasticsearch_dsl_drf.tests.TestOrdering static method*), 267

DefaultOrderingFilterBackend (*class in django_elasticsearch_dsl_drf.filter_backends.ordering*), 198

DefaultOrderingFilterBackend (*class in django_elasticsearch_dsl_drf.filter_backends.ordering_common*), 193

dict_to_obj() (*in module django_elasticsearch_dsl_drf.wrappers*), 278

DictionaryProxy (*class in django_elasticsearch_dsl_drf.utils*), 276

django_elasticsearch_dsl_drf (*module*), 278

django_elasticsearch_dsl_drf.analyzers (*module*), 271

django_elasticsearch_dsl_drf.apps (*module*), 271

django_elasticsearch_dsl_drf.compat (*module*), 272

django_elasticsearch_dsl_drf.constants (*module*), 272

django_elasticsearch_dsl_drf.fields (*module*), 159

django_elasticsearch_dsl_drf.fields.common (*module*), 154

django_elasticsearch_dsl_drf.fields.helpers (*module*), 156

django_elasticsearch_dsl_drf.fields.nested_fields (*module*), 156

django_elasticsearch_dsl_drf.filter_backends (*module*), 239

django_elasticsearch_dsl_drf.filter_backends.aggregations (*module*), 162

django_elasticsearch_dsl_drf.filter_backends.aggregations.bucket_aggregations (*module*), 162

django_elasticsearch_dsl_drf.filter_backends.aggregations.metric_aggregations (*module*), 162

django_elasticsearch_dsl_drf.filter_backends.aggregations.pipeline_aggregations (*module*), 162

django_elasticsearch_dsl_drf.filter_backends.facets (*module*), 234

django_elasticsearch_dsl_drf.filter_backends.filtering (*module*), 179

django_elasticsearch_dsl_drf.filter_backends.filtering.common (*module*), 162

django_elasticsearch_dsl_drf.filter_backends.filtering.geo_spatial (*module*), 170

django_elasticsearch_dsl_drf.filter_backends.filtering.ids (*module*), 174

django_elasticsearch_dsl_drf.filter_backends.filter (*module*), 176

django_elasticsearch_dsl_drf.filter_backends.filter (*module*), 177

django_elasticsearch_dsl_drf.filter_backends.highl (*module*), 237

django_elasticsearch_dsl_drf.filter_backends.mixins (*module*), 238

django_elasticsearch_dsl_drf.filter_backends.order (*module*), 198

django_elasticsearch_dsl_drf.filter_backends.order (*module*), 193

django_elasticsearch_dsl_drf.filter_backends.order (*module*), 196

django_elasticsearch_dsl_drf.filter_backends.search (*module*), 215

django_elasticsearch_dsl_drf.filter_backends.search (*module*), 211

django_elasticsearch_dsl_drf.filter_backends.search (*module*), 212

django_elasticsearch_dsl_drf.filter_backends.search (*module*), 212

django_elasticsearch_dsl_drf.filter_backends.search (*module*), 214

django_elasticsearch_dsl_drf.filter_backends.search (*module*), 207

django_elasticsearch_dsl_drf.filter_backends.search (*module*), 203

django_elasticsearch_dsl_drf.filter_backends.search (*module*), 203

django_elasticsearch_dsl_drf.filter_backends.search (*module*), 203

django_elasticsearch_dsl_drf.filter_backends.search (*module*), 204

django_elasticsearch_dsl_drf.filter_backends.search (*module*), 204

django_elasticsearch_dsl_drf.filter_backends.search (*module*), 205

django_elasticsearch_dsl_drf.filter_backends.search (*module*), 206

django_elasticsearch_dsl_drf.filter_backends.search (*module*), 214

django_elasticsearch_dsl_drf.filter_backends.search (*module*), 214

django_elasticsearch_dsl_drf.filter_backends.sugges (*module*), 227

django_elasticsearch_dsl_drf.filter_backends.sugges (*module*), 218

django_elasticsearch_dsl_drf.filter_backends.sugges (*module*), 223

drf.helpers (*module*), 272

sch_dsl_drf.pagination (*module*), 273

`django_elasticsearch_dsl_drf.pip_helpers` (*module*), 275
`django_elasticsearch_dsl_drf.serializers` (*module*), 275
`django_elasticsearch_dsl_drf.tests` (*module*), 257
`django_elasticsearch_dsl_drf.tests.base` (*module*), 240
`django_elasticsearch_dsl_drf.tests.data_mixins` (*module*), 240
`django_elasticsearch_dsl_drf.tests.test_faceted_search` (*module*), 240
`django_elasticsearch_dsl_drf.tests.test_filtering` (*module*), 241
`django_elasticsearch_dsl_drf.tests.test_filtering_geo_spatial` (*module*), 244
`django_elasticsearch_dsl_drf.tests.test_filtering_global_aggregations` (*module*), 245
`django_elasticsearch_dsl_drf.tests.test_filtering_nested` (*module*), 245
`django_elasticsearch_dsl_drf.tests.test_filtering_viewset` (*module*), 247
`django_elasticsearch_dsl_drf.tests.test_functional_suggesters` (*module*), 249
`django_elasticsearch_dsl_drf.tests.test_helpers` (*module*), 250
`django_elasticsearch_dsl_drf.tests.test_highlight` (*module*), 250
`django_elasticsearch_dsl_drf.tests.test_more_like_this` (*module*), 250
`django_elasticsearch_dsl_drf.tests.test_ordering_common` (*module*), 250
`django_elasticsearch_dsl_drf.tests.test_ordering_geo_spatial` (*module*), 252
`django_elasticsearch_dsl_drf.tests.test_pagination` (*module*), 252
`django_elasticsearch_dsl_drf.tests.test_pip_helpers` (*module*), 252
`django_elasticsearch_dsl_drf.tests.test_search` (*module*), 253
`django_elasticsearch_dsl_drf.tests.test_search_multi_match` (*module*), 254
`django_elasticsearch_dsl_drf.tests.test_search_simple_query_string` (*module*), 254
`django_elasticsearch_dsl_drf.tests.test_serializers` (*module*), 255
`django_elasticsearch_dsl_drf.tests.test_suggesters` (*module*), 256
`django_elasticsearch_dsl_drf.tests.test_views` (*module*), 256
`django_elasticsearch_dsl_drf.tests.test_wrappers` (*module*), 257
`django_elasticsearch_dsl_drf.utils` (*module*), 276
`django_elasticsearch_dsl_drf.versions` (*module*), 276
`django_elasticsearch_dsl_drf.viewsets` (*module*), 277
`django_elasticsearch_dsl_drf.wrappers` (*module*), 278
`django_paginator_class` (*django_elasticsearch_dsl_drf.pagination.PageNumberPagination attribute*), 274
`document` (*django_elasticsearch_dsl_drf.viewsets.BaseDocumentViewSet attribute*), 277
`document_uid_field` (*django_elasticsearch_dsl_drf.viewsets.BaseDocumentViewSet attribute*), 277
`DocumentGeoSpatial` (*class in django_elasticsearch_dsl_drf.serializers*), 275
`DocumentSerializerMeta` (*class in django_elasticsearch_dsl_drf.serializers*), 275
`DocumentViewSetFilter` (*class in django_elasticsearch_dsl_drf.viewsets*), 277

E

`EmptySearch` (*class in django_elasticsearch_dsl_drf.utils*), 276
`exclude` (*django_elasticsearch_dsl_drf.serializers.Meta attribute*), 276
`execute()` (*django_elasticsearch_dsl_drf.utils.EmptySearch method*), 276
`extract_field_name()` (*django_elasticsearch_dsl_drf.filter_backends.suggester.functional method*), 222
`extract_field_name()` (*django_elasticsearch_dsl_drf.filter_backends.suggester.Function method*), 233

F

`faceted_search_param` (*django_elasticsearch_dsl_drf.filter_backends.faceted_search.Fac attribute*), 236
`FacetedSearchFilterBackend` (*class in django_elasticsearch_dsl_drf.filter_backends.faceted_search*), 234
`field_aliases` (*django_elasticsearch_dsl_drf.serializers.Meta attribute*), 276
`field_options` (*django_elasticsearch_dsl_drf.serializers.Meta attribute*), 276
`fields` (*django_elasticsearch_dsl_drf.serializers.Meta attribute*), 276
`filter_queryset()` (*django_elasticsearch_dsl_drf.filter_backends.faceted_search.Fac method*), 236

filter_queryset() (*django_elasticsearch_dsl_drf.filter_backends.filtering.common.FilteringFilterBackend method*), 169
filter_queryset() (*django_elasticsearch_dsl_drf.filter_backends.filtering.FilteringFilterBackend method*), 184
filter_queryset() (*django_elasticsearch_dsl_drf.filter_backends.filtering.geo_spatial.GeoSpatialFilteringFilterBackend method*), 172
filter_queryset() (*django_elasticsearch_dsl_drf.filter_backends.filtering.GeoSpatialFilteringFilterBackend method*), 187
filter_queryset() (*django_elasticsearch_dsl_drf.filter_backends.filtering.ids.IdsFilterBackend method*), 175
filter_queryset() (*django_elasticsearch_dsl_drf.filter_backends.filtering.IdsFilterBackend method*), 189
filter_queryset() (*django_elasticsearch_dsl_drf.filter_backends.highlight.HighlightBackend method*), 237
filter_queryset() (*django_elasticsearch_dsl_drf.filter_backends.ordering.common.DefaultOrderingFilterBackend method*), 194
filter_queryset() (*django_elasticsearch_dsl_drf.filter_backends.ordering.common.OrderingFilterBackend method*), 195
filter_queryset() (*django_elasticsearch_dsl_drf.filter_backends.ordering.DefaultOrderingFilterBackend method*), 199
filter_queryset() (*django_elasticsearch_dsl_drf.filter_backends.ordering.geo_spatial.GeoSpatialOrderingFilterBackend method*), 196
filter_queryset() (*django_elasticsearch_dsl_drf.filter_backends.ordering.GeoSpatialOrderingFilterBackend method*), 200
filter_queryset() (*django_elasticsearch_dsl_drf.filter_backends.ordering.OrderingFilterBackend method*), 202
filter_queryset() (*django_elasticsearch_dsl_drf.filter_backends.search.base.BaseSearchFilterBackend method*), 211
filter_queryset() (*django_elasticsearch_dsl_drf.filter_backends.search.BaseSearchFilterBackend method*), 215
filter_queryset() (*django_elasticsearch_dsl_drf.filter_backends.search.historical.SearchFilterBackend method*), 214
filter_queryset() (*django_elasticsearch_dsl_drf.filter_backends.search.SearchFilterBackend method*), 218
filter_queryset() (*django_elasticsearch_dsl_drf.filter_backends.suggester.functional.FunctionalSuggesterFilterBackend method*), 222
filter_queryset() (*django_elasticsearch_dsl_drf.filter_backends.suggester.FunctionalSuggesterFilterBackend method*), 233
filter_queryset() (*django_elasticsearch_dsl_drf.filter_backends.suggester.native.SuggesterFilterBackend method*), 226
filter_queryset() (*django_elasticsearch_dsl_drf.filter_backends.suggester.SuggesterFilterBackend method*), 229
FilterBackendMixin (*class in django_elasticsearch_dsl_drf.filter_backends.mixins*), 238
FilteringFilterBackend (*class in django_elasticsearch_dsl_drf.filter_backends.filtering*), 179
FilteringFilterBackend (*class in django_elasticsearch_dsl_drf.filter_backends.filtering.common*), 162
FloatField (*class in django_elasticsearch_dsl_drf.fields*), 160
FloatField (*class in django_elasticsearch_dsl_drf.fields.common*), 155
functional_suggest() (*django_elasticsearch_dsl_drf.viewsets.FunctionalSuggestMixin method*), 277
FunctionalSuggesterFilterBackend (*class in django_elasticsearch_dsl_drf.filter_backends.suggester*), 231
FunctionalSuggesterFilterBackend (*class in django_elasticsearch_dsl_drf.filter_backends.suggester.functional*), 220
FunctionalSuggestMixin (*class in django_elasticsearch_dsl_drf.viewsets*), 277

G

GeoPointField (*class in django_elasticsearch_dsl_drf.fields*), 160
GeoPointField (*class in django_elasticsearch_dsl_drf.fields.nested_fields*), 158
GeoShapeField (*class in django_elasticsearch_dsl_drf.fields*), 160
GeoShapeField (*class in django_elasticsearch_dsl_drf.fields.nested_fields*), 157
GeoSpatialFilteringFilterBackend (*class in django_elasticsearch_dsl_drf.filter_backends.filtering*), 185
GeoSpatialFilteringFilterBackend (*class in django_elasticsearch_dsl_drf.filter_backends.filtering.geo_spatial*), 170
GeoSpatialOrderingFilterBackend (*class in django_elasticsearch_dsl_drf.filter_backends.ordering*),

199
GeoSpatialOrderingFilterBackend (*class in django_elasticsearch_dsl_drf.filter_backends.ordering.geo_spatial*), 196
get_coreschema_field() (*django_elasticsearch_dsl_drf.filter_backends.filtering.common.FilteringFilterBackend method*), 169
get_coreschema_field() (*django_elasticsearch_dsl_drf.filter_backends.filtering.FilteringFilterBackend method*), 185
get_coreschema_field() (*django_elasticsearch_dsl_drf.filter_backends.filtering.nested.NestedFilteringFilterBackend method*), 177
get_coreschema_field() (*django_elasticsearch_dsl_drf.filter_backends.filtering.NestedFilteringFilterBackend method*), 191
get_coreschema_field() (*django_elasticsearch_dsl_drf.filter_backends.filtering.post_filter.PostFilterFilteringFilterBackend method*), 179
get_coreschema_field() (*django_elasticsearch_dsl_drf.filter_backends.filtering.PostFilterFilteringFilterBackend method*), 193
get_coreschema_field() (*django_elasticsearch_dsl_drf.filter_backends.search.base.BaseSearchFilterBackend method*), 211
get_coreschema_field() (*django_elasticsearch_dsl_drf.filter_backends.search.BaseSearchFilterBackend method*), 215
get_coreschema_field() (*django_elasticsearch_dsl_drf.filter_backends.search.historical.SearchFilterBackend method*), 214
get_coreschema_field() (*django_elasticsearch_dsl_drf.filter_backends.search.SearchFilterBackend method*), 218
get_count() (*django_elasticsearch_dsl_drf.pagination.LimitOffsetPagination method*), 273
get_count() (*django_elasticsearch_dsl_drf.pagination.PageNumberPagination method*), 274
get_default_ordering_params() (*django_elasticsearch_dsl_drf.filter_backends.ordering.common.DefaultOrderingFilterBackend class method*), 194
get_default_ordering_params() (*django_elasticsearch_dsl_drf.filter_backends.ordering.DefaultOrderingFilterBackend class method*), 199
get_document_for_model() (*in module django_elasticsearch_dsl_drf.helpers*), 272
get_elasticsearch_version() (*in module django_elasticsearch_dsl_drf.versions*), 276
get_faceted_search_query_params() (*django_elasticsearch_dsl_drf.filter_backends.faceted_search.FacetedSearchFilterBackend method*), 236
get_facets() (*django_elasticsearch_dsl_drf.pagination.LimitOffsetPagination method*), 273
get_facets() (*django_elasticsearch_dsl_drf.pagination.PageNumberPagination method*), 274
get_field() (*django_elasticsearch_dsl_drf.filter_backends.search.query_spatial method*), 205
get_field() (*django_elasticsearch_dsl_drf.filter_backends.search.query_class method*), 209
get_field() (*django_elasticsearch_dsl_drf.filter_backends.search.query_class method*), 207
get_field() (*django_elasticsearch_dsl_drf.filter_backends.search.query_class method*), 210
get_fields() (*django_elasticsearch_dsl_drf.serializers.DocumentSerial method*), 275
get_fields() (*django_elasticsearch_dsl_drf.filter_backends.filtering.nested.NestedFilteringFilterBackend method*), 177
get_fields() (*django_elasticsearch_dsl_drf.filter_backends.filtering.NestedFilteringFilterBackend method*), 191
get_fields() (*django_elasticsearch_dsl_drf.filter_backends.filtering.post_filter.PostFilterFilteringFilterBackend method*), 169
get_fields() (*django_elasticsearch_dsl_drf.filter_backends.filtering.PostFilterFilteringFilterBackend method*), 185
get_fields() (*django_elasticsearch_dsl_drf.filter_backends.filtering.geo_spatial method*), 172
get_fields() (*django_elasticsearch_dsl_drf.filter_backends.filtering.GeoSpatial method*), 187
get_fields() (*django_elasticsearch_dsl_drf.filter_backends.filtering.nested.Nes method*), 177
get_fields() (*django_elasticsearch_dsl_drf.filter_backends.filtering.NestedFilt method*), 191
get_fields() (*django_elasticsearch_dsl_drf.filter_backends.filtering.common.F method*), 169
get_fields() (*django_elasticsearch_dsl_drf.filter_backends.filtering.FilteringF method*), 185
get_fields() (*django_elasticsearch_dsl_drf.filter_backends.filtering.geo_spatial method*), 172
get_fields() (*django_elasticsearch_dsl_drf.filter_backends.filtering.GeoSpatial method*), 187
get_fields() (*django_elasticsearch_dsl_drf.filter_backends.filtering.nested.Nes method*), 177
get_fields() (*django_elasticsearch_dsl_drf.filter_backends.filtering.NestedFilt method*), 191
get_geo_bounding_box_params() (*django_elasticsearch_dsl_drf.filter_backends.filtering.geo_spatial class method*), 172
get_geo_bounding_box_params() (*django_elasticsearch_dsl_drf.filter_backends.filtering.GeoSpatial class method*), 187
get_geo_distance_params() (*django_elasticsearch_dsl_drf.filter_backends.filtering.geo_spatial class method*), 173
get_geo_distance_params() (*django_elasticsearch_dsl_drf.filter_backends.filtering.GeoSpatial class method*), 188
get_geo_distance_params() (*django_elasticsearch_dsl_drf.filter_backends.ordering.geo_spatial class method*), 197
get_geo_distance_params() (*django_elasticsearch_dsl_drf.filter_backends.ordering.GeoSpatial class method*), 200
get_geo_pagination_params()

(*django_elasticsearch_dsl_drf.filter_backends.filtering.geo_spatial.GeoSpatialFilteringFilterBackend* class method), 173
get_geo_polygon_params() (*django_elasticsearch_dsl_drf.filter_backends.filtering.GeoSpatialFilteringFilterBackend* class method), 188
get_geo_spatial_field_name() (*django_elasticsearch_dsl_drf.filter_backends.ordering.geo_spatial.GeoSpatialOrderingFilterBackend* method), 197
get_geo_spatial_field_name() (*django_elasticsearch_dsl_drf.filter_backends.ordering.GeoSpatial.GeoSpatialOrderingFilterBackend* method), 200
get_gte_lte_params() (*django_elasticsearch_dsl_drf.filter_backends.filtering.common.RangeFilterBackend* class method), 169
get_gte_lte_params() (*django_elasticsearch_dsl_drf.filter_backends.filtering.FilteringFilterBackend* class method), 185
get_highlight_query_params() (*django_elasticsearch_dsl_drf.filter_backends.highlight.HighlightBackend* method), 238
get_ids_query_params() (*django_elasticsearch_dsl_drf.filter_backends.filtering.ids.IdsFilterBackend* method), 175
get_ids_query_params() (*django_elasticsearch_dsl_drf.filter_backends.filtering.IdsFilterBackend* method), 190
get_ids_values() (*django_elasticsearch_dsl_drf.filter_backends.filtering.ids.IdsFilterBackend* method), 175
get_ids_values() (*django_elasticsearch_dsl_drf.filter_backends.filtering.IdsFilterBackend* method), 190
get_index_and_mapping_for_model() (*in module django_elasticsearch_dsl_drf.helpers*), 272
get_installed_packages() (*in module django_elasticsearch_dsl_drf.pip_helpers*), 275
get_object() (*django_elasticsearch_dsl_drf.viewsets.BaseDocumentViewSet* method), 277
get_ordering_query_params() (*django_elasticsearch_dsl_drf.filter_backends.ordering.common.DefaultOrdering* method), 194
get_ordering_query_params() (*django_elasticsearch_dsl_drf.filter_backends.ordering.common.Ordering* method), 196
get_ordering_query_params() (*django_elasticsearch_dsl_drf.filter_backends.ordering.Default.Ordering* method), 199
get_ordering_query_params() (*django_elasticsearch_dsl_drf.filter_backends.ordering.geo_spatial.GeoSpatialOrderingFilterBackend* method), 197
get_ordering_query_params() (*django_elasticsearch_dsl_drf.filter_backends.ordering.GeoSpatial.GeoSpatialOrderingFilterBackend* method), 201
get_ordering_query_params() (*django_elasticsearch_dsl_drf.filter_backends.ordering.Ordering* method), 202
get_paginated_response() (*django_elasticsearch_dsl_drf.pagination.LimitOffsetPagination* method), 273
get_paginated_response() (*django_elasticsearch_dsl_drf.pagination.PageNumberPagination* method), 274
get_paginated_response_context() (*django_elasticsearch_dsl_drf.pagination.LimitOffsetPagination* method), 273
get_paginated_response_context() (*django_elasticsearch_dsl_drf.pagination.PageNumberPagination* method), 274
get_query_backends() (*django_elasticsearch_dsl_drf.filter_backends.search.base.BaseSearch* method), 211
get_query_backends() (*django_elasticsearch_dsl_drf.filter_backends.search.BaseSearch* method), 215
get_query_options() (*django_elasticsearch_dsl_drf.filter_backends.search.query_back* class method), 205
get_query_options() (*django_elasticsearch_dsl_drf.filter_backends.search.query_back* class method), 209
get_query_options() (*django_elasticsearch_dsl_drf.filter_backends.search.query_back* class method), 207
get_query_options() (*django_elasticsearch_dsl_drf.filter_backends.search.query_back* class method), 211
get_queryset() (*django_elasticsearch_dsl_drf.viewsets.BaseDocumen* method), 277
get_range_params() (*django_elasticsearch_dsl_drf.filter_backends.filtering.common.F* class method), 169
get_range_params() (*django_elasticsearch_dsl_drf.filter_backends.filtering.FilteringF* class method), 185
get_schema_fields() (*django_elasticsearch_dsl_drf.filter_backends.filtering.common.F* method), 170
get_schema_fields() (*django_elasticsearch_dsl_drf.filter_backends.filtering.FilteringF* method), 185
get_schema_fields() (*django_elasticsearch_dsl_drf.filter_backends.filtering.nested.Nes* method), 177
get_schema_fields() (*django_elasticsearch_dsl_drf.filter_backends.filtering.NestedFilt* method), 192
get_schema_fields() (*django_elasticsearch_dsl_drf.filter_backends.filtering.post_filter.*

method), 179
`get_schema_fields()` (*django_elasticsearch_dsl_drf.filter_backends.filtering.PostFilterFilteringFilterBackend method*), 193
`get_schema_fields()` (*django_elasticsearch_dsl_drf.filter_backends.ordering.common.OrderingFilterBackend method*), 196
`get_schema_fields()` (*django_elasticsearch_dsl_drf.filter_backends.ordering.OrderingFilterBackend method*), 202
`get_schema_fields()` (*django_elasticsearch_dsl_drf.filter_backends.search.base.BaseSearchFilterBackend method*), 211
`get_schema_fields()` (*django_elasticsearch_dsl_drf.filter_backends.search.BaseSearchFilterBackend method*), 215
`get_schema_fields()` (*django_elasticsearch_dsl_drf.filter_backends.search.historical.HistoricalSearchFilterBackend method*), 214
`get_schema_fields()` (*django_elasticsearch_dsl_drf.filter_backends.search.SearchFilterBackend method*), 218
`get_search_query_params()` (*django_elasticsearch_dsl_drf.filter_backends.search.base.BaseSearchFilterBackend method*), 211
`get_search_query_params()` (*django_elasticsearch_dsl_drf.filter_backends.search.BaseSearchFilterBackend method*), 215
`get_search_query_params()` (*django_elasticsearch_dsl_drf.filter_backends.search.historical.HistoricalSearchFilterBackend method*), 214
`get_search_query_params()` (*django_elasticsearch_dsl_drf.filter_backends.search.SearchFilterBackend method*), 218
`get_suggester_context()` (*django_elasticsearch_dsl_drf.filter_backends.suggester.native.SuggesterFilterBackend class method*), 226
`get_suggester_context()` (*django_elasticsearch_dsl_drf.filter_backends.suggester.SuggesterFilterBackend class method*), 229
`get_suggester_query_params()` (*django_elasticsearch_dsl_drf.filter_backends.suggester.functional.FunctionalSuggesterFilterBackend method*), 222
`get_suggester_query_params()` (*django_elasticsearch_dsl_drf.filter_backends.suggester.FunctionalSuggesterFilterBackend method*), 233
`get_suggester_query_params()` (*django_elasticsearch_dsl_drf.filter_backends.suggester.native.SuggesterFilterBackend method*), 227
`get_suggester_query_params()` (*django_elasticsearch_dsl_drf.filter_backends.suggester.SuggesterFilterBackend method*), 231
`get_value()` (*django_elasticsearch_dsl_drf.fields.BooleanField method*), 159
`get_value()` (*django_elasticsearch_dsl_drf.fields.CharField method*), 159
`get_value()` (*django_elasticsearch_dsl_drf.fields.common.BooleanFiel method*), 155
`get_value()` (*django_elasticsearch_dsl_drf.fields.common.CharField method*), 155
`get_value()` (*django_elasticsearch_dsl_drf.fields.common.DateField method*), 155
`get_value()` (*django_elasticsearch_dsl_drf.fields.common.FloatField method*), 155
`get_value()` (*django_elasticsearch_dsl_drf.fields.common.IntegerField method*), 156
`get_value()` (*django_elasticsearch_dsl_drf.fields.common.IPAddressFi method*), 156
`get_value()` (*django_elasticsearch_dsl_drf.fields.DateField method*), 159
`get_value()` (*django_elasticsearch_dsl_drf.fields.FloatField method*), 160
`get_value()` (*django_elasticsearch_dsl_drf.fields.IntegerField method*), 160
`get_value()` (*django_elasticsearch_dsl_drf.fields.IPAddressField method*), 161
`get_value()` (*django_elasticsearch_dsl_drf.fields.ListField method*), 161
`get_value()` (*django_elasticsearch_dsl_drf.fields.nested_fields.ListFiel method*), 159
`get_value()` (*django_elasticsearch_dsl_drf.fields.nested_fields.ObjectF method*), 158
`get_value()` (*django_elasticsearch_dsl_drf.fields.ObjectField method*), 161

H

`highlight()` (*django_elasticsearch_dsl_drf.utils.EmptySearch method*), 276
`highlight_param` (*django_elasticsearch_dsl_drf.filter_backends.highli attribute*), 238
`HighlightBackend` (*class in django_elasticsearch_dsl_drf.filter_backends.highlight*), 237

I

`ids_query_param` (*django_elasticsearch_dsl_drf.filter_backends.filteri attribute*), 175
`ids_query_param` (*django_elasticsearch_dsl_drf.filter_backends.filteri attribute*), 190
`IdsFilterBackend` (*class in django_elasticsearch_dsl_drf.filter_backends.filtering*), 189
`IdsFilterBackend` (*class in django_elasticsearch_dsl_drf.filter_backends.filtering.ids*), 174
`ignore` (*django_elasticsearch_dsl_drf.viewsets.BaseDocumentViewSet attribute*), 277

`ignore_fields` (*django_elasticsearch_dsl_drf.serializers.Meta attribute*), 276
`index_aliases` (*django_elasticsearch_dsl_drf.serializers.Meta attribute*), 276
`index_classes` (*django_elasticsearch_dsl_drf.serializers.Meta attribute*), 276
`IntegerField` (*class in django_elasticsearch_dsl_drf.fields*), 160
`IntegerField` (*class in django_elasticsearch_dsl_drf.fields.common*), 155
`IPAddressField` (*class in django_elasticsearch_dsl_drf.fields*), 160
`IPAddressField` (*class in django_elasticsearch_dsl_drf.fields.common*), 156

K

`KeywordField()` (*in module django_elasticsearch_dsl_drf.compat*), 272

L

`label` (*django_elasticsearch_dsl_drf.apps.Config attribute*), 272
`LimitOffsetPagination` (*class in django_elasticsearch_dsl_drf.pagination*), 273
`ListField` (*class in django_elasticsearch_dsl_drf.fields*), 161
`ListField` (*class in django_elasticsearch_dsl_drf.fields.nested_fields*), 158

M

`matching` (*django_elasticsearch_dsl_drf.filter_backends.search.base.BaseSearchFilterBackend attribute*), 211
`matching` (*django_elasticsearch_dsl_drf.filter_backends.search.BaseSearchFilterBackend attribute*), 215
`matching` (*django_elasticsearch_dsl_drf.filter_backends.search.multi_match.MultiMatchSearchFilterBackend attribute*), 214
`matching` (*django_elasticsearch_dsl_drf.filter_backends.search.MultiMatchSearchFilterBackend attribute*), 216
`matching` (*django_elasticsearch_dsl_drf.filter_backends.search.simple_query_string.SimpleQueryStringSearchFilterBackend attribute*), 215
`matching` (*django_elasticsearch_dsl_drf.filter_backends.search.SimpleQueryStringSearchFilterBackend attribute*), 218
`MatchPhrasePrefixQueryBackend` (*class in django_elasticsearch_dsl_drf.filter_backends.search.query_backends*), 208
`MatchPhrasePrefixQueryBackend` (*class in django_elasticsearch_dsl_drf.filter_backends.search.query_backends.match_phrase_prefix*), 204
`MatchPhraseQueryBackend` (*class in django_elasticsearch_dsl_drf.filter_backends.search.query_backe*
208
`MatchPhraseQueryBackend` (*class in django_elasticsearch_dsl_drf.filter_backends.search.query_backe*
203
`MatchQueryBackend` (*class in django_elasticsearch_dsl_drf.filter_backends.search.query_backe*
207
`MatchQueryBackend` (*class in django_elasticsearch_dsl_drf.filter_backends.search.query_backe*
203
`Meta` (*class in django_elasticsearch_dsl_drf.serializers*), 276
`more_like_this()` (*django_elasticsearch_dsl_drf.viewsets.MoreLikeT*
method), 277
`more_like_this()` (*in module django_elasticsearch_dsl_drf.helpers*), 272
`MoreLikeThisMixin` (*class in django_elasticsearch_dsl_drf.viewsets*), 277
`MultiMatchQueryBackend` (*class in django_elasticsearch_dsl_drf.filter_backends.search.query_backe*
208
`MultiMatchQueryBackend` (*class in django_elasticsearch_dsl_drf.filter_backends.search.query_backe*
204
`MultiMatchSearchFilterBackend` (*class in django_elasticsearch_dsl_drf.filter_backends.search*), 216
`MultiMatchSearchFilterBackend` (*class in django_elasticsearch_dsl_drf.filter_backends.search.multi_match*
214

N

`name` (*django_elasticsearch_dsl_drf.apps.Config attribute*), 272
`NestedField` (*class in django_elasticsearch_dsl_drf.fields*), 161
`NestedField` (*class in django_elasticsearch_dsl_drf.fields.nested_fields*), 157
`NestedFilteringFilterBackend` (*class in django_elasticsearch_dsl_drf.filter_backends.filtering*), 190
`NestedFilteringFilterBackend` (*class in django_elasticsearch_dsl_drf.filter_backends.filtering.nested*), 176
`NestedQueryBackend` (*class in django_elasticsearch_dsl_drf.filter_backends.search.query_backe*
209
`NestedQueryBackend` (*class in django_elasticsearch_dsl_drf.filter_backends.search.query_backe*
205

O

obj_to_dict() (*in module django_elasticsearch_dsl_drf.wrappers*), 278
ObjectField (*class in django_elasticsearch_dsl_drf.fields*), 161
ObjectField (*class in django_elasticsearch_dsl_drf.fields.nested_fields*), 157
ordering_param (*django_elasticsearch_dsl_drf.filter_backends.ordering.common.DefaultOrderingFilterBackend attribute*), 195
ordering_param (*django_elasticsearch_dsl_drf.filter_backends.ordering.common.OrderingFilterBackend attribute*), 196
ordering_param (*django_elasticsearch_dsl_drf.filter_backends.ordering.DefaultOrderingFilterBackend attribute*), 199
ordering_param (*django_elasticsearch_dsl_drf.filter_backends.ordering.geo_spatial.GeoSpatialOrderingFilterBackend attribute*), 198
ordering_param (*django_elasticsearch_dsl_drf.filter_backends.ordering.GeoSpatialOrderingFilterBackend attribute*), 201
ordering_param (*django_elasticsearch_dsl_drf.filter_backends.ordering.OrderingFilterBackend attribute*), 202
OrderingFilterBackend (*class in django_elasticsearch_dsl_drf.filter_backends.ordering*), 201
OrderingFilterBackend (*class in django_elasticsearch_dsl_drf.filter_backends.ordering.common*), 195

P

Page (*class in django_elasticsearch_dsl_drf.pagination*), 274
page() (*django_elasticsearch_dsl_drf.pagination.Paginator method*), 274
PageNumberPagination (*class in django_elasticsearch_dsl_drf.pagination*), 274
paginate_queryset() (*django_elasticsearch_dsl_drf.pagination.LimitOffsetPagination method*), 274
paginate_queryset() (*django_elasticsearch_dsl_drf.pagination.PageNumberPagination method*), 274
pagination_class (*django_elasticsearch_dsl_drf.viewsets.BaseDocumentViewSet attribute*), 277
Paginator (*class in django_elasticsearch_dsl_drf.pagination*), 274
PostFilterFilteringFilterBackend (*class in django_elasticsearch_dsl_drf.filter_backends.filtering*), 192
PostFilterFilteringFilterBackend (*class in django_elasticsearch_dsl_drf.filter_backends.filtering.post_filter*), 177
prepare_faceted_search_fields() (*django_elasticsearch_dsl_drf.filter_backends.faceted_search.Fac class method*), 236
prepare_filter_fields() (*django_elasticsearch_dsl_drf.filter_backends.filtering.common.F class method*), 170
prepare_filter_fields() (*django_elasticsearch_dsl_drf.filter_backends.filtering.FilteringF class method*), 185
prepare_filter_fields() (*django_elasticsearch_dsl_drf.filter_backends.filtering.geo_spatia class method*), 174
prepare_filter_fields() (*django_elasticsearch_dsl_drf.filter_backends.filtering.GeoSpatia class method*), 189
prepare_filter_fields() (*django_elasticsearch_dsl_drf.filter_backends.filtering.nested.Nes class method*), 177
prepare_filter_fields() (*django_elasticsearch_dsl_drf.filter_backends.filtering.NestedFilt class method*), 192
prepare_filter_fields() (*django_elasticsearch_dsl_drf.filter_backends.filtering.post_filter class method*), 179
prepare_filter_fields() (*django_elasticsearch_dsl_drf.filter_backends.filtering.PostFilter class method*), 193
prepare_highlight_fields() (*django_elasticsearch_dsl_drf.filter_backends.highlight.Highligh class method*), 238
prepare_suggester_fields() (*django_elasticsearch_dsl_drf.filter_backends.suggester.functiona class method*), 222
prepare_suggester_fields() (*django_elasticsearch_dsl_drf.filter_backends.suggester.Function class method*), 234
prepare_suggester_fields() (*django_elasticsearch_dsl_drf.filter_backends.suggester.native.Su class method*), 227
prepare_suggester_fields() (*django_elasticsearch_dsl_drf.filter_backends.suggester.Suggeste class method*), 231
pytestmark (*django_elasticsearch_dsl_drf.tests.base.BaseRestFramewo attribute*), 240
pytestmark (*django_elasticsearch_dsl_drf.tests.base.BaseTestCase attribute*), 240
pytestmark (*django_elasticsearch_dsl_drf.tests.test_faceted_search.Test attribute*), 241
pytestmark (*django_elasticsearch_dsl_drf.tests.test_filtering_common.T attribute*), 241
pytestmark (*django_elasticsearch_dsl_drf.tests.test_filtering_geo_spatia attribute*), 244
pytestmark (*django_elasticsearch_dsl_drf.tests.test_filtering_global_ag attribute*), 245

pytestmark (*django_elasticsearch_dsl_drf.tests.test_filtering_nested.TestFilteringNested attribute*), 245
pytestmark (*django_elasticsearch_dsl_drf.tests.test_filtering_post_filter.TestFilteringPostFilter attribute*), 247
pytestmark (*django_elasticsearch_dsl_drf.tests.test_functional_suggesters.TestFunctionalSuggesters attribute*), 249
pytestmark (*django_elasticsearch_dsl_drf.tests.test_helpers.TestHelpers attribute*), 250
pytestmark (*django_elasticsearch_dsl_drf.tests.test_highlighting.TestHighlighting attribute*), 250
pytestmark (*django_elasticsearch_dsl_drf.tests.test_more_like_this.TestMoreLikeThis attribute*), 250
pytestmark (*django_elasticsearch_dsl_drf.tests.test_ordering.TestOrdering attribute*), 251
pytestmark (*django_elasticsearch_dsl_drf.tests.test_ordering_geo_spatial.TestOrderingGeoSpatial attribute*), 252
pytestmark (*django_elasticsearch_dsl_drf.tests.test_pagination.TestPagination attribute*), 252
pytestmark (*django_elasticsearch_dsl_drf.tests.test_pip_helpers.TestPipHelpers attribute*), 252
pytestmark (*django_elasticsearch_dsl_drf.tests.test_search.TestSearch attribute*), 253
pytestmark (*django_elasticsearch_dsl_drf.tests.test_search_custom_cache.TestSearchCustomCache attribute*), 253
pytestmark (*django_elasticsearch_dsl_drf.tests.test_search_multi_match_search.TestMultiMatchSearch attribute*), 254
pytestmark (*django_elasticsearch_dsl_drf.tests.test_search_simple_query_string.TestSimpleQueryStringSearch attribute*), 254
pytestmark (*django_elasticsearch_dsl_drf.tests.test_serializers.TestSerializers attribute*), 255
pytestmark (*django_elasticsearch_dsl_drf.tests.test_suggesters.TestContextSuggesters attribute*), 256
pytestmark (*django_elasticsearch_dsl_drf.tests.test_suggesters.TestSuggesters attribute*), 256
pytestmark (*django_elasticsearch_dsl_drf.tests.test_suggesters.TestSuggestersEmptyIndex attribute*), 256
pytestmark (*django_elasticsearch_dsl_drf.tests.test_views.TestViews attribute*), 257
pytestmark (*django_elasticsearch_dsl_drf.tests.test_wrappers.TestWrappers attribute*), 257
pytestmark (*django_elasticsearch_dsl_drf.tests.TestFacetedSearch attribute*), 257
pytestmark (*django_elasticsearch_dsl_drf.tests.TestFilteringCommon attribute*), 258
pytestmark (*django_elasticsearch_dsl_drf.tests.TestFilteringGeoSpatial attribute*), 260
pytestmark (*django_elasticsearch_dsl_drf.tests.TestFilteringGlobalAggregations attribute*), 261
pytestmark (*django_elasticsearch_dsl_drf.tests.TestFilteringNested attribute*), 262
pytestmark (*django_elasticsearch_dsl_drf.tests.TestFilteringPostFilter attribute*), 263
pytestmark (*django_elasticsearch_dsl_drf.tests.TestFunctionalSuggesters attribute*), 266
pytestmark (*django_elasticsearch_dsl_drf.tests.TestHelpers attribute*), 266
pytestmark (*django_elasticsearch_dsl_drf.tests.TestHighlight attribute*), 266
pytestmark (*django_elasticsearch_dsl_drf.tests.TestMultiMatchSearch attribute*), 266
pytestmark (*django_elasticsearch_dsl_drf.tests.TestOrdering attribute*), 268
pytestmark (*django_elasticsearch_dsl_drf.tests.TestOrderingGeoSpatial attribute*), 269
pytestmark (*django_elasticsearch_dsl_drf.tests.TestPagination attribute*), 269
pytestmark (*django_elasticsearch_dsl_drf.tests.TestPipHelpers attribute*), 269
pytestmark (*django_elasticsearch_dsl_drf.tests.TestSearch attribute*), 269
pytestmark (*django_elasticsearch_dsl_drf.tests.TestSerializers attribute*), 270
pytestmark (*django_elasticsearch_dsl_drf.tests.TestSimpleQueryStringS attribute*), 267
pytestmark (*django_elasticsearch_dsl_drf.tests.TestSuggesters attribute*), 270
pytestmark (*django_elasticsearch_dsl_drf.tests.TestViews attribute*), 271
pytestmark (*django_elasticsearch_dsl_drf.tests.TestWrappers attribute*), 271

Q

query_backends (*django_elasticsearch_dsl_drf.filter_backends.search. attribute*), 211
query_backends (*django_elasticsearch_dsl_drf.filter_backends.search. attribute*), 215
query_backends (*django_elasticsearch_dsl_drf.filter_backends.search. attribute*), 212
query_backends (*django_elasticsearch_dsl_drf.filter_backends.search. attribute*), 215
query_backends (*django_elasticsearch_dsl_drf.filter_backends.search. attribute*), 214
query_backends (*django_elasticsearch_dsl_drf.filter_backends.search. attribute*), 216
query_backends (*django_elasticsearch_dsl_drf.filter_backends.search. attribute*), 215
query_backends (*django_elasticsearch_dsl_drf.filter_backends.search. attribute*), 218
query_type (*django_elasticsearch_dsl_drf.filter_backends.search.query_ attribute*), 203
query_type (*django_elasticsearch_dsl_drf.filter_backends.search.query_ attribute*), 204
query_type (*django_elasticsearch_dsl_drf.filter_backends.search.query_ attribute*), 204
query_type (*django_elasticsearch_dsl_drf.filter_backends.search.query_ attribute*), 208
query_type (*django_elasticsearch_dsl_drf.filter_backends.search.query_ attribute*), 208

query_type (*django_elasticsearch_dsl_drf.filter_backends.search.multi_match.MultiMatchSearchFilterBackend* attribute), 207

query_type (*django_elasticsearch_dsl_drf.filter_backends.search.multi_match.MultiMatchQueryBackend* attribute), 205

query_type (*django_elasticsearch_dsl_drf.filter_backends.search.nested.NestedQueryBackend* attribute), 209

query_type (*django_elasticsearch_dsl_drf.filter_backends.search.nested.NestedFilterBackend* attribute), 206

query_type (*django_elasticsearch_dsl_drf.filter_backends.search.post_filter.PostFilterBackend* attribute), 210

query_type (*django_elasticsearch_dsl_drf.filter_backends.search.simple_query_string.SimpleQueryStringQueryBackend* attribute), 207

query_type (*django_elasticsearch_dsl_drf.filter_backends.search.simple_query_string.SimpleQueryStringFilterBackend* attribute), 211

S

search_fields (*django_elasticsearch_dsl_drf.serializers.Meta* attribute), 276

search_param (*django_elasticsearch_dsl_drf.filter_backends.search.base.BaseSearchFilterBackend* attribute), 211

search_param (*django_elasticsearch_dsl_drf.filter_backends.search.BaseSearchFilterBackend* attribute), 215

search_param (*django_elasticsearch_dsl_drf.filter_backends.search.historical.SearchFilterBackend* attribute), 214

search_param (*django_elasticsearch_dsl_drf.filter_backends.search.multi_match.MultiMatchSearchFilterBackend* attribute), 214

search_param (*django_elasticsearch_dsl_drf.filter_backends.search.MultiMatchSearchFilterBackend* attribute), 216

search_param (*django_elasticsearch_dsl_drf.filter_backends.search.SearchFilterBackend* attribute), 218

search_param (*django_elasticsearch_dsl_drf.filter_backends.search.simple_query_string.SimpleQueryStringSearchFilterBackend* attribute), 215

search_param (*django_elasticsearch_dsl_drf.filter_backends.search.SimpleQueryStringSearchFilterBackend* attribute), 218

SearchFilterBackend (*class in django_elasticsearch_dsl_drf.filter_backends.search*), 216

SearchFilterBackend (*class in django_elasticsearch_dsl_drf.filter_backends.search.historical*), 212

serialize_queryset() (*django_elasticsearch_dsl_drf.filter_backends.suggester.functional.FunctionalSuggesterFilterBackend* method), 222

serialize_queryset() (*django_elasticsearch_dsl_drf.filter_backends.suggester.FunctionalSuggesterFilterBackend* method), 234

serializers (*django_elasticsearch_dsl_drf.serializers.Meta* attribute), 276

setUpClass() (*django_elasticsearch_dsl_drf.tests.base.BaseRestFrameworkTestCase* class method), 240

setUpClass() (*django_elasticsearch_dsl_drf.tests.base.BaseTestCase* class method), 240

setUpClass() (*django_elasticsearch_dsl_drf.tests.test_faceted_search.TestFacetedSearch* class method), 241

setUpClass() (*django_elasticsearch_dsl_drf.tests.test_filtering_common.TestFilteringCommon* class method), 241

setUpClass() (*django_elasticsearch_dsl_drf.tests.test_filtering_geo_spatial.TestFilteringGeoSpatial* class method), 244

setUpClass() (*django_elasticsearch_dsl_drf.tests.test_filtering_global_lookups.TestFilteringGlobalLookups* class method), 245

setUpClass() (*django_elasticsearch_dsl_drf.tests.test_filtering_nested.TestFilteringNested* class method), 245

setUpClass() (*django_elasticsearch_dsl_drf.tests.test_filtering_post_filter.TestFilteringPostFilter* class method), 247

setUpClass() (*django_elasticsearch_dsl_drf.tests.test_simple_query_string.TestSimpleQueryStringQueryBackend* class method), 249

setUpClass() (*django_elasticsearch_dsl_drf.tests.test_pip_helpers.TestHelpers* class method), 250

setUpClass() (*django_elasticsearch_dsl_drf.tests.test_highlight.TestHighlight* class method), 250

setUpClass() (*django_elasticsearch_dsl_drf.tests.test_more_like_this.TestMoreLikeThis* class method), 250

setUpClass() (*django_elasticsearch_dsl_drf.tests.test_ordering_common* class method), 251

setUpClass() (*django_elasticsearch_dsl_drf.tests.test_ordering_geo_spatial* class method), 252

setUpClass() (*django_elasticsearch_dsl_drf.tests.test_pagination.TestPagination* class method), 252

setUpClass() (*django_elasticsearch_dsl_drf.tests.test_pip_helpers.TestPipHelpers* class method), 252

setUpClass() (*django_elasticsearch_dsl_drf.tests.test_search.TestSearch* class method), 253

setUpClass() (*django_elasticsearch_dsl_drf.tests.test_search_multi_match* class method), 254

setUpClass() (*django_elasticsearch_dsl_drf.tests.test_search_simple_query_string* class method), 254

setUpClass() (*django_elasticsearch_dsl_drf.tests.test_suggesters.TestCompletionSuggester* class method), 256

setUpClass() (*django_elasticsearch_dsl_drf.tests.test_suggesters.TestSuggesterFilterBackend* class method), 256

setUpClass() (*django_elasticsearch_dsl_drf.tests.test_suggesters.TestSuggesterFilterBackend* class method), 256

setUpClass() (*django_elasticsearch_dsl_drf.tests.test_views.TestViews* class method), 257

setUpClass() (*django_elasticsearch_dsl_drf.tests.test_wrappers.TestWrapper* class method), 257

setUpClass() (*django_elasticsearch_dsl_drf.tests.TestFacetedSearch* class method), 257

setUpClass() (*django_elasticsearch_dsl_drf.tests.TestFilteringCommon* class method), 258

setUpClass() (*django_elasticsearch_dsl_drf.tests.TestFilteringGeoSpatial* class method), 260

setUpClass() (*django_elasticsearch_dsl_drf.tests.TestFilteringGlobalLookups* class method), 261

setUpClass() (*django_elasticsearch_dsl_drf.tests.TestFilteringNested* class method), 262

setUpClass() (*django_elasticsearch_dsl_drf.tests.TestFilteringPostFilter* class method), 263

setUpClass() (*django_elasticsearch_dsl_drf.tests.TestFunctionalSuggesters class method*), 266
setUpClass() (*django_elasticsearch_dsl_drf.tests.TestHelpers class method*), 266
setUpClass() (*django_elasticsearch_dsl_drf.tests.TestHighlight class method*), 266
setUpClass() (*django_elasticsearch_dsl_drf.tests.TestMultiMatchSearch class method*), 266
setUpClass() (*django_elasticsearch_dsl_drf.tests.TestOrdering class method*), 268
setUpClass() (*django_elasticsearch_dsl_drf.tests.TestOrderingGeoSpatial class method*), 269
setUpClass() (*django_elasticsearch_dsl_drf.tests.TestPagination class method*), 269
setUpClass() (*django_elasticsearch_dsl_drf.tests.TestPipHelpers class method*), 269
setUpClass() (*django_elasticsearch_dsl_drf.tests.TestSearch class method*), 269
setUpClass() (*django_elasticsearch_dsl_drf.tests.TestSimpleQueryStringSearch class method*), 267
setUpClass() (*django_elasticsearch_dsl_drf.tests.TestSuggesters class method*), 270
setUpClass() (*django_elasticsearch_dsl_drf.tests.TestViews class method*), 271
setUpClass() (*django_elasticsearch_dsl_drf.tests.TestWrappers class method*), 271
SimpleQueryStringQueryBackend (*class in django_elasticsearch_dsl_drf.filter_backends.search.query_backends*), 210
SimpleQueryStringQueryBackend (*class in django_elasticsearch_dsl_drf.filter_backends.search.query_backends.simple_query_string*), 206
SimpleQueryStringSearchFilterBackend (*class in django_elasticsearch_dsl_drf.filter_backends.search*), 218
SimpleQueryStringSearchFilterBackend (*class in django_elasticsearch_dsl_drf.filter_backends.search.simple_query_string*), 214
sort() (*django_elasticsearch_dsl_drf.utils.EmptySearch method*), 276
sort_by_list() (*in module django_elasticsearch_dsl_drf.helpers*), 273
split_lookup_complex_multiple_value() (*django_elasticsearch_dsl_drf.filter_backends.mixins.FilterBackendMixin class method*), 239
split_lookup_complex_value() (*django_elasticsearch_dsl_drf.filter_backends.mixins.FilterBackendMixin class method*), 239
split_lookup_filter() (*django_elasticsearch_dsl_drf.filter_backends.mixins.FilterBackendMixin class method*), 239
split_lookup_name() (*django_elasticsearch_dsl_drf.filter_backends.mixins.FilterBackendMixin class method*), 239
SuggesterFilterBackend (*in module django_elasticsearch_dsl_drf.compat*), 272
suggest() (*django_elasticsearch_dsl_drf.viewsets.SuggestMixin method*), 277
SuggesterFilterBackend (*class in django_elasticsearch_dsl_drf.filter_backends.suggester*), 227
SuggesterFilterBackend (*class in django_elasticsearch_dsl_drf.filter_backends.suggester.native*), 224
SuggesterSpatial (*class in django_elasticsearch_dsl_drf.viewsets*), 277

T

test_address_default_nested_order_by() (*django_elasticsearch_dsl_drf.tests.test_ordering_common.TestO method*), 251
test_address_default_nested_order_by() (*django_elasticsearch_dsl_drf.tests.TestOrdering method*), 268
test_address_default_order_by() (*django_elasticsearch_dsl_drf.tests.test_ordering_common.TestO method*), 251
test_address_default_order_by() (*django_elasticsearch_dsl_drf.tests.TestOrdering method*), 268
test_address_order_by_nested_field_continent_ascend (*django_elasticsearch_dsl_drf.tests.test_ordering_common.TestO method*), 251
test_address_order_by_nested_field_continent_ascend (*django_elasticsearch_dsl_drf.tests.TestOrdering method*), 268
test_address_order_by_nested_field_continent_descen (*django_elasticsearch_dsl_drf.tests.test_ordering_common.TestO method*), 251
test_address_order_by_nested_field_continent_descen (*django_elasticsearch_dsl_drf.tests.TestOrdering method*), 268
test_address_order_by_nested_field_country_ascendin (*django_elasticsearch_dsl_drf.tests.test_ordering_common.TestO method*), 251
test_address_order_by_nested_field_country_ascendin (*django_elasticsearch_dsl_drf.tests.TestOrdering method*), 268
test_address_order_by_nested_field_country_descendi (*django_elasticsearch_dsl_drf.tests.test_ordering_common.TestO method*), 251
test_address_order_by_nested_field_country_descendi (*django_elasticsearch_dsl_drf.tests.TestOrdering method*), 268
test_author_default_order_by() (*django_elasticsearch_dsl_drf.tests.test_ordering_common.TestO method*), 251
test_author_default_order_by()

(*django_elasticsearch_dsl_drf.tests.TestOrdering method*), 268
test_author_order_by_field_id_ascending() (*django_elasticsearch_dsl_drf.tests.test_ordering_common.TestOrdering method*), 251
test_author_order_by_field_id_ascending() (*django_elasticsearch_dsl_drf.tests.TestOrdering method*), 268
test_author_order_by_field_id_descending() (*django_elasticsearch_dsl_drf.tests.test_ordering_common.TestOrdering method*), 251
test_author_order_by_field_id_descending() (*django_elasticsearch_dsl_drf.tests.TestOrdering method*), 268
test_author_order_by_field_name_ascending() (*django_elasticsearch_dsl_drf.tests.test_ordering_common.TestOrdering method*), 251
test_author_order_by_field_name_ascending() (*django_elasticsearch_dsl_drf.tests.TestOrdering method*), 268
test_author_order_by_field_name_descending() (*django_elasticsearch_dsl_drf.tests.test_ordering_common.TestOrdering method*), 251
test_author_order_by_field_name_descending() (*django_elasticsearch_dsl_drf.tests.TestOrdering method*), 268
test_book_default_order_by() (*django_elasticsearch_dsl_drf.tests.test_ordering_common.TestOrdering method*), 251
test_book_default_order_by() (*django_elasticsearch_dsl_drf.tests.TestOrdering method*), 268
test_book_order_by_field_id_ascending() (*django_elasticsearch_dsl_drf.tests.test_ordering_common.TestOrdering method*), 251
test_book_order_by_field_id_ascending() (*django_elasticsearch_dsl_drf.tests.TestOrdering method*), 268
test_book_order_by_field_id_descending() (*django_elasticsearch_dsl_drf.tests.test_ordering_common.TestOrdering method*), 251
test_book_order_by_field_id_descending() (*django_elasticsearch_dsl_drf.tests.TestOrdering method*), 268
test_book_order_by_field_title_ascending() (*django_elasticsearch_dsl_drf.tests.test_ordering_common.TestOrdering method*), 251
test_book_order_by_field_title_ascending() (*django_elasticsearch_dsl_drf.tests.TestOrdering method*), 268
test_book_order_by_field_title_descending() (*django_elasticsearch_dsl_drf.tests.test_ordering_common.TestOrdering method*), 251
test_book_order_by_field_title_descending() (*django_elasticsearch_dsl_drf.tests.TestOrdering method*), 268
test_book_order_by_non_existent_field() (*django_elasticsearch_dsl_drf.tests.test_ordering_common.TestOrdering method*), 251
test_book_order_by_non_existent_field() (*django_elasticsearch_dsl_drf.tests.TestOrdering method*), 268
test_check_if_installed() (*django_elasticsearch_dsl_drf.tests.test_pip_helpers.TestPipHelpers method*), 252
test_check_if_installed() (*django_elasticsearch_dsl_drf.tests.TestPipHelpers method*), 269
test_compound_search_boost_by_field() (*django_elasticsearch_dsl_drf.tests.test_search.TestSearch method*), 253
test_compound_search_boost_by_field() (*django_elasticsearch_dsl_drf.tests.TestSearch method*), 269
test_compound_search_by_field() (*django_elasticsearch_dsl_drf.tests.test_search.TestSearch method*), 253
test_compound_search_by_field() (*django_elasticsearch_dsl_drf.tests.TestSearch method*), 269
test_compound_search_by_field_multi_terms() (*django_elasticsearch_dsl_drf.tests.test_search.TestSearch method*), 253
test_compound_search_by_field_multi_terms() (*django_elasticsearch_dsl_drf.tests.TestSearch method*), 270
test_compound_search_by_nested_field() (*django_elasticsearch_dsl_drf.tests.test_search.TestSearch method*), 253
test_compound_search_by_nested_field() (*django_elasticsearch_dsl_drf.tests.TestSearch method*), 270
test_default_filter_lookup() (*django_elasticsearch_dsl_drf.tests.test_filtering_common.TestFilteringCommon method*), 241
test_default_filter_lookup() (*django_elasticsearch_dsl_drf.tests.TestFilteringCommon method*), 258
test_detail_view() (*django_elasticsearch_dsl_drf.tests.test_views.TestViews method*), 257
test_detail_view() (*django_elasticsearch_dsl_drf.tests.TestViews method*), 271
test_detail_view_with_custom_lookup() (*django_elasticsearch_dsl_drf.tests.test_views.TestViews method*), 257
test_detail_view_with_custom_lookup()

(*django_elasticsearch_dsl_drf.tests.TestViews method*), 271
test_dict_to_obj() (*django_elasticsearch_dsl_drf.tests.test_wrappers.TestWrappers method*), 257
test_dict_to_obj() (*django_elasticsearch_dsl_drf.tests.TestWrappers method*), 271
test_field_filter_contains() (*django_elasticsearch_dsl_drf.tests.test_filtering_common.TestFilteringCommon method*), 241
test_field_filter_contains() (*django_elasticsearch_dsl_drf.tests.test_filtering_nested.TestFilteringNested method*), 245
test_field_filter_contains() (*django_elasticsearch_dsl_drf.tests.test_filtering_post_filter.TestFilteringPostFilter method*), 247
test_field_filter_contains() (*django_elasticsearch_dsl_drf.tests.TestFilteringCommon method*), 258
test_field_filter_contains() (*django_elasticsearch_dsl_drf.tests.TestFilteringNested method*), 262
test_field_filter_contains() (*django_elasticsearch_dsl_drf.tests.TestFilteringPostFilter method*), 263
test_field_filter_endswith() (*django_elasticsearch_dsl_drf.tests.test_filtering_common.TestFilteringCommon method*), 241
test_field_filter_endswith() (*django_elasticsearch_dsl_drf.tests.test_filtering_nested.TestFilteringNested method*), 245
test_field_filter_endswith() (*django_elasticsearch_dsl_drf.tests.test_filtering_post_filter.TestFilteringPostFilter method*), 247
test_field_filter_endswith() (*django_elasticsearch_dsl_drf.tests.TestFilteringCommon method*), 258
test_field_filter_endswith() (*django_elasticsearch_dsl_drf.tests.TestFilteringNested method*), 262
test_field_filter_endswith() (*django_elasticsearch_dsl_drf.tests.TestFilteringPostFilter method*), 263
test_field_filter_exclude() (*django_elasticsearch_dsl_drf.tests.test_filtering_common.TestFilteringCommon method*), 241
test_field_filter_exclude() (*django_elasticsearch_dsl_drf.tests.test_filtering_nested.TestFilteringNested method*), 245
test_field_filter_exclude() (*django_elasticsearch_dsl_drf.tests.test_filtering_post_filter.TestFilteringPostFilter method*), 247
test_field_filter_exclude() (*django_elasticsearch_dsl_drf.tests.TestFilteringCommon method*), 258
test_field_filter_exclude() (*django_elasticsearch_dsl_drf.tests.TestFilteringNested method*), 262
test_field_filter_exclude() (*django_elasticsearch_dsl_drf.tests.TestFilteringPostFilter method*), 263
test_field_filter_exists_false() (*django_elasticsearch_dsl_drf.tests.test_filtering_common.TestFilteringCommon method*), 241
test_field_filter_exists_false() (*django_elasticsearch_dsl_drf.tests.test_filtering_nested.TestFilteringNested method*), 245
test_field_filter_exists_false() (*django_elasticsearch_dsl_drf.tests.test_filtering_post_filter.TestFilteringPostFilter method*), 247
test_field_filter_exists_false() (*django_elasticsearch_dsl_drf.tests.TestFilteringCommon method*), 258
test_field_filter_exists_false() (*django_elasticsearch_dsl_drf.tests.TestFilteringNested method*), 262
test_field_filter_exists_false() (*django_elasticsearch_dsl_drf.tests.TestFilteringPostFilter method*), 263
test_field_filter_exists_true() (*django_elasticsearch_dsl_drf.tests.test_filtering_common.TestFilteringCommon method*), 241
test_field_filter_exists_true() (*django_elasticsearch_dsl_drf.tests.test_filtering_nested.TestFilteringNested method*), 246
test_field_filter_exists_true() (*django_elasticsearch_dsl_drf.tests.test_filtering_post_filter.TestFilteringPostFilter method*), 247
test_field_filter_exists_true() (*django_elasticsearch_dsl_drf.tests.TestFilteringCommon method*), 258
test_field_filter_exists_true() (*django_elasticsearch_dsl_drf.tests.TestFilteringNested method*), 262
test_field_filter_exists_true() (*django_elasticsearch_dsl_drf.tests.TestFilteringPostFilter method*), 263
test_field_filter_geo_bounding_box() (*django_elasticsearch_dsl_drf.tests.test_filtering_geo_spatial.TestFilteringGeoSpatial method*), 244
test_field_filter_geo_bounding_box() (*django_elasticsearch_dsl_drf.tests.TestFilteringGeoSpatial method*), 260
test_field_filter_geo_bounding_box_fail_test() (*django_elasticsearch_dsl_drf.tests.test_filtering_geo_spatial.TestFilteringGeoSpatial method*), 244
test_field_filter_geo_bounding_box_fail_test()

(*django_elasticsearch_dsl_drf.tests.TestFilteringGeoSpatial*
method), 260
test_field_filter_geo_distance()
(*django_elasticsearch_dsl_drf.tests.test_filtering_geo_spatial*
method), 244
test_field_filter_geo_distance()
(*django_elasticsearch_dsl_drf.tests.test_ordering_geo_spatial*
method), 252
test_field_filter_geo_distance()
(*django_elasticsearch_dsl_drf.tests.TestFilteringGeoSpatial*
method), 261
test_field_filter_geo_distance()
(*django_elasticsearch_dsl_drf.tests.TestOrderingGeoSpatial*
method), 269
test_field_filter_geo_distance_distance_type_field()
(*django_elasticsearch_dsl_drf.tests.test_filtering_geo_spatial*
method), 244
test_field_filter_geo_distance_distance_type_field()
(*django_elasticsearch_dsl_drf.tests.TestFilteringGeoSpatial*
method), 261
test_field_filter_geo_distance_not_enough_args()
(*django_elasticsearch_dsl_drf.tests.test_filtering_geo_spatial*
method), 244
test_field_filter_geo_distance_not_enough_args()
(*django_elasticsearch_dsl_drf.tests.TestFilteringGeoSpatial*
method), 261
test_field_filter_geo_polygon()
(*django_elasticsearch_dsl_drf.tests.test_filtering_geo_spatial*
method), 244
test_field_filter_geo_polygon()
(*django_elasticsearch_dsl_drf.tests.TestFilteringGeoSpatial*
method), 261
test_field_filter_geo_polygon_fail_test()
(*django_elasticsearch_dsl_drf.tests.test_filtering_geo_spatial*
method), 244
test_field_filter_geo_polygon_fail_test()
(*django_elasticsearch_dsl_drf.tests.TestFilteringGeoSpatial*
method), 261
test_field_filter_geo_polygon_string_options()
(*django_elasticsearch_dsl_drf.tests.test_filtering_geo_spatial*
method), 244
test_field_filter_geo_polygon_string_options()
(*django_elasticsearch_dsl_drf.tests.TestFilteringGeoSpatial*
method), 261
test_field_filter_geo_polygon_string_options_fail_test()
(*django_elasticsearch_dsl_drf.tests.test_filtering_geo_spatial*
method), 244
test_field_filter_geo_polygon_string_options_fail_test()
(*django_elasticsearch_dsl_drf.tests.TestFilteringGeoSpatial*
method), 261
test_field_filter_gt()
(*django_elasticsearch_dsl_drf.tests.test_filtering_common.TestFilteringCommon*
method), 242
test_field_filter_gt()
(*django_elasticsearch_dsl_drf.tests.TestFilteringGeoSpatial*
method), 247
test_field_filter_gt()
(*django_elasticsearch_dsl_drf.tests.TestFilteringCommon*
method), 258
test_field_filter_gt()
(*django_elasticsearch_dsl_drf.tests.TestFilteringPostFilter*
method), 264
test_field_filter_gt_with_boost()
(*django_elasticsearch_dsl_drf.tests.test_filtering_common.TestFil*
method), 242
test_field_filter_gt_with_boost()
(*django_elasticsearch_dsl_drf.tests.test_filtering_post_filter.TestF*
method), 247
test_field_filter_gt_with_boost()
(*django_elasticsearch_dsl_drf.tests.TestFilteringCommon*
method), 258
test_field_filter_gt_with_boost()
(*django_elasticsearch_dsl_drf.tests.TestFilteringPostFilter*
method), 264
test_field_filter_gte()
(*django_elasticsearch_dsl_drf.tests.test_filtering_common.TestFil*
method), 242
test_field_filter_gte()
(*django_elasticsearch_dsl_drf.tests.test_filtering_post_filter.TestF*
method), 247
test_field_filter_gte()
(*django_elasticsearch_dsl_drf.tests.TestFilteringCommon*
method), 258
test_field_filter_gte()
(*django_elasticsearch_dsl_drf.tests.TestFilteringPostFilter*
method), 264
test_field_filter_in()
(*django_elasticsearch_dsl_drf.tests.test_filtering_common.TestFil*
method), 242
test_field_filter_in()
(*django_elasticsearch_dsl_drf.tests.test_filtering_nested.TestFilte*
method), 246
test_field_filter_in()
(*django_elasticsearch_dsl_drf.tests.test_filtering_post_filter.TestF*
method), 248
test_field_filter_in()
(*django_elasticsearch_dsl_drf.tests.TestFilteringCommon*
method), 259
test_field_filter_in()
(*django_elasticsearch_dsl_drf.tests.TestFilteringNested*
method), 262
test_field_filter_in()
(*django_elasticsearch_dsl_drf.tests.TestFilteringPostFilter*
method), 264
test_field_filter_isnull_false()
(*django_elasticsearch_dsl_drf.tests.test_filtering_common.TestFil*
method), 242
test_field_filter_isnull_false()

(*django_elasticsearch_dsl_drf.tests.test_filtering_post_filter.TestFilteringPostFilter* *method*), 248
`test_field_filter_isnull_false()` (*django_elasticsearch_dsl_drf.tests.TestFilteringCommon* *method*), 259
`test_field_filter_isnull_false()` (*django_elasticsearch_dsl_drf.tests.TestFilteringPostFilter* *method*), 264
`test_field_filter_isnull_true()` (*django_elasticsearch_dsl_drf.tests.test_filtering_common.TestFilteringCommon* *method*), 242
`test_field_filter_isnull_true()` (*django_elasticsearch_dsl_drf.tests.test_filtering_post_filter.TestFilteringPostFilter* *method*), 248
`test_field_filter_isnull_true()` (*django_elasticsearch_dsl_drf.tests.TestFilteringCommon* *method*), 259
`test_field_filter_isnull_true()` (*django_elasticsearch_dsl_drf.tests.TestFilteringPostFilter* *method*), 264
`test_field_filter_lt()` (*django_elasticsearch_dsl_drf.tests.test_filtering_common.TestFilteringCommon* *method*), 242
`test_field_filter_lt()` (*django_elasticsearch_dsl_drf.tests.test_filtering_post_filter.TestFilteringPostFilter* *method*), 248
`test_field_filter_lt()` (*django_elasticsearch_dsl_drf.tests.TestFilteringCommon* *method*), 259
`test_field_filter_lt()` (*django_elasticsearch_dsl_drf.tests.TestFilteringPostFilter* *method*), 264
`test_field_filter_lt_with_boost()` (*django_elasticsearch_dsl_drf.tests.test_filtering_common.TestFilteringCommon* *method*), 242
`test_field_filter_lt_with_boost()` (*django_elasticsearch_dsl_drf.tests.test_filtering_post_filter.TestFilteringPostFilter* *method*), 248
`test_field_filter_lt_with_boost()` (*django_elasticsearch_dsl_drf.tests.TestFilteringCommon* *method*), 259
`test_field_filter_lt_with_boost()` (*django_elasticsearch_dsl_drf.tests.TestFilteringPostFilter* *method*), 264
`test_field_filter_lte()` (*django_elasticsearch_dsl_drf.tests.test_filtering_common.TestFilteringCommon* *method*), 242
`test_field_filter_lte()` (*django_elasticsearch_dsl_drf.tests.test_filtering_post_filter.TestFilteringPostFilter* *method*), 248
`test_field_filter_lte()` (*django_elasticsearch_dsl_drf.tests.TestFilteringCommon* *method*), 259
`test_field_filter_lte()` (*django_elasticsearch_dsl_drf.tests.TestFilteringPostFilter* *method*), 264
`test_field_filter_prefix()` (*django_elasticsearch_dsl_drf.tests.test_filtering_common.TestFilteringCommon* *method*), 243
`test_field_filter_prefix()` (*django_elasticsearch_dsl_drf.tests.test_filtering_nested.TestFilteringNested* *method*), 246
`test_field_filter_prefix()` (*django_elasticsearch_dsl_drf.tests.test_filtering_post_filter.TestFilteringPostFilter* *method*), 248
`test_field_filter_prefix()` (*django_elasticsearch_dsl_drf.tests.TestFilteringCommon* *method*), 259
`test_field_filter_prefix()` (*django_elasticsearch_dsl_drf.tests.TestFilteringNested* *method*), 262
`test_field_filter_prefix()` (*django_elasticsearch_dsl_drf.tests.TestFilteringPostFilter* *method*), 265
`test_field_filter_range()` (*django_elasticsearch_dsl_drf.tests.test_filtering_common.TestFilteringCommon* *method*), 243
`test_field_filter_range()` (*django_elasticsearch_dsl_drf.tests.test_filtering_nested.TestFilteringNested* *method*), 246
`test_field_filter_range()` (*django_elasticsearch_dsl_drf.tests.test_filtering_post_filter.TestFilteringPostFilter* *method*), 248
`test_field_filter_range()` (*django_elasticsearch_dsl_drf.tests.TestFilteringCommon* *method*), 259
`test_field_filter_range()` (*django_elasticsearch_dsl_drf.tests.TestFilteringNested* *method*), 262
`test_field_filter_range()` (*django_elasticsearch_dsl_drf.tests.TestFilteringPostFilter* *method*), 265
`test_field_filter_range_with_boost()` (*django_elasticsearch_dsl_drf.tests.test_filtering_common.TestFilteringCommon* *method*), 243
`test_field_filter_range_with_boost()` (*django_elasticsearch_dsl_drf.tests.test_filtering_nested.TestFilteringNested* *method*), 246
`test_field_filter_range_with_boost()` (*django_elasticsearch_dsl_drf.tests.test_filtering_post_filter.TestFilteringPostFilter* *method*), 248
`test_field_filter_range_with_boost()` (*django_elasticsearch_dsl_drf.tests.TestFilteringCommon* *method*), 259
`test_field_filter_range_with_boost()` (*django_elasticsearch_dsl_drf.tests.TestFilteringNested* *method*), 262
`test_field_filter_range_with_boost()`

(*django_elasticsearch_dsl_drf.tests.TestFilteringPostFilter method*), 265
test_field_filter_term() (*django_elasticsearch_dsl_drf.tests.test_filtering_common.TestFilteringCommon method*), 243
test_field_filter_term() (*django_elasticsearch_dsl_drf.tests.test_filtering_nested.TestFilteringNested method*), 246
test_field_filter_term() (*django_elasticsearch_dsl_drf.tests.test_filtering_post_filter.TestFilteringPostFilter method*), 248
test_field_filter_term() (*django_elasticsearch_dsl_drf.tests.TestFilteringCommon method*), 260
test_field_filter_term() (*django_elasticsearch_dsl_drf.tests.TestFilteringNested method*), 262
test_field_filter_term() (*django_elasticsearch_dsl_drf.tests.TestFilteringPostFilter method*), 265
test_field_filter_term_explicit() (*django_elasticsearch_dsl_drf.tests.test_filtering_common.TestFilteringCommon method*), 243
test_field_filter_term_explicit() (*django_elasticsearch_dsl_drf.tests.test_filtering_nested.TestFilteringNested method*), 246
test_field_filter_term_explicit() (*django_elasticsearch_dsl_drf.tests.test_filtering_post_filter.TestFilteringPostFilter method*), 249
test_field_filter_term_explicit() (*django_elasticsearch_dsl_drf.tests.TestFilteringCommon method*), 260
test_field_filter_term_explicit() (*django_elasticsearch_dsl_drf.tests.TestFilteringNested method*), 262
test_field_filter_term_explicit() (*django_elasticsearch_dsl_drf.tests.TestFilteringPostFilter method*), 265
test_field_filter_terms_list() (*django_elasticsearch_dsl_drf.tests.test_filtering_common.TestFilteringCommon method*), 243
test_field_filter_terms_list() (*django_elasticsearch_dsl_drf.tests.test_filtering_nested.TestFilteringNested method*), 246
test_field_filter_terms_list() (*django_elasticsearch_dsl_drf.tests.test_filtering_post_filter.TestFilteringPostFilter method*), 249
test_field_filter_terms_list() (*django_elasticsearch_dsl_drf.tests.TestFilteringCommon method*), 260
test_field_filter_terms_list() (*django_elasticsearch_dsl_drf.tests.TestFilteringNested method*), 263
test_field_filter_terms_list() (*django_elasticsearch_dsl_drf.tests.TestFilteringPostFilter method*), 265
test_field_filter_terms_string() (*django_elasticsearch_dsl_drf.tests.test_filtering_common.TestFilteringCommon method*), 243
test_field_filter_terms_string() (*django_elasticsearch_dsl_drf.tests.test_filtering_nested.TestFilteringNested method*), 246
test_field_filter_terms_string() (*django_elasticsearch_dsl_drf.tests.test_filtering_post_filter.TestFilteringPostFilter method*), 249
test_field_filter_terms_string() (*django_elasticsearch_dsl_drf.tests.TestFilteringCommon method*), 260
test_field_filter_terms_string() (*django_elasticsearch_dsl_drf.tests.TestFilteringNested method*), 263
test_field_filter_terms_string() (*django_elasticsearch_dsl_drf.tests.TestFilteringPostFilter method*), 265
test_field_filter_wildcard() (*django_elasticsearch_dsl_drf.tests.test_filtering_common.TestFilteringCommon method*), 243
test_field_filter_wildcard() (*django_elasticsearch_dsl_drf.tests.test_filtering_nested.TestFilteringNested method*), 246
test_field_filter_wildcard() (*django_elasticsearch_dsl_drf.tests.test_filtering_post_filter.TestFilteringPostFilter method*), 249
test_field_filter_wildcard() (*django_elasticsearch_dsl_drf.tests.TestFilteringCommon method*), 260
test_field_filter_wildcard() (*django_elasticsearch_dsl_drf.tests.TestFilteringNested method*), 263
test_field_filter_wildcard() (*django_elasticsearch_dsl_drf.tests.TestFilteringPostFilter method*), 265
test_filter_by_field() (*django_elasticsearch_dsl_drf.tests.test_helpers.TestHelpers method*), 250
test_filter_by_field() (*django_elasticsearch_dsl_drf.tests.TestHelpers method*), 266
test_get_installed_packages() (*django_elasticsearch_dsl_drf.tests.test_pip_helpers.TestPipHelpers method*), 253
test_get_installed_packages() (*django_elasticsearch_dsl_drf.tests.TestPipHelpers method*), 269
test_get_installed_packages_with_versions() (*django_elasticsearch_dsl_drf.tests.test_pip_helpers.TestPipHelpers method*), 253
test_get_installed_packages_with_versions()

(*django_elasticsearch_dsl_drf.tests.TestPipHelpers method*), 269
test_ids_empty_filter() (*django_elasticsearch_dsl_drf.tests.test_filtering_common.TestFilteringCommon method*), 243
test_ids_empty_filter() (*django_elasticsearch_dsl_drf.tests.TestFilteringCommon method*), 260
test_ids_filter() (*django_elasticsearch_dsl_drf.tests.test_filtering_common.TestFilteringCommon method*), 243
test_ids_filter() (*django_elasticsearch_dsl_drf.tests.test_filtering_post_filter.TestFilteringPostFilter method*), 249
test_ids_filter() (*django_elasticsearch_dsl_drf.tests.TestFilteringCommon method*), 260
test_ids_filter() (*django_elasticsearch_dsl_drf.tests.TestFilteringPostFilter method*), 265
test_list_results_with_facets() (*django_elasticsearch_dsl_drf.tests.test_faceted_search.TestFacetedSearch method*), 241
test_list_results_with_facets() (*django_elasticsearch_dsl_drf.tests.test_filtering_global_aggregations.TestFilteringGlobalAggregations method*), 245
test_list_results_with_facets() (*django_elasticsearch_dsl_drf.tests.test_filtering_post_filter.TestFilteringPostFilter method*), 249
test_list_results_with_facets() (*django_elasticsearch_dsl_drf.tests.TestFacetedSearch method*), 257
test_list_results_with_facets() (*django_elasticsearch_dsl_drf.tests.TestFilteringGlobalAggregations method*), 261
test_list_results_with_facets() (*django_elasticsearch_dsl_drf.tests.TestFilteringPostFilter method*), 265
test_list_results_with_highlights() (*django_elasticsearch_dsl_drf.tests.test_highlight.TestHighlight method*), 250
test_list_results_with_highlights() (*django_elasticsearch_dsl_drf.tests.TestHighlight method*), 266
test_listing_view() (*django_elasticsearch_dsl_drf.tests.test_views.TestViews method*), 257
test_listing_view() (*django_elasticsearch_dsl_drf.tests.TestViews method*), 271
test_more_like_this() (*django_elasticsearch_dsl_drf.tests.test_more_like_this.TestMoreLikeThis method*), 250
test_nested_field_filter_term() (*django_elasticsearch_dsl_drf.tests.test_filtering_common.TestFil method*), 243
test_nested_field_filter_term() (*django_elasticsearch_dsl_drf.tests.TestFilteringCommon method*), 260
test_nested_fields_suggesters_completion() (*django_elasticsearch_dsl_drf.tests.test_suggesters.TestSuggester method*), 256
test_nested_fields_suggesters_completion() (*django_elasticsearch_dsl_drf.tests.TestSuggesters method*), 270
test_obj_to_dict() (*django_elasticsearch_dsl_drf.tests.test_wrappers.TestWrappers method*), 257
test_obj_to_dict() (*django_elasticsearch_dsl_drf.tests.TestWrappers method*), 271
test_pagination() (*django_elasticsearch_dsl_drf.tests.test_pagination.TestPaginatio method*), 252
test_pagination() (*django_elasticsearch_dsl_drf.tests.TestPagination method*), 269
test_schema_field_not_required() (*django_elasticsearch_dsl_drf.tests.test_filtering_common.TestFil method*), 243
test_schema_field_not_required() (*django_elasticsearch_dsl_drf.tests.test_filtering_nested.TestFilte method*), 246
test_schema_field_not_required() (*django_elasticsearch_dsl_drf.tests.test_filtering_post_filter.TestF method*), 249
test_schema_field_not_required() (*django_elasticsearch_dsl_drf.tests.test_ordering_common.TestO method*), 252
test_schema_field_not_required() (*django_elasticsearch_dsl_drf.tests.test_search.TestSearch method*), 253
test_schema_field_not_required() (*django_elasticsearch_dsl_drf.tests.test_search_multi_match.Test method*), 254
test_schema_field_not_required() (*django_elasticsearch_dsl_drf.tests.test_search_simple_query_str method*), 254
test_schema_field_not_required() (*django_elasticsearch_dsl_drf.tests.TestFilteringCommon method*), 260
test_schema_field_not_required() (*django_elasticsearch_dsl_drf.tests.TestFilteringNested method*), 263
test_schema_field_not_required() (*django_elasticsearch_dsl_drf.tests.TestFilteringPostFilter method*), 265
test_schema_field_not_required()

(*django_elasticsearch_dsl_drf.tests.TestMultiMatchSearch method*), 266
test_schema_field_not_required() (*django_elasticsearch_dsl_drf.tests.TestOrdering method*), 268
test_schema_field_not_required() (*django_elasticsearch_dsl_drf.tests.TestSearch method*), 270
test_schema_field_not_required() (*django_elasticsearch_dsl_drf.tests.TestSimpleQueryStringSearch method*), 267
test_schema_fields_with_filter_fields_list() (*django_elasticsearch_dsl_drf.tests.test_filtering_common.TestFilteringCommon method*), 243
test_schema_fields_with_filter_fields_list() (*django_elasticsearch_dsl_drf.tests.test_filtering_nested.TestFilteringNested method*), 246
test_schema_fields_with_filter_fields_list() (*django_elasticsearch_dsl_drf.tests.test_filtering_post_filter.TestFilteringPostFilter method*), 249
test_schema_fields_with_filter_fields_list() (*django_elasticsearch_dsl_drf.tests.test_ordering_common.TestOrdering method*), 252
test_schema_fields_with_filter_fields_list() (*django_elasticsearch_dsl_drf.tests.test_search.TestSearch method*), 253
test_schema_fields_with_filter_fields_list() (*django_elasticsearch_dsl_drf.tests.test_search_multi_match.TestMultiMatchSearch method*), 254
test_schema_fields_with_filter_fields_list() (*django_elasticsearch_dsl_drf.tests.test_search_simple_query_string.TestSimpleQueryStringSearch method*), 254
test_schema_fields_with_filter_fields_list() (*django_elasticsearch_dsl_drf.tests.TestFilteringCommon method*), 260
test_schema_fields_with_filter_fields_list() (*django_elasticsearch_dsl_drf.tests.TestFilteringNested method*), 263
test_schema_fields_with_filter_fields_list() (*django_elasticsearch_dsl_drf.tests.TestFilteringPostFilter method*), 265
test_schema_fields_with_filter_fields_list() (*django_elasticsearch_dsl_drf.tests.TestMultiMatchSearch method*), 266
test_schema_fields_with_filter_fields_list() (*django_elasticsearch_dsl_drf.tests.TestOrdering method*), 268
test_schema_fields_with_filter_fields_list() (*django_elasticsearch_dsl_drf.tests.TestSearch method*), 270
test_schema_fields_with_filter_fields_list() (*django_elasticsearch_dsl_drf.tests.TestSimpleQueryStringSearch method*), 267
test_search() (*django_elasticsearch_dsl_drf.tests.test_search_multi_match.TestMultiMatchSearch method*), 254
test_search() (*django_elasticsearch_dsl_drf.tests.TestMultiMatchSearch method*), 266
test_search_any_word_in_indexed_fields() (*django_elasticsearch_dsl_drf.tests.test_search.TestSearchCustom method*), 253
test_search_boost() (*django_elasticsearch_dsl_drf.tests.test_search.TestSearch method*), 253
test_search_boost() (*django_elasticsearch_dsl_drf.tests.test_search_multi_match.TestMultiMatchSearch method*), 254
test_search_boost() (*django_elasticsearch_dsl_drf.tests.TestMultiMatchSearch method*), 266
test_search_boost() (*django_elasticsearch_dsl_drf.tests.TestSearch method*), 270
test_search_boost_compound() (*django_elasticsearch_dsl_drf.tests.test_search.TestSearch method*), 253
test_search_boost_compound() (*django_elasticsearch_dsl_drf.tests.TestSearch method*), 270
test_search_boost_selected_fields() (*django_elasticsearch_dsl_drf.tests.test_search_multi_match.TestMultiMatchSearch method*), 254
test_search_boost_selected_fields() (*django_elasticsearch_dsl_drf.tests.test_search_simple_query_string.TestSimpleQueryStringSearch method*), 254
test_search_boost_selected_fields() (*django_elasticsearch_dsl_drf.tests.TestMultiMatchSearch method*), 266
test_search_boost_selected_fields() (*django_elasticsearch_dsl_drf.tests.TestSimpleQueryStringSearch method*), 267
test_search_by_field() (*django_elasticsearch_dsl_drf.tests.test_search.TestSearch method*), 253
test_search_by_field() (*django_elasticsearch_dsl_drf.tests.TestSearch method*), 270
test_search_by_field_multi_terms() (*django_elasticsearch_dsl_drf.tests.test_search.TestSearch method*), 253
test_search_by_field_multi_terms() (*django_elasticsearch_dsl_drf.tests.TestSearch method*), 270
test_search_by_nested_field() (*django_elasticsearch_dsl_drf.tests.test_search.TestSearch method*), 253
test_search_by_nested_field() (*django_elasticsearch_dsl_drf.tests.TestSearch method*), 270
test_search_boost() (*django_elasticsearch_dsl_drf.tests.TestMultiMatchSearch*

test_search_selected_fields() (*django_elasticsearch_dsl_drf.tests.test_search_multi_match_search.TestMultiMatchSearch method*), 254
test_search_selected_fields() (*django_elasticsearch_dsl_drf.tests.test_search_simple_query_string_search.TestSimpleQueryStringSearch method*), 255
test_search_selected_fields() (*django_elasticsearch_dsl_drf.tests.TestMultiMatchSearch method*), 266
test_search_selected_fields() (*django_elasticsearch_dsl_drf.tests.TestSimpleQueryStringSearch method*), 267
test_search_with_quotes() (*django_elasticsearch_dsl_drf.tests.test_search_simple_query_string_search.TestSimpleQueryStringSearch method*), 255
test_search_with_quotes() (*django_elasticsearch_dsl_drf.tests.TestSimpleQueryStringSearch method*), 267
test_search_with_quotes_alternative() (*django_elasticsearch_dsl_drf.tests.test_search_simple_query_string_search.TestSimpleQueryStringSearch method*), 255
test_search_with_quotes_alternative() (*django_elasticsearch_dsl_drf.tests.TestSimpleQueryStringSearch method*), 267
test_search_with_quotes_boost() (*django_elasticsearch_dsl_drf.tests.test_search_simple_query_string_search.TestSimpleQueryStringSearch method*), 255
test_search_with_quotes_boost() (*django_elasticsearch_dsl_drf.tests.TestSimpleQueryStringSearch method*), 267
test_search_with_quotes_boost_alternative() (*django_elasticsearch_dsl_drf.tests.test_search_simple_query_string_search.TestSimpleQueryStringSearch method*), 255
test_search_with_quotes_boost_alternative() (*django_elasticsearch_dsl_drf.tests.TestSimpleQueryStringSearch method*), 267
test_search_without_quotes() (*django_elasticsearch_dsl_drf.tests.test_search_simple_query_string_search.TestSimpleQueryStringSearch method*), 255
test_search_without_quotes() (*django_elasticsearch_dsl_drf.tests.TestSimpleQueryStringSearch method*), 267
test_search_without_quotes_boost() (*django_elasticsearch_dsl_drf.tests.test_search_simple_query_string_search.TestSimpleQueryStringSearch method*), 255
test_search_without_quotes_boost() (*django_elasticsearch_dsl_drf.tests.TestSimpleQueryStringSearch method*), 267
test_serializer_document_equals_to_none() (*django_elasticsearch_dsl_drf.tests.test_serializers.TestSerializers method*), 255
test_serializer_document_equals_to_none() (*django_elasticsearch_dsl_drf.tests.TestSerializers method*), 270
test_serializer_fields_and_exclude() (*django_elasticsearch_dsl_drf.tests.test_serializers.TestSerializers method*), 255
test_serializer_fields_and_exclude() (*django_elasticsearch_dsl_drf.tests.TestSerializers method*), 270
test_serializer_meta_del_attr() (*django_elasticsearch_dsl_drf.tests.test_serializers.TestSerializers method*), 255
test_serializer_meta_del_attr() (*django_elasticsearch_dsl_drf.tests.TestSerializers method*), 270
test_serializer_meta_set_attr() (*django_elasticsearch_dsl_drf.tests.test_serializers.TestSerializers method*), 255
test_serializer_meta_set_attr() (*django_elasticsearch_dsl_drf.tests.TestSerializers method*), 270
test_serializer_no_document_specified() (*django_elasticsearch_dsl_drf.tests.test_serializers.TestSerializers method*), 255
test_serializer_no_document_specified() (*django_elasticsearch_dsl_drf.tests.TestSerializers method*), 270
test_suggesters_completion() (*django_elasticsearch_dsl_drf.tests.test_functional_suggesters.TestFunctionalSuggesters method*), 249
test_suggesters_completion() (*django_elasticsearch_dsl_drf.tests.test_suggesters.TestSuggesters method*), 256
test_suggesters_completion() (*django_elasticsearch_dsl_drf.tests.TestFunctionalSuggesters method*), 266
test_suggesters_completion() (*django_elasticsearch_dsl_drf.tests.TestSuggesters method*), 270
test_suggesters_completion_context() (*django_elasticsearch_dsl_drf.tests.test_suggesters.TestContextSuggesters method*), 256
test_suggesters_completion_no_args_provided() (*django_elasticsearch_dsl_drf.tests.test_functional_suggesters.TestFunctionalSuggesters method*), 249
test_suggesters_completion_no_args_provided() (*django_elasticsearch_dsl_drf.tests.test_suggesters.TestSuggesters method*), 256
test_suggesters_completion_no_args_provided() (*django_elasticsearch_dsl_drf.tests.TestFunctionalSuggesters method*), 266
test_suggesters_completion_no_args_provided() (*django_elasticsearch_dsl_drf.tests.TestSuggesters method*), 270
test_suggesters_on_empty_index() (*django_elasticsearch_dsl_drf.tests.test_suggesters.TestSuggesters method*), 256

test_suggesters_phrase() (*django_elasticsearch_dsl_drf.tests.test_suggesters.TestSuggesters method*), 256
test_suggesters_phrase() (*django_elasticsearch_dsl_drf.tests.TestSuggesters method*), 271
test_suggesters_term() (*django_elasticsearch_dsl_drf.tests.test_suggesters.TestSuggesters method*), 256
test_suggesters_term() (*django_elasticsearch_dsl_drf.tests.TestSuggesters method*), 271
test_various_complex_fields() (*django_elasticsearch_dsl_drf.tests.test_filtering_common.TestFilteringCommon method*), 243
test_various_complex_fields() (*django_elasticsearch_dsl_drf.tests.test_filtering_post_filter.TestFilteringPostFilter method*), 249
test_various_complex_fields() (*django_elasticsearch_dsl_drf.tests.TestFilteringCommon method*), 260
test_various_complex_fields() (*django_elasticsearch_dsl_drf.tests.TestFilteringPostFilter method*), 265
test_wrapper_as_json() (*django_elasticsearch_dsl_drf.tests.test_wrappers.TestWrappers method*), 257
test_wrapper_as_json() (*django_elasticsearch_dsl_drf.tests.TestWrappers method*), 271
TestContextSuggesters (*class in django_elasticsearch_dsl_drf.tests.test_suggesters*), 256
TestFacetedSearch (*class in django_elasticsearch_dsl_drf.tests*), 257
TestFacetedSearch (*class in django_elasticsearch_dsl_drf.tests.test_faceted_search*), 240
TestFilteringCommon (*class in django_elasticsearch_dsl_drf.tests*), 257
TestFilteringCommon (*class in django_elasticsearch_dsl_drf.tests.test_filtering_common*), 241
TestFilteringGeoSpatial (*class in django_elasticsearch_dsl_drf.tests*), 260
TestFilteringGeoSpatial (*class in django_elasticsearch_dsl_drf.tests.test_filtering_geo_spatial*), 244
TestFilteringGlobalAggregations (*class in django_elasticsearch_dsl_drf.tests*), 261
TestFilteringGlobalAggregations (*class in django_elasticsearch_dsl_drf.tests.test_filtering_global_aggregations*), 245
TestFilteringNested (*class in django_elasticsearch_dsl_drf.tests*), 261
TestFilteringNested (*class in django_elasticsearch_dsl_drf.tests.test_filtering_nested*), 245
TestFilteringPostFilter (*class in django_elasticsearch_dsl_drf.tests*), 263
TestFilteringPostFilter (*class in django_elasticsearch_dsl_drf.tests.test_filtering_post_filter*), 247
TestFunctionalSuggesters (*class in django_elasticsearch_dsl_drf.tests*), 265
TestFunctionalSuggesters (*class in django_elasticsearch_dsl_drf.tests.test_functional_suggesters*), 248
TestHelpers (*class in django_elasticsearch_dsl_drf.tests*), 266
TestHelpers.TestFilteringPostFilter (*class in django_elasticsearch_dsl_drf.tests.test_helpers*), 250
TestHighlight (*class in django_elasticsearch_dsl_drf.tests*), 266
TestHighlight (*class in django_elasticsearch_dsl_drf.tests.test_highlight*), 250
TestMoreLikeThis (*class in django_elasticsearch_dsl_drf.tests.test_more_like_this*), 250
TestMultiMatchSearch (*class in django_elasticsearch_dsl_drf.tests*), 266
TestMultiMatchSearch (*class in django_elasticsearch_dsl_drf.tests.test_search_multi_match*), 254
TestOrdering (*class in django_elasticsearch_dsl_drf.tests*), 267
TestOrdering (*class in django_elasticsearch_dsl_drf.tests.test_ordering_common*), 250
TestOrderingGeoSpatial (*class in django_elasticsearch_dsl_drf.tests*), 269
TestOrderingGeoSpatial (*class in django_elasticsearch_dsl_drf.tests.test_ordering_geo_spatial*), 252
TestPagination (*class in django_elasticsearch_dsl_drf.tests*), 269
TestPagination (*class in django_elasticsearch_dsl_drf.tests.test_pagination*), 252
TestPipHelpers (*class in django_elasticsearch_dsl_drf.tests*), 269
TestPipHelpers (*class in django_elasticsearch_dsl_drf.tests.test_pip_helpers*), 252
TestSearch (*class in django_elasticsearch_dsl_drf.tests*), 269

`TestSearch` (*class in django_elasticsearch_dsl_drf.tests.test_search*), 253
`TestSearchCustomCases` (*class in django_elasticsearch_dsl_drf.tests.test_search*), 253
`TestSerializers` (*class in django_elasticsearch_dsl_drf.tests*), 270
`TestSerializers` (*class in django_elasticsearch_dsl_drf.tests.test_serializers*), 255
`TestSimpleQueryStringSearch` (*class in django_elasticsearch_dsl_drf.tests*), 267
`TestSimpleQueryStringSearch` (*class in django_elasticsearch_dsl_drf.tests.test_search_simple_query_string*), 254
`TestSuggesters` (*class in django_elasticsearch_dsl_drf.tests*), 270
`TestSuggesters` (*class in django_elasticsearch_dsl_drf.tests.test_suggesters*), 256
`TestSuggestersEmptyIndex` (*class in django_elasticsearch_dsl_drf.tests.test_suggesters*), 256
`TestViews` (*class in django_elasticsearch_dsl_drf.tests*), 271
`TestViews` (*class in django_elasticsearch_dsl_drf.tests.test_views*), 256
`TestWrappers` (*class in django_elasticsearch_dsl_drf.tests*), 271
`TestWrappers` (*class in django_elasticsearch_dsl_drf.tests.test_wrappers*), 257
`to_dict()` (*django_elasticsearch_dsl_drf.utils.DictionaryProxy method*), 276
`to_dict()` (*django_elasticsearch_dsl_drf.utils.EmptySearch method*), 276
`to_internal_value()` (*django_elasticsearch_dsl_drf.fields.ListField method*), 161
`to_internal_value()` (*django_elasticsearch_dsl_drf.fields.nested_fields.ListField method*), 159
`to_internal_value()` (*django_elasticsearch_dsl_drf.fields.nested_fields.ObjectField method*), 158
`to_internal_value()` (*django_elasticsearch_dsl_drf.fields.ObjectField method*), 162
`to_representation()` (*django_elasticsearch_dsl_drf.fields.BooleanField method*), 159
`to_representation()` (*django_elasticsearch_dsl_drf.fields.CharField method*), 159
`to_representation()` (*django_elasticsearch_dsl_drf.fields.common.BooleanField method*), 155
`to_representation()` (*django_elasticsearch_dsl_drf.fields.common.CharField method*), 155
`to_representation()` (*django_elasticsearch_dsl_drf.fields.common.DateField method*), 155
`to_representation()` (*django_elasticsearch_dsl_drf.fields.common.FloatField method*), 155
`to_representation()` (*django_elasticsearch_dsl_drf.fields.common.IntegerField method*), 156
`to_representation()` (*django_elasticsearch_dsl_drf.fields.common.IPAddressField method*), 156
`to_representation()` (*django_elasticsearch_dsl_drf.fields.DateField method*), 159
`to_representation()` (*django_elasticsearch_dsl_drf.fields.FloatField method*), 160
`to_representation()` (*django_elasticsearch_dsl_drf.fields.IntegerField method*), 160
`to_representation()` (*django_elasticsearch_dsl_drf.fields.IPAddressField method*), 161
`to_representation()` (*django_elasticsearch_dsl_drf.fields.ListField method*), 161
`to_representation()` (*django_elasticsearch_dsl_drf.fields.nested_fields.ListField method*), 159
`to_representation()` (*django_elasticsearch_dsl_drf.fields.nested_fields.ObjectField method*), 158
`to_representation()` (*django_elasticsearch_dsl_drf.fields.ObjectField method*), 162
`to_representation()` (*in module django_elasticsearch_dsl_drf.fields.helpers*), 156

U

`update()` (*django_elasticsearch_dsl_drf.serializers.DocumentSerializer method*), 275

W

`Wrapper` (*class in django_elasticsearch_dsl_drf.wrappers*),

278